

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO
Gulf Coast Growth Ventures LLC

AUTHORIZING THE OPERATION OF
Gulf Coast Growth Ventures
Olefins, Derivative and Utilities
All Other Basic Organic Chemical Manufacturing

LOCATED AT
San Patricio County, Texas
Latitude 27° 55' 47" Longitude 97° 19' 19"
Regulated Entity Number: RN109753731

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: O4169 Issuance Date: December 30, 2020

For the Commission

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions:	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting.....	1
Additional Monitoring Requirements	10
New Source Review Authorization Requirements	11
Compliance Requirements.....	12
Risk Management Plan	12
Protection of Stratospheric Ozone	13
Alternative Requirements.....	13
Permit Location	13
Permit Shield (30 TAC § 122.148)	13
Attachments	14
Applicable Requirements Summary.....	15
Additional Monitoring Requirements	222
Permit Shield	275
New Source Review Authorization References	286
Alternative Requirement.....	299
Appendix A.....	310
Acronym List	311
Appendix B.....	312

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
 - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
 - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
 - E. Emission units subject to 40 CFR Part 63, Subpart F, G, H, YY, EEEE, FFFF, ZZZZ, and DDDDD as identified in the attached Applicable Requirements Summary table are

subject to 30 TAC Chapter 113, Subchapter C, § 113.110, § 113.120, § 113.130, § 113.560, § 113.880, § 113.890, § 113.1090, and § 113.1130, respectively, which incorporate the 40 CFR Part 63 Subparts by reference.

2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
 - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
 - A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
 - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(1)(E)
 - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
 - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive

ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the “Applicable Requirements Summary” attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:

- (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
- (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer’s eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (5) Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity

requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)
- (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
 - (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to

condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A).
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

C. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:

- (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
- (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)
- (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)

D. Outdoor burning, as stated in 30 TAC § 111.201, shall not be authorized unless the following requirements are satisfied:

- (i) Title 30 TAC § 111.205 (relating to Exception for Fire Training)
- (ii) Title 30 TAC § 111.207 (relating to Exception for Recreation, Ceremony, Cooking, and Warmth)
- (iii) Title 30 TAC § 111.219 (relating to General Requirements for Allowable Outdoor Burning)
- (iv) Title 30 TAC § 111.221 (relating to Responsibility for Consequences of Outdoor Burning)

4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: "Storage of Volatile Organic Compounds," the permit holder shall comply with the requirements of 30 TAC § 115.112(c)(1).
5. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter C requirements:
 - A. When filling gasoline storage vessels with a nominal capacity greater than 1,000 gallons (Stage I) at motor vehicle fuel dispensing facilities, which have dispensed less than 100,000 gallons of gasoline in any calendar month after October 31, 2014, the permit holder shall comply with the following requirements specified in 30 TAC Chapter 115, Subchapter C:
 - (i) Title 30 TAC § 115.222(3) (relating to Control Requirements), as it applies to liquid gasoline leaks, visible vapors, or significant odors
 - (ii) Title 30 TAC § 115.222(6) (relating to Control Requirements)
 - (iii) Title 30 TAC § 115.224(1) (relating to Inspection Requirements), as it applies to liquid gasoline leaks, visible vapors, or significant odors
 - (iv) Title 30 TAC § 115.226(2)(B) (relating to Recordkeeping Requirements)
6. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
7. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 61, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 61.05 (relating to Prohibited Activities)
 - B. Title 40 CFR § 61.07 (relating to Application for Approval of Construction or Modification)
 - C. Title 40 CFR § 61.09 (relating to Notification of Start-up)
 - D. Title 40 CFR § 61.10 (relating to Source Reporting and Request Waiver)
 - E. Title 40 CFR § 61.12 (relating to Compliance with Standards and Maintenance Requirements)

- F. Title 40 CFR § 61.13 (relating to Emissions Tests and Waiver of Emission Tests)
 - G. Title 40 CFR § 61.14 (relating to Monitoring Requirements)
 - H. Title 40 CFR § 61.15 (relating to Modification)
 - I. Title 40 CFR § 61.19 (relating to Circumvention)
8. For facilities where total annual benzene quantity from waste is greater than or equal to 10 megagrams per year and subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:
- A. Title 40 CFR § 61.342(c)(1)(i) - (iii) (relating to Standards: General)
 - B. Title 40 CFR § 61.342(e)(2)(i) - (ii) (relating to Standards: General)
 - C. Title 40 CFR § 61.342(f)(1), and (2) (relating to Standards: General)
 - D. Title 40 CFR § 61.342(g) (relating to Standards: General)
 - E. Title 40 CFR § 61.350(a) and (b) (relating to Standards: Delay of Repair)
 - F. Title 40 CFR § 61.355(a)(1)(iii), (a)(2), (a)(6), (b), and (c)(1) - (3) (relating to Test Methods, Procedures, and Compliance Provisions)
 - G. Title 40 CFR § 61.355(k)(1) - (6), and (7)(i) - (iv) (relating to Test Methods, Procedures, and Compliance Provisions), for calculation procedures
 - H. Title 40 CFR § 61.356(a) (relating to Recordkeeping Requirements)
 - I. Title 40 CFR § 61.356(b), and (b)(1) (relating to Recordkeeping Requirements)
 - J. Title 40 CFR § 61.356(b)(4) (relating to Recordkeeping Requirements)
 - K. Title 40 CFR § 61.356(b)(5) (relating to Recordkeeping Requirements)
 - L. Title 40 CFR § 61.356(c) (relating to Recordkeeping Requirements)
 - M. Title 40 CFR § 61.357(a), (d)(1), (d)(2) (d)(6) and (d)(8) (relating to Reporting Requirements)
 - N. Title 40 CFR § 61.357(d)(5) (relating to Reporting Requirements)
9. For facilities with containers subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:
- A. Title 40 CFR § 61.345(a)(1) - (3), (b), and (c) (relating to Standards: Containers)
 - B. Title 40 CFR § 61.355(h) (relating to Test Methods, Procedures and Compliance Provisions)
 - C. Title 40 CFR § 61.356(g) (relating to Recordkeeping Requirements)
 - D. Title 40 CFR § 61.356(h) (relating to Recordkeeping Requirements)

10. For facilities with individual drain systems subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:
 - A. Title 40 CFR § 61.346(a)(1)(i)(A), (B), (ii), (2), and (3) (relating to Standards: Individual Drain Systems)
 - B. Title 40 CFR § 61.346(b)(1), (2), (2)(i), (3), (4)(i) - (iv), and (5) (relating to Standards: Individual Drain Systems)
 - C. Title 40 CFR § 61.346(b)(2)(ii)(A) (relating to Standards: Individual Drain Systems), for junction boxes
 - D. Title 40 CFR § 61.355(h) (relating to Test Methods, Procedures and Compliance Provisions)
 - E. Title 40 CFR § 61.356(g) (relating to Recordkeeping Requirements)
 - F. Title 40 CFR § 61.356(h) (relating to Recordkeeping Requirements)
11. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
12. For the chemical manufacturing process specified in 40 CFR Part 63, Subpart F, the permit holder shall comply with 40 CFR § 63.103(a) (relating to General Compliance, Reporting, and Recordkeeping Provisions) (Title 30 TAC Chapter 113, Subchapter C, § 113.110 incorporated by reference).
13. For the chemical manufacturing facilities with a 40 CFR Part 63, Subpart G Group 2 wastewater stream, the permit holder shall comply with (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
 - A. Title 40 CFR § 63.132(b), (b)(1), (b)(1)(i), (b)(2), and (b)(2)(i) (relating to Process Wastewater Provisions - General)
 - B. Title 40 CFR § 63.146(b)(1) (relating to Process Wastewater Provisions - Reporting)
 - C. Title 40 CFR § 63.147(b)(8) (relating to Process Wastewater Provisions - Recordkeeping)
14. For the chemical manufacturing facilities subject to leak detection requirements in 40 CFR Part 63, Subpart G, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
 - A. General Leak Detection Requirements:
 - (i) Title 40 CFR § 63.148(d)(1) - (3), and (e) (relating to Leak Inspection Provisions)
 - (ii) Title 40 CFR § 63.148(c), (g), (g)(2), (h), and (h)(2) (relating to Leak Inspection Provisions), for monitoring and testing requirements
 - (iii) Title 40 CFR §§ 63.148(g)(2), (h)(2), (i)(1) - (2), (i)(4)(i) - (viii), (i)(5), and 63.152(a)(1) - (5), for recordkeeping requirements
 - (iv) Title 40 CFR §§ 63.148(j), 63.151(a)(6)(i) - (iii), (b)(1) - (2), (j)(1) - (3), 63.152(a)(1) - (5), (b), (b)(1)(i) - (ii), and (b)(4), for reporting requirements

- B. For closed vent system or vapor collection systems constructed of hard piping:
 - (i) Title 40 CFR § 63.148(b)(1)(ii) (relating to Leak Inspection Provisions), for monitoring and testing requirements
 - (ii) Title 40 CFR § 63.148(i)(6) (relating to Leak Inspection Provisions), for recordkeeping requirements
 - C. For facilities operating flow indicators:
 - (i) Title 40 CFR § 63.148(f)(1) (relating to Leak Inspection Provisions), for monitoring and testing requirements
 - (ii) Title 40 CFR § 63.148(f)(1), (i)(3)(i) (relating to Leak Inspection Provisions), for recordkeeping requirements
 - (iii) Title 40 CFR § 63.148(j)(2) (relating to Leak Inspection Provisions), for reporting requirements
15. For transfer of waste from ethylene production facilities subject to 40 CFR Part 63, Subpart YY the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.560 incorporated by reference):
- A. Title 40 CFR § 63.1096(a) - (d) (Title 30 TAC Chapter 113, Subchapter C, § 113.550 incorporated by reference)
 - B. Title 40 CFR § 63.1109(a) and (c)
16. For benzene laden waste streams from ethylene process facilities subject to 40 CFR Part 63, Subpart YY with total annual benzene quantity from the facility of 10 megagrams per year or more the permit holder shall comply with the following requirements as specified in 40 CFR § 63.1095(b)(2) (Title 30 TAC Chapter 113, Subchapter C, § 113.560 incorporated by reference):
- A. For facilities with waste managed in containers the permit holder shall comply with the following requirements:
 - (i) Title 40 CFR § 61.355(h) (relating to Test Methods, Procedures and Compliance Provisions)
 - (ii) Title 40 CFR § 61.356(g) (relating to Recordkeeping Requirements)
 - (iii) Title 40 CFR § 61.356(h) (relating to Recordkeeping Requirements)
 - B. For facilities with waste managed in individual drain systems the permit holder shall comply with the following requirements:
 - (i) Title 40 CFR § 61.346(a)(1)(i)(A), (B), (ii), (2), and (3) (relating to Standards: Individual Drain Systems)
 - (ii) Title 40 CFR § 61.346(b)(1), (2), (2)(i), (3), (4)(i) - (iv), and (5) (relating to Standards: Individual Drain Systems)
 - (iii) Title 40 CFR § 61.346(b)(2)(ii)(A) (relating to Standards: Individual Drain Systems), for junction boxes

- (iv) Title 40 CFR § 61.355(h) (relating to Test Methods, Procedures and Compliance Provisions)
 - (v) Title 40 CFR § 61.356(g) (relating to Recordkeeping Requirements)
 - (vi) Title 40 CFR § 61.356(h) (relating to Recordkeeping Requirements)
17. For miscellaneous chemical process facilities subject to maintenance wastewater requirements as specified in 40 CFR § 63.2485, Table 7, the permit holder shall comply with the requirements of 40 CFR § 63.105 (relating to Maintenance Wastewater Requirements) (Title 30 TAC Chapter 113, Subchapter C, § 113.890 incorporated by reference).
 18. For miscellaneous chemical process facilities with Group 2 wastewater streams subject to wastewater operations requirements in 40 CFR Part 63, Subpart FFFF, the permit holder shall comply with the requirements of 40 CFR § 63.132(b), (b)(1), (b)(1)(i), (b)(2), and (b)(2)(i) as specified in § 63.2485(a) (Title 30 TAC Chapter 113, Subchapter C, § 113.890 incorporated by reference).

Additional Monitoring Requirements

19. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached “CAM Summary” upon issuance of the permit. In addition, the permit holder shall comply with the following:
 - A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).
 - B. The permit holder shall report, consistent with the averaging time identified in the “CAM Summary,” deviations as defined by the deviation limit in the “CAM Summary.” Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).
 - C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the “CAM Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).
 - D. The permit holder shall operate the monitoring, identified in the attached “CAM Summary,” in accordance with the provisions of 40 CFR § 64.7.
 - E. The permit holder shall comply with either of the following requirements for any capture system associated with the VOC control device subject to CAM. If the results of the following inspections indicate that the capture system is not working properly, the permit holder shall promptly take necessary corrective actions:
 - (i) Once a year the permit holder shall inspect the capture system in compliance of CAM for leaks in accordance with 40 CFR Part 60, Appendix A, Test Method 21. Leaks shall be indicated by an instrument reading greater than or equal to 500

ppm above background or as defined by the underlying applicable requirement;
or

- (ii) Once a month, the permit holder shall conduct a visual, audible, and/or olfactory inspection of the capture system in compliance of CAM to detect leaking components.

F. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.

20. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

21. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule (including the terms, conditions, monitoring, recordkeeping, and reporting identified in registered PBRs and permits by rule identified in the PBR Supplemental Tables dated January 24, 2023 in the application for project 32277), standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
- A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
22. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
23. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating

noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

Compliance Requirements

24. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
25. Use of Discrete Emission Credits to comply with the applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) If applicable, offsets for Title 30 TAC Chapter 116
 - (iv) Temporarily exceed state NSR permit allowables
 - B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
 - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
 - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Risk Management Plan

26. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

27. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
- A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

Alternative Requirements

28. The permit holder shall comply with the approved alternative means of control (AMOC); alternative monitoring, recordkeeping, or reporting requirements; or requirements determined to be equivalent to an otherwise applicable requirement contained in the Alternative Requirements attachment of this permit. Units complying with an approved alternative requirement have reference to the approval in the Applicable Requirements summary listing for the unit. The permit holder shall maintain the original documentation, from the TCEQ Executive Director, demonstrating the method or limitation utilized. Documentation shall be maintained and made available in accordance with 30 TAC § 122.144.

Permit Location

29. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

30. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Alternative Requirement

Applicable Requirements Summary

Unit Summary	16
---------------------------	-----------

Applicable Requirements Summary	76
--	-----------

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
ADMINGEN	SRIC ENGINES	N/A	60III-3	40 CFR Part 60, Subpart IIII	No changing attributes.
ADMINGEN	SRIC ENGINES	N/A	63ZZZZ-10	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
C-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-10	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
C-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-16	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Smokeless flare
C-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-16A	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria and demonstrating substantially equivalent reduction efficiencies approved by the TCEQ Executive Director.
C-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-20	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
CCD81-LOAD	LOADING/UNLOADING OPERATIONS	N/A	R5212-11	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
C_FUG	FUGITIVE EMISSION UNITS	N/A	60DDD-ALL	40 CFR Part 60, Subpart DDD	No changing attributes.
C_FUG	FUGITIVE EMISSION UNITS	N/A	63FFFF-ALL	40 CFR Part 63, Subpart FFFF	No changing attributes.
DREFUSTN	LOADING/UNLOADING OPERATIONS	N/A	R5212-2	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
E-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-10	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
E-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-16	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Smokeless flare
E-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-16A	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria and demonstrating substantially equivalent reduction efficiencies approved by the TCEQ Executive Director.
E-VENTGAS	EMISSION POINTS/STATIONARY	N/A	R5121-20	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used.,

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS				Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.
E_FUG	FUGITIVE EMISSION UNITS	N/A	60DDD-ALL	40 CFR Part 60, Subpart DDD	No changing attributes.
E_FUG	FUGITIVE EMISSION UNITS	N/A	63FFFF-ALL	40 CFR Part 63, Subpart FFFF	No changing attributes.
G-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-10	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
G-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-16	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Smokeless flare
GAD03	STORAGE TANKS/VESSELS	N/A	R5112-14	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GBD05	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-10	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
GBD05	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-16	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Smokeless flare
GBD05	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63G-5A	40 CFR Part 63, Subpart G	Electing Control = Electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1)

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					without calculating the TRE index value., Control Device = Flare
GBD05	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63G-5B	40 CFR Part 63, Subpart G	Electing Control = Electing to control the process vent to the levels required in 40 CFR § 63.113(a)(2) without calculating the TRE index value, Control Device = Thermal incinerator.
GBX02	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GED03	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GED03	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63G-2A	40 CFR Part 63, Subpart G	Electing Control = Electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) without calculating the TRE index value., Control Device = Flare
GED03	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63G-2B	40 CFR Part 63, Subpart G	Electing Control = Electing to control the process vent to the levels required in 40 CFR § 63.113(a)(2) without calculating the TRE index value, Control Device = Thermal incinerator.
GFFLARE01	FLARES	N/A	R1111-2	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GFFLARE01	FLARES	N/A	60A-1	40 CFR Part 60, Subpart A	Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)
GFFLARE01	FLARES	N/A	60A-2	40 CFR Part 60, Subpart A	Flare Exit Velocity = Flare exit

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec)., Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).
GFFLARE01	FLARES	N/A	60A-3	40 CFR Part 60, Subpart A	Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec)., Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm)
GFFLARE01	FLARES	N/A	63A-1	40 CFR Part 63, Subpart A	Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)
GFFLARE01	FLARES	N/A	63A-2	40 CFR Part 63, Subpart A	Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec)., Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).
GFFLARE01	FLARES	N/A	63A-3	40 CFR Part 63, Subpart A	Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec)., Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm).
GLYUNLOAD	LOADING/UNLOADING OPERATIONS	N/A	R5212-2	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
GLYUNLOAD	LOADING/UNLOADING	N/A	63EEEE-1	40 CFR Part 63, Subpart	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	OPERATIONS			EEEE	
GRPBLRSTK	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	BOILER A, BOILER B, BOILER C	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GRPBOILER	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	USSG01A, USSG01B, USSG01C	60Db-1	40 CFR Part 60, Subpart Db	Heat Input Gas/Oil = The facility combusts natural gas or distillate oil in excess of 30% of the heat input from the combustion of all fuels.
GRPBOILER	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	USSG01A, USSG01B, USSG01C	60Db-2	40 CFR Part 60, Subpart Db	Heat Input Gas/Oil = The facility does not combust natural gas or distillate oil in excess of 30 % of the heat input from the combustion of all fuels., D-Series Fuel Type #2 = Gaseous fossil fuel other than natural gas and coal-derived synthetic fuel meeting the definition of natural gas.
GRPBOILER	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	USSG01A, USSG01B, USSG01C	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	Table Applicability = designed to utilize a continuous oxygen trim system
GRPBOILER	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	USSG01A, USSG01B, USSG01C	63DDDDD-2	40 CFR Part 63, Subpart DDDDD	Table Applicability = designed to burn Gas 1 fuel AND has no continuous oxygen trim AND has heat input equal to or greater than 10 MMBtu/hr.
GRPCPEBPL	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CCR01, CDFIL01	R5121-10	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPCPEBPL	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CCR01, CDFIL01	R5121-16	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Smokeless flare
GRPCPEBPL	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CCR01, CDFIL01	R5121-16A	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria and demonstrating substantially equivalent reduction efficiencies approved by the TCEQ Executive Director.
GRPCPEBPL	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CCR01, CDFIL01	R5121-20	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Other vapor control/recovery system, as defined in 30 TAC § 115.10
GRPCPEBPL	CHEMICAL MANUFACTURING PROCESS	CCR01, CDFIL01	63FFFF-14	40 CFR Part 63, Subpart FFFF	Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested., Prior Eval = Data from a prior evaluation or assessment is not used., Bypass Line = Bypass line valves are secured in the closed position with a car-seal or lock-and- key configuration., Designated HAL = The emission stream is not designated as halogenated., Vent

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process by venting through a closed-vent system to a flare per Table 2.1.c., Determined HAL = The emission stream is determined not to be halogenated.
GRPCPEBPL	CHEMICAL MANUFACTURING PROCESS	CCR01, CDFIL01	63FFFF-14A	40 CFR Part 63, Subpart FFFF	Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested., Prior Eval = Data from a prior evaluation or assessment is not used., Bypass Line = Bypass line valves are secured in the closed position with a car-seal or lock-and-key configuration., Designated HAL = The emission stream is not designated as halogenated., Vent Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process by venting through a closed-vent system to a flare per Table 2.1.c., Determined HAL = The emission stream is determined not to be halogenated.
GRPCPEBPL	CHEMICAL MANUFACTURING PROCESS	CCR01, CDFIL01	63FFFF-15	40 CFR Part 63, Subpart FFFF	Bypass Line = Bypass line valves are secured in the closed position with a car-seal or lock-and-key

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					configuration., Formaldehyde = The stream does not contain formaldehyde., Small Device = A small control device (defined in § 63.2550) is not being used., Meets 63.988(b)(2) = The control device does not meet the criteria in § 63.988(b)(2)., Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., CEMS = A CEMS is not used., SS Device Type = Incinerator other than a catalytic incinerator., Determined HAL = The emission stream is determined not to be halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Vent Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process to an outlet concentration of 20 ppmv or less as TOC or total organic HAP by venting to any combination of control devices except a flare., Assessment Waiver = The Administrator has not granted a waiver of compliance

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					assessment or no waiver has been requested.
GRPCPEBPL	CHEMICAL MANUFACTURING PROCESS	CCR01, CDFIL01	63FFFF-16	40 CFR Part 63, Subpart FFFF	Bypass Line = Bypass line valves are secured in the closed position with a car-seal or lock-and-key configuration., Formaldehyde = The stream does not contain formaldehyde., Small Device = A small control device (defined in § 63.2550) is not being used., Meets 63.988(b)(2) = The control device meets the criteria in § 63.988(b)(2)., Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., CEMS = A CEMS is not used., SS Device Type = Boiler or process heater with a design heat input capacity equal to or greater than 44 megawatts (MW) or in which all vent streams are introduced with the primary fuel or are used as the primary fuel., Determined HAL = The emission stream is determined not to be halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Vent

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process to an outlet concentration of 20 ppmv or less as TOC or total organic HAP by venting to any combination of control devices except a flare., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested.
GRPCPEBPL	CHEMICAL MANUFACTURING PROCESS	CCR01, CDFIL01	63FFFF-17	40 CFR Part 63, Subpart FFFF	Bypass Line = Bypass line valves are secured in the closed position with a car-seal or lock-and-key configuration., Formaldehyde = The stream does not contain formaldehyde., Small Device = A small control device (defined in § 63.2550) is not being used., Meets 63.988(b)(2) = The control device does not meet the criteria in § 63.988(b)(2)., Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., CEMS = A CEMS is not used., SS Device Type = Incinerator other than a catalytic incinerator., Determined HAL = The emission stream is determined not to be halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Alt 63SS

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Vent Emission Control = Reduce collective organic HAP emissions from the sum of all batch process vents within the process by 98% by weight or more by venting emissions from a sufficient number of the vents to any combination of non-flare control devices per Table 2.1.a., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested.
GRPCPEBPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CADR04A, CADR04B, CCD21, CCD22, CCD23, CCD24, CCGT01, CEC01A, CED01, CED02, CED03, CEE01, CEFIL01, CEMEM01A	R5121-10	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
GRPCPEBPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CADR04A, CADR04B, CCD21, CCD22, CCD23, CCD24, CCGT01, CEC01A, CED01, CED02, CED03, CEE01, CEFIL01, CEMEM01A	R5121-16	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Smokeless flare

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPCPEBPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CADR04A, CADR04B, CCD21, CCD22, CCD23, CCD24, CCGT01, CEC01A, CED01, CED02, CED03, CEE01, CEFIL01, CEMEM01A	R5121-16A	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria and demonstrating substantially equivalent reduction efficiencies approved by the TCEQ Executive Director.
GRPCPEBPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CADR04A, CADR04B, CCD21, CCD22, CCD23, CCD24, CCGT01, CEC01A, CED01, CED02, CED03, CEE01, CEFIL01, CEMEM01A	R5121-20	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.
GRPCPEBPV	CHEMICAL MANUFACTURING PROCESS	CADR04A, CADR04B, CCD21, CCD22, CCD23, CCD24, CCGT01, CEC01A, CED01, CED02, CED03, CEE01, CEFIL01, CEMEM01A	63FFFF-10	40 CFR Part 63, Subpart FFFF	Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested., Prior Eval = Data from a prior evaluation or assessment is not used., Bypass Line = No bypass lines., Designated HAL = The emission stream is not designated as halogenated., Vent Emission Control = Reduce uncontrolled organic HAP emissions from all

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					batch process vents within the process by venting through a closed-vent system to a flare per Table 2.1.c., Determined HAL = The emission stream is determined not to be halogenated.
GRPCPEBPV	CHEMICAL MANUFACTURING PROCESS	CADR04A, CADR04B, CCD21, CCD22, CCD23, CCD24, CCGT01, CEC01A, CED01, CED02, CED03, CEE01, CEFIL01, CEMEM01A	63FFFF-10A	40 CFR Part 63, Subpart FFFF	Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested., Prior Eval = Data from a prior evaluation or assessment is not used., Bypass Line = No bypass lines., Designated HAL = The emission stream is not designated as halogenated., Vent Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process by venting through a closed-vent system to a flare per Table 2.1.c., Determined HAL = The emission stream is determined not to be halogenated.
GRPCPEBPV	CHEMICAL MANUFACTURING PROCESS	CADR04A, CADR04B, CCD21, CCD22, CCD23, CCD24, CCGT01, CEC01A, CED01, CED02, CED03, CEE01, CEFIL01,	63FFFF-11	40 CFR Part 63, Subpart FFFF	Bypass Line = No bypass lines., Formaldehyde = The stream does not contain formaldehyde., Small Device = A small control device (defined in § 63.2550) is not being used., Meets 63.988(b)(2) = The control device does not meet the

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		CEMEM01A			criteria in § 63.988(b)(2)., Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., CEMS = A CEMS is not used., SS Device Type = Incinerator other than a catalytic incinerator., Determined HAL = The emission stream is determined not to be halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Vent Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process to an outlet concentration of 20 ppmv or less as TOC or total organic HAP by venting to any combination of control devices except a flare., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested.
GRPCPEBPV	CHEMICAL MANUFACTURING PROCESS	CADR04A, CADR04B, CCD21, CCD22, CCD23, CCD24, CCGT01, CEC01A, CED01,	63FFFF-12	40 CFR Part 63, Subpart FFFF	Bypass Line = No bypass lines., Formaldehyde = The stream does not contain formaldehyde., Small Device = A small control device (defined in § 63.2550) is not being

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		CED02, CED03, CEE01, CEFIL01, CEMEM01A			used., Meets 63.988(b)(2) = The control device meets the criteria in § 63.988(b)(2)., Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., CEMS = A CEMS is not used., SS Device Type = Boiler or process heater with a design heat input capacity equal to or greater than 44 megawatts (MW) or in which all vent streams are introduced with the primary fuel or are used as the primary fuel., Determined HAL = The emission stream is determined not to be halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Vent Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process to an outlet concentration of 20 ppmv or less as TOC or total organic HAP by venting to any combination of control devices except a flare., HAL Device Type = No halogen scrubber or other halogen reduction device is

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					used., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested.
GRPCPEBPV	CHEMICAL MANUFACTURING PROCESS	CADR04A, CADR04B, CCD21, CCD22, CCD23, CCD24, CCGT01, CEC01A, CED01, CED02, CED03, CEE01, CEFIL01, CEMEM01A	63FFF-13	40 CFR Part 63, Subpart FFFF	Bypass Line = No bypass lines., Formaldehyde = The stream does not contain formaldehyde., Small Device = A small control device (defined in § 63.2550) is not being used., Meets 63.988(b)(2) = The control device does not meet the criteria in § 63.988(b)(2)., Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., CEMS = A CEMS is not used., SS Device Type = Incinerator other than a catalytic incinerator., Determined HAL = The emission stream is determined not to be halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Vent Emission Control = Reduce collective organic HAP emissions from the sum of all batch process vents within the process by 98% by weight or more by venting emissions from a sufficient number of the vents

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					to any combination of non-flare control devices per Table 2.1.a., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested.
GRPCPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CCT01, CDD03, CEMEM01B	R5121-10	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
GRPCPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CCT01, CDD03, CEMEM01B	R5121-16	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Smokeless flare
GRPCPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CCT01, CDD03, CEMEM01B	R5121-16A	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria and demonstrating substantially equivalent reduction efficiencies approved by the TCEQ Executive Director.
GRPCPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CCT01, CDD03, CEMEM01B	R5121-20	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Other vapor control/recovery system, as defined in 30 TAC § 115.10
GRPCPECPV	EMISSION POINTS/STATIONARY	CCT01, CDD03, CEMEM01B	63FFFF-1	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS				threshold (5.0 for a new source and 1.9 for an existing source) and a flare is being used for control., Determined Hal = The emission stream is determined to be non-halogenated., Designated Grp1 = The emission stream is designated as Group 1., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., Designated Hal = The emission stream is not designated as halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Bypass Line = No bypass lines., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or a waiver has not been requested.
GRPCPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CCT01, CDD03, CEMEM01B	63FFFF-1A	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a flare is being used for control., Determined Hal = The emission stream is determined to be non-halogenated., Designated Grp1 = The emission stream is designated as Group 1., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., Designated Hal = The emission stream is not designated as halogenated., Prior

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Eval = The data from a prior evaluation or assessment is not used., Bypass Line = No bypass lines., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or a waiver has not been requested.
GRPCPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CCT01, CDD03, CEMEM01B	63FFFF-2	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a non-flare CD is being used to meet 98% reduction per § 63.2455(a) - Table 1.1.a.i., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Formaldehyde = The stream does not contain formaldehyde., Bypass Line = No bypass lines., Prior Eval = The data from a prior evaluation or assessment is not used., CEMS = A CEMS is not used., Designated Grp1 = The emission stream is designated as Group 1., Small Device = A small control device (defined in § 63.2550) is not being used., 1257A1 = No design evaluation as specified in § 63.1257(a)(1) is being conducted., Designated Hal = The emission stream is not designated as halogenated., Negative Pressure =

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					The closed vent system is operated and maintained at or above atmospheric pressure., SS Device Type = Incinerator other than a catalytic incinerator., Meets 63.988(b)(2) = The control device does not meet the criteria in § 63.985(b)(2)., Determined Hal = The emission stream is determined to be non-halogenated., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver is requested.
GRPCPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CCT01, CDD03, CEMEM01B	63FFFF-3	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a non-flare CD is being used to meet 98% reduction per § 63.2455(a) - Table 1.1.a.i., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Formaldehyde = The stream does not contain formaldehyde., Bypass Line = No bypass lines., Prior Eval = The data from a prior evaluation or assessment is not used., CEMS = A CEMS is not used., Designated Grp1 = The emission stream is designated as Group 1., Small Device = A small control device

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					(defined in § 63.2550) is not being used., 1257A1 = No design evaluation as specified in § 63.1257(a)(1) is being conducted., Designated Hal = The emission stream is not designated as halogenated., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., SS Device Type = Boiler or process heater with a design heat input capacity equal to or greater than 44 megawatts (MW) or in which all vent streams are introduced with the primary fuel or are used as the primary fuel., Meets 63.988(b)(2) = The control device meets criteria in § 63.985(b)(2)., Determined Hal = The emission stream is determined to be non-halogenated., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver is requested.
GRPCPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CCT01, CDD03, CEMEM01B	63FFFF-4	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a non-flare CD is being used to meet a ppmv standard per § 63.2455(a) - Table 1.1.a.i., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Administrator or have not been requested., Formaldehyde = The stream does not contain formaldehyde., Bypass Line = No bypass lines., Prior Eval = The data from a prior evaluation or assessment is not used., CEMS = A CEMS is not used., Designated Grp1 = The emission stream is designated as Group 1., Small Device = A small control device (defined in § 63.2550) is not being used., Designated Hal = The emission stream is not designated as halogenated., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., SS Device Type = Incinerator other than a catalytic incinerator., Meets 63.988(b)(2) = The control device does not meet the criteria in § 63.985(b)(2)., Determined Hal = The emission stream is determined to be non-halogenated., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver is requested.
GRPEMPEBPL	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECR01, EDFIL01	R5121-10	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPEMPEBPL	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECR01, EDFIL01	R5121-16	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Smokeless flare
GRPEMPEBPL	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECR01, EDFIL01	R5121-16A	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria and demonstrating substantially equivalent reduction efficiencies approved by the TCEQ Executive Director.
GRPEMPEBPL	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECR01, EDFIL01	R5121-20	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Other vapor control/recovery system, as defined in 30 TAC § 115.10
GRPEMPEBPL	CHEMICAL MANUFACTURING PROCESS	ECR01, EDFIL01	63FFFF-14	40 CFR Part 63, Subpart FFFF	Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested., Prior Eval = Data from a prior evaluation or assessment is not used., Bypass Line = Bypass line valves are secured in the closed position with a car-seal or lock-and- key configuration., Designated HAL = The emission stream is not designated as halogenated., Vent

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process by venting through a closed-vent system to a flare per Table 2.1.c., Determined HAL = The emission stream is determined not to be halogenated.
GRPEMPEBPL	CHEMICAL MANUFACTURING PROCESS	ECR01, EDFIL01	63FFFF-14A	40 CFR Part 63, Subpart FFFF	Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested., Prior Eval = Data from a prior evaluation or assessment is not used., Bypass Line = Bypass line valves are secured in the closed position with a car-seal or lock-and-key configuration., Designated HAL = The emission stream is not designated as halogenated., Vent Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process by venting through a closed-vent system to a flare per Table 2.1.c., Determined HAL = The emission stream is determined not to be halogenated.
GRPEMPEBPL	CHEMICAL MANUFACTURING PROCESS	ECR01, EDFIL01	63FFFF-15	40 CFR Part 63, Subpart FFFF	Bypass Line = Bypass line valves are secured in the closed position with a car-seal or lock-and-key

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					configuration., Formaldehyde = The stream does not contain formaldehyde., Small Device = A small control device (defined in § 63.2550) is not being used., Meets 63.988(b)(2) = The control device does not meet the criteria in § 63.988(b)(2)., Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., CEMS = A CEMS is not used., SS Device Type = Incinerator other than a catalytic incinerator., Determined HAL = The emission stream is determined not to be halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Vent Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process to an outlet concentration of 20 ppmv or less as TOC or total organic HAP by venting to any combination of control devices except a flare., Assessment Waiver = The Administrator has not granted a waiver of compliance

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					assessment or no waiver has been requested.
GRPEMPEBPL	CHEMICAL MANUFACTURING PROCESS	ECR01, EDFIL01	63FFFF-16	40 CFR Part 63, Subpart FFFF	Bypass Line = Bypass line valves are secured in the closed position with a car-seal or lock-and-key configuration., Formaldehyde = The stream does not contain formaldehyde., Small Device = A small control device (defined in § 63.2550) is not being used., Meets 63.988(b)(2) = The control device meets the criteria in § 63.988(b)(2)., Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., CEMS = A CEMS is not used., SS Device Type = Boiler or process heater with a design heat input capacity equal to or greater than 44 megawatts (MW) or in which all vent streams are introduced with the primary fuel or are used as the primary fuel., Determined HAL = The emission stream is determined not to be halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Vent

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process to an outlet concentration of 20 ppmv or less as TOC or total organic HAP by venting to any combination of control devices except a flare., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested.
GRPEMPEBPL	CHEMICAL MANUFACTURING PROCESS	ECR01, EDFIL01	63FFFF-17	40 CFR Part 63, Subpart FFFF	Bypass Line = Bypass line valves are secured in the closed position with a car-seal or lock-and-key configuration., Formaldehyde = The stream does not contain formaldehyde., Small Device = A small control device (defined in § 63.2550) is not being used., Meets 63.988(b)(2) = The control device does not meet the criteria in § 63.988(b)(2)., Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., CEMS = A CEMS is not used., SS Device Type = Incinerator other than a catalytic incinerator., Determined HAL = The emission stream is determined not to be halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Alt 63SS

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Vent Emission Control = Reduce collective organic HAP emissions from the sum of all batch process vents within the process by 98% by weight or more by venting emissions from a sufficient number of the vents to any combination of non-flare control devices per Table 2.1.a., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested.
GRPEMPEBPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	EADR04A, EADR04B, EADR05A, EADR05B, EADR06, EADR07A, EADR07B, EADR09, EADR10, ECD21, ECD22, ECD23, ECD24, ECGTO1, EEC01A, EED01, EED02, EED03, EEE01, EEFIL01, EEMEM01A	R5121-10	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
GRPEMPEBPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	EADR04A, EADR04B, EADR05A, EADR05B, EADR06,	R5121-16	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Smokeless flare

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		EADR07A, EADR07B, EADR09, EADR10, ECD21, ECD22, ECD23, ECD24, ECGTO1, EEC01A, EED01, EED02, EED03, EEE01, EEFIL01, EEMEM01A			
GRPEMPEBPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	EADR04A, EADR04B, EADR05A, EADR05B, EADR06, EADR07A, EADR07B, EADR09, EADR10, ECD21, ECD22, ECD23, ECD24, ECGTO1, EEC01A, EED01, EED02, EED03, EEE01, EEFIL01, EEMEM01A	R5121-16A	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria and demonstrating substantially equivalent reduction efficiencies approved by the TCEQ Executive Director.
GRPEMPEBPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	EADR04A, EADR04B, EADR05A, EADR05B, EADR06, EADR07A, EADR07B, EADR09, EADR10, ECD21, ECD22, ECD23, ECD24, ECGTO1, EEC01A, EED01, EED02, EED03, EEE01, EEFIL01, EEMEM01A	R5121-20	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		EEMEM01A			
GRPEMPEBPV	CHEMICAL MANUFACTURING PROCESS	EADR04A, EADR04B, EADR05A, EADR05B, EADR06, EADR07A, EADR07B, EADR09, EADR10, ECD21, ECD22, ECD23, ECD24, ECGTO1, EEC01A, EED01, EED02, EED03, EEE01, EEFIL01, EEMEM01A	63FFF-10	40 CFR Part 63, Subpart FFFF	Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested., Prior Eval = Data from a prior evaluation or assessment is not used., Bypass Line = No bypass lines., Designated HAL = The emission stream is not designated as halogenated., Vent Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process by venting through a closed-vent system to a flare per Table 2.1.c., Determined HAL = The emission stream is determined not to be halogenated.
GRPEMPEBPV	CHEMICAL MANUFACTURING PROCESS	EADR04A, EADR04B, EADR05A, EADR05B, EADR06, EADR07A, EADR07B, EADR09, EADR10, ECD21, ECD22, ECD23, ECD24, ECGTO1, EEC01A, EED01, EED02, EED03, EEE01, EEFIL01,	63FFF-10A	40 CFR Part 63, Subpart FFFF	Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested., Prior Eval = Data from a prior evaluation or assessment is not used., Bypass Line = No bypass lines., Designated HAL = The emission stream is not designated

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		EEMEM01A			as halogenated., Vent Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process by venting through a closed-vent system to a flare per Table 2.1.c., Determined HAL = The emission stream is determined not to be halogenated.
GRPEMPEBPV	CHEMICAL MANUFACTURING PROCESS	EADR04A, EADR04B, EADR05A, EADR05B, EADR06, EADR07A, EADR07B, EADR09, EADR10, ECD21, ECD22, ECD23, ECD24, ECGT01, EEC01A, EED01, EED02, EED03, EEE01, EEFIL01, EEMEM01A	63FFF-11	40 CFR Part 63, Subpart FFFF	Bypass Line = No bypass lines., Formaldehyde = The stream does not contain formaldehyde., Small Device = A small control device (defined in § 63.2550) is not being used., Meets 63.988(b)(2) = The control device does not meet the criteria in § 63.988(b)(2)., Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., CEMS = A CEMS is not used., SS Device Type = Incinerator other than a catalytic incinerator., Determined HAL = The emission stream is determined not to be halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Vent Emission Control = Reduce

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					uncontrolled organic HAP emissions from all batch process vents within the process to an outlet concentration of 20 ppmv or less as TOC or total organic HAP by venting to any combination of control devices except a flare., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested.
GRPEMPEBPV	CHEMICAL MANUFACTURING PROCESS	EADR04A, EADR04B, EADR05A, EADR05B, EADR06, EADR07A, EADR07B, EADR09, EADR10, ECD21, ECD22, ECD23, ECD24, ECGTO1, EEC01A, EED01, EED02, EED03, EEE01, EEFIL01, EEMEM01A	63FFFF-12	40 CFR Part 63, Subpart FFFF	Bypass Line = No bypass lines., Formaldehyde = The stream does not contain formaldehyde., Small Device = A small control device (defined in § 63.2550) is not being used., Meets 63.988(b)(2) = The control device meets the criteria in § 63.988(b)(2)., Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., CEMS = A CEMS is not used., SS Device Type = Boiler or process heater with a design heat input capacity equal to or greater than 44 megawatts (MW) or in which all vent streams are introduced with the primary fuel or are used as the primary fuel., Determined HAL = The emission stream is determined not to be halogenated., Prior Eval = The data from a prior evaluation or

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					assessment is not used., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Vent Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process to an outlet concentration of 20 ppmv or less as TOC or total organic HAP by venting to any combination of control devices except a flare., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested.
GRPEMPEBPV	CHEMICAL MANUFACTURING PROCESS	EADR04A, EADR04B, EADR05A, EADR05B, EADR06, EADR07A, EADR07B, EADR09, EADR10, ECD21, ECD22, ECD23, ECD24, ECGT01, EEC01A, EED01, EED02, EED03, EEE01, EEFIL01, EEMEM01A	63FFFF-13	40 CFR Part 63, Subpart FFFF	Bypass Line = No bypass lines., Formaldehyde = The stream does not contain formaldehyde., Small Device = A small control device (defined in § 63.2550) is not being used., Meets 63.988(b)(2) = The control device does not meet the criteria in § 63.988(b)(2)., Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., CEMS = A CEMS is not used., SS Device Type = Incinerator other than a catalytic incinerator., Determined HAL = The emission stream is

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					determined not to be halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Vent Emission Control = Reduce collective organic HAP emissions from the sum of all batch process vents within the process by 98% by weight or more by venting emissions from a sufficient number of the vents to any combination of non-flare control devices per Table 2.1.a., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver has been requested.
GRPEMPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECT01, EEMEM01B	R5121-10	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
GRPEMPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECT01, EEMEM01B	R5121-16	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Smokeless flare
GRPEMPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECT01, EEMEM01B	R5121-16A	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate method for demonstrating and documenting continuous

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					compliance with applicable control requirements or exemption criteria and demonstrating substantially equivalent reduction efficiencies approved by the TCEQ Executive Director.
GRPEMPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECT01, EEMEM01B	R5121-20	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Other vapor control/recovery system, as defined in 30 TAC § 115.10
GRPEMPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECT01, EEMEM01B	63FFFF-1	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a flare is being used for control., Determined Hal = The emission stream is determined to be non-halogenated., Designated Grp1 = The emission stream is designated as Group 1., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., Designated Hal = The emission stream is not designated as halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Bypass Line = No bypass lines., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or a waiver has not been requested.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPEMPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECT01, EEMEM01B	63FFFF-1A	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a flare is being used for control., Determined Hal = The emission stream is determined to be non-halogenated., Designated Grp1 = The emission stream is designated as Group 1., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., Designated Hal = The emission stream is not designated as halogenated., Prior Eval = The data from a prior evaluation or assessment is not used., Bypass Line = No bypass lines., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or a waiver has not been requested.
GRPEMPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECT01, EEMEM01B	63FFFF-2	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a non-flare CD is being used to meet 98% reduction per § 63.2455(a) - Table 1.1.a.i., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Formaldehyde = The stream does not contain

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					formaldehyde., Bypass Line = No bypass lines., Prior Eval = The data from a prior evaluation or assessment is not used., CEMS = A CEMS is not used., Designated Grp1 = The emission stream is designated as Group 1., Small Device = A small control device (defined in § 63.2550) is not being used., 1257A1 = No design evaluation as specified in § 63.1257(a)(1) is being conducted., Designated Hal = The emission stream is not designated as halogenated., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., SS Device Type = Incinerator other than a catalytic incinerator., Meets 63.988(b)(2) = The control device does not meet the criteria in § 63.985(b)(2)., Determined Hal = The emission stream is determined to be non-halogenated., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver is requested.
GRPEMPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECT01, EEMEM01B	63FFFF-3	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a non-flare CD is being used to meet 98% reduction per § 63.2455(a) -

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					<p>Table 1.1.a.i., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Formaldehyde = The stream does not contain formaldehyde., Bypass Line = No bypass lines., Prior Eval = The data from a prior evaluation or assessment is not used., CEMS = A CEMS is not used., Designated Grp1 = The emission stream is designated as Group 1., Small Device = A small control device (defined in § 63.2550) is not being used., 1257A1 = No design evaluation as specified in § 63.1257(a)(1) is being conducted., Designated Hal = The emission stream is not designated as halogenated., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., SS Device Type = Boiler or process heater with a design heat input capacity equal to or greater than 44 megawatts (MW) or in which all vent streams are introduced with the primary fuel or are used as the primary fuel., Meets 63.988(b)(2) = The control device meets criteria in § 63.985(b)(2)., Determined Hal = The emission stream is determined to be</p>

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					non-halogenated., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver is requested.
GRPEMPECPV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ECT01, EEMEM01B	63FFFF-4	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a non-flare CD is being used to meet a ppmv standard per § 63.2455(a) - Table 1.1.a.i., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Formaldehyde = The stream does not contain formaldehyde., Bypass Line = No bypass lines., Prior Eval = The data from a prior evaluation or assessment is not used., CEMS = A CEMS is not used., Designated Grp1 = The emission stream is designated as Group 1., Small Device = A small control device (defined in § 63.2550) is not being used., Designated Hal = The emission stream is not designated as halogenated., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., SS Device Type = Incinerator other than a catalytic incinerator., Meets

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					63.988(b)(2) = The control device does not meet the criteria in § 63.985(b)(2)., Determined Hal = The emission stream is determined to be non-halogenated., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or no waiver is requested.
GRPEMRGGEN	SRIC ENGINES	GUDGEN01, UKDGEN01, UKDGEN02	60III-3	40 CFR Part 60, Subpart IIII	No changing attributes.
GRPEMRGGEN	SRIC ENGINES	GUDGEN01, UKDGEN01, UKDGEN02	63ZZZZ-10	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
GRPEQTANK	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ZWTK01, ZWTK02	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPEXTRUD	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CLDC03, ELDC03	R5121-4	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPFURNSTK	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	OFAF01, OFBF01, OFDF01, OFDF01, OFEF01, OFFF01, OFGF01, OFHF01	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GRPFWP	SRIC ENGINES	ZFP02B, ZFP02C	60III-1	40 CFR Part 60, Subpart IIII	No changing attributes.
GRPFWP	SRIC ENGINES	ZFP02B, ZFP02C	63ZZZZ-10	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
GRPGLYLOAD	LOADING/UNLOADING OPERATIONS	RLOAD-GB, RLOAD-HG, RLOAD-MEG,	R5212-4	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		TLOAD-MEG			
GRPGLYLOAD	LOADING/UNLOADING OPERATIONS	RLOAD-GB, RLOAD-HG, RLOAD-MEG, TLOAD-MEG	63G-10	40 CFR Part 63, Subpart G	No changing attributes.
GRPGLYTANK	STORAGE TANKS/VESSELS	GDTK01, GETK01, GETK02A, GETK02B	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
GRPGRANULE	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CDDCO4, CDFAN01, CLDC01, EDDCO4, EDFAN01, ELDC01	R5121-4	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPHFOTANK	STORAGE TANKS/VESSELS	ZTTK06A, ZTTK06B	R5112-21	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare, Construction Date = On or after May 12, 1973, Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria., Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 25,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia
GRPHFOTANK	STORAGE TANKS/VESSELS	ZTTK06A, ZTTK06B	R5112-21A	30 TAC Chapter 115, Storage of VOCs	Alternate Control Requirement = Using alternate method for demonstrating and documenting

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					continuous compliance with applicable control requirements or exemption criteria, and demonstrating substantially equivalent reduction efficiencies approved by the TCEQ executive director.
GRPHFOTANK	STORAGE TANKS/VESSELS	ZTTK06A, ZTTK06B	R5112-22	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Direct-flame incinerator, Construction Date = On or after May 12, 1973, Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria., Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 25,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia
GRPHFOTANK	STORAGE TANKS/VESSELS	ZTTK06A, ZTTK06B	R5112-25	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Other control device, Construction Date = On or after May 12, 1973, Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.,

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 25,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia
GRPHFOTANK	STORAGE TANKS/VESSELS	ZTTK06A, ZTTK06B	63YY-BLR	40 CFR Part 63, Subpart YY	Control Device Type = Steam Generating Unit (Boiler)
GRPHFOTANK	STORAGE TANKS/VESSELS	ZTTK06A, ZTTK06B	63YY-FL	40 CFR Part 63, Subpart YY	Control Device Type = Flare
GRPHFOTANK	STORAGE TANKS/VESSELS	ZTTK06A, ZTTK06B	63YY-FLA	40 CFR Part 63, Subpart YY	Control Device Type = Flare complying with MACT CC
GRPHFOTANK	STORAGE TANKS/VESSELS	ZTTK06A, ZTTK06B	63YY-INC	40 CFR Part 63, Subpart YY	Control Device Type = Incenerator
GRPHFOTANK	STORAGE TANKS/VESSELS	ZTTK06A, ZTTK06B	63YY-INC1	40 CFR Part 63, Subpart YY	No changing attributes.
GRPHON-PV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	GBD02, GDD07, GDE11	R5121-10	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
GRPHON-PV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	GBD02, GDD07, GDE11	R5121-16	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Smokeless flare
GRPHON-PV	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	GBD02, GDD07, GDE11	63G-3A	40 CFR Part 63, Subpart G	Electing Control = Electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) without calculating the TRE index value., Control Device = Flare
GRPHON-PV	EMISSION	GBD02, GDD07,	63G-3B	40 CFR Part 63, Subpart G	Electing Control = Electing to control

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	POINTS/STATIONARY VENTS/PROCESS VENTS	GDE11			the process vent to the levels required in 40 CFR § 63.113(a)(2) without calculating the TRE index value, Control Device = Thermal incinerator.
GRPLOADOUT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CMDC01, CPFAN01, EMDC01, EPFAN01	R5121-4	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPPellet	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	CMFAN01, CMFAN02, EMFAN01, EMFAN02	R5121-4	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPSKIMMER	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	ZWFOS01, ZWFOS02	R5131-2	30 TAC Chapter 115, Water Separation	No changing attributes.
GRPUNLOAD	LOADING/UNLOADING OPERATIONS	DMSUNLOAD, RLUNLOAD-A, RLUNLOAD-B, TKUNLOAD-A, TKUNLOAD-B	R5212-3	30 TAC Chapter 115, Loading and Unloading of VOC	Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
GRPUNLOAD	LOADING/UNLOADING OPERATIONS	DMSUNLOAD, RLUNLOAD-A, RLUNLOAD-B, TKUNLOAD-A, TKUNLOAD-B	R5212-6	30 TAC Chapter 115, Loading and Unloading of VOC	Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
G_FUG	FUGITIVE EMISSION UNITS	N/A	60VVA-ALL	40 CFR Part 60, Subpart VVa	No changing attributes.
G_FUG	FUGITIVE EMISSION UNITS	N/A	63H-ALL	40 CFR Part 63, Subpart H	No changing attributes.
MEOHUNLOAD	LOADING/UNLOADING OPERATIONS	N/A	R5212-3	30 TAC Chapter 115, Loading and Unloading of	Vapor Tight = All liquid and vapor lines are equipped with fittings

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				VOC	which make vapor-tight connections that close automatically when disconnected.
MEOHUNLOAD	LOADING/UNLOADING OPERATIONS	N/A	R5212-6	30 TAC Chapter 115, Loading and Unloading of VOC	Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
MEOHUNLOAD	LOADING/UNLOADING OPERATIONS	N/A	63EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
O-REGEN	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-5	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
O-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-10	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
O-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-16	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Smokeless flare
O-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-16A	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria and demonstrating substantially equivalent reduction efficiencies approved by the TCEQ Executive Director.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
O-VENTGAS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-20	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.
O_FUG	FUGITIVE EMISSION UNITS	N/A	60VVA-ALL	40 CFR Part 60, Subpart VVa	No changing attributes.
O_FUG	FUGITIVE EMISSION UNITS	N/A	63YY-ALL	40 CFR Part 63, Subpart YY	No changing attributes.
PE-REGEN	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
PE-REGEN	CHEMICAL MANUFACTURING PROCESS	N/A	63FFFF-9	40 CFR Part 63, Subpart FFFF	No changing attributes.
PROEXTRUD	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-02	40 CFR Part 60, Subpart DDD	No changing attributes.
PROGRANUL1	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-02	40 CFR Part 60, Subpart DDD	No changing attributes.
PROGRANUL2	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-02	40 CFR Part 60, Subpart DDD	No changing attributes.
PROGRANUL3	POLYMER MANUFACTURING	N/A	60DDD-03	40 CFR Part 60, Subpart DDD	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	PROCESSES				
PROLDOUT1	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-02	40 CFR Part 60, Subpart DDD	No changing attributes.
PROLDOUT2	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-03	40 CFR Part 60, Subpart DDD	No changing attributes.
PROMEGCMPU	CHEMICAL MANUFACTURING PROCESS	N/A	63F-1	40 CFR Part 63, Subpart F	No changing attributes.
PROPELLET	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-02	40 CFR Part 60, Subpart DDD	No changing attributes.
PROPEMCPU	CHEMICAL MANUFACTURING PROCESS	N/A	63FFFF-MCPU	40 CFR Part 63, Subpart FFFF	No changing attributes.
RAD02	STORAGE TANKS/VESSELS	N/A	R5112-11	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
RJT01	MISCELLANEOUS UNITS	N/A	60NNN-1	40 CFR Part 60, Subpart NNN	No changing attributes.
RJT01	MISCELLANEOUS UNITS	N/A	65CAR-BLR	40 CFR Part 65, Subpart D	Control Device Type: Steam Generating Unit (Boiler)
RJT01	MISCELLANEOUS UNITS	N/A	65CAR-FL	40 CFR Part 65, Subpart D	Control Device Type: Flare
RJT01	MISCELLANEOUS UNITS	N/A	65CAR-INC	40 CFR Part 65, Subpart D	Control Device Type: Thermal Incinerator
RLOAD-C3	LOADING/UNLOADING OPERATIONS	N/A	R5212-7	30 TAC Chapter 115, Loading and Unloading of VOC	Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					disconnected.
RLOAD-C3	LOADING/UNLOADING OPERATIONS	N/A	R5212-8	30 TAC Chapter 115, Loading and Unloading of VOC	Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
RLOAD-HFO	LOADING/UNLOADING OPERATIONS	N/A	R5212-5	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
SLOPUNLOAD	LOADING/UNLOADING OPERATIONS	N/A	R5212-3	30 TAC Chapter 115, Loading and Unloading of VOC	Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
SLOPUNLOAD	LOADING/UNLOADING OPERATIONS	N/A	R5212-6	30 TAC Chapter 115, Loading and Unloading of VOC	Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
SLOPUNLOAD	LOADING/UNLOADING OPERATIONS	N/A	63EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
TLOAD-SLOP	LOADING/UNLOADING OPERATIONS	N/A	R5212-5	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
UCCT01	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63YY-CT	40 CFR Part 63, Subpart YY	No changing attributes.
UFF01A	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
UFF01B	EMISSION	N/A	R1111-1	30 TAC Chapter 111, Visible	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	POINTS/STATIONARY VENTS/PROCESS VENTS			Emissions	
UFFLARE01	FLARES	N/A	R1111-2A	30 TAC Chapter 111, Visible Emissions	No changing attributes.
UFFLARE01	FLARES	N/A	63CC-01	40 CFR Part 63, Subpart CC	No changing attributes.
UFFLARE02	FLARES	N/A	R1111-2	30 TAC Chapter 111, Visible Emissions	No changing attributes.
UFFLARE02	FLARES	N/A	60A-1	40 CFR Part 60, Subpart A	Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)
UFFLARE02	FLARES	N/A	60A-2	40 CFR Part 60, Subpart A	Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec)., Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).
UFFLARE02	FLARES	N/A	60A-3	40 CFR Part 60, Subpart A	Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec)., Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm)
UFFLARE02	FLARES	N/A	63A-1	40 CFR Part 63, Subpart A	Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)
UFFLARE02	FLARES	N/A	63A-2	40 CFR Part 63, Subpart A	Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec)., Heating Value of Gas = Heating value is less than

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					or equal to 1000 Btu/scf (37.3 MJ/scm).
UFFLARE02	FLARES	N/A	63A-3	40 CFR Part 63, Subpart A	Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec)., Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm).
U_FUG	FUGITIVE EMISSION UNITS	N/A	60DDD-ALL	40 CFR Part 60, Subpart DDD	No changing attributes.
U_FUG	FUGITIVE EMISSION UNITS	N/A	60VVA-ALL	40 CFR Part 60, Subpart VVa	No changing attributes.
U_FUG	FUGITIVE EMISSION UNITS	N/A	63FFFF-ALL	40 CFR Part 63, Subpart FFFF	No changing attributes.
U_FUG	FUGITIVE EMISSION UNITS	N/A	63H-ALL	40 CFR Part 63, Subpart H	No changing attributes.
U_FUG	FUGITIVE EMISSION UNITS	N/A	63YY-ALL	40 CFR Part 63, Subpart YY	No changing attributes.
U_LAB	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
WASHUNLOAD	LOADING/UNLOADING OPERATIONS	N/A	R5212-2	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
WASHUNLOAD	LOADING/UNLOADING OPERATIONS	N/A	63EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
ZMTK01	STORAGE TANKS/VESSELS	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
ZTD08	STORAGE	N/A	R5112-26	30 TAC Chapter 115,	Tank Description = Tank using a

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS			Storage of VOCs	vapor recovery system (VRS), Control Device Type = Flare, Construction Date = On or after May 12, 1973, Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria., Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 25,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 11 psia
ZTD08	STORAGE TANKS/VESSELS	N/A	R5112-26A	30 TAC Chapter 115, Storage of VOCs	Alternate Control Requirement = Using alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria, and demonstrating substantially equivalent reduction efficiencies approved by the TCEQ executive director.
ZTD08	STORAGE TANKS/VESSELS	N/A	R5112-27	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Direct-flame incinerator, Construction Date = On or after May 12, 1973, Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					requirements or exemption criteria., Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 25,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 11 psia
ZTD08	STORAGE TANKS/VESSELS	N/A	R5112-30	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Other control device, Construction Date = On or after May 12, 1973, Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria., Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 25,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 11 psia
ZTD08	STORAGE TANKS/VESSELS	N/A	63FFFF-5	40 CFR Part 63, Subpart FFFF	Prior Eval = The data from a prior evaluation or assessment is not being used., Bypass Line = No bypass lines., Emission Standard = HAP vapor pressure is less than 76.6 and a flare is being used for control per § 63.2470(a)-Table 4.1.b.iii., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or a waiver was not requested.,

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., Determined HAL = The emission stream is determined not to be halogenated.
ZTD08	STORAGE TANKS/VESSELS	N/A	63FFFF-5A	40 CFR Part 63, Subpart FFFF	Prior Eval = The data from a prior evaluation or assessment is not being used., Bypass Line = No bypass lines., Emission Standard = HAP vapor pressure is less than 76.6 and a flare is being used for control per § 63.2470(a)-Table 4.1.b.iii., Assessment Waiver = The Administrator has not granted a waiver of compliance assessment or a waiver was not requested., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., Determined HAL = The emission stream is determined not to be halogenated.
ZTD08	STORAGE TANKS/VESSELS	N/A	63FFFF-6	40 CFR Part 63, Subpart FFFF	HAL Device Type = No halogen scrubber or other halogen reduction device is used., Prior Test = The data from a prior performance test is not used., Test Waiver = The Administrator has not granted a waiver of the performance test or no

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					<p>waiver has been requested., Bypass Line = No bypass lines., Designated HAL = The emission stream is not designated as halogenated., Determined HAL = The emission stream is determined not to be halogenated., Emission Standard = HAP vapor pressure is < 76.6 and a non-flare CD is being used to meet a ppmv standard per § 63.2470(a)-Table 4.1.b.ii, SS Device Type = Incinerator other than a catalytic incinerator., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., CEMS = A continuous parameter monitoring system is used., Meets 63.998(b)(2) = The control device does not meet criteria in § 63.985(b)(2)., Formaldehyde = The stream does not contain formaldehyde.</p>
ZTD08	STORAGE TANKS/VESSELS	N/A	63FFFF-7	40 CFR Part 63, Subpart FFFF	<p>HAL Device Type = No halogen scrubber or other halogen reduction device is used., Prior Test = The data from a prior performance test is not used., Test Waiver = The Administrator has not granted a waiver of the performance test or no waiver has been requested., Bypass</p>

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					<p>Line = No bypass lines., Designated HAL = The emission stream is not designated as halogenated., Determined HAL = The emission stream is determined not to be halogenated., Emission Standard = HAP vapor pressure is < 76.6 and a non-flare CD is being used to meet 95% reduction per § 63.2470(a)-Table 4.1.b.ii, SS Device Type = Boiler or process heater with a design heat input capacity equal to or greater than 44 megawatts (MW) or in which all vent streams are introduced with the primary fuel or are used as the primary fuel., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., CEMS = A continuous parameter monitoring system is used., Meets 63.998(b)(2) = The control device meets criteria in § 63.985(b)(2)., Formaldehyde = The stream does not contain formaldehyde.</p>
ZTD08	STORAGE TANKS/VESSELS	N/A	63FFFF-8	40 CFR Part 63, Subpart FFFF	<p>HAL Device Type = No halogen scrubber or other halogen reduction device is used., Prior Test = The data from a prior performance test is not used., Test Waiver = The</p>

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					<p>Administrator has not granted a waiver of the performance test or no waiver has been requested., Bypass Line = No bypass lines., Designated HAL = The emission stream is not designated as halogenated., Determined HAL = The emission stream is determined not to be halogenated., Emission Standard = HAP vapor pressure is < 76.6 and a non-flare CD is being used to meet 95% reduction per § 63.2470(a)-Table 4.1.b.ii, SS Device Type = Incinerator other than a catalytic incinerator., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., CEMS = A continuous parameter monitoring system is used., Meets 63.998(b)(2) = The control device does not meet criteria in § 63.985(b)(2)., Formaldehyde = The stream does not contain formaldehyde.</p>
ZTD12	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-1	30 TAC Chapter 115, Water Separation	No changing attributes.
ZTD12	VOLATILE ORGANIC COMPOUND WATER	N/A	61FF-10	40 CFR Part 61, Subpart FF	Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	SEPARATORS				<p>DEVICE, Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349, Alternate Monitoring Parameters = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART FF, Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC), By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE, Engineering Calculations = ENGINEERING CALCULATIONS ARE USED TO DEMONSTRATE CONTROL DEVICE PERFORMANCE, Control Device Type/Operation = THERMAL VAPOR INCINERATOR REDUCING ORGANICS BY 95 WEIGHT PERCENT OR GREATER</p>
ZTD12	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-11	40 CFR Part 61, Subpart FF	<p>Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE, Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349, Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT</p>

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC), By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE, Control Device Type/Operation = FLARE
ZTD12	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-11A	40 CFR Part 61, Subpart FF	Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE, Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349, Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC), By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE, Control Device Type/Operation = FLARE
ZTD12	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-12	40 CFR Part 61, Subpart FF	Fuel Gas System = GASEOUS EMISSIONS ARE ROUTED TO A FUEL GAS SYSTEM
ZTTK02	STORAGE TANKS/VESSELS	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
ZTTK03	STORAGE TANKS/VESSELS	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
ZTTK04	STORAGE TANKS/VESSELS	N/A	R5112-20	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
ZTTK04	STORAGE	N/A	60Kb-35	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS				
ZTTK04	STORAGE TANKS/VESSELS	N/A	61FF-1	40 CFR Part 61, Subpart FF	No changing attributes.
ZTTK04	STORAGE TANKS/VESSELS	N/A	63YY-1	40 CFR Part 63, Subpart YY	No changing attributes.
ZTTK05	STORAGE TANKS/VESSELS	N/A	R5112-20	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
ZTTK05	STORAGE TANKS/VESSELS	N/A	60Kb-35	40 CFR Part 60, Subpart Kb	No changing attributes.

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ADMINGEN	EU	60III-3	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
ADMINGEN	EU	60III-3	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than 560 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with an	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						NMHC+NO _x emission limit of 6.4 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).			
ADMINGEN	EU	60III-3	PM	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
ADMINGEN	EU	63ZZZ-10	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) § 63.6640(f)(2) § 63.6640(f)(2)(i) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this	None	None	§ 63.6645(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).			
C-VENTGAS	EP	R5121-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(A)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
C-VENTGAS	EP	R5121-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(B) § 60.18	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
C-VENTGAS	EP	R5121-16A	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.123(c) § 115.910	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 of this title if emission reductions are demonstrated to be substantially equivalent.	[G]§ 115.125 § 115.126(2) ** See Alternative Requirement	§ 115.126 § 115.126(2)	None
C-VENTGAS	EP	R5121-20	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(C)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(C).			
CCD81-LOAD	EU	R5212-11	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(b)(2) § 115.212(b)(2) § 115.214(b)(1)(B) § 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division except as specified.	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
C_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-4(a) § 60.482-4(b)(1) § 60.482-4(c) § 60.482-4(d)(1) § 60.482-4(d)(2) § 60.482-9(a) § 60.482-9(b) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
C_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-3(a) [G]§ 60.482-3(b) § 60.482-3(c) § 60.482-3(d) § 60.482-3(e)(1) § 60.482-3(e)(2) § 60.482-3(f)	Comply with the requirements as stated in §60.482-3 for compressors.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-3(g)(1) § 60.482-3(g)(2) § 60.482-3(h) [G]§ 60.482-3(i) § 60.482-3(j) § 60.482-9(a) § 60.482-9(b) § 60.486(k) § 60.562-2(d) § 60.562-2(e)				
C_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-2(a)(2) § 60.482-2(b)(1) [G]§ 60.482-2(b)(2) § 60.482-2(c)(1) [G]§ 60.482-2(c)(2) § 60.482-2(d) [G]§ 60.482-2(d)(1) § 60.482-2(d)(2) § 60.482-2(d)(3) [G]§ 60.482-2(d)(4) [G]§ 60.482-2(d)(5) [G]§ 60.482-2(d)(6) [G]§ 60.482-2(e) § 60.482-2(f) [G]§ 60.482-2(g) § 60.482-2(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	§ 60.482-1(f)(1) § 60.482-1(f)(2) [G]§ 60.482-1(f)(3) § 60.482-2(a)(1) [G]§ 60.482-2(b)(2) [G]§ 60.482-2(d)(4) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) § 60.486(f) [G]§ 60.486(h) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
C_FUG	EU	60DDD-	VOC/TOC	40 CFR Part 60,	§ 60.562-2(a)	Comply with the	§ 60.485(a)	§ 60.482-1(g)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		Subpart DDD	§ 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-5(a) [G]§ 60.482-5(b) § 60.482-5(c) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	requirements in as stated in §60.482-5 for sampling connection systems.	[G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
C_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-6(a)(1) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
C_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	§ 60.482-1(f)(1) § 60.482-1(f)(2) [G]§ 60.482-1(f)(3) § 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.486(k) § 60.562-2(d) § 60.562-2(e)				
C_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
C_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
C_FUG	EU	60DDD-	VOC/TOC	40 CFR Part 60,	§ 60.562-2(a)	Comply with the	§ 60.482-8(a)(1)	§ 60.482-1(g)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		Subpart DDD	§ 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
C_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(d) § 60.486(k) § 60.562-2(e)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(5) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
C_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid or heavy-liquid service.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
C_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) [G]§ 60.482-1(e) § 60.486(k)	Comply with the requirements in as stated in §60.482-1(e) for equipment in VOC service < 300 hours/year.	None	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(6) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
C_FUG	EU	63FFFF-ALL	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a)-Table 6 § 63.1019(d) § 63.1022(a) § 63.1022(b) § 63.1022(b)(1) § 63.1022(b)(3) § 63.1022(b)(4) § 63.1022(b)(5) § 63.1022(c)(1) [G]§ 63.1022(c)(2) § 63.1022(d)(1) § 63.1022(e) § 63.1023(a) § 63.1023(e)(1) § 63.1024(a) [G]§ 63.1024(c) [G]§ 63.1024(d) § 63.1024(e) § 63.1025(a)(1) § 63.1025(b)(2) [G]§ 63.1025(b)(4) § 63.1025(d)(1) [G]§ 63.1026(b) [G]§ 63.1026(c) § 63.1026(d) [G]§ 63.1026(e)(1) § 63.1026(e)(2) [G]§ 63.1027(b) § 63.1027(d) [G]§ 63.1028(c) § 63.1028(d) [G]§ 63.1028(e)(1) § 63.1028(e)(2)	For equipment in organic HAP service, comply with the requirements of 40 CFR Part 63, Subpart UU except as specified in 63.2480.	[G]§ 63.1022(c)(4) § 63.1023(a) [G]§ 63.1023(a)(1) § 63.1023(a)(2)(i) § 63.1023(a)(2)(iii) [G]§ 63.1023(b) [G]§ 63.1023(c) § 63.1023(d) § 63.1025(a)(2) § 63.1025(b) § 63.1025(b)(1) [G]§ 63.1025(b)(3) [G]§ 63.1025(b)(4) [G]§ 63.1025(c) [G]§ 63.1025(d)(2) [G]§ 63.1025(e) [G]§ 63.1026(b) [G]§ 63.1026(c) § 63.1026(d) [G]§ 63.1026(e)(1) § 63.1026(e)(4) § 63.1026(e)(5) § 63.1026(e)(6) [G]§ 63.1027(b) § 63.1027(c) [G]§ 63.1027(e) [G]§ 63.1028(c) [G]§ 63.1028(e)(1) § 63.1028(e)(4) § 63.1028(e)(5) § 63.1028(e)(7) [G]§ 63.1029 § 63.1031(c)	§ 63.1022(b)(5) § 63.1022(c)(3) [G]§ 63.1022(c)(4) § 63.1022(d)(2) [G]§ 63.1022(f) § 63.1023(e)(2) [G]§ 63.1024(d) [G]§ 63.1024(f) [G]§ 63.1025(b)(3) [G]§ 63.1025(b)(4) [G]§ 63.1026(b) [G]§ 63.1026(e)(1) [G]§ 63.1027(b) [G]§ 63.1028(e)(1) § 63.1031(d)(2) [G]§ 63.1035(d)(2) § 63.1035(d)(3) [G]§ 63.1035(e) § 63.1038(a) [G]§ 63.1038(b) [G]§ 63.1038(c)(1) [G]§ 63.1038(c)(2) § 63.1038(c)(3) [G]§ 63.1038(c)(4) [G]§ 63.1038(c)(6) [G]§ 63.1038(c)(7) [G]§ 63.2480(e)(3) [G]§ 63.2480(e)(6) [G]§ 63.2480(e)(7) § 63.2525(a) [G]§ 63.2525(q) § 63.2525(t)	[G]§ 63.1025(b)(4) § 63.1039(a) [G]§ 63.1039(a)(1) § 63.1039(b) [G]§ 63.1039(b)(1) § 63.1039(b)(2) § 63.1039(b)(3) § 63.1039(b)(4) § 63.1039(b)(5) § 63.1039(b)(6) § 63.1039(b)(8) § 63.2515(a) § 63.2515(b)(2) § 63.2515(c) § 63.2515(d) § 63.2520(a) [G]§ 63.2520(b) [G]§ 63.2520(d) § 63.2520(e) § 63.2520(e)(1) [G]§ 63.2520(e)(15) § 63.2520(e)(2) § 63.2520(e)(3) § 63.2520(e)(5) § 63.2520(e)(5)(i) [G]§ 63.2520(e)(5)(ii) § 63.2520(e)(9) [G]§ 63.2520(h) [G]§ 63.2520(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1028(e)(6) [G]§ 63.1029 [G]§ 63.1031(b) § 63.1031(c) § 63.1031(d)(1) [G]§ 63.1031(f) § 63.1032(b) [G]§ 63.1032(c) § 63.1032(d) [G]§ 63.1033 [G]§ 63.1035(a) § 63.1035(b) § 63.1035(c) § 63.1035(d) § 63.1035(d)(1) [G]§ 63.1035(d)(5) [G]§ 63.1035(d)(7) [G]§ 63.1035(d)(8) § 63.2450(a)(2) [G]§ 63.2480(b) § 63.2480(e) § 63.2480(e)(1) [G]§ 63.2480(e)(2) [G]§ 63.2480(e)(3) [G]§ 63.2480(e)(6) [G]§ 63.2480(e)(7) [G]§ 63.2480(f)(18)		[G]§ 63.1035(d)(2) § 63.1035(d)(4) [G]§ 63.1035(d)(6) [G]§ 63.2480(e)(2) [G]§ 63.2480(e)(3)		
DREFUSTN	EU	R5212-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(b)(2) § 115.212(b)(2) § 115.214(b)(1)(B) § 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division except as specified.	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
E-VENTGAS	EP	R5121-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(A)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
E-VENTGAS	EP	R5121-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(B) § 60.18	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
E-VENTGAS	EP	R5121-16A	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.123(c) § 115.910	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, alternate	[G]§ 115.125 § 115.126(2) ** See Alternative Requirement	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 of this title if emission reductions are demonstrated to be substantially equivalent.			
E-VENTGAS	EP	R5121-20	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(C)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
E_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g)	Comply with the requirements in as stated in §60.482-4 for pressure relief	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-4(a) § 60.482-4(b)(1) § 60.482-4(c) § 60.482-4(d)(1) § 60.482-4(d)(2) § 60.482-9(a) § 60.482-9(b) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	devices in gas/vapor service.	[G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.562-2(e)	§ 60.562-2(e) § 60.565(l)
E_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-3(a) [G]§ 60.482-3(b) § 60.482-3(c) § 60.482-3(d) § 60.482-3(e)(1) § 60.482-3(e)(2) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) § 60.482-3(h) [G]§ 60.482-3(i) § 60.482-3(j) § 60.482-9(a) § 60.482-9(b) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements as stated in §60.482-3 for compressors.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
E_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-2(a)(2) § 60.482-2(b)(1) [G]§ 60.482-2(b)(2)	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	§ 60.482-1(f)(1) § 60.482-1(f)(2) [G]§ 60.482-1(f)(3) § 60.482-2(a)(1) [G]§ 60.482-2(b)(2) [G]§ 60.482-2(d)(4) § 60.485(a)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-2(c)(1) [G]§ 60.482-2(c)(2) § 60.482-2(d) [G]§ 60.482-2(d)(1) § 60.482-2(d)(2) § 60.482-2(d)(3) [G]§ 60.482-2(d)(4) [G]§ 60.482-2(d)(5) [G]§ 60.482-2(d)(6) [G]§ 60.482-2(e) § 60.482-2(f) [G]§ 60.482-2(g) § 60.482-2(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)		[G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.562-2(d)	[G]§ 60.486(e)(4) § 60.486(f) [G]§ 60.486(h) § 60.486(j) § 60.562-2(e)	
E_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-5(a) [G]§ 60.482-5(b) § 60.482-5(c) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
E_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-6(a)(1) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c)	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-6(d) § 60.482-6(e) § 60.486(k) § 60.562-2(d) § 60.562-2(e)				
E_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	§ 60.482-1(f)(1) § 60.482-1(f)(2) [G]§ 60.482-1(f)(3) § 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
E_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.482-9(f) § 60.486(k)	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.562-2(d) § 60.562-2(e)				
E_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
E_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
E_FUG	EU	60DDD-	VOC/TOC	40 CFR Part 60,	§ 60.562-2(a)	Comply with the	None	[G]§ 60.486(a)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		Subpart DDD	§ 60.482-1(d) § 60.486(k) § 60.562-2(e)	requirements as stated in §60.482-1(d) for equipment in vacuum service.		§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5) § 60.486(j) § 60.562-2(e)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
E_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid or heavy-liquid service.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
E_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) [G]§ 60.482-1(e) § 60.486(k)	Comply with the requirements in as stated in §60.482-1(e) for equipment in VOC service < 300 hours/year.	None	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(6) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
E_FUG	EU	63FFFF-ALL	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a)-Table 6 § 63.1019(d) § 63.1022(a) § 63.1022(b) § 63.1022(b)(1) § 63.1022(b)(3) § 63.1022(b)(4) § 63.1022(b)(5) § 63.1022(c)(1) [G]§ 63.1022(c)(2) § 63.1022(d)(1)	For equipment in organic HAP service, comply with the requirements of 40 CFR Part 63, Subpart UU except as specified in 63.2480.	[G]§ 63.1022(c)(4) § 63.1023(a) [G]§ 63.1023(a)(1) § 63.1023(a)(2)(i) § 63.1023(a)(2)(iii) [G]§ 63.1023(b) [G]§ 63.1023(c) § 63.1023(d) § 63.1025(a)(2) § 63.1025(b) § 63.1025(b)(1)	§ 63.1022(b)(5) § 63.1022(c)(3) [G]§ 63.1022(c)(4) § 63.1022(d)(2) [G]§ 63.1022(f) § 63.1023(e)(2) [G]§ 63.1024(d) [G]§ 63.1024(f) [G]§ 63.1025(b)(3) [G]§ 63.1025(b)(4) [G]§ 63.1026(b)	[G]§ 63.1025(b)(4) § 63.1039(a) [G]§ 63.1039(a)(1) § 63.1039(b) [G]§ 63.1039(b)(1) § 63.1039(b)(2) § 63.1039(b)(3) § 63.1039(b)(4) § 63.1039(b)(5) § 63.1039(b)(6) § 63.1039(b)(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1022(e) § 63.1023(a) § 63.1023(e)(1) § 63.1024(a) [G]§ 63.1024(c) [G]§ 63.1024(d) § 63.1024(e) § 63.1025(a)(1) § 63.1025(b)(2) [G]§ 63.1025(b)(4) § 63.1025(d)(1) [G]§ 63.1026(b) [G]§ 63.1026(c) § 63.1026(d) [G]§ 63.1026(e)(1) § 63.1026(e)(2) [G]§ 63.1027(b) § 63.1027(d) [G]§ 63.1028(c) § 63.1028(d) [G]§ 63.1028(e)(1) § 63.1028(e)(2) § 63.1028(e)(6) [G]§ 63.1029 [G]§ 63.1031(b) § 63.1031(c) § 63.1031(d)(1) [G]§ 63.1031(f) § 63.1032(b) [G]§ 63.1032(c) § 63.1032(d) [G]§ 63.1033 [G]§ 63.1035(a) § 63.1035(b) § 63.1035(c) § 63.1035(d) § 63.1035(d)(1) [G]§ 63.1035(d)(5) [G]§ 63.1035(d)(7) [G]§ 63.1035(d)(8)		[G]§ 63.1025(b)(3) [G]§ 63.1025(b)(4) [G]§ 63.1025(c) [G]§ 63.1025(d)(2) [G]§ 63.1025(e) [G]§ 63.1026(b) [G]§ 63.1026(c) § 63.1026(d) [G]§ 63.1026(e)(1) § 63.1026(e)(4) § 63.1026(e)(5) § 63.1026(e)(6) [G]§ 63.1027(b) § 63.1027(c) [G]§ 63.1027(e) [G]§ 63.1028(c) [G]§ 63.1028(e)(1) § 63.1028(e)(4) § 63.1028(e)(5) § 63.1028(e)(7) [G]§ 63.1029 § 63.1031(c) [G]§ 63.1035(d)(2) § 63.1035(d)(4) [G]§ 63.1035(d)(6) [G]§ 63.2480(e)(2) [G]§ 63.2480(e)(3)	[G]§ 63.1026(e)(1) [G]§ 63.1027(b) [G]§ 63.1028(e)(1) § 63.1031(d)(2) [G]§ 63.1035(d)(2) § 63.1035(d)(3) [G]§ 63.1035(e) § 63.1038(a) [G]§ 63.1038(b) [G]§ 63.1038(c)(1) [G]§ 63.1038(c)(2) § 63.1038(c)(3) [G]§ 63.1038(c)(4) [G]§ 63.1038(c)(6) [G]§ 63.1038(c)(7) [G]§ 63.2480(e)(3) [G]§ 63.2480(e)(6) [G]§ 63.2480(e)(7) § 63.2525(a) [G]§ 63.2525(q) § 63.2525(t)	§ 63.2515(a) § 63.2515(b)(2) § 63.2515(c) § 63.2515(d) § 63.2520(a) [G]§ 63.2520(b) [G]§ 63.2520(d) § 63.2520(e) § 63.2520(e)(1) [G]§ 63.2520(e)(15) § 63.2520(e)(2) § 63.2520(e)(3) § 63.2520(e)(5) § 63.2520(e)(5)(i) [G]§ 63.2520(e)(5)(ii) § 63.2520(e)(9) [G]§ 63.2520(h) [G]§ 63.2520(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.2450(a)(2) [G]§ 63.2480(b) § 63.2480(e) § 63.2480(e)(1) [G]§ 63.2480(e)(2) [G]§ 63.2480(e)(3) [G]§ 63.2480(e)(6) [G]§ 63.2480(e)(7) [G]§ 63.2480(f)(18)				
G-VENTGAS	EP	R5121-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(A)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
G-VENTGAS	EP	R5121-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(B) § 60.18	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specified in §115.122(c)(1)(A)-(C).			
GAD03	EU	R5112-14	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(c)(1)	Tanks shall not store VOC, other than crude oil or condensate, unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(b).	** See Periodic Monitoring Summary	None	None
GBD05	EP	R5121-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(A)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GBD05	EP	R5121-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(B) § 60.18	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).			
GBD05	EP	63G-5A	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	[G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GBD05	EP	63G-5B	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(2) § 63.113(h) [G]§ 63.115(f)	Reduce emissions of total organic HAPs by 98 wt.% or to a concentration of 20 ppm by volume; whichever is less stringent or as	§ 63.114(a) § 63.114(a)(1)(i) § 63.114(e) [G]§ 63.115(f) [G]§ 63.116(c)	§ 63.114(a)(1) § 63.117(a)(4) § 63.117(a)(4)(i) § 63.117(a)(4)(ii) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) § 63.117(a)(4) § 63.117(a)(4)(i) § 63.117(a)(4)(ii) § 63.117(f) § 63.118(f)(1) § 63.118(f)(2) [G]§ 63.151(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specified. §63.113(a)(2)(i)-(ii)			§ 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GBX02	EP	R1111-1	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(C) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 15% averaged over a six minute period for any source with a total flow rate of at least 100,000 acfm unless a CEMS is installed.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
GED03	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(c)(1)(B) § 115.127(c)(1)	A vent gas stream having a combined weight of the VOC or classes of compounds specified in §115.121(c)(1)(B)-	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(C) of this title equal to or less than 100 lbs in a continuous 24-hour period is exempt from the requirements of §115.121(c)(1) of this title.			
GED03	EP	63G-2A	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 60.662(b) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) § 63.114(d)(1) [G]§ 63.115(f) [G]§ 63.116(a)	§ 63.114(d)(1) [G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) § 63.118(a)(3) [G]§ 63.152(a) [G]§ 63.152(f)	[G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(3) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(iii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GED03	EP	63G-2B	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(2) § 60.662(a) § 63.113(h) [G]§ 63.115(f)	Reduce emissions of total organic HAPs by 98 wt.% or to a concentration of 20 ppm by volume; whichever is less	§ 63.114(a) § 63.114(a)(1)(i) § 63.114(d)(1) § 63.114(e) [G]§ 63.115(f) [G]§ 63.116(c)	§ 63.114(a)(1) § 63.114(d)(1) § 63.117(a)(4) § 63.117(a)(4)(i) § 63.117(a)(4)(ii) § 63.117(f) § 63.118(a)(1) § 63.118(a)(2)	§ 63.114(e) § 63.117(a)(4) § 63.117(a)(4)(i) § 63.117(a)(4)(ii) § 63.117(f) § 63.118(f)(1) § 63.118(f)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						stringent or as specified. §63.113(a)(2)(i)-(ii)		§ 63.118(a)(3) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.118(f)(3) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GFFLARE01	CD	R1111-2	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
GFFLARE01	CD	60A-1	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GFFLARE01	CD	60A-2	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(iii) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4) § 60.18(f)(5)	None	None
GFFLARE01	CD	60A-3	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(ii) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
GFFLARE01	CD	63A-1	Opacity	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
GFFLARE01	CD	63A-2	Opacity	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(iii)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						this chapter shall be used.			
GFFLARE01	CD	63A-3	Opacity	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(ii)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
GLYUNLOAD	EU	R5212-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(b)(2) § 115.212(b)(2) § 115.214(b)(1)(B) § 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division except as specified.	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
GLYUNLOAD	EU	63EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2343(a) § 63.2334(a) § 63.2338(b)(2) § 63.2342(a)(2) § 63.2350(a) § 63.2350(d)	For each transfer rack that only unloads organic liquids, keep documentation that verifies the transfer rack is not required to be controlled.	None	§ 63.2343(a)	None
GRPBLRSTK	EP	R1111-1	Opacity	30 TAC Chapter 111, Visible	§ 111.111(a)(1)(C) § 111.111(a)(1)(E)	Visible emissions from any stationary	[G]§ 111.111(a)(1)(F) ** See Periodic	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Emissions		vent shall not exceed an opacity of 15% averaged over a six minute period for any source with a total flow rate of at least 100,000 acfm unless a CEMS is installed.	Monitoring Summary		
GRPBOILER	EU	60Db-1	NO _x	40 CFR Part 60, Subpart Db	§ 60.44b(l)(2) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities with a low heat release rate and combusting natural gas or distillate oil in excess of 30% of the heat input from the combustion of all fuels, a limit determined by use of the specified formula.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(3) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(h) § 60.49b(i) § 60.49b(v) § 60.49b(w)
GRPBOILER	EU	60Db-1	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
GRPBOILER	EU	60Db-1	PM (Opacity)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed,	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).			
GRPBOILER	EU	60Db-1	SO ₂	40 CFR Part 60, Subpart Db	§ 60.42b(k)(2)	Units firing only very low sulfur oil and/or a mixture of gaseous fuels with a potential SO ₂ emission rate of 140 ng/J (0.32 lb/MMBtu) heat input or less are exempt from the SO ₂ emissions limit in §60.42b(k)(1).	§ 60.47b(f) ** See Alternative Requirement	§ 60.45b(k) § 60.49b(o) § 60.49b(r) [G]§ 60.49b(r)(2)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(r) [G]§ 60.49b(r)(2)
GRPBOILER	EU	60Db-2	NO _x	40 CFR Part 60, Subpart Db	§ 60.44b(l)(1) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities combusting coal, oil, or natural gas, or a mixture of these fuels, or any other fuels: a limit of 86 ng/JI (0.20 lb/million Btu) heat input unless the affected facility meets the specified requirements.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(3) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(h) § 60.49b(i) § 60.49b(v) § 60.49b(w)
GRPBOILER	EU	60Db-2	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).			
GRPBOILER	EU	60Db-2	PM (Opacity)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
GRPBOILER	EU	60Db-2	SO ₂	40 CFR Part 60, Subpart Db	§ 60.42b(k)(2)	Units firing only very low sulfur oil and/or a mixture of gaseous fuels with a potential SO ₂ emission rate of 140 ng/J (0.32 lb/MMBtu) heat input or less are exempt from the SO ₂ emissions limit in §60.42b(k)(1).	§ 60.47b(f) ** See Alternative Requirement	§ 60.45b(k) § 60.49b(o) § 60.49b(r) [G]§ 60.49b(r)(2)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(r) [G]§ 60.49b(r)(2)
GRPBOILER	EU	63DDDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7500(a) § 63.7500(a)(1) § 63.7500(a)(3) § 63.7500(f) § 63.7505(a) § 63.7540(a)	For a new or existing boiler or process heater with a continuous oxygen trim system that maintains an optimum air to fuel ratio, conduct a	§ 63.7510(g) § 63.7515(d) [G]§ 63.7521(f) § 63.7540(a) [G]§ 63.7540(a)(10) § 63.7540(a)(12) § 63.7540(a)(13)	[G]§ 63.7540(a)(10)(vi) § 63.7555(a) § 63.7555(a)(1) § 63.7555(a)(2) [G]§ 63.7560	[G]§ 63.7540(a)(10)(vi) § 63.7540(b) § 63.7545(a) § 63.7545(c) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(8)(i) § 63.7550(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.7540(a)(10) § 63.7540(a)(12) § 63.7540(a)(13)	tune-up of the boiler or process heater every 5 years as specified in § 63.7540.			[G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
GRPBOILER	EU	63DDDDD-2	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.3 § 63.7500(a) § 63.7500(a)(1) § 63.7500(a)(3) § 63.7500(f) § 63.7505(a) § 63.7540(a) [G]§ 63.7540(a)(10) § 63.7540(a)(13)	For a new or existing boiler or process heater without a continuous oxygen trim system and with heat input capacity of 10 million Btu per hour or greater, conduct of tune-up of the boiler or process heater annually as specified in § 63.7540.	§ 63.7510(g) § 63.7515(d) [G]§ 63.7521(f) § 63.7540(a) [G]§ 63.7540(a)(10) § 63.7540(a)(13)	[G]§ 63.7540(a)(10)(vi) § 63.7555(a) § 63.7555(a)(1) § 63.7555(a)(2) [G]§ 63.7560	[G]§ 63.7540(a)(10)(vi) § 63.7540(b) § 63.7545(a) § 63.7545(c) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(8)(i) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
GRPCPEBP L	EP	R5121-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(A)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).			
GRPCPEBP L	EP	R5121-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(B) § 60.18	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPCPEBP L	EP	R5121-16A	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.123(c) § 115.910	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the	[G]§ 115.125 § 115.126(2) ** See Alternative Requirement	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						executive director in accordance with §115.910 of this title if emission reductions are demonstrated to be substantially equivalent.			
GRPCPEBP L	EP	R5121-20	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(C)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPCPEBP L	EP	63FFFF-14	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.11(b) § 63.2450(b) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(i)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(a)(3)(iii) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(b)(1) § 63.987(c) § 63.998(a)(1) [G]§ 63.998(a)(1)(i) § 63.998(a)(1)(ii)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2460(c)(3)(i) § 63.987(b)(1) § 63.997(c)(3) § 63.998(a)(1)(iii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii) § 63.999(c)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.983(d)(2) § 63.983(d)(3) § 63.987(a) § 63.987(b)(1) § 63.987(b)(3) [G]§ 63.997(c)(1) § 63.997(c)(3)		[G]§ 63.983(b)(3) [G]§ 63.983(b)(4) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) [G]§ 63.987(b)(3)(i) § 63.987(b)(3)(ii) § 63.987(b)(3)(iii) § 63.987(b)(3)(iv) § 63.987(c) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i) § 63.997(c)(3)(ii)	§ 63.998(a)(1)(iii)(A) § 63.998(a)(1)(iii)(B) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv) [G]§ 63.999(d)(1) [G]§ 63.999(d)(2)
GRPCPEBP L	EP	63FFFF-14A	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) [G]§ 63.2450(e)(5) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.2535(m)(2) [G]§ 63.670 § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) [G]§ 63.671 § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(b)(4) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) [G]§ 63.2525(m) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) [G]§ 63.998(d)(1) § 63.998(d)(5)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2460(c)(3)(i) § 63.2520(d)(3) [G]§ 63.2520(e)(11) § 63.987(b)(1) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.983(d)(1)(ii)		
GRPCPEBP L	EP	63FFFF-15	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2450(i)(1) § 63.2450(i)(2) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(b)(4) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d)	§ 63.2450(k)(6) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.2460(c)(3)(i) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) § 63.997(e)(2)(i)(B) § 63.997(e)(2)(ii) § 63.997(e)(2)(iii) § 63.997(e)(2)(iii)(A) [G]§ 63.997(e)(2)(iii)(B) [G]§ 63.997(e)(2)(iii)(C) [G]§ 63.997(e)(2)(iii)(D) [G]§ 63.997(e)(2)(iii)(E)		
GRPCPEBP L	EP	63FFFF-16	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.988(a)(3) § 63.988(b)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(b)(4) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3)	§ 63.2450(k)(6) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.996(c)(2)(ii) § 63.998(a)(2)(ii)(B)(5) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.2460(c)(3)(i) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.996(c)(5) § 63.996(c)(6) § 63.997(c)(3)		§ 63.983(d)(1) § 63.983(d)(1)(ii) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii)		
GRPCPEBP L	EP	63FFFF-17	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2460(a)-Table 2.1.a § 63.2460(b) § 63.2460(c)(7) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(b)(4) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i)	§ 63.2450(k)(6) § 63.2460(c)(3)(ii) § 63.2460(c)(6) [G]§ 63.2525(d) § 63.2525(g) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.2460(c)(3)(i) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) [G]§ 63.997(e)(2)(i)(A) § 63.997(e)(2)(ii) § 63.997(e)(2)(iv) § 63.997(e)(2)(iv)(A) [G]§ 63.997(e)(2)(iv)(B) § 63.997(e)(2)(iv)(C) § 63.997(e)(2)(iv)(D) § 63.997(e)(2)(iv)(F) § 63.997(e)(2)(iv)(G) [G]§ 63.997(e)(2)(iv)(H)		
GRPCPEBP V	EP	R5121-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(A)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPCPEBP V	EP	R5121-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(B) § 60.18	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPCPEBP V	EP	R5121-16A	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.123(c) § 115.910	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 of this title if emission reductions are demonstrated to be substantially	[G]§ 115.125 § 115.126(2) ** See Alternative Requirement	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						equivalent.			
GRPCPEBP V	EP	R5121-20	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(C)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPCPEBP V	EP	63FFFF-10	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.11(b) § 63.2450(b) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.987(a) § 63.987(b)(1) § 63.987(b)(3) [G]§ 63.997(c)(1) § 63.997(c)(3)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) [G]§ 63.987(b)(3)(i) § 63.987(b)(3)(ii) § 63.987(b)(3)(iii)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(b)(1) § 63.987(c) § 63.998(a)(1) [G]§ 63.998(a)(1)(i) § 63.998(a)(1)(ii) § 63.998(a)(1)(iii)(A) § 63.998(a)(1)(iii)(B) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) [G]§ 63.998(d)(1)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2460(c)(3)(i) § 63.987(b)(1) § 63.997(c)(3) § 63.998(a)(1)(iii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(3) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv) [G]§ 63.999(d)(1) [G]§ 63.999(d)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.987(b)(3)(iv) § 63.987(c) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i) § 63.997(c)(3)(ii)	§ 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	
GRPCPEBP V	EP	63FFFF-10A	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) [G]§ 63.2450(e)(5) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.2535(m)(2) [G]§ 63.670 § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) [G]§ 63.671 § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) [G]§ 63.2525(m) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(b)(1) [G]§ 63.998(d)(1) § 63.998(d)(5)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2460(c)(3)(i) § 63.2520(d)(3) [G]§ 63.2520(e)(11) § 63.987(b)(1) § 63.999(c)(1) § 63.999(c)(2)(i)
GRPCPEBP V	EP	63FFFF-11	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2450(i)(1) § 63.2450(i)(2) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi)	§ 63.2450(k)(6) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1)	§ 63.2450(q) § 63.2460(c)(3)(i) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)		§ 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) § 63.997(e)(2)(i)(B) § 63.997(e)(2)(ii) § 63.997(e)(2)(iii) § 63.997(e)(2)(iii)(A) [G]§ 63.997(e)(2)(iii)(B) [G]§ 63.997(e)(2)(iii)(C) [G]§ 63.997(e)(2)(iii)(D) [G]§ 63.997(e)(2)(iii)(E)	§ 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)
GRPCPEBP	EP	63FFFF-	112(B)	40 CFR Part 63,	§ 63.2460(a)	You must meet	[G]§ 63.115(d)(2)(v)	§ 63.2450(k)(6)	§ 63.2450(q)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
V		12	HAPS	Subpart FFFF	§ 63.2450(b) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) § 63.983(d)(2) [G]§ 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.988(a)(3) § 63.988(b)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) § 63.997(c)(3)	each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	§ 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii)	§ 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.996(c)(2)(ii) § 63.998(a)(2)(ii)(B)(5) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2460(c)(3)(i) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)
GRPCPEBP V	EP	63FFFF-13	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2460(a)-Table 2.1.a § 63.2460(b) § 63.2460(c)(7) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii)	§ 63.2450(k)(6) § 63.2460(c)(3)(ii) § 63.2460(c)(6) [G]§ 63.2525(d) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii) § 63.998(a)(2)(i)	§ 63.2450(q) § 63.2460(c)(3)(i) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	(c).	§ 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) [G]§ 63.997(e)(2)(i)(A) § 63.997(e)(2)(ii) § 63.997(e)(2)(iv) § 63.997(e)(2)(iv)(A) [G]§ 63.997(e)(2)(iv)(B) § 63.997(e)(2)(iv)(C) § 63.997(e)(2)(iv)(D) § 63.997(e)(2)(iv)(F) § 63.997(e)(2)(iv)(G)	§ 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	[G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 63.997(e)(2)(iv)(H)		
GRPCPECP V	EP	R5121-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(A)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPCPECP V	EP	R5121-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(B) § 60.18	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPCPECP V	EP	R5121-16A	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.123(c) § 115.910	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis	[G]§ 115.125 § 115.126(2) ** See Alternative Requirement	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Counties, alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 of this title if emission reductions are demonstrated to be substantially equivalent.			
GRPCPECP V	EP	R5121-20	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(C)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPCPECP V	EP	63FFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.ii § 63.11(b)	For each Group 1 continuous process vent, the owner or	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.983(b)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.987(b)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.2450(b) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.987(a) § 63.987(b)(1) § 63.987(b)(3) [G]§ 63.997(c)(1) § 63.997(c)(3)	operator must reduce emissions of total organic HAP by venting emissions through a closed vent system to a flare.	[G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) [G]§ 63.987(b)(3)(i) § 63.987(b)(3)(ii) § 63.987(b)(3)(iii) § 63.987(b)(3)(iv) § 63.987(c) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i) § 63.997(c)(3)(ii)	§ 63.983(b) [G]§ 63.983(d)(2) § 63.987(b)(1) § 63.987(c) § 63.998(a)(1) [G]§ 63.998(a)(1)(i) § 63.998(a)(1)(ii) § 63.998(a)(1)(iii)(A) § 63.998(a)(1)(iii)(B) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.997(c)(3) § 63.998(a)(1)(iii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(3) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv) [G]§ 63.999(d)(1) [G]§ 63.999(d)(2)
GRPCPECP V	EP	63FFFF-1A	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.ii § 63.2450(b) [G]§ 63.2450(e)(5) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.2535(m)(2) [G]§ 63.670 § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3)	For each Group 1 continuous process vent, the owner or operator must reduce emissions of total organic HAP by venting emissions through a closed vent system to a flare.	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) [G]§ 63.671 § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) [G]§ 63.2525(m) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(b)(1) § 63.998(d)(1) § 63.998(d)(5)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2520(d)(3) [G]§ 63.2520(e)(11) § 63.987(b)(1) § 63.997(c)(3) § 63.999(c)(2)(i)
GRPCPECP V	EP	63FFFF-2	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.i § 63.2450(b)	For each Group 1 continuous process vent, the owner or	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g)	§ 63.2450(k)(6) § 63.2525(g) § 63.983(b)	§ 63.2450(q) § 63.988(b)(1) § 63.996(b)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	operator must reduce emissions of total organic HAP by greater than or equal to 98 percent by weight by venting emissions through a closed-vent system to any combination of control devices (except flare).	§ 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) [G]§ 63.997(e)(2)(i)(A) § 63.997(e)(2)(ii) § 63.997(e)(2)(iv) § 63.997(e)(2)(iv)(A) [G]§ 63.997(e)(2)(iv)(B) § 63.997(e)(2)(iv)(C) § 63.997(e)(2)(iv)(D) § 63.997(e)(2)(iv)(F) § 63.997(e)(2)(iv)(G)	[G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 63.997(e)(2)(iv)(H)		
GRPCPECP V	EP	63FFFF-3	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.i § 63.2450(b) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.988(a)(3) § 63.988(b)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) § 63.997(c)(3)	For each Group 1 continuous process vent, the owner or operator must reduce emissions of total organic HAP by greater than or equal to 98 percent by weight by venting emissions through a closed-vent system to any combination of control devices (except flare).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii)	§ 63.2450(k)(6) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.996(c)(2)(ii) § 63.998(a)(2)(ii)(B)(5) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) [G]§ 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)
GRPCPECP V	EP	63FFFF-4	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.i § 63.2450(b) § 63.2450(i)(1) § 63.2450(i)(2) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1)	For each Group 1 continuous process vent, the owner or operator must reduce emissions to an outlet process concentration less than or equal to 20 ppmv as organic HAP or TOC by venting emissions	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2)	§ 63.2450(k)(6) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1)	§ 63.2450(q) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	through a closed-vent system to any combination of control devices (except flare).	[G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) § 63.997(e)(2)(i)(B) § 63.997(e)(2)(ii) § 63.997(e)(2)(iii) § 63.997(e)(2)(iii)(A) [G]§ 63.997(e)(2)(iii)(B) [G]§ 63.997(e)(2)(iii)(C) [G]§ 63.997(e)(2)(iii)(D) [G]§ 63.997(e)(2)(iii)(E)	[G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)
GRPEMPEB PL	EP	R5121-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(A)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).			
GRPEMPEB PL	EP	R5121-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(B) § 60.18	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPEMPEB PL	EP	R5121-16A	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.123(c) § 115.910	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria	[G]§ 115.125 § 115.126(2) ** See Alternative Requirement	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						in this division may be approved by the executive director in accordance with §115.910 of this title if emission reductions are demonstrated to be substantially equivalent.			
GRPEMPEB PL	EP	R5121-20	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(C)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPEMPEB PL	EP	63FFFF-14	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.11(b) § 63.2450(b) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(b)(1) § 63.987(c) § 63.998(a)(1)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2460(c)(3)(i) § 63.987(b)(1) § 63.997(c)(3) § 63.998(a)(1)(iii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.987(a) § 63.987(b)(1) § 63.987(b)(3) [G]§ 63.997(c)(1) § 63.997(c)(3)		[G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(b)(4) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) [G]§ 63.987(b)(3)(i) § 63.987(b)(3)(ii) § 63.987(b)(3)(iii) § 63.987(b)(3)(iv) § 63.987(c) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i) § 63.997(c)(3)(ii)	[G]§ 63.998(a)(1)(i) § 63.998(a)(1)(ii) § 63.998(a)(1)(iii)(A) § 63.998(a)(1)(iii)(B) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.999(c)(2)(iii) § 63.999(c)(3) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv) [G]§ 63.999(d)(1) [G]§ 63.999(d)(2)
GRPEMPEB PL	EP	63FFFF-14A	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) [G]§ 63.2450(e)(5) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.2535(m)(2) [G]§ 63.670 § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) [G]§ 63.671 § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(b)(4) [G]§ 63.983(c)(1) § 63.983(c)(2)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) [G]§ 63.2525(m) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) [G]§ 63.998(d)(1) § 63.998(d)(5)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2460(c)(3)(i) § 63.2520(d)(3) [G]§ 63.2520(e)(11) § 63.987(b)(1) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii)		
GRPEMPEB PL	EP	63FFFF-15	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2450(i)(1) § 63.2450(i)(2) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(b)(4) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3)	§ 63.2450(k)(6) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.2460(c)(3)(i) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) § 63.997(e)(2)(i)(B) § 63.997(e)(2)(ii) § 63.997(e)(2)(iii) § 63.997(e)(2)(iii)(A) [G]§ 63.997(e)(2)(iii)(B) [G]§ 63.997(e)(2)(iii)(C) [G]§ 63.997(e)(2)(iii)(D) [G]§ 63.997(e)(2)(iii)(E)		
GRPEMPEB PL	EP	63FFFF-16	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.988(a)(3) § 63.988(b)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(b)(4) [G]§ 63.983(c)(1)	§ 63.2450(k)(6) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.996(c)(2)(ii) § 63.998(a)(2)(ii)(B)(5) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.2460(c)(3)(i) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) § 63.997(c)(3)		§ 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii)		
GRPEMPEB PL	EP	63FFFF-17	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2460(a)-Table 2.1.a § 63.2460(b) § 63.2460(c)(7) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(b)(4) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1)	§ 63.2450(k)(6) § 63.2460(c)(3)(ii) § 63.2460(c)(6) [G]§ 63.2525(d) § 63.2525(g) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.2460(c)(3)(i) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) [G]§ 63.997(e)(2)(i)(A) § 63.997(e)(2)(ii) § 63.997(e)(2)(iv) § 63.997(e)(2)(iv)(A) [G]§ 63.997(e)(2)(iv)(B) § 63.997(e)(2)(iv)(C) § 63.997(e)(2)(iv)(D) § 63.997(e)(2)(iv)(F) § 63.997(e)(2)(iv)(G) [G]§ 63.997(e)(2)(iv)(H)		
GRPEMPEB PV	EP	R5121-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(A)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.122(c)(1)(A)-(C).			
GRPEMPEB PV	EP	R5121-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(B) § 60.18	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPEMPEB PV	EP	R5121-16A	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.123(c) § 115.910	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 of this title if emission	[G]§ 115.125 § 115.126(2) ** See Alternative Requirement	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						reductions are demonstrated to be substantially equivalent.			
GRPEMPEB PV	EP	R5121-20	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(C)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPEMPEB PV	EP	63FFFF-10	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.11(b) § 63.2450(b) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.987(a) § 63.987(b)(1) § 63.987(b)(3) [G]§ 63.997(c)(1)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(b)(1) § 63.987(c) § 63.998(a)(1) [G]§ 63.998(a)(1)(i) § 63.998(a)(1)(ii) § 63.998(a)(1)(iii)(A) § 63.998(a)(1)(iii)(B) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2460(c)(3)(i) § 63.987(b)(1) § 63.997(c)(3) § 63.998(a)(1)(iii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(3) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv) [G]§ 63.999(d)(1) [G]§ 63.999(d)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.997(c)(3)		[G]§ 63.987(b)(3)(i) § 63.987(b)(3)(ii) § 63.987(b)(3)(iii) § 63.987(b)(3)(iv) § 63.987(c) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i) § 63.997(c)(3)(ii)	[G]§ 63.998(b)(5) [G]§ 63.998(c)(1) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	
GRPEMPEB PV	EP	63FFFF- 10A	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) [G]§ 63.2450(e)(5) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.2535(m)(2) [G]§ 63.670 § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) [G]§ 63.671 § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) [G]§ 63.2525(m) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(b)(1) [G]§ 63.998(d)(1) § 63.998(d)(5)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2460(c)(3)(i) § 63.2520(d)(3) [G]§ 63.2520(e)(11) § 63.987(b)(1) § 63.999(c)(1) § 63.999(c)(2)(i)
GRPEMPEB PV	EP	63FFFF- 11	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2450(i)(1) § 63.2450(i)(2) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6)	§ 63.2450(k)(6) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii)	§ 63.2450(q) § 63.2460(c)(3)(i) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	specified in §63.2460(b) and (c).	§ 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) § 63.997(e)(2)(i)(B) § 63.997(e)(2)(ii) § 63.997(e)(2)(iii) § 63.997(e)(2)(iii)(A) [G]§ 63.997(e)(2)(iii)(B) [G]§ 63.997(e)(2)(iii)(C) [G]§ 63.997(e)(2)(iii)(D)	§ 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	[G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 63.997(e)(2)(iii)(E)		
GRPEMPEB PV	EP	63FFFF-12	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.988(a)(3) § 63.988(b)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) § 63.997(c)(3)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii)	§ 63.2450(k)(6) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.996(c)(2)(ii) § 63.998(a)(2)(ii)(B)(5) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.2460(c)(3)(i) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)
GRPEMPEB PV	EP	63FFFF-13	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2460(a)-Table 2.1.a § 63.2460(b) § 63.2460(c)(7) § 63.982(c)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4)	§ 63.2450(k)(6) § 63.2460(c)(3)(ii) § 63.2460(c)(6) [G]§ 63.2525(d) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2)	§ 63.2450(q) § 63.2460(c)(3)(i) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	requirement specified in §63.2460(b) and (c).	§ 63.2450(k)(6) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) [G]§ 63.997(e)(2)(i)(A) § 63.997(e)(2)(ii) § 63.997(e)(2)(iv) § 63.997(e)(2)(iv)(A) [G]§ 63.997(e)(2)(iv)(B) § 63.997(e)(2)(iv)(C)	§ 63.988(b)(1) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	[G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.997(e)(2)(iv)(D) § 63.997(e)(2)(iv)(F) § 63.997(e)(2)(iv)(G) [G]§ 63.997(e)(2)(iv)(H)		
GRPEMPEC PV	EP	R5121-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(A)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPEMPEC PV	EP	R5121-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(B) § 60.18	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPEMPEC PV	EP	R5121-16A	VOC	30 TAC Chapter 115, Vent Gas	§ 115.123(c) § 115.910	For all persons in Aransas, Bexar,	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Controls		Calhoun, Matagorda, San Patricio, and Travis Counties, alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 of this title if emission reductions are demonstrated to be substantially equivalent.	** See Alternative Requirement		
GRPEMPEC PV	EP	R5121-20	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(C)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPEMPEC PV	EP	63FFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.ii § 63.11(b) § 63.2450(b) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.987(a) § 63.987(b)(1) § 63.987(b)(3) [G]§ 63.997(c)(1) § 63.997(c)(3)	For each Group 1 continuous process vent, the owner or operator must reduce emissions of total organic HAP by venting emissions through a closed vent system to a flare.	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) [G]§ 63.987(b)(3)(i) § 63.987(b)(3)(ii) § 63.987(b)(3)(iii) § 63.987(b)(3)(iv) § 63.987(c) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i) § 63.997(c)(3)(ii)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(b)(1) § 63.987(c) § 63.998(a)(1) [G]§ 63.998(a)(1)(i) § 63.998(a)(1)(ii) § 63.998(a)(1)(iii)(A) § 63.998(a)(1)(iii)(B) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.987(b)(1) § 63.997(c)(3) § 63.998(a)(1)(iii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(3) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv) [G]§ 63.999(d)(1) [G]§ 63.999(d)(2)
GRPEMPEC PV	EP	63FFFF-1A	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.ii § 63.2450(b) [G]§ 63.2450(e)(5) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.2535(m)(2) [G]§ 63.670 § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3)	For each Group 1 continuous process vent, the owner or operator must reduce emissions of total organic HAP by venting emissions through a closed vent system to a flare.	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) [G]§ 63.671 § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) [G]§ 63.2525(m) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(b)(1) [G]§ 63.998(d)(1) § 63.998(d)(5)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2520(d)(3) [G]§ 63.2520(e)(11) § 63.987(b)(1) § 63.997(c)(3) § 63.999(c)(2)(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPEMPEC PV	EP	63FFFF-2	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.i § 63.2450(b) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	For each Group 1 continuous process vent, the owner or operator must reduce emissions of total organic HAP by greater than or equal to 98 percent by weight by venting emissions through a closed-vent system to any combination of control devices (except flare).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) [G]§ 63.997(e)(2)(i)(A) § 63.997(e)(2)(ii) § 63.997(e)(2)(iv) § 63.997(e)(2)(iv)(A) [G]§ 63.997(e)(2)(iv)(B) § 63.997(e)(2)(iv)(C)	§ 63.2450(k)(6) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.997(e)(2)(iv)(D) § 63.997(e)(2)(iv)(F) § 63.997(e)(2)(iv)(G) [G]§ 63.997(e)(2)(iv)(H)		
GRPEMPEC PV	EP	63FFFF-3	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.i § 63.2450(b) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.988(a)(3) § 63.988(b)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) § 63.997(c)(3)	For each Group 1 continuous process vent, the owner or operator must reduce emissions of total organic HAP by greater than or equal to 98 percent by weight by venting emissions through a closed-vent system to any combination of control devices (except flare).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii)	§ 63.2450(k)(6) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.996(c)(2)(ii) § 63.998(a)(2)(ii)(B)(5) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)
GRPEMPEC PV	EP	63FFFF-4	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.i § 63.2450(b) § 63.2450(i)(1) § 63.2450(i)(2) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1)	For each Group 1 continuous process vent, the owner or operator must reduce emissions to an outlet process concentration less than or equal to 20	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6)	§ 63.2450(k)(6) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(A)	§ 63.2450(q) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	ppmv as organic HAP or TOC by venting emissions through a closed-vent system to any combination of control devices (except flare).	§ 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) § 63.997(e)(2)(i)(B) § 63.997(e)(2)(ii) § 63.997(e)(2)(iii) § 63.997(e)(2)(iii)(A) [G]§ 63.997(e)(2)(iii)(B) [G]§ 63.997(e)(2)(iii)(C) [G]§ 63.997(e)(2)(iii)(D) [G]§ 63.997(e)(2)(iii)(E)	§ 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	[G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)
GRPEMRG GEN	EU	60III-3	CO	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a)	Owners and operators of emergency stationary CI ICE, that are not fire	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).			
GRPEMRG GEN	EU	60III-3	NMHC and NO _x	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than 560 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with an NMHC+NO _x emission limit of 6.4 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						40 CFR 89.112(a).			
GRPEMRG GEN	EU	60IIII-3	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
GRPEMRG GEN	EU	63ZZZZ-10	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) § 63.6640(f)(2) § 63.6640(f)(2)(i) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of	None	None	§ 63.6645(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§63.6645(f).			
GRPEQTANK	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(c)(1)(B) § 115.127(c)(1)	A vent gas stream having a combined weight of the VOC or classes of compounds specified in §115.121(c)(1)(B)-(C) of this title equal to or less than 100 lbs in a continuous 24-hour period is exempt from the requirements of §115.121(c)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRPEXTRUD	EP	R5121-4	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(c)(1)(C) § 115.127(c)(1)	A vent gas stream having a concentration of the VOC specified in §115.121(c)(1)(B) and (C) of this title less than 30,000 ppmv is exempt from the requirements of §115.121(c)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRPFURNSTK	EP	R1111-1	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(C) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 15% averaged over a six minute period for any source with a total flow rate of at least	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						100,000 acfm unless a CEMS is installed.			
GRPFWP	EU	60IIII-1	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
GRPFWP	EU	60IIII-1	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.			
GRPFWP	EU	63ZZZZ-10	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) § 63.6640(f)(2) § 63.6640(f)(2)(i) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).	None	None	§ 63.6645(f)
GRPGLYLO AD	EU	R5212-4	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(b)(2) § 115.214(b)(1)(B) § 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division except as specified.	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
GRPGLYLO AD	EU	63G-10	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.126(c)	For each Group 2 transfer rack, maintain records as	None	§ 63.130(f) § 63.130(f)(1) § 63.130(f)(2)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						required in § 63.130(f). No other provisions for transfer racks apply to the Group 2 transfer rack.		§ 63.130(f)(3) § 63.130(f)(3)(i) § 63.130(f)(3)(ii)	
GRPGLYTANK	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
GRPGRANULE	EP	R5121-4	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(c)(1)(C) § 115.127(c)(1)	A vent gas stream having a concentration of the VOC specified in §115.121(c)(1)(B) and (C) of this title less than 30,000 ppmv is exempt from the requirements of §115.121(c)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRPHOTANK	EU	R5112-21	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(c)(1)	Tanks shall not store VOC, other than crude oil or condensate, unless the required pressure is maintained, or they are equipped with the appropriate	** See Periodic Monitoring Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						control device specified in Table I(b).			
GRPHFOTANK	EU	R5112-21A	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.113 § 115.910	Alternate means of compliance with the applicable control requirements or exemption criteria in this division may be approved per 30 TAC §115.910, if emission reductions are substantially equal.	** See Alternative Requirement	None	None
GRPHFOTANK	EU	R5112-22	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(c)(1)	Tanks shall not store VOC, other than crude oil or condensate, unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(b).	** See Periodic Monitoring Summary	None	None
GRPHFOTANK	EU	R5112-25	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(c)(1)	Tanks shall not store VOC, other than crude oil or condensate, unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(b).	** See Periodic Monitoring Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPHFOTA NK	EU	63YY-BLR	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103(e) - Table 7.b.1.ii § 63.1103(e)(1)(i)(A) § 63.1103(e)(3) § 63.1108(a)(1) § 63.1108(a)(2) § 63.1108(a)(5) § 63.1108(a)(6) § 63.1108(a)(7) [G]§ 63.1108(b)(1) [G]§ 63.1108(b)(2) § 63.1108(b)(3) [G]§ 63.1108(b)(4) § 63.1108(b)(5) § 63.1108(c) [G]§ 63.1108(d) [G]§ 63.1111(a) § 63.982(a)(1) § 63.982(c) § 63.982(c)(1) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.984(a)(1)	For a storage vessel with specified capacity and vapor pressure, reduce emissions of total organic HAP by 98 weight-percent by venting emissions through a closed vent system to any combination of control devices and meet the requirements of §63.982(a)(1).	§ 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.985(a) § 63.985(b)(2)(i) § 63.997(c)(3)	§ 63.1103(e)(10)(iii) § 63.1109(a) § 63.1109(b) § 63.1109(c) § 63.1109(d) § 63.983(b) [G]§ 63.983(d)(2) § 63.985(c)(2) § 63.998(a)(2)(ii)(B)(5) [G]§ 63.998(d)(1) [G]§ 63.998(d)(2) [G]§ 63.998(d)(3) § 63.998(d)(5)	[G]§ 63.1100(g) § 63.1110(a) § 63.1110(a)(1) § 63.1110(a)(2) § 63.1110(a)(4) § 63.1110(a)(5) § 63.1110(a)(6) § 63.1110(a)(7) § 63.1110(a)(8) § 63.1110(b)(1) § 63.1110(b)(2) [G]§ 63.1110(c) [G]§ 63.1110(d) [G]§ 63.1110(e) [G]§ 63.1110(f) [G]§ 63.1110(g) [G]§ 63.1110(h) [G]§ 63.1111(b) § 63.985(c)(1) § 63.997(c)(3) [G]§ 63.999(b)(2) § 63.999(c)(1) § 63.999(c)(2)(i) [G]§ 63.999(c)(4) [G]§ 63.999(c)(5)
GRPHFOTA NK	EU	63YY-FL	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103(e) - Table 7.b.1.ii § 63.1103(b) § 63.1103(e)(1)(i)(A) § 63.1103(e)(3) § 63.1108(a)(1) § 63.1108(a)(2) § 63.1108(a)(5) § 63.1108(a)(6) § 63.1108(a)(7) [G]§ 63.1108(b)(1) [G]§ 63.1108(b)(2)	For a storage vessel with specified capacity and vapor pressure, reduce emissions of total organic HAP by 98 weight-percent by venting emissions through a closed vent system to any combination of	[G]§ 63.1108(b)(1) § 63.1108(b)(4) [G]§ 63.1108(b)(4)(i) § 63.1108(b)(4)(ii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1)	§ 63.1103(e)(10)(iii) § 63.1109(a) § 63.1109(b) § 63.1109(c) § 63.1109(d) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(b)(1) § 63.987(c) § 63.998(a)(1) [G]§ 63.998(a)(1)(i) § 63.998(a)(1)(ii)	§ 63.1100(g) § 63.1110(a) § 63.1110(a)(1) [G]§ 63.1110(a)(10) § 63.1110(a)(2) § 63.1110(a)(4) § 63.1110(a)(5) § 63.1110(a)(6) § 63.1110(a)(7) § 63.1110(a)(8) § 63.1110(b)(1) § 63.1110(b)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1108(b)(3) [G]§ 63.1108(b)(4) § 63.1108(b)(5) § 63.1108(c) [G]§ 63.1108(d) [G]§ 63.1111(a) § 63.982(a)(1) § 63.982(b) § 63.983(a) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.987(a) § 63.987(b)(1) § 63.987(b)(3) [G]§ 63.997(c)(1) § 63.997(c)(3)	control devices and meet the requirements of §63.982(a)(1).	§ 63.983(d)(1)(ii) § 63.987(b)(3)(i) § 63.987(b)(3)(ii) § 63.987(b)(3)(iii) § 63.987(b)(3)(iv) § 63.987(c) § 63.997(a) § 63.997(c)(1) § 63.997(c)(1)(ii) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i) § 63.997(c)(3)(ii)	§ 63.998(a)(1)(iii)(A) § 63.998(a)(1)(iii)(B) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(d)(1) [G]§ 63.998(d)(2) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	[G]§ 63.1110(c) [G]§ 63.1110(d) [G]§ 63.1110(e) [G]§ 63.1110(f) [G]§ 63.1110(g) [G]§ 63.1110(h) [G]§ 63.1111(b) § 63.987(b)(1) § 63.997(c)(3) § 63.998(a)(1)(iii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(3) [G]§ 63.999(c)(4)
GRPHFOTA NK	EU	63YY-FLA	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103(e) - Table 7.b.1.iii.B § 63.1103(e)(1)(i)(A) § 63.1103(e)(3) § 63.1103(e)(4) § 63.1103(e)(4)(ii) § 63.1103(e)(4)(iii) § 63.1103(e)(4)(iv) § 63.1103(e)(4)(ix) § 63.1103(e)(4)(vii) § 63.1103(e)(4)(vii)(A) § 63.1103(e)(4)(vii)(B) § 63.1103(e)(4)(vii)(C) § 63.1103(e)(4)(vii)(D) § 63.1103(e)(4)(vii)(E) § 63.1103(e)(4)(vii)(F) § 63.1103(e)(4)(xiii) § 63.1108(a)(4)(i) § 63.1108(a)(4)(ii)	For a storage vessel with specified capacity and vapor pressure, reduce emissions of total organic HAP by 98 weight-percent by venting emissions through a closed vent system to a flare and meet the requirements of §63.983, §63.1103(e)(4), and §63.1103(e)(9).	§ 63.1103(e)(4)(ix) § 63.1103(e)(4)(vii) [G]§ 63.1108(b)(1) § 63.1108(b)(4) [G]§ 63.1108(b)(4)(i) [G]§ 63.1108(b)(4)(ii) [G]§ 63.1109(e) [G]§ 63.671 § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii)	§ 63.1109(a) § 63.1109(b) § 63.1109(c) § 63.1109(d) § 63.1109(d)(1) [G]§ 63.1109(e) § 63.983(b) [G]§ 63.983(d)(2) [G]§ 63.998(d)(1)(i) [G]§ 63.998(d)(1)(iii) § 63.998(d)(1)(iv) [G]§ 63.998(d)(1) [G]§ 63.998(d)(2)	[G]§ 63.1100(g) § 63.1103(e)(4)(iii) § 63.1110(a) § 63.1110(a)(1) [G]§ 63.1110(a)(10) § 63.1110(a)(2) § 63.1110(a)(4) § 63.1110(a)(5) § 63.1110(a)(6) § 63.1110(a)(8) § 63.1110(b)(1) § 63.1110(b)(2) [G]§ 63.1110(c) [G]§ 63.1110(d) § 63.1110(e) § 63.1110(e)(1) § 63.1110(e)(2) [G]§ 63.1110(e)(4)(iii) [G]§ 63.1110(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1108(a)(6) § 63.1108(a)(7) [G]§ 63.1108(b)(1) [G]§ 63.1108(b)(2) § 63.1108(b)(3) [G]§ 63.1108(b)(4) § 63.1108(b)(5) § 63.1108(c) [G]§ 63.1108(d) [G]§ 63.670 § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3)			[G]§ 63.1110(g) [G]§ 63.1110(h) [G]§ 63.1111(c) § 63.999(c)(1) § 63.999(c)(2) § 63.999(c)(2)(i) [G]§ 63.999(c)(4)	
GRPHFOTANK	EU	63YY-INC	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103(e) - Table 7.b.1.ii § 63.1103(e)(1)(i)(A) § 63.1103(e)(3) § 63.1108(a)(1) § 63.1108(a)(2) § 63.1108(a)(5) § 63.1108(a)(6) § 63.1108(a)(7) [G]§ 63.1108(b)(1) [G]§ 63.1108(b)(2) § 63.1108(b)(3) [G]§ 63.1108(b)(4) § 63.1108(b)(5) § 63.1108(c) [G]§ 63.1108(d) [G]§ 63.1111(a) § 63.982(a)(1) § 63.982(c) § 63.982(c)(1) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1)	For a storage vessel with specified capacity and vapor pressure, reduce emissions of total organic HAP by 98 weight-percent by venting emissions through a closed vent system to any combination of control devices and meet the requirements of §63.982(a)(1).	[G]§ 63.1108(b)(1) § 63.1108(b)(4)(i) § 63.1108(b)(4)(ii) [G]§ 63.1108(b)(4) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.985(a) § 63.985(b) § 63.985(b)(1) § 63.985(b)(1)(ii) § 63.985(c)(2) § 63.997(a) § 63.997(c)(1) § 63.997(c)(1)(ii) § 63.997(c)(2) § 63.997(c)(3)	§ 63.1103(e)(10)(iii) § 63.1109(a) § 63.1109(b) § 63.1109(c) § 63.1109(d) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(d)(2) § 63.985(c)(2) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) [G]§ 63.998(c)(2) [G]§ 63.998(d)(1) [G]§ 63.998(d)(2) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	[G]§ 63.1100(g) § 63.1110(a) § 63.1110(a)(1) [G]§ 63.1110(a)(10) § 63.1110(a)(2) § 63.1110(a)(4) § 63.1110(a)(5) § 63.1110(a)(6) § 63.1110(a)(7) § 63.1110(a)(8) § 63.1110(a)(9) § 63.1110(b)(1) § 63.1110(b)(2) [G]§ 63.1110(c) [G]§ 63.1110(d) [G]§ 63.1110(e) [G]§ 63.1110(f) [G]§ 63.1110(h) [G]§ 63.1111(b) § 63.985(b)(1) § 63.985(b)(1)(ii) § 63.985(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.985(a) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)		§ 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) [G]§ 63.997(e)(2)(i)(A) § 63.997(e)(2)(iv) § 63.997(e)(2)(iv)(A) [G]§ 63.997(e)(2)(iv)(B) § 63.997(e)(2)(iv)(C) § 63.997(e)(2)(iv)(D) § 63.997(e)(2)(iv)(F) § 63.997(e)(2)(iv)(G) [G]§ 63.997(e)(2)(iv)(H)		§ 63.997(c)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(2) § 63.999(c)(1) § 63.999(c)(2)(i) [G]§ 63.999(c)(4) [G]§ 63.999(c)(5)
GRPHFOTA NK	EU	63YY- INC1	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103(e) - Table 7.b.ii § 63.1103(e)(1)(i)(A) § 63.1103(e)(3) § 63.1108(a)(1) § 63.1108(a)(2) § 63.1108(a)(5) § 63.1108(a)(6) § 63.1108(a)(7) [G]§ 63.1108(b)(1) [G]§ 63.1108(b)(2) § 63.1108(b)(3) [G]§ 63.1108(b)(4) § 63.1108(b)(5) [G]§ 63.1108(d) [G]§ 63.1111(a) § 63.982(a)(1) § 63.982(c) § 63.982(c)(1) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i)	For a storage vessel with specified capacity and vapor pressure, reduce emissions of total organic HAP by 98 weight-percent by venting emissions through a closed vent system to any combination of control devices and meet the requirements of §63.982(a)(1).	[G]§ 63.1108(b)(1) [G]§ 63.1108(b)(4) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.985(b) § 63.985(b)(1) § 63.985(b)(1)(ii) § 63.997(a) § 63.997(c)(1) § 63.997(c)(1)(ii) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv)	§ 63.1103(e)(10)(iii) § 63.1109(a) § 63.1109(b) § 63.1109(c) § 63.1109(d) [G]§ 63.1110(a)(9) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(d)(2) § 63.985(c)(2) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(c)(2) [G]§ 63.998(d)(1) [G]§ 63.998(d)(2) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	[G]§ 63.1100(g) § 63.1110(a) § 63.1110(a)(1) [G]§ 63.1110(a)(10) § 63.1110(a)(2) § 63.1110(a)(4) § 63.1110(a)(5) § 63.1110(a)(6) § 63.1110(a)(7) § 63.1110(a)(8) [G]§ 63.1110(a)(9) § 63.1110(b)(1) § 63.1110(b)(2) [G]§ 63.1110(c) [G]§ 63.1110(d) [G]§ 63.1110(e) [G]§ 63.1110(f) [G]§ 63.1110(g) [G]§ 63.1110(h) § 63.1111(b) § 63.985(b)(1) [G]§ 63.985(b)(1)(ii) § 63.985(c)(1) § 63.997(c)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.983(d)(2) § 63.983(d)(3) § 63.985(a) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)		[G]§ 63.997(e)(1)(v) § 63.997(e)(2)(i)(B) § 63.997(e)(2)(iii) § 63.997(e)(2)(iii)(A) [G]§ 63.997(e)(2)(iii)(B) [G]§ 63.997(e)(2)(iii)(C) [G]§ 63.997(e)(2)(iii)(D) [G]§ 63.997(e)(2)(iii)(E)		[G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(2) § 63.999(c)(1) § 63.999(c)(2)(i) [G]§ 63.999(c)(4) [G]§ 63.999(c)(5)
GRPHON-PV	EP	R5121-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(A)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
GRPHON-PV	EP	R5121-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(B) § 60.18	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.122(c)(1)(A)-(C).			
GRPHON-PV	EP	63G-3A	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 60.702(b) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. §63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	[G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GRPHON-PV	EP	63G-3B	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(2) § 60.702(a) § 63.113(h) [G]§ 63.115(f)	Reduce emissions of total organic HAPs by 98 wt.% or to a concentration of 20 ppm by volume; whichever is less stringent or as specified. §63.113(a)(2)(i)-(ii)	§ 63.114(a) § 63.114(a)(1)(i) § 63.114(e) [G]§ 63.115(f) [G]§ 63.116(c)	§ 63.114(a)(1) § 63.117(a)(4) § 63.117(a)(4)(i) § 63.117(a)(4)(ii) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) § 63.117(a)(4) § 63.117(a)(4)(i) § 63.117(a)(4)(ii) § 63.117(f) § 63.118(f)(1) § 63.118(f)(2) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									[G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GRPLOADO UT	EP	R5121-4	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(c)(1)(C) § 115.127(c)(1)	A vent gas stream having a concentration of the VOC specified in §115.121(c)(1)(B) and (C) of this title less than 30,000 ppmv is exempt from the requirements of §115.121(c)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRPPELLE T	EP	R5121-4	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(c)(1)(C) § 115.127(c)(1)	A vent gas stream having a concentration of the VOC specified in §115.121(c)(1)(B) and (C) of this title less than 30,000 ppmv is exempt from the requirements of §115.121(c)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRPSKIMM ER	EU	R5131-2	VOC	30 TAC Chapter 115, Water	§ 115.132(c)(3) § 115.131(c)	VOC water separator	** See Periodic Monitoring Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Separation		compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(c) of this title.			
GRPUNLOAD	EU	R5212-3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(b)(3) § 115.212(b)(2) § 115.212(b)(3)(A) § 115.212(b)(3)(A)(i) § 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.212(b)(3)(D) § 115.214(b)(1)(B)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.214(b)(1)(A)(ii) § 115.214(b)(1)(A)(iii)	None	None
GRPUNLOAD	EU	R5212-6	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(b)(3) § 115.212(b)(2) § 115.212(b)(3)(A) § 115.212(b)(3)(A)(ii) § 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.212(b)(3)(D) § 115.214(b)(1)(B)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.214(b)(1)(A)(ii) § 115.214(b)(1)(A)(iii)	None	None
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-1a(d) § 60.482-1a(a) § 60.482-1a(b) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	Equipment that is in vacuum service is excluded from the requirements of §60.482-2a to §60.482-10a, if it is identified as required in §60.486a(e)(5).	[G]§ 60.485a(b)(1) § 60.485a(b)(2)	§ 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) § 60.486a(e)(5)	None
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-11a(b)(2) § 60.482-11a(b)(3) § 60.482-11a(b)(3)(i) § 60.482-11a(d)	If an instrument reading greater than or equal to 500 ppm is	§ 60.482-11a(a) § 60.482-11a(b) § 60.482-11a(b)(1) § 60.482-11a(b)(3)	§ 60.482-11a(b)(3)(v) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b)	§ 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(5) § 60.487a(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-11a(e) [G]§ 60.482-11a(f)(1) § 60.482-11a(f)(2) § 60.482-11a(g) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	measured in connectors in gas and vapor and light liquid service, a leak is detected.	§ 60.482-11a(b)(3)(ii) [G]§ 60.482-11a(b)(3)(iii) § 60.482-11a(b)(3)(iv) § 60.482-11a(c) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(e)	[G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8) § 60.486a(e)(9) § 60.486a(f) § 60.486a(f)(1)	§ 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ix) § 60.487a(c)(2)(vii) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-8a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.482-9a(c) § 60.482-9a(c)(1) § 60.482-9a(c)(2) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	At a connector in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-8a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2)	At a pressure relief device in light liquid or heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d) [G]§ 60.485a(e)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	detected.			§ 60.487a(c)(4) § 60.487a(e)
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-8a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.482-9a(c) § 60.482-9a(c)(1) § 60.482-9a(e) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	At a valve in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-8a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2)	At a pump in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(d) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)			§ 60.487a(c)(4) § 60.487a(e)	
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-7a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-7a(a)(1) [G]§ 60.482-7a(d) [G]§ 60.482-7a(e) [G]§ 60.482-7a(f) [G]§ 60.482-7a(g) [G]§ 60.482-7a(h) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	At a valve in gas vapor service if an instrument reading of 500 ppm or greater is measured, a leak is detected.	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g) § 60.482-7a(a)(1) [G]§ 60.482-7a(a)(2) [G]§ 60.482-7a(c) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(e)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1) § 60.486a(f)(2)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(2) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ii) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-6a(a)(1) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-6a(a)(2) § 60.482-6a(b) § 60.482-6a(c) § 60.482-6a(d) § 60.482-6a(e) § 60.485a(b)	Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve, except as provided in §60.482–1a(c) and paragraphs (d) and (e) of this section.	§ 60.482-1a(g) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)				
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-5a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-5a(b) § 60.482-5a(c) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	Each sampling connection system shall be equipped with a closed-purge, closed-loop, or closed-vent system, except as provided in §60.482-1a(c) and paragraph (c) of this section.	§ 60.482-1a(g) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-4a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-4a(b)(1) § 60.482-4a(b)(2) § 60.482-4a(c) § 60.482-4a(d)(1) § 60.482-4a(d)(2) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	Except during pressure releases, each pressure relief device in gas/vapor service shall be operated with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as determined by the methods specified in §60.485a(c).	§ 60.482-1a(g) § 60.482-4a(b)(2) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) § 60.486a(e)(10) § 60.486a(e)(3) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-3a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-3a(b)	Each compressor shall be equipped with a seal system that includes a barrier fluid system	§ 60.482-1a(g) § 60.482-3a(e)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(4) § 60.487a(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-3a(c) § 60.482-3a(d) § 60.482-3a(e)(2) § 60.482-3a(f) [G]§ 60.482-3a(g) § 60.482-3a(h) [G]§ 60.482-3a(i) § 60.482-3a(j) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	and that prevents leakage of VOC to the atmosphere, except as provided in §60.482-3a(c) and paragraphs (h), (i), and (j) of this section.	§ 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d)	§ 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8) [G]§ 60.486a(h)	§ 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(2)(v) § 60.487a(c)(2)(vi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	[G]§ 60.482-2a(b)(1) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-2a(b)(2) § 60.482-2a(b)(2)(ii) § 60.482-2a(c)(1) [G]§ 60.482-2a(c)(2) § 60.482-2a(d) [G]§ 60.482-2a(d)(1) § 60.482-2a(d)(2) § 60.482-2a(d)(3) [G]§ 60.482-2a(d)(6) [G]§ 60.482-2a(e) § 60.482-2a(f) [G]§ 60.482-2a(g) § 60.482-2a(h) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(d) § 60.482-9a(f) § 60.485a(b)	The instrument reading that defines a leak in a pump in light liquid service is 5,000 parts per million (ppm) or greater for pumps handling polymerizing monomers or 2,000 ppm or greater for all other pumps, as specified in paragraphs (b)(1)(i) and (ii) of this section. §60.482-2a(b)(1)(i)-(ii)	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g) § 60.482-2a(a)(1) § 60.482-2a(a)(2) § 60.482-2a(b)(2)(i) [G]§ 60.482-2a(d)(4) [G]§ 60.482-2a(d)(5) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(e)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) § 60.486a(e)(7) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1) [G]§ 60.486a(h)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(3) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(iii) § 60.487a(c)(2)(iv) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)				
G_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	[G]§ 60.482-1a(e) § 60.482-1a(a) § 60.482-1a(b) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	Equipment that an owner or operator designates as being in VOC service less than 300 hours (hr)/yr is excluded from the requirements of §§ 60.482-2a through 60.482-11a if it is identified as required in §60.486a(e)(6) and it meets any of the conditions specified in paragraphs (e)(1) through (3) of this section. §60.482-1a(e)(1)-(3)	[G]§ 60.485a(b)(1) § 60.485a(b)(2)	§ 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) § 60.486a(e)(6)	None
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).			
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h)	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.171				
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
G_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g)	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(h) [G]§ 63.171				§ 63.182(c)(4) [G]§ 63.182(d)
MEOHUNLO AD	EU	R5212-3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(b)(3) § 115.212(b)(2) § 115.212(b)(3)(A) § 115.212(b)(3)(A)(i) § 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.212(b)(3)(D) § 115.214(b)(1)(B)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.214(b)(1)(A)(ii) § 115.214(b)(1)(A)(iii)	None	None
MEOHUNLO AD	EU	R5212-6	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(b)(3) § 115.212(b)(2) § 115.212(b)(3)(A) § 115.212(b)(3)(A)(ii) § 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.212(b)(3)(D) § 115.214(b)(1)(B)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.214(b)(1)(A)(ii) § 115.214(b)(1)(A)(iii)	None	None
MEOHUNLO AD	EU	63EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2343(a) § 63.2334(a) § 63.2338(b)(2) § 63.2342(a)(2) § 63.2350(a) § 63.2350(d)	For each transfer rack that only unloads organic liquids, keep documentation that verifies the transfer rack is not required to be controlled.	None	§ 63.2343(a)	None
O-REGEN	EP	R5121-5	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(c)(2)	A vent gas stream specified in §115.121(c)(2) which emits less than or equal to five tons of total uncontrolled VOC in any one calendar year is exempt from the requirements of §115.121(c)(2) of	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						this title.			
O-VENTGAS	EP	R5121-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(A)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
O-VENTGAS	EP	R5121-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(B) § 60.18	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
O-VENTGAS	EP	R5121-16A	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.123(c) § 115.910	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis	[G]§ 115.125 § 115.126(2) ** See Alternative Requirement	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Counties, alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 of this title if emission reductions are demonstrated to be substantially equivalent.			
O-VENTGAS	EP	R5121-20	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(c)(1) § 115.121(c)(1) § 115.122(c)(1)(C)	For all persons in Aransas, Bexar, Calhoun, Matagorda, San Patricio, and Travis Counties, any vent gas streams affected by §115.121(c)(1) must be controlled properly using one of the control requirements specified in §115.122(c)(1)(A)-(C).	[G]§ 115.125 § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(2)	None
O_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-1a(d) § 60.482-1a(a) § 60.482-1a(b)	Equipment that is in vacuum service is excluded from the	[G]§ 60.485a(b)(1) § 60.485a(b)(2)	§ 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	requirements of §60.482-2a to §60.482-10a, if it is identified as required in §60.486a(e)(5).		§ 60.486a(e)(5)	
O_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	[G]§ 60.482-1a(e) § 60.482-1a(a) § 60.482-1a(b) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	Equipment that an owner or operator designates as being in VOC service less than 300 hours (hr)/yr is excluded from the requirements of §§ 60.482-2a through 60.482-11a if it is identified as required in §60.486a(e)(6) and it meets any of the conditions specified in paragraphs (e)(1) through (3) of this section. §60.482-1a(e)(1)-(3)	[G]§ 60.485a(b)(1) § 60.485a(b)(2)	§ 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) § 60.486a(e)(6)	None
O_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	[G]§ 60.482-2a(b)(1) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-2a(b)(2) § 60.482-2a(b)(2)(ii) § 60.482-2a(c)(1) [G]§ 60.482-2a(c)(2) § 60.482-2a(d) [G]§ 60.482-2a(d)(1) § 60.482-2a(d)(2) § 60.482-2a(d)(3) [G]§ 60.482-2a(d)(6)	The instrument reading that defines a leak in a pump in light liquid service is 5,000 parts per million (ppm) or greater for pumps handling polymerizing monomers or 2,000 ppm or greater for all other pumps, as specified in	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g) § 60.482-2a(a)(1) § 60.482-2a(a)(2) § 60.482-2a(b)(2)(i) [G]§ 60.482-2a(d)(4) [G]§ 60.482-2a(d)(5) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) § 60.486a(e)(7) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(3) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(iii) § 60.487a(c)(2)(iv) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-2a(e) § 60.482-2a(f) [G]§ 60.482-2a(g) § 60.482-2a(h) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(d) § 60.482-9a(f) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	paragraphs (b)(1)(i) and (ii) of this section. §60.482-2a(b)(1)(i)-(ii)	§ 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(e)	[G]§ 60.486a(h)	
O_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-3a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-3a(b) § 60.482-3a(c) § 60.482-3a(d) § 60.482-3a(e)(2) § 60.482-3a(f) [G]§ 60.482-3a(g) § 60.482-3a(h) [G]§ 60.482-3a(i) § 60.482-3a(j) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	Each compressor shall be equipped with a seal system that includes a barrier fluid system and that prevents leakage of VOC to the atmosphere, except as provided in §60.482-3a(c) and paragraphs (h), (i), and (j) of this section.	§ 60.482-1a(g) § 60.482-3a(e)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8) [G]§ 60.486a(h)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(4) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(2)(v) § 60.487a(c)(2)(vi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
O_FUG	EU	60VVA-	VOC	40 CFR Part 60,	§ 60.482-4a(a)	Except during	§ 60.482-1a(g)	§ 60.482-1a(g)	§ 60.487a(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		Subpart VVa	§ 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-4a(b)(1) § 60.482-4a(b)(2) § 60.482-4a(c) § 60.482-4a(d)(1) § 60.482-4a(d)(2) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	pressure releases, each pressure relief device in gas/vapor service shall be operated with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as determined by the methods specified in §60.485a(c).	§ 60.482-4a(b)(2) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d)	§ 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) § 60.486a(e)(10) § 60.486a(e)(3) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8)	§ 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
O_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-5a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-5a(b) § 60.482-5a(c) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	Each sampling connection system shall be equipped with a closed-purge, closed-loop, or closed-vent system, except as provided in §60.482-1a(c) and paragraph (c) of this section.	§ 60.482-1a(g) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
O_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-6a(a)(1) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-6a(a)(2) § 60.482-6a(b) § 60.482-6a(c) § 60.482-6a(d) § 60.482-6a(e) § 60.485a(b)	Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve, except as provided in §60.482-1a(c) and paragraphs (d) and (e) of this section.	§ 60.482-1a(g) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)				
O_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-7a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-7a(a)(1) [G]§ 60.482-7a(d) [G]§ 60.482-7a(e) [G]§ 60.482-7a(f) [G]§ 60.482-7a(g) [G]§ 60.482-7a(h) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	At a valve in gas vapor service if an instrument reading of 500 ppm or greater is measured, a leak is detected.	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g) § 60.482-7a(a)(1) [G]§ 60.482-7a(a)(2) [G]§ 60.482-7a(c) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(e)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1) § 60.486a(f)(2)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(2) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ii) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
O_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-8a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(d) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1)	At a pump in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.486a(a)(2) § 60.486a(k)				
O_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-8a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.482-9a(c) § 60.482-9a(c)(1) § 60.482-9a(e) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	At a valve in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
O_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-8a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1)	At a pressure relief device in light liquid or heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d) [G]§ 60.485a(e)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.486a(a)(2) § 60.486a(k)				
O_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-8a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.482-9a(c) § 60.482-9a(c)(1) § 60.482-9a(c)(2) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	At a connector in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
O_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-11a(b)(2) § 60.482-11a(b)(3) § 60.482-11a(b)(3)(i) § 60.482-11a(d) [G]§ 60.482-11a(e) [G]§ 60.482-11a(f)(1) § 60.482-11a(f)(2) § 60.482-11a(g) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	If an instrument reading greater than or equal to 500 ppm is measured in connectors in gas and vapor and light liquid service, a leak is detected.	§ 60.482-11a(a) § 60.482-11a(b) § 60.482-11a(b)(1) § 60.482-11a(b)(3) § 60.482-11a(b)(3)(ii) [G]§ 60.482-11a(b)(3)(iii) § 60.482-11a(b)(3)(iv) § 60.482-11a(c) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(e)	§ 60.482-11a(b)(3)(v) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8) § 60.486a(e)(9) § 60.486a(f) § 60.486a(f)(1)	§ 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(5) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ix) § 60.487a(c)(2)(vii) § 60.487a(c)(2)(viii) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
O_FUG	EU	63YY-ALL	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103(e)-Table 7.f.1	For equipment defined in	[G]§ 63.1022(c)(4) § 63.1023(a)	§ 63.1022(b)(5) § 63.1022(c)(3)	[G]§ 63.1025(b)(4) § 63.1039(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1019(d) § 63.1022(a) § 63.1022(b) § 63.1022(b)(1) § 63.1022(b)(3) § 63.1022(b)(4) § 63.1022(b)(5) § 63.1022(c)(1) [G]§ 63.1022(c)(2) § 63.1022(d)(1) § 63.1022(e) § 63.1023(a) § 63.1023(e)(1) § 63.1024(a) [G]§ 63.1024(c) [G]§ 63.1024(d) § 63.1024(e) § 63.1025(a)(1) § 63.1025(b)(2) [G]§ 63.1025(b)(4) § 63.1025(d)(1) [G]§ 63.1026(b) [G]§ 63.1026(c) § 63.1026(d) [G]§ 63.1026(e)(1) § 63.1026(e)(2) [G]§ 63.1027(b) § 63.1027(d) [G]§ 63.1028(c) § 63.1028(d) [G]§ 63.1028(e)(1) § 63.1028(e)(2) § 63.1028(e)(6) [G]§ 63.1029 [G]§ 63.1031(b) § 63.1031(c) § 63.1031(d)(1) [G]§ 63.1031(f) § 63.1032(b) [G]§ 63.1032(c)	A, A § 63.1101 that contains or contacts > 5 % by wt organic HAP and the equipment is not in vacuum service, comply with the requirements of subpart UU.	[G]§ 63.1023(a)(1) § 63.1023(a)(2)(i) § 63.1023(a)(2)(iii) [G]§ 63.1023(b) [G]§ 63.1023(c) § 63.1023(d) § 63.1025(a)(2) § 63.1025(b) § 63.1025(b)(1) [G]§ 63.1025(b)(3) [G]§ 63.1025(b)(4) [G]§ 63.1025(c) [G]§ 63.1025(d)(2) [G]§ 63.1025(e) [G]§ 63.1026(b) [G]§ 63.1026(c) § 63.1026(d) [G]§ 63.1026(e)(1) § 63.1026(e)(4) § 63.1026(e)(5) § 63.1026(e)(6) [G]§ 63.1027(b) § 63.1027(c) [G]§ 63.1027(e) [G]§ 63.1028(c) [G]§ 63.1028(e)(1) § 63.1028(e)(4) § 63.1028(e)(5) § 63.1028(e)(7) [G]§ 63.1029 § 63.1031(c) [G]§ 63.1035(d)(2) § 63.1035(d)(4) [G]§ 63.1035(d)(6) [G]§ 63.1107(h)(2) [G]§ 63.1107(h)(3) [G]§ 63.1108(b)(4)(i) § 63.1108(b)(4)(ii)	[G]§ 63.1022(c)(4) § 63.1022(d)(2) [G]§ 63.1022(f) § 63.1023(e)(2) [G]§ 63.1024(d) [G]§ 63.1024(f) [G]§ 63.1025(b)(3) [G]§ 63.1025(b)(4) [G]§ 63.1026(b) [G]§ 63.1026(e)(1) [G]§ 63.1027(b) [G]§ 63.1028(e)(1) § 63.1031(d)(2) [G]§ 63.1035(d)(2) § 63.1035(d)(3) [G]§ 63.1035(e) § 63.1038(a) [G]§ 63.1038(b) [G]§ 63.1038(c)(1) [G]§ 63.1038(c)(2) § 63.1038(c)(3) [G]§ 63.1038(c)(4) [G]§ 63.1038(c)(6) [G]§ 63.1038(c)(7) [G]§ 63.1107(h)(3) [G]§ 63.1107(h)(6) [G]§ 63.1107(h)(7) § 63.1109(a) § 63.1109(b) § 63.1109(c) § 63.1109(d)	[G]§ 63.1039(a)(1) § 63.1039(b) [G]§ 63.1039(b)(1) § 63.1039(b)(2) § 63.1039(b)(3) § 63.1039(b)(4) § 63.1039(b)(5) § 63.1039(b)(6) § 63.1039(b)(8) § 63.1109(b) § 63.1110(a) § 63.1110(a)(1) [G]§ 63.1110(a)(10) § 63.1110(a)(2) § 63.1110(a)(4) § 63.1110(a)(5) § 63.1110(a)(6) § 63.1110(a)(7) § 63.1110(a)(8) § 63.1110(b)(1) § 63.1110(b)(2) [G]§ 63.1110(c) [G]§ 63.1110(d) [G]§ 63.1110(e) [G]§ 63.1110(f) [G]§ 63.1110(g) [G]§ 63.1110(h) [G]§ 63.1111(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1032(d) [G]§ 63.1033 [G]§ 63.1035(a) § 63.1035(b) § 63.1035(c) § 63.1035(d) § 63.1035(d)(1) [G]§ 63.1035(d)(5) [G]§ 63.1035(d)(7) [G]§ 63.1035(d)(8) [G]§ 63.1100(d)(5) § 63.1103(e)(1)(i)(D) § 63.1103(e)(3) § 63.1107(a) § 63.1107(b) § 63.1107(c) § 63.1107(d) § 63.1107(h) § 63.1107(h)(1) [G]§ 63.1107(h)(2) [G]§ 63.1107(h)(3) [G]§ 63.1107(h)(6) [G]§ 63.1107(h)(7) § 63.1107(h)(8) [G]§ 63.1108(a)(4) § 63.1108(a)(5) § 63.1108(a)(6) § 63.1108(a)(7) § 63.1108(b)(3) § 63.1108(b)(4) § 63.1108(b)(4)(iii) § 63.1108(b)(5) § 63.1108(c) [G]§ 63.1108(d) [G]§ 63.1111(a) § 63.1112(a)(1) § 63.1112(b)(1)				
PE-REGEN	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas	§ 115.127(c)(1)(B) § 115.127(c)(1)	A vent gas stream having a combined	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Controls		weight of the VOC or classes of compounds specified in §115.121(c)(1)(B)-(C) of this title equal to or less than 100 lbs in a continuous 24-hour period is exempt from the requirements of §115.121(c)(1) of this title.		§ 115.126(4)	
PE-REGEN	EP	63FFFF-9	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2460(b)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.1257(d)(2)(i) [G]§ 63.1257(d)(2)(ii) § 63.2460(b)(1) § 63.2460(b)(2) § 63.2460(b)(3) [G]§ 63.2460(b)(4) § 63.2460(b)(7)	§ 63.2460(b)(6)(i) § 63.2460(b)(7)	§ 63.2460(b)(6) § 63.2460(b)(6)(i) § 63.2460(b)(6)(ii) § 63.2460(b)(7)
PROEXTRU D	PRO	60DDD-02	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(g)	Vent streams emitting continuous emissions with uncontrolled annual emissions of < 1.6 Mg/yr (1.76 Tons/yr) or with weight % TOC of < 0.10 % from facilities as specified, exempted from §60.562-1(a)(1).	[G]§ 60.564(d)	§ 60.565(a) § 60.565(a)(10) § 60.565(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(k) § 60.565(k)(6) § 60.565(k)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PROGRANU L1	PRO	60DDD-02	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(g)	Vent streams emitting continuous emissions with uncontrolled annual emissions of < 1.6 Mg/yr (1.76 Tons/yr) or with weight % TOC of < 0.10 % from facilities as specified, exempted from §60.562-1(a)(1).	[G]§ 60.564(d)	§ 60.565(a) § 60.565(a)(10) § 60.565(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(k) § 60.565(k)(6) § 60.565(k)(7)
PROGRANU L2	PRO	60DDD-02	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(g)	Vent streams emitting continuous emissions with uncontrolled annual emissions of < 1.6 Mg/yr (1.76 Tons/yr) or with weight % TOC of < 0.10 % from facilities as specified, exempted from §60.562-1(a)(1).	[G]§ 60.564(d)	§ 60.565(a) § 60.565(a)(10) § 60.565(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(k) § 60.565(k)(6) § 60.565(k)(7)
PROGRANU L3	PRO	60DDD-03	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(1) § 60.562-1(a)(1)(ii) § 60.562-1(d) § 60.562-1(e)	For each vent stream that emits continuous emissions from affected facility, use procedures in paragraphs (a)(1)(ii)-(iii) for determining which continuous emissions to control as specified.	[G]§ 60.563(a) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(d)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) [G]§ 60.565(b)(2) [G]§ 60.565(g) § 60.565(j)	§ 60.565(a) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PROLDOUT 1	PRO	60DDD-02	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(g)	Vent streams emitting continuous emissions with uncontrolled annual emissions of < 1.6 Mg/yr (1.76 Tons/yr) or with weight % TOC of < 0.10 % from facilities as specified, exempted from §60.562-1(a)(1).	[G]§ 60.564(d)	§ 60.565(a) § 60.565(a)(10) § 60.565(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(k) § 60.565(k)(6) § 60.565(k)(7)
PROLDOUT 2	PRO	60DDD-03	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(1) § 60.562-1(a)(1)(ii) § 60.562-1(d) § 60.562-1(e)	For each vent stream that emits continuous emissions from affected facility, use procedures in paragraphs (a)(1)(ii)-(iii) for determining which continuous emissions to control as specified.	[G]§ 60.563(a) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(d)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) [G]§ 60.565(b)(2) [G]§ 60.565(g) § 60.565(j)	§ 60.565(a) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(l)
PROME GC MPU	PRO	63F-1	112(B) HAPS	40 CFR Part 63, Subpart F	§ 63.100(b) [G]§ 63.102(a) [G]§ 63.102(c) § 63.104(a) [G]§ 63.104(d) § 63.104(e) § 63.104(e)(1) [G]§ 63.104(e)(2) § 63.105(d)	Except as provided in paragraphs (b)(4) and (c) of this section, the provisions of subparts F, G, and H apply to chemical manufacturing process units that meet the criteria.	§ 63.103(b)(1) § 63.103(b)(3) § 63.103(b)(4) [G]§ 63.103(b)(5) § 63.103(b)(6) [G]§ 63.104(c)	[G]§ 63.103(c) [G]§ 63.104(c) [G]§ 63.104(e)(2) [G]§ 63.104(f)(1) [G]§ 63.105(b) § 63.105(c) § 63.105(e)	§ 63.103(b)(2) [G]§ 63.103(b)(5) [G]§ 63.103(d) [G]§ 63.104(f)(2)
PROPELLE T	PRO	60DDD-02	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(g)	Vent streams emitting continuous emissions with	[G]§ 60.564(d)	§ 60.565(a) § 60.565(a)(10) § 60.565(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(k)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						uncontrolled annual emissions of < 1.6 Mg/yr (1.76 Tons/yr) or with weight % TOC of < 0.10 % from facilities as specified, exempted from §60.562-1(a)(1).			§ 60.565(k)(6) § 60.565(k)(7)
PROPEMCP U	PRO	63FFFF-MCPU	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2440(a) § 63.2450(a) § 63.2450(l) § 63.2460(c)(1)	This subpart applies to each miscellaneous organic chemical manufacturing affected source.	§ 63.2445(d) § 63.2460(c)(2)(v)	§ 63.2525 § 63.2525(a) [G]§ 63.2525(b) § 63.2525(c) § 63.2525(f) § 63.2525(j)	§ 63.2435(d) § 63.2445(c) § 63.2450(g)(5) § 63.2450(m) § 63.2450(m)(1) § 63.2450(m)(2) § 63.2460(c)(1) § 63.2515(a) § 63.2515(b)(2) § 63.2515(c) § 63.2520(a) [G]§ 63.2520(b) [G]§ 63.2520(c) [G]§ 63.2520(d) § 63.2520(e) § 63.2520(e)(1) [G]§ 63.2520(e)(10) § 63.2520(e)(2) § 63.2520(e)(3) § 63.2520(e)(4) § 63.2520(e)(5) § 63.2520(e)(5)(i) [G]§ 63.2520(e)(5)(ii) [G]§ 63.2520(e)(5)(iii) § 63.2520(e)(6) § 63.2520(e)(7) § 63.2520(e)(9)
RAD02	EU	R5112-11	VOC	30 TAC Chapter	§ 115.112(c)(1)	Tanks shall not	** See Periodic	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Storage of VOCs		store VOC, other than crude oil or condensate, unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(b).	Monitoring Summary		
RJT01	EP	60NNN-1	VOC/TOC	40 CFR Part 60, Subpart NNN	§ 60.660(d)(1)	Owners or operators of process vents that are subject to this subpart may choose to comply with the provisions of 40 CFR part 65, subpart D, to satisfy the requirements of §§60.662 through 60.665 and 60.668.	None	None	None
RJT01	EP	65CAR-BLR	VOC	40 CFR Part 65, Subpart D	§ 65.63(a)(2) § 65.1(d) § 65.1(e) § 65.140 § 65.142(b)(2) § 65.143(a)(1) § 65.143(a)(2) [G]§ 65.149(a) § 65.149(b)(2) § 65.149(b)(2)(ii) § 65.3(a)(1) § 65.3(a)(3) § 65.3(a)(4) § 65.3(a)(5) § 65.3(b)(3)	For a Group 1 process vent, reduce emissions of regulated material or TOC by at least 98 weight-percent or to a concentration of less than 20 parts per million by volume.	None	§ 65.163(c)(1) § 65.163(c)(2) § 65.4(a)(1) § 65.4(b) § 65.4(c) § 65.4(c)(1) § 65.4(c)(3) [G]§ 65.6(b)	§ 65.165(f) § 65.166(a) [G]§ 65.166(b) § 65.167(b) [G]§ 65.5(a) [G]§ 65.5(b) [G]§ 65.5(d) [G]§ 65.5(e) [G]§ 65.5(f) [G]§ 65.5(g) [G]§ 65.5(h) [G]§ 65.5(i) [G]§ 65.6(c) § 65.67(b)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 65.3(b)(5) § 65.3(c) [G]§ 65.3(d) [G]§ 65.6(b) § 65.62(a) § 65.62(b)(1) § 65.63(a)				
RJT01	EP	65CAR-FL	VOC	40 CFR Part 65, Subpart D	§ 65.63(a)(1) § 65.1(d) § 65.1(e) § 65.140 § 65.142(b)(1) § 65.143(a)(1) § 65.143(a)(2) [G]§ 65.147(a) § 65.3(a)(1) § 65.3(a)(3) § 65.3(a)(4) § 65.3(a)(5) § 65.3(b)(3) [G]§ 65.3(b)(5) § 65.3(c) [G]§ 65.3(d) [G]§ 65.6(b) § 65.62(a) § 65.62(b)(1) § 65.63(a)	For a Group 1 process vent, reduce emissions of regulated material using a flare meeting the applicable requirements of § 65.142(b).	§ 65.147(b)(1) § 65.147(b)(2) [G]§ 65.147(b)(3) § 65.147(c) [G]§ 65.157(b) [G]§ 65.157(c)	§ 65.147(b)(1) § 65.147(c) § 65.159(a) [G]§ 65.159(b) § 65.159(c) § 65.159(d)(1) § 65.159(d)(2) § 65.161(a)(1) § 65.163(c)(1) § 65.163(c)(2) § 65.4(a)(1) § 65.4(b) § 65.4(c) § 65.4(c)(1) § 65.4(c)(3) [G]§ 65.6(b)	§ 65.147(b)(1) § 65.147(b)(2) § 65.159(d)(1) [G]§ 65.164(a) [G]§ 65.164(b) § 65.166(a) [G]§ 65.166(b) § 65.166(c) § 65.167(b) [G]§ 65.5(a) [G]§ 65.5(b) [G]§ 65.5(d) [G]§ 65.5(e) [G]§ 65.5(f) [G]§ 65.5(g) [G]§ 65.5(h) [G]§ 65.5(i) [G]§ 65.6(c) § 65.67(b)(3)
RJT01	EP	65CAR-INC	VOC	40 CFR Part 65, Subpart D	§ 65.63(a)(2) § 65.1(d) § 65.1(e) § 65.140 § 65.142(b)(2) § 65.143(a)(1) § 65.143(a)(2) § 65.148(a)(1) § 65.148(a)(2) § 65.3(a)(1) § 65.3(a)(3)	For a Group 1 process vent, reduce emissions of regulated material or TOC by at least 98 weight-percent or to a concentration of less than 20 parts per million by volume.	§ 65.148(b)(1) § 65.148(c)(1) § 65.148(c)(1)(i) § 65.148(c)(2) [G]§ 65.158(a) [G]§ 65.158(b)	§ 65.148(c)(1) § 65.160(a) § 65.160(b) § 65.160(b)(1)(i) § 65.161(a)(1) [G]§ 65.161(c) [G]§ 65.162(a) [G]§ 65.162(b) § 65.163(c)(1) § 65.163(c)(2) § 65.4(a)(1)	§ 65.160(b) § 65.160(b)(1)(i) [G]§ 65.164(a) [G]§ 65.164(b) [G]§ 65.165(c) § 65.166(a) [G]§ 65.166(b) § 65.166(f)(1) § 65.167(b) [G]§ 65.5(a) [G]§ 65.5(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 65.3(a)(4) § 65.3(a)(5) § 65.3(b)(3) [G]§ 65.3(b)(5) § 65.3(c) [G]§ 65.3(d) [G]§ 65.6(b) § 65.62(a) § 65.62(b)(1) § 65.63(a)			§ 65.4(b) § 65.4(c) § 65.4(c)(1) § 65.4(c)(3) [G]§ 65.6(b)	[G]§ 65.5(d) [G]§ 65.5(e) [G]§ 65.5(f) [G]§ 65.5(g) [G]§ 65.5(h) [G]§ 65.5(i) [G]§ 65.6(c) § 65.67(b)(3)
RLOAD-C3	EU	R5212-7	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(b)(1) § 115.212(b)(1)(B) § 115.212(b)(3)(A) § 115.212(b)(3)(A)(i) § 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.212(b)(3)(E) § 115.214(b)(1)(B)	In Aransas, Bexar, Calhoun, Gregg, Matagorda, Nueces, San Patricio, Travis, and Victoria Counties, vapors caused by the loading of VOC with a TVP greater than or equal to 1.5 psia must be controlled using one of the methods specified in §115.212(b)(1)(A)-(C).	§ 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.214(b)(1)(A)(ii) § 115.214(b)(1)(A)(iii) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(8) § 115.215(9)	§ 115.216 § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(ii) § 115.216(3)(B)	None
RLOAD-C3	EU	R5212-8	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(b)(1) § 115.212(b)(1)(B) § 115.212(b)(3)(A) § 115.212(b)(3)(A)(ii) § 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.212(b)(3)(E) § 115.214(b)(1)(B)	In Aransas, Bexar, Calhoun, Gregg, Matagorda, Nueces, San Patricio, Travis, and Victoria Counties, vapors caused by the loading of VOC with a TVP greater than or equal to 1.5 psia must be controlled using	§ 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.214(b)(1)(A)(ii) § 115.214(b)(1)(A)(iii) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5)	§ 115.216 § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(ii) § 115.216(3)(B)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						one of the methods specified in §115.212(b)(1)(A)-(C).	§ 115.215(8) § 115.215(9)		
RLOAD-HFO	EU	R5212-5	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(b)(3)(A) § 115.214(b)(1)(B) § 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	Plants, excluding gasoline bulk plants, which load <20,000 gallons of VOC into transport vessels per day with a true vapor pressure of 1.5 psia or greater are exempt from this division, except for the specified requirements.	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B) § 115.216(3)(D)	None
SLOPUNLO AD	EU	R5212-3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(b)(3) § 115.212(b)(2) § 115.212(b)(3)(A) § 115.212(b)(3)(A)(i) § 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.212(b)(3)(D) § 115.214(b)(1)(B)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.214(b)(1)(A)(ii) § 115.214(b)(1)(A)(iii)	None	None
SLOPUNLO AD	EU	R5212-6	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(b)(3) § 115.212(b)(2) § 115.212(b)(3)(A) § 115.212(b)(3)(A)(ii) § 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.212(b)(3)(D) § 115.214(b)(1)(B)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.214(b)(1)(A)(ii) § 115.214(b)(1)(A)(iii)	None	None
SLOPUNLO AD	EU	63EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2343(a) § 63.2334(a) § 63.2338(b)(2) § 63.2342(a)(2)	For each transfer rack that only unloads organic liquids, keep	None	§ 63.2343(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.2350(a) § 63.2350(d)	documentation that verifies the transfer rack is not required to be controlled.			
TLOAD-SLOP	EU	R5212-5	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(b)(3)(A) § 115.214(b)(1)(B) § 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	Plants, excluding gasoline bulk plants, which load <20,000 gallons of VOC into transport vessels per day with a true vapor pressure of 1.5 psia or greater are exempt from this division, except for the specified requirements.	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B) § 115.216(3)(D)	None
UCCT01	EU	63YY-CT	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103(e)-Table 7.h § 63.1083 § 63.1085 § 63.1085(f) [G]§ 63.1087(c) § 63.1087(d) § 63.1088 [G]§ 63.1088(d) § 63.1103(e)(1)(i)(F) § 63.1103(e)(3) [G]§ 63.1108(a)(4) § 63.1108(a)(5) § 63.1108(a)(6) § 63.1108(a)(7) [G]§ 63.1108(b)(2) § 63.1108(b)(3) § 63.1108(b)(4) § 63.1108(b)(4)(iii) § 63.1108(b)(5) § 63.1108(c) [G]§ 63.1108(d)	For a heat exchange system in ethylene production service, comply with the heat exchange system requirements of subpart XX of this part.	§ 63.1085(e) § 63.1086 [G]§ 63.1086(e) [G]§ 63.1087(c) § 63.1087(d) [G]§ 63.1088(b) [G]§ 63.1088(d)	§ 63.1085(c) [G]§ 63.1088(d) [G]§ 63.1089 [G]§ 63.1100(d)(4) § 63.1109(a) § 63.1109(b) § 63.1109(c) § 63.1109(d)	§ 63.1085(d) [G]§ 63.1090 § 63.1109(b) § 63.1110(a) § 63.1110(a)(1) [G]§ 63.1110(a)(10) § 63.1110(a)(2) § 63.1110(a)(4) § 63.1110(a)(5) § 63.1110(a)(6) § 63.1110(a)(7) § 63.1110(a)(8) § 63.1110(b)(1) § 63.1110(b)(2) [G]§ 63.1110(c) [G]§ 63.1110(d) [G]§ 63.1110(e) [G]§ 63.1110(f) [G]§ 63.1110(g) [G]§ 63.1110(h) [G]§ 63.1111(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.1111(a) § 63.1112(a)(1) § 63.1112(b)(1)				
UFF01A	EP	R1111-1	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(C) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 15% averaged over a six minute period for any source with a total flow rate of at least 100,000 acfm unless a CEMS is installed.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
UFF01B	EP	R1111-1	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(C) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 15% averaged over a six minute period for any source with a total flow rate of at least 100,000 acfm unless a CEMS is installed.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
UFFFLARE01	CD	R1111-2A	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period. Non-excessive upset events are subject to the provisions under §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UFFLARE01	CD	63CC-01	Opacity	40 CFR Part 63, Subpart CC	§ 63.670(c) § 63.670 § 63.670(e) § 63.670(o) [G]§ 63.670(o)(1) § 63.670(o)(2)(ii) § 63.670(o)(3)(i) [G]§ 63.670(o)(4) [G]§ 63.670(o)(5) § 63.670(o)(6) [G]§ 63.670(o)(7) [G]§ 63.671(c)	Visible emissions. The owner or operator shall specify the smokeless design capacity of each flare and operate with no visible emissions, except for periods not to exceed a total of 5 minutes during any 2 consecutive hours, when regulated material is routed to the flare and the flare vent gas flow rate is less than the smokeless design capacity of the flare. The owner or operator shall monitor for visible emissions from the flare as specified in §63.670(h).	§ 63.670(c) § 63.670(e) [G]§ 63.670(h) [G]§ 63.670(i) [G]§ 63.670(j) [G]§ 63.670(j) § 63.670(l)(5)(ii) [G]§ 63.670(m) [G]§ 63.671(a) [G]§ 63.671(b) [G]§ 63.671(c) [G]§ 63.671(d) [G]§ 63.671(e)	[G]§ 63.670(h) [G]§ 63.670(i) [G]§ 63.670(j) [G]§ 63.670(o)(1) [G]§ 63.670(o)(5) § 63.670(o)(6) [G]§ 63.671(a) [G]§ 63.671(b)	[G]§ 63.670(h) [G]§ 63.670(j) § 63.670(l)(5)(ii) § 63.670(o)(2)(ii)
UFFLARE02	CD	R1111-2	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
UFFLARE02	CD	60A-1	Opacity	40 CFR Part 60,	§ 60.18(b)	Flares shall comply	§ 60.18(d)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart A	§ 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	with paragraphs (c)-(f) of § 60.18.	§ 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)		
UFFLARE02	CD	60A-2	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(iii) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4) § 60.18(f)(5)	None	None
UFFLARE02	CD	60A-3	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(ii) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
UFFLARE02	CD	63A-1	Opacity	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
UFFLARE02	CD	63A-2	Opacity	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3)	Flares shall be designed and operated with no visible emissions,	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(iii)	except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.			
UFFLARE02	CD	63A-3	Opacity	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(ii)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
U_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	§ 60.482-1(f)(1) § 60.482-1(f)(2) [G]§ 60.482-1(f)(3) § 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.486(k) § 60.562-2(d) § 60.562-2(e)				
U_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-6(a)(1) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
U_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-5(a) [G]§ 60.482-5(b) § 60.482-5(c) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
U_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-4(a) § 60.482-4(b)(1) § 60.482-4(c) § 60.482-4(d)(1) § 60.482-4(d)(2) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.562-2(d) § 60.562-2(e)				
U_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-3(a) [G]§ 60.482-3(b) § 60.482-3(c) § 60.482-3(d) § 60.482-3(e)(1) § 60.482-3(e)(2) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) § 60.482-3(h) [G]§ 60.482-3(i) § 60.482-3(j) § 60.482-9(a) § 60.482-9(b) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements as stated in §60.482-3 for compressors.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
U_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-2(a)(2) § 60.482-2(b)(1) [G]§ 60.482-2(b)(2) § 60.482-2(c)(1) [G]§ 60.482-2(c)(2) § 60.482-2(d) [G]§ 60.482-2(d)(1) § 60.482-2(d)(2) § 60.482-2(d)(3) [G]§ 60.482-2(d)(4) [G]§ 60.482-2(d)(5)	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	§ 60.482-1(f)(1) § 60.482-1(f)(2) [G]§ 60.482-1(f)(3) § 60.482-2(a)(1) [G]§ 60.482-2(b)(2) [G]§ 60.482-2(d)(4) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) § 60.486(f) [G]§ 60.486(h) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-2(d)(6) [G]§ 60.482-2(e) § 60.482-2(f) [G]§ 60.482-2(g) § 60.482-2(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)				
U_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
U_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d)	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)				
U_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
U_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(d) § 60.486(k) § 60.562-2(e)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(5) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
U_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) [G]§ 60.482-1(e) § 60.486(k)	Comply with the requirements in as stated in §60.482-1(e) for equipment in VOC service < 300 hours/year.	None	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(6) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
U_FUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.482-9(f) § 60.486(k) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid or heavy-liquid service.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.562-2(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.562-2(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.562-2(e) § 60.565(l)
U_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-8a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	At a pressure relief device in light liquid or heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d) [G]§ 60.485a(e)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
U_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-8a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2)	At a valve in heavy liquid service, if an instrument reading of 10,000 ppm or greater is	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.482-9a(c) § 60.482-9a(c)(1) § 60.482-9a(e) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	measured, a leak is detected.	§ 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
U_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-8a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.482-9a(c) § 60.482-9a(c)(1) § 60.482-9a(c)(2) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	At a connector in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
U_FUG	EU	60VVA-	VOC	40 CFR Part 60,	§ 60.482-4a(a)	Except during	§ 60.482-1a(g)	§ 60.482-1a(g)	§ 60.487a(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		Subpart VVa	§ 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-4a(b)(1) § 60.482-4a(b)(2) § 60.482-4a(c) § 60.482-4a(d)(1) § 60.482-4a(d)(2) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	pressure releases, each pressure relief device in gas/vapor service shall be operated with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as determined by the methods specified in §60.485a(c).	§ 60.482-4a(b)(2) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d)	§ 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) § 60.486a(e)(10) § 60.486a(e)(3) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8)	§ 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
U_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-11a(b)(2) § 60.482-11a(b)(3) § 60.482-11a(b)(3)(i) § 60.482-11a(d) [G]§ 60.482-11a(e) [G]§ 60.482-11a(f)(1) § 60.482-11a(f)(2) § 60.482-11a(g) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	If an instrument reading greater than or equal to 500 ppm is measured in connectors in gas and vapor and light liquid service, a leak is detected.	§ 60.482-11a(a) § 60.482-11a(b) § 60.482-11a(b)(1) § 60.482-11a(b)(3) § 60.482-11a(b)(3)(ii) [G]§ 60.482-11a(b)(3)(iii) § 60.482-11a(b)(3)(iv) § 60.482-11a(c) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(e)	§ 60.482-11a(b)(3)(v) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8) § 60.486a(e)(9) § 60.486a(f) § 60.486a(f)(1)	§ 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(5) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ix) § 60.487a(c)(2)(vii) § 60.487a(c)(2)(viii) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
U_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-5a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-5a(b) § 60.482-5a(c) § 60.485a(b) § 60.485a(f)	Each sampling connection system shall be equipped with a closed-purge, closed-loop, or closed-vent system, except as provided in	§ 60.482-1a(g) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	§60.482–1a(c) and paragraph (c) of this section.			§ 60.487a(c)(4) § 60.487a(e)
U_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-3a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-3a(b) § 60.482-3a(c) § 60.482-3a(d) § 60.482-3a(e)(2) § 60.482-3a(f) [G]§ 60.482-3a(g) § 60.482-3a(h) [G]§ 60.482-3a(i) § 60.482-3a(j) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	Each compressor shall be equipped with a seal system that includes a barrier fluid system and that prevents leakage of VOC to the atmosphere, except as provided in §60.482–3a(c) and paragraphs (h), (i), and (j) of this section.	§ 60.482-1a(g) § 60.482-3a(e)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8) [G]§ 60.486a(h)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(4) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(2)(v) § 60.487a(c)(2)(vi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
U_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	[G]§ 60.482-1a(e) § 60.482-1a(a) § 60.482-1a(b) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	Equipment that an owner or operator designates as being in VOC service less than 300 hours (hr)/yr is excluded from the requirements of §§ 60.482-2a through 60.482-11a if it is identified as required in §60.486a(e)(6) and	[G]§ 60.485a(b)(1) § 60.485a(b)(2)	§ 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) § 60.486a(e)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						it meets any of the conditions specified in paragraphs (e)(1) through (3) of this section. §60.482-1a(e)(1)-(3)			
U_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-7a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-7a(a)(1) [G]§ 60.482-7a(d) [G]§ 60.482-7a(e) [G]§ 60.482-7a(f) [G]§ 60.482-7a(g) [G]§ 60.482-7a(h) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	At a valve in gas vapor service if an instrument reading of 500 ppm or greater is measured, a leak is detected.	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g) § 60.482-7a(a)(1) [G]§ 60.482-7a(a)(2) [G]§ 60.482-7a(c) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(e)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1) § 60.486a(f)(2)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(2) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ii) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
U_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-1a(d) § 60.482-1a(a) § 60.482-1a(b) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	Equipment that is in vacuum service is excluded from the requirements of §60.482-2a to §60.482-10a, if it is identified as required in §60.486a(e)(5).	[G]§ 60.485a(b)(1) § 60.485a(b)(2)	§ 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) § 60.486a(e)(5)	None
U_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-8a(b) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e)	At a pump in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-8a(a) § 60.482-8a(a)(2) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(d) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	detected.	[G]§ 60.485a(d)	§ 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
U_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	[G]§ 60.482-2a(b)(1) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-2a(b)(2) § 60.482-2a(b)(2)(ii) § 60.482-2a(c)(1) [G]§ 60.482-2a(c)(2) § 60.482-2a(d) [G]§ 60.482-2a(d)(1) § 60.482-2a(d)(2) § 60.482-2a(d)(3) [G]§ 60.482-2a(d)(6) [G]§ 60.482-2a(e) § 60.482-2a(f) [G]§ 60.482-2a(g) § 60.482-2a(h) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(d) § 60.482-9a(f) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1)	The instrument reading that defines a leak in a pump in light liquid service is 5,000 parts per million (ppm) or greater for pumps handling polymerizing monomers or 2,000 ppm or greater for all other pumps, as specified in paragraphs (b)(1)(i) and (ii) of this section. §60.482-2a(b)(1)(i)-(ii)	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g) § 60.482-2a(a)(1) § 60.482-2a(a)(2) § 60.482-2a(b)(2)(i) [G]§ 60.482-2a(d)(4) [G]§ 60.482-2a(d)(5) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(e)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) § 60.486a(e)(7) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1) [G]§ 60.486a(h)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(3) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(iii) § 60.487a(c)(2)(iv) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.486a(a)(2) § 60.486a(k)				
U_FUG	EU	60VVA-ALL	VOC	40 CFR Part 60, Subpart VVa	§ 60.482-6a(a)(1) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-6a(a)(2) § 60.482-6a(b) § 60.482-6a(c) § 60.482-6a(d) § 60.482-6a(e) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve, except as provided in §60.482-1a(c) and paragraphs (d) and (e) of this section.	§ 60.482-1a(g) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
U_FUG	EU	63FFFF-ALL	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a)-Table 6 § 63.1019(d) § 63.1022(a) § 63.1022(b) § 63.1022(b)(1) § 63.1022(b)(3) § 63.1022(b)(4) § 63.1022(b)(5) § 63.1022(c)(1) [G]§ 63.1022(c)(2) § 63.1022(d)(1) § 63.1022(e) § 63.1023(a) § 63.1023(e)(1) § 63.1024(a) [G]§ 63.1024(c) [G]§ 63.1024(d) § 63.1024(e) § 63.1025(a)(1) § 63.1025(b)(2) [G]§ 63.1025(b)(4) § 63.1025(d)(1)	For equipment in organic HAP service, comply with the requirements of 40 CFR Part 63, Subpart UU except as specified in 63.2480.	[G]§ 63.1022(c)(4) § 63.1023(a) [G]§ 63.1023(a)(1) § 63.1023(a)(2)(i) § 63.1023(a)(2)(iii) [G]§ 63.1023(b) [G]§ 63.1023(c) § 63.1023(d) § 63.1025(a)(2) § 63.1025(b) § 63.1025(b)(1) [G]§ 63.1025(b)(3) [G]§ 63.1025(b)(4) [G]§ 63.1025(c) [G]§ 63.1025(d)(2) [G]§ 63.1025(e) [G]§ 63.1026(b) [G]§ 63.1026(c) § 63.1026(d) [G]§ 63.1026(e)(1) § 63.1026(e)(4) § 63.1026(e)(5)	§ 63.1022(b)(5) § 63.1022(c)(3) [G]§ 63.1022(c)(4) § 63.1022(d)(2) [G]§ 63.1022(f) § 63.1023(e)(2) [G]§ 63.1024(d) [G]§ 63.1024(f) [G]§ 63.1025(b)(3) [G]§ 63.1025(b)(4) [G]§ 63.1026(b) [G]§ 63.1026(e)(1) [G]§ 63.1027(b) [G]§ 63.1028(e)(1) § 63.1031(d)(2) [G]§ 63.1035(d)(2) § 63.1035(d)(3) [G]§ 63.1035(e) § 63.1038(a) [G]§ 63.1038(b) [G]§ 63.1038(c)(1) [G]§ 63.1038(c)(2)	[G]§ 63.1025(b)(4) § 63.1039(a) [G]§ 63.1039(a)(1) § 63.1039(b) [G]§ 63.1039(b)(1) § 63.1039(b)(2) § 63.1039(b)(3) § 63.1039(b)(4) § 63.1039(b)(5) § 63.1039(b)(6) § 63.1039(b)(8) § 63.2515(a) § 63.2515(b)(2) § 63.2515(c) § 63.2515(d) § 63.2520(a) [G]§ 63.2520(b) [G]§ 63.2520(d) § 63.2520(e) § 63.2520(e)(1) [G]§ 63.2520(e)(15) § 63.2520(e)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.1026(b) [G]§ 63.1026(c) § 63.1026(d) [G]§ 63.1026(e)(1) § 63.1026(e)(2) [G]§ 63.1027(b) § 63.1027(d) [G]§ 63.1028(c) § 63.1028(d) [G]§ 63.1028(e)(1) § 63.1028(e)(2) § 63.1028(e)(6) [G]§ 63.1029 [G]§ 63.1031(b) § 63.1031(c) § 63.1031(d)(1) [G]§ 63.1031(f) § 63.1032(b) [G]§ 63.1032(c) § 63.1032(d) [G]§ 63.1033 [G]§ 63.1035(a) § 63.1035(b) § 63.1035(c) § 63.1035(d) § 63.1035(d)(1) [G]§ 63.1035(d)(5) [G]§ 63.1035(d)(7) [G]§ 63.1035(d)(8) § 63.2450(a)(2) [G]§ 63.2480(b) § 63.2480(e) § 63.2480(e)(1) [G]§ 63.2480(e)(2) [G]§ 63.2480(e)(3) [G]§ 63.2480(e)(6) [G]§ 63.2480(e)(7) [G]§ 63.2480(f)(18)		§ 63.1026(e)(6) [G]§ 63.1027(b) § 63.1027(c) [G]§ 63.1027(e) [G]§ 63.1028(c) [G]§ 63.1028(e)(1) § 63.1028(e)(4) § 63.1028(e)(5) § 63.1028(e)(7) [G]§ 63.1029 § 63.1031(c) [G]§ 63.1035(d)(2) § 63.1035(d)(4) [G]§ 63.1035(d)(6) [G]§ 63.2480(e)(2) [G]§ 63.2480(e)(3)	§ 63.1038(c)(3) [G]§ 63.1038(c)(4) [G]§ 63.1038(c)(6) [G]§ 63.1038(c)(7) [G]§ 63.2480(e)(3) [G]§ 63.2480(e)(6) [G]§ 63.2480(e)(7) § 63.2525(a) [G]§ 63.2525(q) § 63.2525(t)	§ 63.2520(e)(3) § 63.2520(e)(5) § 63.2520(e)(5)(i) [G]§ 63.2520(e)(5)(ii) § 63.2520(e)(9) [G]§ 63.2520(h) [G]§ 63.2520(i)
U_FUG	EU	63H-ALL	112(B)	40 CFR Part 63,	[G]§ 63.168	Standards: Valves	[G]§ 63.168	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart H	§ 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h)	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.171				
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c)	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171		[G]§ 63.180(d)	[G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
U_FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
U_FUG	EU	63YY-ALL	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103(e)-Table 7.f.1 § 63.1019(d) § 63.1022(a) § 63.1022(b) § 63.1022(b)(1) § 63.1022(b)(3) § 63.1022(b)(4) § 63.1022(b)(5) § 63.1022(c)(1) [G]§ 63.1022(c)(2) § 63.1022(d)(1) § 63.1022(e) § 63.1023(a) § 63.1023(e)(1) § 63.1024(a) [G]§ 63.1024(c) [G]§ 63.1024(d) § 63.1024(e) § 63.1025(a)(1) § 63.1025(b)(2) [G]§ 63.1025(b)(4) § 63.1025(d)(1)	For equipment defined in Å,Å§63.1101 that contains or contacts > 5 % by wt organic HAP and the equipment is not in vacuum service, comply with the requirements of subpart UU.	[G]§ 63.1022(c)(4) § 63.1023(a) [G]§ 63.1023(a)(1) § 63.1023(a)(2)(i) § 63.1023(a)(2)(iii) [G]§ 63.1023(b) [G]§ 63.1023(c) § 63.1023(d) § 63.1025(a)(2) § 63.1025(b) § 63.1025(b)(1) [G]§ 63.1025(b)(3) [G]§ 63.1025(b)(4) [G]§ 63.1025(c) [G]§ 63.1025(d)(2) [G]§ 63.1025(e) [G]§ 63.1026(b) [G]§ 63.1026(c) § 63.1026(d) [G]§ 63.1026(e)(1) § 63.1026(e)(4) § 63.1026(e)(5) § 63.1026(e)(6)	§ 63.1022(b)(5) § 63.1022(c)(3) [G]§ 63.1022(c)(4) § 63.1022(d)(2) [G]§ 63.1022(f) § 63.1023(e)(2) [G]§ 63.1024(d) [G]§ 63.1024(f) [G]§ 63.1025(b)(3) [G]§ 63.1025(b)(4) [G]§ 63.1026(b) [G]§ 63.1026(e)(1) [G]§ 63.1027(b) [G]§ 63.1028(e)(1) § 63.1031(d)(2) [G]§ 63.1035(d)(2) § 63.1035(d)(3) [G]§ 63.1035(e) § 63.1038(a) [G]§ 63.1038(b) [G]§ 63.1038(c)(1) [G]§ 63.1038(c)(2) § 63.1038(c)(3)	[G]§ 63.1025(b)(4) § 63.1039(a) [G]§ 63.1039(a)(1) § 63.1039(b) [G]§ 63.1039(b)(1) § 63.1039(b)(2) § 63.1039(b)(3) § 63.1039(b)(4) § 63.1039(b)(5) § 63.1039(b)(6) § 63.1039(b)(8) § 63.1109(b) § 63.1110(a) § 63.1110(a)(1) [G]§ 63.1110(a)(10) § 63.1110(a)(2) § 63.1110(a)(4) § 63.1110(a)(5) § 63.1110(a)(6) § 63.1110(a)(7) § 63.1110(a)(8) § 63.1110(b)(1) § 63.1110(b)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.1026(b) [G]§ 63.1026(c) § 63.1026(d) [G]§ 63.1026(e)(1) § 63.1026(e)(2) [G]§ 63.1027(b) § 63.1027(d) [G]§ 63.1028(c) § 63.1028(d) [G]§ 63.1028(e)(1) § 63.1028(e)(2) § 63.1028(e)(6) [G]§ 63.1029 [G]§ 63.1031(b) § 63.1031(c) § 63.1031(d)(1) [G]§ 63.1031(f) § 63.1032(b) [G]§ 63.1032(c) § 63.1032(d) [G]§ 63.1033 [G]§ 63.1035(a) § 63.1035(b) § 63.1035(c) § 63.1035(d) § 63.1035(d)(1) [G]§ 63.1035(d)(5) [G]§ 63.1035(d)(7) [G]§ 63.1035(d)(8) [G]§ 63.1100(d)(5) § 63.1103(e)(1)(i)(D) § 63.1103(e)(3) § 63.1107(a) § 63.1107(b) § 63.1107(c) § 63.1107(d) § 63.1107(h) § 63.1107(h)(1) [G]§ 63.1107(h)(2) [G]§ 63.1107(h)(3)	[G]§ 63.1027(b) § 63.1027(c) [G]§ 63.1027(e) [G]§ 63.1028(c) [G]§ 63.1028(e)(1) § 63.1028(e)(4) § 63.1028(e)(5) § 63.1028(e)(7) [G]§ 63.1029 § 63.1031(c) [G]§ 63.1035(d)(2) § 63.1035(d)(4) [G]§ 63.1035(d)(6) [G]§ 63.1107(h)(2) [G]§ 63.1107(h)(3) [G]§ 63.1108(b)(4)(i) § 63.1108(b)(4)(ii)	[G]§ 63.1038(c)(4) [G]§ 63.1038(c)(6) [G]§ 63.1038(c)(7) [G]§ 63.1107(h)(3) [G]§ 63.1107(h)(6) [G]§ 63.1107(h)(7) § 63.1109(a) § 63.1109(b) § 63.1109(c) § 63.1109(d)	[G]§ 63.1110(c) [G]§ 63.1110(d) [G]§ 63.1110(e) [G]§ 63.1110(f) [G]§ 63.1110(g) [G]§ 63.1110(h) [G]§ 63.1111(b)	

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.1107(h)(6) [G]§ 63.1107(h)(7) § 63.1107(h)(8) [G]§ 63.1108(a)(4) § 63.1108(a)(5) § 63.1108(a)(6) § 63.1108(a)(7) § 63.1108(b)(3) § 63.1108(b)(4) § 63.1108(b)(4)(iii) § 63.1108(b)(5) § 63.1108(c) [G]§ 63.1108(d) [G]§ 63.1111(a) § 63.1112(a)(1) § 63.1112(b)(1)				
U_LAB	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(c)(1)(B) § 115.127(c)(1)	A vent gas stream having a combined weight of the VOC or classes of compounds specified in §115.121(c)(1)(B)-(C) of this title equal to or less than 100 lbs in a continuous 24-hour period is exempt from the requirements of §115.121(c)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
WASHUNLO AD	EU	R5212-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(b)(2) § 115.212(b)(2) § 115.214(b)(1)(B) § 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						vapor pressure less than 1.5 psia is exempt from the requirements of this division except as specified.			
WASHUNLO AD	EU	63EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2343(a) § 63.2334(a) § 63.2338(b)(2) § 63.2342(a)(2) § 63.2350(a) § 63.2350(d)	For each transfer rack that only unloads organic liquids, keep documentation that verifies the transfer rack is not required to be controlled.	None	§ 63.2343(a)	None
ZMTK01	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(c)(1)	Tanks shall not store VOC, other than crude oil or condensate, unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(b).	** See Periodic Monitoring Summary	None	None
ZTD08	EU	R5112-26	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(c)(1)	Tanks shall not store VOC, other than crude oil or condensate, unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(b).	** See Periodic Monitoring Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ZTD08	EU	R5112-26A	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.113 § 115.910	Alternate means of compliance with the applicable control requirements or exemption criteria in this division may be approved per 30 TAC §115.910, if emission reductions are substantially equal.	** See Alternative Requirement	None	None
ZTD08	EU	R5112-27	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(c)(1)	Tanks shall not store VOC, other than crude oil or condensate, unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(b).	** See Periodic Monitoring Summary	None	None
ZTD08	EU	R5112-30	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(c)(1)	Tanks shall not store VOC, other than crude oil or condensate, unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(b).	** See Periodic Monitoring Summary	None	None
ZTD08	EU	63FFFF-5	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table 4.1.b.iii § 63.11(b)	For each Group 1 storage tank for which the maximum	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2470(c)(1)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2470(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.2450(b) § 63.2470(a) § 63.2470(d) [G]§ 63.2470(f) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.987(a) § 63.987(b)(1) § 63.987(b)(3) [G]§ 63.997(c)(1) § 63.997(c)(3)	true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you may reduce total organic HAP emissions by venting emissions through a closed vent system to a flare.	[G]§ 63.2470(f) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) [G]§ 63.987(b)(3)(i) § 63.987(b)(3)(ii) § 63.987(b)(3)(iii) § 63.987(b)(3)(iv) § 63.987(c) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i) § 63.997(c)(3)(ii)	§ 63.2470(c)(1) § 63.2470(f)(3) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(c) § 63.998(a)(1) [G]§ 63.998(a)(1)(i) § 63.998(a)(1)(ii) § 63.998(a)(1)(iii)(A) § 63.998(a)(1)(iii)(B) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.997(c)(3) § 63.998(a)(1)(iii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(3) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv) [G]§ 63.999(d)(1) [G]§ 63.999(d)(2)
ZTD08	EU	63FFFF-5A	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table 4.1.b.iii § 63.2450(b) [G]§ 63.2450(e)(5) § 63.2470(a) § 63.2470(d) [G]§ 63.2470(f) § 63.2535(m)(2) [G]§ 63.670 § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you may reduce total organic HAP emissions by venting emissions through a closed vent system to a flare.	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2470(c)(1) [G]§ 63.2470(f) [G]§ 63.671 § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.2470(c)(1) § 63.2470(f)(3) [G]§ 63.2525(m) [G]§ 63.670 [G]§ 63.671 § 63.983(b) [G]§ 63.983(d)(2) [G]§ 63.998(d)(1) § 63.998(d)(5)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2470(d) § 63.2520(d)(3) [G]§ 63.2520(e)(11) [G]§ 63.670 [G]§ 63.671 § 63.999(c)(1) § 63.999(c)(2)(i)
ZTD08	EU	63FFFF-6	112(B)	40 CFR Part 63,	§ 63.2470(a)-Table	For each Group 1	[G]§ 63.115(d)(2)(v)	§ 63.2450(k)(6)	§ 63.2450(q)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart FFFF	4.1.b.ii § 63.2450(b) § 63.2450(i)(1) § 63.2450(i)(2) § 63.2470(a) § 63.2470(d) [G]§ 63.2470(f) § 63.982(c) § 63.982(c)(1) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you may reduce total HAP emissions to less than or equal to 20 ppmv of TOC or organic HAP and less than or equal to 20 ppmv of hydrogen halide and halogen HAP by venting emissions through a closed vent system to any combination of control devices (excluding a flare).	§ 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2470(c)(1) [G]§ 63.2470(f) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) § 63.997(e)(2)(i)(B) § 63.997(e)(2)(ii) § 63.997(e)(2)(iii) § 63.997(e)(2)(iii)(A) [G]§ 63.997(e)(2)(iii)(B)	§ 63.2470(c)(1) § 63.2470(f)(3) § 63.2525(g) § 63.2525(h) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(iii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2470(d) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 63.997(e)(2)(iii)(C) [G]§ 63.997(e)(2)(iii)(D) [G]§ 63.997(e)(2)(iii)(E)		
ZTD08	EU	63FFFF-7	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table 4.1.b.ii § 63.2450(b) § 63.2470(a) § 63.2470(d) [G]§ 63.2470(f) § 63.982(c) § 63.982(c)(1) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.988(a)(3) § 63.988(b)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) § 63.997(c)(3)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you may reduce total HAP emissions by greater than or equal to 95 percent by weight by venting emissions through a closed vent system to any combination of control devices (excluding a flare).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2470(c)(1) [G]§ 63.2470(f) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii)	§ 63.2450(k)(6) § 63.2470(c)(1) § 63.2470(f)(3) § 63.2525(g) § 63.2525(h) § 63.983(b) [G]§ 63.983(d)(2) § 63.996(c)(2)(ii) § 63.998(a)(2)(ii)(B)(5) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.2470(d) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)
ZTD08	EU	63FFFF-8	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table 4.1.b.ii § 63.2450(b) § 63.2470(a) § 63.2470(d) [G]§ 63.2470(f) § 63.982(c) § 63.982(c)(1) § 63.983(a)(1)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you may reduce	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2470(c)(1)	§ 63.2450(k)(6) § 63.2470(c)(1) § 63.2470(f)(3) § 63.2525(g) § 63.2525(h) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii)	§ 63.2450(q) § 63.2470(d) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	total HAP emissions by greater than or equal to 95 percent by weight by venting emissions through a closed vent system to any combination of control devices (excluding a flare).	[G]§ 63.2470(f) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) [G]§ 63.997(e)(2)(i)(A) § 63.997(e)(2)(ii) § 63.997(e)(2)(iv) § 63.997(e)(2)(iv)(A) [G]§ 63.997(e)(2)(iv)(B) § 63.997(e)(2)(iv)(C) § 63.997(e)(2)(iv)(D) § 63.997(e)(2)(iv)(F) § 63.997(e)(2)(iv)(G) [G]§ 63.997(e)(2)(iv)(H)	§ 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	[G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)
ZTD12	EU	R5131-1	VOC	30 TAC Chapter 115, Water	§ 115.132(c)(1)	VOC water separators must	** See Periodic Monitoring Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Separation		have each compartment totally enclosed with all openings sealed. Gauging and sampling devices shall be vapor-tight except during use.			
ZTD12	EU	61FF-10	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(A) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) [G]§ 61.355(h)	§ 61.354(c) § 61.354(c)(1) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(A) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A)
ZTD12	EU	61FF-11	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 60.18 § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 60.18(f)(2) § 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) [G]§ 61.355(h)	§ 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
ZTD12	EU	61FF-11A	Benzene	40 CFR Part 61,	§ 61.347(a)(1)	Install, operate, and	§ 61.347(a)(1)(i)(A)	§ 61.356(d)	[G]§ 63.1110(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart FF	§ 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g) § 63.1095(b)(3) [G]§ 63.1103(e)(4) [G]§ 63.670	maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(b) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) [G]§ 61.355(h) [G]§ 63.671	§ 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) [G]§ 63.1109(e) [G]§ 63.670 [G]§ 63.671	§ 63.1110(e)(4) [G]§ 63.670 [G]§ 63.671
ZTD12	EU	61FF-12	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.340(d) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b)	§ 61.356(d) § 61.356(g)	None
ZTTK02	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
ZTTK03	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.			
ZTTK04	EU	R5112-20	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(c)(1) § 115.111(c)(2) § 115.112(c)(2) § 115.112(c)(2)(A) § 115.114(c)(1)(A)	Tanks shall not store VOC, other than crude oil or condensate, unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(b).	§ 115.114(c)(1)(A) ** See Periodic Monitoring Summary	None	§ 115.114(c)(1)(B)
ZTTK04	EU	60Kb-35	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
ZTTK04	EU	61FF-1	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	one of the following §61.351(a)(1)-(3):			§ 61.357(f)
ZTTK04	EU	63YY-1	112(B) HAPS	40 CFR Part 63, Subpart YY	§ 63.1103(e)- Table 7.g.1 § 61.351 § 63.1091 § 63.1095 § 63.1095(b) § 63.1095(b)(2) § 63.1103(e)(1)(i)(E) § 63.1103(e)(3) § 63.1108(a)(4)(iii) § 63.1108(a)(5) § 63.1108(a)(6) § 63.1108(a)(7) [G]§ 63.1108(b)(2) § 63.1108(b)(3) § 63.1108(b)(4) § 63.1108(b)(4)(iii) § 63.1108(b)(5) § 63.1108(c) [G]§ 63.1108(d) [G]§ 63.1111(a)	For processes that generate waste as defined in 63.1103(e)(2), comply with the waste requirements of subpart XX of this part.	§ 63.1091	§ 63.1091 § 63.1109(a) § 63.1109(b) § 63.1109(c) § 63.1109(d) § 63.1111(a)	§ 63.1091 § 63.1110(a) § 63.1110(a)(1) [G]§ 63.1110(a)(10) § 63.1110(a)(2) § 63.1110(a)(4) § 63.1110(a)(5) § 63.1110(a)(6) § 63.1110(a)(7) § 63.1110(a)(8) § 63.1110(b)(1) § 63.1110(b)(2) [G]§ 63.1110(c) [G]§ 63.1110(d) [G]§ 63.1110(e) [G]§ 63.1110(f) [G]§ 63.1110(g) [G]§ 63.1110(h) [G]§ 63.1111(b)
ZTTK05	EU	R5112-20	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(c)(1) § 115.111(c)(2) § 115.112(c)(2) § 115.112(c)(2)(A) § 115.114(c)(1)(A)	Tanks shall not store VOC, other than crude oil or condensate, unless the required pressure is maintained, or they are equipped with the appropriate control device	§ 115.114(c)(1)(A) ** See Periodic Monitoring Summary	None	§ 115.114(c)(1)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specified in Table I(b).			
ZTTK05	EU	60Kb-35	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Additional Monitoring Requirements

Compliance Assurance Monitoring Summary	223
Periodic Monitoring Summary	256

CAM Summary

Unit/Group/Process Information	
ID No.: C-VENTGAS	
Control Device ID No.: UFF01A	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Control Device ID No.: UFF01B	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-10
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: C-VENTGAS	
Control Device ID No.: UFFLARE02	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-16
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: C-VENTGAS	
Control Device ID No.: USSG01A	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01B	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01C	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-20
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: If vent gas is being sent to the boiler and the boiler is not in operation, it shall be reported as a deviation.	
CAM Text: Monitor and record the periods of operation of the steam generating units or process heater. The records must be readily available for inspection.	

CAM Summary

Unit/Group/Process Information	
ID No.: E-VENTGAS	
Control Device ID No.: UFF01A	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Control Device ID No.: UFF01B	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-10
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: E-VENTGAS	
Control Device ID No.: UFFLARE02	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-16
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: E-VENTGAS	
Control Device ID No.: USSG01A	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01B	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01C	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-20
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: If vent gas is being sent to the boiler and the boiler is not in operation, it shall be reported as a deviation.	
CAM Text: Monitor and record the periods of operation of the steam generating units or process heater. The records must be readily available for inspection.	

CAM Summary

Unit/Group/Process Information	
ID No.: G-VENTGAS	
Control Device ID No.: GBX02	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-10
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: G-VENTGAS	
Control Device ID No.: GFFLARE01	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-16
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: GBD05	
Control Device ID No.: GBX02	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-10
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: GBD05	
Control Device ID No.: GFFLARE01	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-16
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPCPEBPL	
Control Device ID No.: UFF01A	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Control Device ID No.: UFF01B	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-10
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPCPEBPL	
Control Device ID No.: UFFLARE02	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-16
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPCPEBPL	
Control Device ID No.: USSG01A	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01B	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01C	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-20
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: If vent gas is being sent to the boiler and the boiler is not in operation, it shall be reported as a deviation.	
CAM Text: Monitor and record the periods of operation of the steam generating units or process heater. The records must be readily available for inspection.	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPCPEBPV	
Control Device ID No.: UFF01A	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Control Device ID No.: UFF01B	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-10
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPCPEBPV	
Control Device ID No.: UFFLARE02	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-16
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPCPEBPV	
Control Device ID No.: USSG01A	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01B	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01C	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-20
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: If vent gas is being sent to the boiler and the boiler is not in operation, it shall be reported as a deviation.	
CAM Text: Monitor and record the periods of operation of the steam generating units or process heater. The records must be readily available for inspection.	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPCPECPV	
Control Device ID No.: UFF01A	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Control Device ID No.: UFF01B	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-10
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPCPECPV	
Control Device ID No.: UFFLARE02	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-16
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPCPECPV	
Control Device ID No.: USSG01A	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01B	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01C	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-20
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: If vent gas is being sent to the boiler and the boiler is not in operation, it shall be reported as a deviation.	
CAM Text: Monitor and record the periods of operation of the steam generating units or process heater. The records must be readily available for inspection.	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPEMPEBPL	
Control Device ID No.: UFF01A	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Control Device ID No.: UFF01B	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-10
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPEMPEBPL	
Control Device ID No.: UFFLARE02	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-16
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPEMPEBPL	
Control Device ID No.: USSG01A	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01B	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01C	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-20
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: If vent gas is being sent to the boiler and the boiler is not in operation, it shall be reported as a deviation.	
CAM Text: Monitor and record the periods of operation of the steam generating units or process heater. The records must be readily available for inspection.	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPEMPEBPV	
Control Device ID No.: UFF01A	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Control Device ID No.: UFF01B	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-10
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPEMPEBPV	
Control Device ID No.: UFFLARE02	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-16
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPEMPEBPV	
Control Device ID No.: USSG01A	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01B	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01C	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-20
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: If vent gas is being sent to the boiler and the boiler is not in operation, it shall be reported as a deviation.	
CAM Text: Monitor and record the periods of operation of the steam generating units or process heater. The records must be readily available for inspection.	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPEMPECPV	
Control Device ID No.: UFF01A	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Control Device ID No.: UFF01B	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-10
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPEMPECPV	
Control Device ID No.: UFFLARE02	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-16
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPEMPECPV	
Control Device ID No.: USSG01A	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01B	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01C	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-20
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: If vent gas is being sent to the boiler and the boiler is not in operation, it shall be reported as a deviation.	
CAM Text: Monitor and record the periods of operation of the steam generating units or process heater. The records must be readily available for inspection.	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPHON-PV	
Control Device ID No.: GBX02	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-10
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPHON-PV	
Control Device ID No.: GFFLARE01	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-16
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: O-VENTGAS	
Control Device ID No.: UFF01A	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Control Device ID No.: UFF01B	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-10
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: O-VENTGAS	
Control Device ID No.: UFFLARE02	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-16
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: O-VENTGAS	
Control Device ID No.: USSG01A	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01B	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01C	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-20
Pollutant: VOC	Main Standard: § 115.122(c)(1)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: If vent gas is being sent to the boiler and the boiler is not in operation, it shall be reported as a deviation.	
CAM Text: Monitor and record the periods of operation of the steam generating units or process heater. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GAD03	
Control Device ID No.: GAD09A-D	Control Device Type: Carbon adsorption system (non-regenerative)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-14
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Carbon Replacement Interval	
Minimum Frequency: At each replacement of carbon canister	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if the carbon is not replaced within the maximum replacement interval.	
<p>Periodic Monitoring Text: Monitor and record the replacement time interval of the carbon canister(s), as determined by the maximum design flow rate and organic concentration in the gas stream vented to the carbon adsorption system. Establish a maximum carbon replacement interval using the most recent performance test, manufacturer's recommendations, engineering calculations, and/or historical data. Any data, collected for a period which exceeds the maximum carbon replacement interval shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GBX02	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if visible emissions are observed or if opacity exceeds 15% averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRPBLRSTK	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if visible emissions are observed or if opacity exceeds 15% averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRPFURNSTK	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if visible emissions are observed or if opacity exceeds 15% averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRPHFOTANK	
Control Device ID No.: UFFLARE02	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-21
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRPHFOTANK	
Control Device ID No.: UFF01A	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Control Device ID No.: UFF01B	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-22
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRPHFOTANK	
Control Device ID No.: USSG01A	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01B	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01C	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-25
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: If vent gas is being sent to the boiler and the boiler is not in operation, it shall be reported as a deviation.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRPSKIMMER	
Control Device ID No.: ZWSRCO1A	Control Device Type: Catalytic incinerator
Control Device ID No.: ZWSRCO1B	Control Device Type: Catalytic incinerator
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5131-2
Pollutant: VOC	Main Standard: § 115.132(c)(3)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: N/A	
Deviation Limit: A minimum catalyst bed combustion temperature of 700°F shall be maintained prior to initial stack testing. After testing, the six-minute average temperature shall be not less than the hourly average maintained during the last satisfactory stack test.	
Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: RAD02	
Control Device ID No.: UFFLARE02	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-11
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: UFF01A	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if visible emissions are observed or if opacity exceeds 15% averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: UFF01B	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if visible emissions are observed or if opacity exceeds 15% averaged over a six-minute period.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: ZMTK01	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-4
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if the applicant fails to keep a record of the tank construction specifications.	
<p>Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: ZMTK01	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-4
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if the repairs are not completed prior to refilling the storage vessel.	
<p>Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: ZTD08	
Control Device ID No.: UFFLARE02	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-26
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if a pilot flame is not present.	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: ZTD08	
Control Device ID No.: UFF01A	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Control Device ID No.: UFF01B	Control Device Type: Thermal incinerator (direct flame incinerator/regenerative thermal oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-27
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: N/A	
Deviation Limit: A minimum combustion temperature of 1400 °F shall be maintained before establishing a minimum combustion temperature using the most recent performance test or stack testing data.	
Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: ZTD08	
Control Device ID No.: USSG01A	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01B	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: USSG01C	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-30
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: If vent gas is being sent to the boiler and the boiler is not in operation, it shall be reported as a deviation.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: ZTD12	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5131-1
Pollutant: VOC	Main Standard: § 115.132(c)(1)
Monitoring Information	
Indicator: VOC Concentration	
Minimum Frequency: Annually	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if any monitoring data greater than the maximum VOC limit of 10,000 ppmv.	
<p>Periodic Monitoring Text: Measure and record the VOC concentration using a portable analyzer to monitor VOC concentration around the immediate area of the compartment in accordance with 40 CFR Part 60, Appendix A, Method 21. Each potential leak interface (i.e., a location where organic vapor leakage could occur) on the cover and associated closer devices shall be checked. Potential leak interfaces that are associated with covers and closure devices include, but are not limited to: the interface of the cover and its foundation mounting; the periphery of any opening on the cover and its associated closure device; and the sealing seat interface on a spring-loaded pressure relief valve. The owner or operator may choose to adjust the detection instrument readings for the background organic concentration level.</p> <p>The monitoring instrumentation shall be maintained and operated in accordance with manufacturer's specifications or other written procedures.</p> <p>Any monitoring data greater than the maximum VOC limit indicated in the Deviation Limit above shall be considered and reported as a deviation as required by § 122.145(2).</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: ZTTK04	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-20
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: ZTTK05	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-20
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: N/A	
Deviation Limit: A deviation shall be reported if the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Permit Shield

Permit Shield	276
----------------------------	------------

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
ADMINGEN	N/A	30 TAC Chapter 117, Subchapter B	Emission unit is not located in the ozone nonattainment area.
ADMINGENTK	N/A	30 TAC Chapter 115, Storage of VOCs	Vessel storing VOC with a true vapor pressure less than 1.5 psia.
ADMINGENTK	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
ADMINGENTK	N/A	40 CFR Part 63, Subpart EEEE	Diesel does not meet definition of organic liquid under MACT EEEE.
C-VENTGAS	N/A	30 TAC Chapter 115, Batch Processes	Vent gas stream is not located in Beaumont/Port Arthur or Houston/Galveston area.
C-VENTGAS	N/A	30 TAC Chapter 115, HRVOC Vent Gas	Vent gas stream is not located in the Houston/Galveston/Brazoria area.
CPE-DIST	N/A	40 CFR Part 60, Subpart NNN	Any distillation unit that is subject to the provisions of NSPS DDD is not an affected facility under NSPS NNN.
CPE-REACT	N/A	40 CFR Part 60, Subpart RRR	Any reactor process that is subject to the provisions of NSPS DDD is not an affected facility under NSPS RRR.
E-VENTGAS	N/A	30 TAC Chapter 115, Batch Processes	Vent gas stream is not located in Beaumont/Port Arthur or Houston/Galveston area.
E-VENTGAS	N/A	30 TAC Chapter 115, HRVOC Vent Gas	Vent gas stream is not located in the Houston/Galveston/Brazoria area.
EPE-DIST	N/A	40 CFR Part 60, Subpart NNN	Any distillation unit that is subject to the provisions of NSPS DDD is not an affected facility under NSPS NNN.
EPE-REACT	N/A	40 CFR Part 60, Subpart RRR	Any reactor process that is subject to the

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			provisions of NSPS DDD is not an affected facility under NSPS RRR.
G-VENTGAS	N/A	30 TAC Chapter 115, HRVOC Vent Gas	Vent gas stream is not located in the Houston/Galveston/Brazoria area.
GAD03	N/A	40 CFR Part 60, Subpart Kb	Vessel capacity is less than 75 cubic meters (19,813 gallons) and operates as a process tank.
GAD03	N/A	40 CFR Part 63, Subpart G	The unit does not meet the definition of a storage vessel since its capacity is less than 38 cubic meters and operates as a surge control vessel.
GBD06	N/A	40 CFR Part 60, Subpart Kb	Surge drum is a process tank and does not meet the definition of a storage vessel.
GBD06	N/A	40 CFR Part 63, Subpart H	Surge control vessel is routed back to the process.
GDD08	N/A	30 TAC Chapter 115, Storage of VOCs	Vessel storing VOC with a true vapor pressure less than 1.5 psia.
GDD08	N/A	40 CFR Part 60, Subpart Kb	Vessel operating as a process tank with capacity less than 151 cubic meters (39,900 gallons) and storing a VOL with a maximum TVP < 2.2 psia (15 kPa).
GDD08	N/A	40 CFR Part 63, Subpart H	Surge control vessel stores VOC with a vapor pressure less than 0.7 kPa (0.10 psia), hence it does not meet the conditions in Table 3 of MACT H.
GDD09	N/A	30 TAC Chapter 115, Storage of VOCs	Vessel storing VOC with a true vapor pressure less than 1.5 psia.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
GDD09	N/A	40 CFR Part 60, Subpart Kb	Vessel capacity is less than 75 cubic meters (19,813 gallons) and operates as a process tank.
GDD09	N/A	40 CFR Part 63, Subpart G	The unit does not meet the definition of a storage vessel since its capacity is less than 38 cubic meters and operates as a surge control vessel.
GDT01	N/A	40 CFR Part 63, Subpart HH	Does not meet the definition of Glycol Dehydration Unit and is not located at an oil and natural gas production facility.
GED04	N/A	30 TAC Chapter 115, Storage of VOCs	Vessel storing VOC with a true vapor pressure less than 1.5 psia.
GED04	N/A	40 CFR Part 60, Subpart Kb	Vessel capacity is less than 75 cubic meters (19,813 gallons) and operates as a process tank.
GED04	N/A	40 CFR Part 63, Subpart G	The unit does not meet the definition of a storage vessel since its capacity is less than 38 cubic meters and operates as a surge control vessel.
GFFLARE01	N/A	30 TAC Chapter 115, HRVOC Vent Gas	Flare is not located in the Houston/ Galveston/Brazoria area.
GREFUSTN	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Facility is a motor vehicle fuel dispensing facility.
GREFUSTN	N/A	40 CFR Part 63, Subpart CCCCCC	Gasoline dispensing facility is not located at an area source.
GRPADDITIVE	CLB03, CLDC06, CLFAN04, ELB01, ELB02, ELB03, ELB04, ELB05,	30 TAC Chapter 115, Vent Gas Controls	The vent gas stream does not contain volatile organic compounds (VOC).

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
	ELDC06, ELFAN01, ELFAN04		
GRPADDITIVE	CLB03, CLDC06, CLFAN04, ELB01, ELB02, ELB03, ELB04, ELB05, ELDC06, ELFAN01, ELFAN04	40 CFR Part 63, Subpart FFFF	The batch process vent gas stream does not contain Hazardous Air Pollutant (HAP).
GRPBOILER	USSG01A, USSG01B, USSG01C	30 TAC Chapter 112, Sulfur Compounds	Boilers do not burn liquid fuels.
GRPBOILER	USSG01A, USSG01B, USSG01C	30 TAC Chapter 117, Subchapter B	Boilers are not located in ozone nonattainment area.
GRPCATLYST	CBFIL01, CCFIL04, CCFIL05, CCFIL06, EBFIL01, ECFIL04, ECFIL05, ECFIL06	30 TAC Chapter 115, Vent Gas Controls	The vent gas stream does not contain volatile organic compounds (VOC).
GRPCATLYST	CBFIL01, CCFIL04, CCFIL05, CCFIL06, EBFIL01, ECFIL04, ECFIL05, ECFIL06	40 CFR Part 63, Subpart FFFF	The batch process vent gas stream does not contain Hazardous Air Pollutant (HAP).
GRPCPEBPV	CADR04A, CADR04B, CCD21, CCD22, CCD23, CCD24, CCGT01, CEC01A, CED01, CED02, CED03, CEE01, CEFIL01, CEMEM01A	40 CFR Part 60, Subpart DDD	MACT FFFF MCPU contains equipment that is also subject to the provisions of NSPS DDD and the site is electing to comply with the requirements for Group 1 process vents to all such equipment in the MCPU.
GRPCPECPV	CCT01, CDD03, CEMEM01B	40 CFR Part 60, Subpart DDD	MACT FFFF MCPU contains equipment that is also subject to the provisions of NSPS DDD and the site is electing to comply with the requirements for Group 1 process vents to all such equipment in the MCPU.
GRPEMPEBPV	EADR04A, EADR04B, EADR05A, EADR05B, EADR06, EADR07A, EADR07B, EADR09, EADR10, ECD21, ECD22, ECD23, ECD24, ECGT01, EEC01A, EED01, EED02,	40 CFR Part 60, Subpart DDD	MACT FFFF MCPU contains equipment that is also subject to the provisions of NSPS DDD and the site is electing to comply with the requirements for Group 1 process vents to all such equipment in the MCPU.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
	EED03, EEE01, EEFIL01, EEMEM01A		
GRPEMPECPV	ECT01, EEMEM01B	40 CFR Part 60, Subpart DDD	MACT FFFF MCPU contains equipment that is also subject to the provisions of NSPS DDD and the site is electing to comply with the requirements for Group 1 process vents to all such equipment in the MCPU.
GRPEMRGGEN	GUDGEN01, UKDGEN01, UKDGEN02	30 TAC Chapter 117, Subchapter B	Emission unit is not located in the ozone nonattainment area.
GRPEQTANK	ZWTK01, ZWTK02	40 CFR Part 60, Subpart Kb	Vessel is a process tank and does not meet the definition of a storage vessel.
GRPEXTRUD	CLDC03, ELDC03	40 CFR Part 63, Subpart FFFF	The continuous process gas stream contains less than 0.005 wt% HAP at the point of discharge to the atmosphere, as defined in 63.107(d).
GRPFURNACE	FA-F01, FB-F01, FC-F01, FD-F01, FE-F01, FF-F01, FG-F01, FH-F01	30 TAC Chapter 112, Sulfur Compounds	Furnaces do not burn liquid fuels.
GRPFURNACE	FA-F01, FB-F01, FC-F01, FD-F01, FE-F01, FF-F01, FG-F01, FH-F01	30 TAC Chapter 117, Subchapter B	Furnaces are not located in ozone nonattainment area.
GRPFURNACE	FA-F01, FB-F01, FC-F01, FD-F01, FE-F01, FF-F01, FG-F01, FH-F01	40 CFR Part 63, Subpart DDDDD	Ethylene cracking furnace covered by 40 CFR 63 Subpart YY is not subject to 40 CFR 63 Subpart DDDDD.
GRPFURNSTK	OFAF01, OFBF01, OFCF01, OFDF01, OFEF01, OFFF01, OFGF01, OFHF01	30 TAC Chapter 115, Vent Gas Controls	The combustion unit exhaust stream is not being used as a control device for any vent gas stream which originates from a non-combustion source.
GRPFWP	ZFP02B, ZFP02C	30 TAC Chapter 117, Subchapter B	Emission unit is not located in the ozone nonattainment area.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
GRPFWPTK	ZFTK02B, ZFTK02C	30 TAC Chapter 115, Storage of VOCs	Storage tank capacity less than 1,000 gallons.
GRPFWPTK	ZFTK02B, ZFTK02C	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
GRPFWPTK	ZFTK02B, ZFTK02C	40 CFR Part 63, Subpart EEEE	Diesel does not meet definition of organic liquid under MACT EEEE.
GRPGENTK	GUDGEN01TK, UKDGEN01TK, UKDGEN02TK	30 TAC Chapter 115, Storage of VOCs	Storage tank capacity less than 1,000 gallons and storing VOC with TVP less than 1.5 psia.
GRPGENTK	GUDGEN01TK, UKDGEN01TK, UKDGEN02TK	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
GRPGENTK	GUDGEN01TK, UKDGEN01TK, UKDGEN02TK	40 CFR Part 63, Subpart EEEE	Diesel does not meet definition of organic liquid under MACT EEEE.
GRPGLYTANK	GDTK01, GETK01, GETK02A, GETK02B	30 TAC Chapter 115, Storage of VOCs	Storage tank storing VOC with a true vapor pressure less than 1.5 psia.
GRPGLYTANK	GDTK01, GETK01, GETK02A, GETK02B	40 CFR Part 60, Subpart Kb	Tank capacity is greater than 151 cubic meters (39,900 gallons) and storing a VOL with a maximum TVP < 0.5 psia (3.5 kPa).
GRPGRANULE	CDDCO4, CDFAN01, CLDC01, EDDCO4, EDFAN01, ELDC01	40 CFR Part 63, Subpart FFFF	The continuous process gas stream contains less than 0.005 wt% HAP at the point of discharge to the atmosphere, as defined in 63.107(d).
GRPHONNNN	GET01, GET02	40 CFR Part 60, Subpart NNN	Process vent controlled to the levels required in §63.113(a)(1) or (a)(2) is exempt from the testing, monitoring, reporting, and recordkeeping provisions of 40 CFR part 60, subpart NNN.
GRPHONRRR	GAR01A, GAR01B, GDR02, GDR05	40 CFR Part 60, Subpart RRR	Process vent controlled to the levels required in §63.113(a)(1) or (a)(2) is exempt from the

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			testing, monitoring, reporting, and recordkeeping provisions of 40 CFR part 60, subpart RRR.
GRPLOADOUT	CMD01, CPFAN01, EMD01, EPFAN01	40 CFR Part 63, Subpart FFFF	The unit does not meet the definition of miscellaneous organic chemical manufacturing process equipment since it is at the end of a process that produces a solid material, and is downstream of the dryers.
GRPNVOC	GBD09, GBTK01, UCTK01, UTD02, UTTK04, ZTTK01	30 TAC Chapter 115, Storage of VOCs	Storage tank does not store volatile organic compounds.
GRPNVOC	GBD09, GBTK01, UCTK01, UTD02, UTTK04, ZTTK01	40 CFR Part 60, Subpart Kb	Tank does not store volatile organic liquids.
GRPPellet	CMFAN01, CMFAN02, EMFAN01, EMFAN02	40 CFR Part 63, Subpart FFFF	The continuous process gas stream contains less than 0.005 wt% HAP at the point of discharge to the atmosphere, as defined in 63.107(d).
GRPPETANK	CCD81, ELDO1, ELDO2	30 TAC Chapter 115, Storage of VOCs	Tank capacity is less than 1,000 gallons.
GRPPETANK	CCD81, ELDO1, ELDO2	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
GRPPETANK	CCD81, ELDO1, ELDO2	40 CFR Part 63, Subpart FFFF	Storage tank does not meet the definition since it does not store liquids that contain organic HAP and/or hydrogen halide.
GRPPRSTANK	ZTD09, ZTD10A, ZTD10B, ZTD10C, ZTD11A, ZTD11B	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
GRPUNLOAD	DMSUNLOAD, RLUNLOAD-A, RLUNLOAD-B, TKUNLOAD-A, TKUNLOAD-B	40 CFR Part 63, Subpart EEEE	Organic liquids are not unloaded out of transport vehicles at the transfer racks.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
MEOHLOAD	N/A	40 CFR Part 63, Subpart EEEE	Transfer racks, transport vehicles, and containers when used to conduct maintenance activities, such as liquid removal for inspections and maintenance or changeovers.
O-VENTGAS	N/A	30 TAC Chapter 115, HRVOC Vent Gas	Vent gas stream is not located in the Houston/Galveston/Brazoria area.
O_FUG	N/A	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	Synthetic organic chemical manufacturing process is not located in ozone nonattainment area.
O_FUG	N/A	40 CFR Part 61, Subpart J	Equipment subject to NESHAP J and MACT YY is required to comply only with MACT YY.
O_FUG	N/A	40 CFR Part 61, Subpart V	Equipment subject to NESHAP V and MACT YY is required to comply only with MACT YY.
PROADDITIVE	N/A	40 CFR Part 60, Subpart DDD	The vent gas stream does not contain total organic compounds (TOC).
PROCATLYST	N/A	40 CFR Part 60, Subpart DDD	The vent gas stream does not contain total organic compounds (TOC).
RAD02	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
RESIDLOAD	N/A	40 CFR Part 63, Subpart EEEE	Transfer racks, transport vehicles, and containers when used to conduct maintenance activities, such as liquid removal for inspections and maintenance or changeovers.
RLOAD-C3	N/A	40 CFR Part 63, Subpart YY	Transfer rack use vapor balance at all times and does not load HAP containing material.
SCTOTE-GLY	N/A	30 TAC Chapter 115, Storage of VOCs	Storage tank storing VOC with a true vapor

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			pressure less than 1.5 psia.
SCTOTE-GLY	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
SCTOTE-GLY	N/A	40 CFR Part 63, Subpart G	The unit does not meet the definition of a storage vessel since its capacity is less than 38 cubic meters.
TOTES	N/A	30 TAC Chapter 115, Storage of VOCs	Storage tank capacity less than 1,000 gallons.
TOTES	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
UCCT01	N/A	30 TAC Chapter 115, HRVOC Cooling Towers	Cooling tower is not located in the Houston/ Galveston/Brazoria area.
UCCT01	N/A	40 CFR Part 63, Subpart Q	Cooling tower is not operated with chromium-based water treatment chemicals.
UFFLARE01	N/A	30 TAC Chapter 115, HRVOC Vent Gas	Flare is not located in the Houston/ Galveston/Brazoria area.
UFFLARE02	N/A	30 TAC Chapter 115, HRVOC Vent Gas	Flare is not located in the Houston/ Galveston/Brazoria area.
UTD04	N/A	30 TAC Chapter 115, Storage of VOCs	Storage tank storing VOC with a true vapor pressure less than 1.5 psia.
UTD04	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 151 cubic meters (39,900 gallons) and storing a VOL with a maximum TVP < 2.2 psia (15 kPa).
ZMTK01	N/A	40 CFR Part 60, Subpart Kb	Storage vessels located at gasoline service station with capacity less than 75 cubic meters (19,813 gallons).

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
ZMTK01	N/A	40 CFR Part 63, Subpart EEEE	Gasoline does not meet definition of organic liquid under MACT EEEE.
ZMTK02	N/A	30 TAC Chapter 115, Storage of VOCs	Storage tank storing VOC with a true vapor pressure less than 1.5 psia.
ZMTK02	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
ZMTK02	N/A	40 CFR Part 63, Subpart EEEE	Diesel does not meet definition of organic liquid under MACT EEEE.
ZTTK02	N/A	30 TAC Chapter 115, Storage of VOCs	Storage tank storing VOC with a true vapor pressure less than 1.5 psia.
ZTTK02	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is greater than 151 cubic meters (39,900 gallons) and storing a VOL with a maximum TVP < 0.5 psia (3.5 kPa).
ZTTK03	N/A	30 TAC Chapter 115, Storage of VOCs	Storage tank storing VOC with a true vapor pressure less than 1.5 psia.
ZTTK03	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is greater than 151 cubic meters (39,900 gallons) and storing a VOL with a maximum TVP < 0.5 psia (3.5 kPa).
ZTTK05	N/A	40 CFR Part 63, Subpart FFFF	The vessel does not meet the definition of a storage tank since it stores organic liquid that contain HAP only as impurity.

New Source Review Authorization References

New Source Review Authorization References	287
New Source Review Authorization References by Emission Unit	288

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: GHGPSDTX170	Issuance Date: 02/04/2021
PSD Permit No.: PSDTX1518	Issuance Date: 09/23/2022
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 146425	Issuance Date: 09/23/2022
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
ADMINGEN	ADMIN EMERGENCY GENERATOR NO. 1	146425, GHGPSDTX170, PSDTX1518
ADMINGENTK	ADMIN EMERGENCY GENERATOR NO. 1 TANK	146425, PSDTX1518
BOILER A	UTILITIES BOILER A STACK	146425, PSDTX1518
BOILER B	UTILITIES BOILER B STACK	146425, PSDTX1518
BOILER C	UTILITIES BOILER C STACK	146425, PSDTX1518
C-VENTGAS	CPE PROCESS VENT GAS	146425, PSDTX1518
CADR04A	1-BUTENE DRYER	146425, PSDTX1518
CADR04B	1-BUTENE DRYER	146425, PSDTX1518
CBFIL01	CATALYST CYLINDER VENT FILTER	146425, PSDTX1518
CCD21	PRODUCT CHAMBER 1	146425, PSDTX1518
CCD22	PRODUCT BLOW TANK 1	146425, PSDTX1518
CCD23	PRODUCT CHAMBER 2	146425, PSDTX1518
CCD24	PRODUCT BLOW TANK 2	146425, PSDTX1518
CCD81	SEAL POT	146425, PSDTX1518
CCD81-LOAD	DILUTED TEAL LOADING	146425, PSDTX1518
CCFIL04	CATALYST FEEDER 1/CATALYST HOLD TANK 1 FILTER VENT	146425, PSDTX1518
CCFIL05	CATALYST FEEDER 2/CATALYST HOLD TANK 2 FILTER VENT	146425, PSDTX1518
CCFIL06	CATALYST FEEDER 3/CATALYST HOLD TANK 3 FILTER VENT	146425, PSDTX1518
CCGT01	BLOWDOWN TURBINE	146425, PSDTX1518
CCR01	REACTOR	146425, PSDTX1518
CCT01	VENT COLUMN	146425, PSDTX1518

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
CDD03	LOW PURGE BIN DUST COLLECTOR VENT	146425, PSDTX1518
CDDCO4	SEED BED BIN DUST COLLECTOR	146425, PSDTX1518
CDFAN01	GRANULES HOPPER VENT DUST COLLECTOR	146425, PSDTX1518
CDFIL01	PURGE BIN VENT FILTER	146425, PSDTX1518
CEC01A	RECOVERY COMPRESSOR (2ND STAGE)	146425, PSDTX1518
CED01	RECOVERED LIQUIDS DRUM	146425, PSDTX1518
CED02	CONVEYING GAS SURGE DRUM	146425, PSDTX1518
CED03	RECOVERY COMPRESSOR INTERSTAGE ACCUMULATOR	146425, PSDTX1518
CEE01	RECOVERY VAPOR INTERCHANGER	146425, PSDTX1518
CEFIL01	RECOVERY COMPRESSOR INTAKE FILTER	146425, PSDTX1518
CEMEM01A	HYDROCARBON RECOVERY MEMBRANE UNIT	146425, PSDTX1518
CEMEM01B	NITROGEN RECOVERY MEMBRANE UNIT	146425, PSDTX1518
CLB03	ADDITIVE VACUUM BLOWER CLB03	146425, PSDTX1518
CLDC01	GRANULES FEED BIN DUST COLLECTOR	146425, PSDTX1518
CLDC03	EXTRUDER FEED CONVEYOR DUST COLLECTOR	146425, PSDTX1518
CLDC06	ZINC OXIDE DRYING HOPPER DUST COLLECTOR	146425, PSDTX1518
CLFAN04	WEIGH FEEDER HOPPER EXTRACTION VENT	146425, PSDTX1518
CMDC01	PELLET SURGE BIN DUST COLLECTOR	146425, PSDTX1518
CMFAN01	PELLET DRYER 1 VENT	146425, PSDTX1518
CMFAN02	PELLET DRYER 2 VENT	146425, PSDTX1518
CPE-DIST	CPE DISTILLATION UNITS	146425, PSDTX1518

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
CPE-REACT	CPE REACTORS	146425, PSDTX1518
CPFAN01	PELLET SILOS DUST COLLECTOR	146425, PSDTX1518
C_FUG	CPE UNIT FUGITIVES	146425, GHGPSDTX170, PSDTX1518
DMSUNLOAD	DMS UNLOADING	146425, PSDTX1518
DREFUSTN	MISCELLANEOUS DIESEL UNLOADING	146425, PSDTX1518, 106.472/09/04/2000
E-VENTGAS	EMPE PROCESS VENT GAS	146425, PSDTX1518
EADR04A	HEXENE DRYER	146425, PSDTX1518
EADR04B	HEXENE DRYER	146425, PSDTX1518
EADR05A	CA1 DRYER	146425, PSDTX1518
EADR05B	CA1 DRYER	146425, PSDTX1518
EADR06	CA2 DRYER	146425, PSDTX1518
EADR07A	ETHYLENE PURIFICATION VESSEL	146425, PSDTX1518
EADR07B	ETHYLENE PURIFICATION VESSEL	146425, PSDTX1518
EADR09	ETHYLENE CO REMOVAL VESSEL	146425, PSDTX1518
EADR10	ETHYLENE DEOXO VESSEL	146425, PSDTX1518
EBFIL01	CATALYST CYLINDER VENT FILTER	146425, PSDTX1518
ECD21	PRODUCT CHAMBER 1	146425, PSDTX1518
ECD22	PRODUCT BLOW TANK 1	146425, PSDTX1518
ECD23	PRODUCT CHAMBER 2	146425, PSDTX1518
ECD24	PRODUCT BLOW TANK 2	146425, PSDTX1518
ECFIL04	CATALYST FEEDER 1/CATALYST HOLD TANK 1 FILTER VENT	146425, PSDTX1518

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
ECFIL05	CATALYST FEEDER 2/CATALYST HOLD TANK 2 FILTER VENT	146425, PSDTX1518
ECFIL06	CATALYST FEEDER 3/CATALYST HOLD TANK 3 FILTER VENT	146425, PSDTX1518
ECGTO1	BLOWDOWN TURBINE	146425, PSDTX1518
ECR01	REACTOR	146425, PSDTX1518
ECT01	VENT COLUMN	146425, PSDTX1518
EDDCO4	SEED BED BIN DUST COLLECTOR	146425, PSDTX1518
EDFAN01	GRANULES HOPPER VENT DUST COLLECTOR	146425, PSDTX1518
EDFIL01	PURGE BIN VENT FILTER	146425, PSDTX1518
EEC01A	RECOVERY COMPRESSOR (2ND STAGE)	146425, PSDTX1518
EED01	RECOVERED LIQUIDS DRUM	146425, PSDTX1518
EED02	CONVEYING GAS SURGE DRUM	146425, PSDTX1518
EED03	RECOVERY COMPRESSOR INTERSTAGE ACCUMULATOR	146425, PSDTX1518
EEE01	RECOVERY VAPOR INTERCHANGER	146425, PSDTX1518
EEFIL01	RECOVERY COMPRESSOR INTAKE FILTER	146425, PSDTX1518
EEMEM01A	HYDROCARBON RECOVERY MEMBRANE UNIT	146425, PSDTX1518
EEMEM01B	NITROGEN RECOVERY MEMBRANE UNIT	146425, PSDTX1518
ELB01	ADDITIVE VACUUM BLOWER ELB01	146425, PSDTX1518
ELB02	ADDITIVE VACUUM BLOWER ELB02	146425, PSDTX1518
ELB03	ADDITIVE VACUUM BLOWER ELB03	146425, PSDTX1518
ELB04	ADDITIVE VACUUM BLOWER ELB04	146425, PSDTX1518
ELB05	ADDITIVE VACUUM BLOWER ELB05	146425, PSDTX1518

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
ELDC01	GRANULES FEED BIN DUST COLLECTOR	146425, PSDTX1518
ELDC03	EXTRUDER FEED CONVEYOR DUST COLLECTOR	146425, PSDTX1518
ELDC06	ZINC OXIDE DRYING HOPPER DUST COLLECTOR	146425, PSDTX1518
ELDO1	PRIMARY RUN TANK	146425, PSDTX1518
ELDO2	SECONDARY RUN TANK	146425, PSDTX1518
ELFAN01	SOLID ADDITIVES VENT DUST COLLECTOR	146425, PSDTX1518
ELFAN04	WEIGH FEEDER HOPPER EXTRACTION VENT	146425, PSDTX1518
EMDC01	PELLET SURGE BIN DUST COLLECTOR	146425, PSDTX1518
EMFAN01	PELLET DRYER 1 VENT	146425, PSDTX1518
EMFAN02	PELLET DRYER 2 VENT	146425, PSDTX1518
EPE-DIST	EMPE DISTILLATION UNITS	146425, PSDTX1518
EPE-REACT	EMPE REACTORS	146425, PSDTX1518
EPFAN01	PELLET SILOS DUST COLLECTOR	146425, PSDTX1518
E_FUG	EPE UNIT FUGITIVES	146425, GHGPSDTX170, PSDTX1518
FA-F01	PYROLYSIS FURNACE A	146425, PSDTX1518
FB-F01	PYROLYSIS FURNACE B	146425, PSDTX1518
FC-F01	PYROLYSIS FURNACE C	146425, PSDTX1518
FD-F01	PYROLYSIS FURNACE D	146425, PSDTX1518
FE-F01	PYROLYSIS FURNACE E	146425, PSDTX1518
FF-F01	PYROLYSIS FURNACE F	146425, PSDTX1518
FG-F01	PYROLYSIS FURNACE G	146425, PSDTX1518

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
FH-F01	PYROLYSIS FURNACE H	146425, PSDTX1518
G-VENTGAS	GLYCOL PROCESS VENT GAS	146425, PSDTX1518
GAD03	MODERATOR FEED VESSEL	146425, PSDTX1518
GAR01A	EO REACTOR 01A	146425, PSDTX1518
GAR01B	EO REACTOR 01B	146425, PSDTX1518
GBD02	RECYCLE GAS COMPRESSOR SUCTION KO DRUM	146425, PSDTX1518
GBD05	CO2 STRIPPER OVERHEAD VENT	146425, PSDTX1518
GBD06	EO CONCENTRATOR SURGE DRUM	146425, PSDTX1518
GBD09	CARBONATE DISSOLVING DRUM	146425, PSDTX1518
GBTK01	CARBONATE STORAGE TANK	146425, PSDTX1518
GBX02	MEG THERMAL OXIDIZER	146425, GHGPSDTX170, PSDTX1518
GDD07	CO2 SEPARATION VESSEL	146425, PSDTX1518
GDD08	CATALYST CHARGE VESSEL	146425, PSDTX1518
GDD09	CATALYST DRIPS VESSEL	146425, PSDTX1518
GDE11	EG-2 REACTOR TOP CONDENSER VENT	146425, PSDTX1518
GDR02	EC-2 REACTOR	146425, PSDTX1518
GDR05	EG-2 REACTOR	146425, PSDTX1518
GDT01	GLYCOL DEHYDRATOR	146425, PSDTX1518
GDTK01	CATALYST STORAGE TANK	146425, PSDTX1518
GED03	VACUUM SYSTEM CONDENSATE VESSEL	146425, PSDTX1518
GED04	GLYCOL DRAIN COLLECTION VESSEL	146425, PSDTX1518

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
GET01	MEG PURIFICATION COLUMN	146425, PSDTX1518
GET02	MEG RECYCLE COLUMN	146425, PSDTX1518
GETK01	GLYCOL SLOPS TANK	146425, PSDTX1518
GETK02A	MEG RUNDOWN TANK 2A	146425, PSDTX1518
GETK02B	MEG RUNDOWN TANK 2B	146425, PSDTX1518
GFFLARE01	MEG ELEVATED FLARE	146425, GHGPSDTX170, PSDTX1518
GLYUNLOAD	GLYCOL UNLOADING	146425, PSDTX1518
GREFUSTN	GASOLINE VEHICLE REFUELING STATION	146425, PSDTX1518, 106.473/09/04/2000
GUDGEN01	GLYCOL EMERGENCY GENERATOR NO. 1	146425, GHGPSDTX170, PSDTX1518
GUDGEN01TK	GLYCOL EMERGENCY GENERATOR TANK	146425, PSDTX1518
G_FUG	GLYCOL UNIT FUGITIVES	146425, GHGPSDTX170, PSDTX1518
MEOHLOAD	METHANOL LOADING MSS	146425, PSDTX1518
MEOHUNLOAD	METHANOL UNLOADING	146425, PSDTX1518
O-REGEN	OLEFINS REGENERATION VENT (RFD24)	146425, GHGPSDTX170, PSDTX1518
O-VENTGAS	OLEFINS PROCESS VENT GAS	146425, PSDTX1518
OFAF01	FURNACE A STACK	146425, GHGPSDTX170, PSDTX1518
OFBF01	FURNACE B STACK	146425, GHGPSDTX170, PSDTX1518
OFCF01	FURNACE C STACK	146425, GHGPSDTX170, PSDTX1518
OFDF01	FURNACE D STACK	146425, GHGPSDTX170, PSDTX1518
OFEF01	FURNACE E STACK	146425, GHGPSDTX170, PSDTX1518
OFFF01	FURNACE F STACK	146425, GHGPSDTX170, PSDTX1518

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
OFGF01	FURNACE G STACK	146425, GHGPSDTX170, PSDTX1518
OFHF01	FURNACE H STACK	146425, GHGPSDTX170, PSDTX1518
O_FUG	OLEFIN UNIT FUGITIVES	146425, GHGPSDTX170, PSDTX1518
PE-REGEN	PE REGENERATION VENT (EADR09/10)	146425, GHGPSDTX170, PSDTX1518
PROADDITIVE	CPE & EMPE ADDITIVE SOURCES	146425, PSDTX1518
PROCATLYST	CPE & EMPE CATALYST TRANSFER SOURCES	146425, PSDTX1518
PROEXTRUD	CPE & EMPE EXTRUDER SOURCES	146425, PSDTX1518
PROGRANUL1	CPE & EMPE GRANULE SOURCES	146425, PSDTX1518
PROGRANUL2	CPE & EMPE GRANULE SOURCES	146425, PSDTX1518
PROGRANUL3	CPE & EMPE GRANULE SOURCES	146425, PSDTX1518
PROLDOUT1	CPE & EMPE LOADOUT SOURCES	146425, PSDTX1518
PROLDOUT2	CPE & EMPE LOADOUT SOURCES	146425, PSDTX1518
PROMEGCMPU	MEG CHEMICAL MANUFACTURING PROCESS UNIT (CMPU)	146425, PSDTX1518
PROPELLET	CPE & EMPE PELLET PRODUCT SOURCES	146425, PSDTX1518
PROPEMCPU	PE MISC CHEM MANUFACTURING PU (MCPU)	146425, PSDTX1518
RAD02	DMS STORAGE DRUM	146425, PSDTX1518
RESIDLOAD	RESIDUE LOADING MSS	146425, PSDTX1518
RJT01	BENZENE STRIPPER	146425, PSDTX1518
RLOAD-C3	RAIL LOADING PROPYLENE (ZTLA04A-4D)	146425, PSDTX1518
RLOAD-GB	RAIL LOADING GLYCOL BLEED (ZTLA07A-7B)	146425, PSDTX1518
RLOAD-HFO	RAIL LOADING HFO (ZTLA05A-5B)	146425, PSDTX1518

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
RLOAD-HG	RAIL LOADING HEAVY GLYCOL (ZTLA06A-6B)	146425, PSDTX1518
RLOAD-MEG	RAIL LOADING MEG (ZTLA02A-2D)	146425, PSDTX1518
RLUNLOAD-A	RAIL UNLOADING AREA A	146425, PSDTX1518
RLUNLOAD-B	RAIL UNLOADING AREA B	146425, PSDTX1518
SCTOTE-GLY	SPENT CATALYST TOTE	146425, PSDTX1518
SLOPUNLOAD	SLOP UNLOADING	146425, PSDTX1518
TKUNLOAD-A	TRUCK UNLOADING AREA A	146425, PSDTX1518
TKUNLOAD-B	TRUCK UNLOADING AREA B	146425, PSDTX1518
TLOAD-MEG	TRUCK LOADING MEG (ZTLA01A-1B)	146425, PSDTX1518
TLOAD-SLOP	TRUCK LOADING SLOP OIL (ZTLA03A-3B)	146425, PSDTX1518
TOTES	SITE TOTES	146425, PSDTX1518
UCCT01	UTILITIES COOLING TOWER	146425, PSDTX1518
UCTK01	HYPOCHLORITE STORAGE TANK	146425, PSDTX1518
UFF01A	OFFSITES & UTILITIES THERMAL OXIDIZER A	146425, GHGPSDTX170, PSDTX1518
UFF01B	OFFSITES & UTILITIES THERMAL OXIDIZER B	146425, GHGPSDTX170, PSDTX1518
UFFLARE01	MULTI-POINT GROUND FLARE	146425, GHGPSDTX170, PSDTX1518
UFFLARE02	SHARED ELEVATED LP FLARE	146425, GHGPSDTX170, PSDTX1518
UKDGEN01	OLEFINS EMERGENCY GENERATOR NO. 1	146425, GHGPSDTX170, PSDTX1518
UKDGEN01TK	OLEFINS EMERGENCY GENERATOR NO. 1 TANK	146425, PSDTX1518
UKDGEN02	UTILITIES EMERGENCY GENERATOR NO. 2	146425, GHGPSDTX170, PSDTX1518
UKDGEN02TK	UTILITIES EMERGENCY GENERATOR NO. 2 TANK	146425, PSDTX1518

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
USSG01A	UTILITIES BOILER A	146425, GHGPSDTX170, PSDTX1518
USSG01B	UTILITIES BOILER B	146425, GHGPSDTX170, PSDTX1518
USSG01C	UTILITIES BOILER C	146425, GHGPSDTX170, PSDTX1518
UTD02	AQUEOUS AMMONIA STORAGE DRUM	146425, PSDTX1518
UTD04	WASH OIL STORAGE DRUM	146425, PSDTX1518
UTTK04	SULFURIC ACID STORAGE TANK	146425, PSDTX1518
U_FUG	UTILITIES FUGITIVES	146425, GHGPSDTX170, PSDTX1518
U_LAB	LABORATORY OPERATION VENTS	146425, PSDTX1518
WASHUNLOAD	WASH OIL UNLOADING	146425, PSDTX1518
ZFP02B	FIREWATER PUMP NO. 1	146425, GHGPSDTX170, PSDTX1518
ZFP02C	FIREWATER PUMP NO. 2	146425, GHGPSDTX170, PSDTX1518
ZFTK02B	FIREWATER PUMP DIESEL TANK 2B	146425, PSDTX1518
ZFTK02C	FIREWATER PUMP DIESEL TANK 2C	146425, PSDTX1518
ZMTK01	GASOLINE INFRASTRUCTURE TANK	146425, PSDTX1518
ZMTK02	DIESEL INFRASTRUCTURE TANK	146425, PSDTX1518
ZTD08	CONDENSING AGENT 1 STORAGE BULLET	146425, PSDTX1518
ZTD09	CONDENSING AGENT 2 STORAGE BULLET	146425, PSDTX1518
ZTD10A	DILUTE PROPYLENE STORAGE BULLET	146425, PSDTX1518
ZTD10B	DILUTE PROPYLENE STORAGE BULLET	146425, PSDTX1518
ZTD10C	DILUTE PROPYLENE STORAGE BULLET	146425, PSDTX1518
ZTD11A	BUTENE STORAGE BULLET	146425, PSDTX1518

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
ZTD11B	BUTENE STORAGE BULLET	146425, PSDTX1518
ZTD12	OILY WATER COALESCER	146425, PSDTX1518
ZTTK01	CAUSTIC STORAGE TANK	146425, PSDTX1518
ZTTK02	HEAVY GLYCOL STORAGE TANK	146425, PSDTX1518
ZTTK03	GLYCOL BLEED STORAGE TANK	146425, PSDTX1518
ZTTK04	SLOP OIL STORAGE TANK	146425, PSDTX1518
ZTTK05	HEXENE STORAGE TANK	146425, PSDTX1518
ZTTK06A	HEAVY FUEL OIL STORAGE TANK	146425, PSDTX1518
ZTTK06B	HEAVY FUEL OIL STORAGE TANK	146425, PSDTX1518
ZWFOS01	EQUALIZATION TANK 1 OIL SKIMMER	146425, PSDTX1518
ZWFOS02	EQUALIZATION TANK 2 OIL SKIMMER	146425, PSDTX1518
ZWTK01	EQUALIZATION TANK 1	146425, PSDTX1518
ZWTK02	EQUALIZATION TANK 2	146425, PSDTX1518

**This column may include Permit by Rule (PBR) numbers and version dates, PBR Registration numbers in brackets, Standard Permit Registration numbers, Minor NSR permit numbers, and Major NSR permit numbers.

Alternative Requirement

Alternative Requirement.....	300
-------------------------------------	------------

Jon Niermann, *Chairman*
Emily Lindley, *Commissioner*
Bobby Janecka, *Commissioner*
Toby Baker, *Executive Director*



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

July 16, 2021

MR TERRY BOLES
PRESIDENT
GULF COAST GROWTH VENTURES LLC
1735 HUGHES LANDING BLVD
THE WOODLANDS TX 77380-1688

Re: Alternative Method of Compliance (AMOC) No. 181
Utility Boilers Alternative Fuel Sampling
Regulated Entity Number: RN109753731
Customer Reference Number: CN605632439
Associated Permit Numbers: 146425, PSDTX1518, and O4169

Dear Mr Boles:

This correspondence is in response to Gulf Coast Growth Ventures LLC's (GCGV's) June 14, 2021 request for alternative fuel sampling of the Utility Boilers to comply with sulfur dioxide (SO₂) requirements under 40 CFR 60 Subpart Db, Industrial-Commercial-Institutional Steam Generating Units (NSPS Db).

GCGV has three (3) new gas-fired boilers (EPNs USSG01A, USSG01B, USSG01C) which are fired by inherently low sulfur fuel gases or process gases. These boilers are applicable to 40 CFR 60 Subpart Db (NSPS Db) requiring weekly grab sampling of the fuel. Permit No. 146425 and PSDTX1518 requires semi-annual testing of the fuel gas stream to the boilers and a continuous total sulfur analyzer on the vent stream to the boilers. We understand GCGV is proposing to conduct a fuel gas sample once every three calendar months (quarterly) and use data gathered by the online total sulfur analyzer for the vent gas to demonstrate compliance with NSPS Db SO₂ standards.

The Texas Commission on Environmental Quality (TCEQ) Executive Director has made a final decision to approve your AMOC request based on the more accurate continuous sulfur analyzer and the federal rules allowing quarterly testing of the fuel gas. The TCEQ has been delegated authority to enforce the above cited standards and is authorized to approve this AMOC. You are reminded that approval of any AMOC shall not abrogate the Executive Director or Administrator's authority under the Act or in any way prohibit later canceling the AMOC. By copy of this letter we are informing the Environmental Protection Agency, Region 6, of this decision as required by TCEQ's delegation of authority.

This AMOC approval may supersede certain requirements or representations in Permit Nos. 146425 and PSDTX1518. To ensure effective and consistent enforceability, we request that GCGV incorporate this AMOC into the permit(s) through submittal of alteration(s) no later than 90 days after this approval.

This approval may also change applicable requirements for the site, which are identified in the site operating permit (SOP) O4169. The TCEQ recommends the submittal of a SOP administrative revision if any changes are necessary. Changes meeting the criteria for an administrative revision can be operated before issuance of the revision if a complete application is submitted to the TCEQ and this information is maintained with the SOP records at the site.

P.O. Box 13087 • Austin, Texas 78711-3087 • 512-239-1000 • tceq.texas.gov

How is our customer service? tceq.texas.gov/customersurvey

printed on recycled paper

July 16, 2021
Page 2
MR TERRY BOLES

Re: Permit Numbers: 146425, PSDTX1518, and O4169

If you need further information or have any questions, please contact Ms. Anne Inman, P.E. at (512) 239-1276 or write to the Texas Commission on Environmental Quality, Office of Air, Air Permits Division, MC-163, P.O. Box 13087, Austin, Texas 78711-3087.

Sincerely,

A handwritten signature in black ink, appearing to read 'Samuel Short', followed by a long horizontal line.

Samuel Short, Deputy Director
Air Permits Division
Office of Air
Texas Commission on Environmental Quality

cc: Air Section Manager, Region 14 - Corpus Christi
Jesse E. Chacon, P.E., Manager, Operating Permits Section, Air Permits Division, OA: MC-163
Rebecca Partee, Manager, Chemical New Source Review Permits Section, Air Permits Division,
OA: MC-163
Air Permits Section Chief, New Source Review Section (6PD-R), U.S. Environmental Protection
Agency, Region 6, Dallas

Project Number: 330170

Jon Niermann, *Chairman*
Emily Lindley, *Commissioner*
Bobby Janecka, *Commissioner*
Toby Baker, *Executive Director*



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

September 16, 2021

MS CHRYSTAL CARTER
ENVIRONMENTAL SENIOR TECHNICAL ADVISOR
GULF COAST GROWTH VENTURES LLC
PO BOX 367
GREGORY TX 78359-0367

Re: Alternative Method of Compliance (AMOC) No. 138 Revision
Multipoint Ground Flare
Update Representations
Regulated Entity Number: RN109753731
Customer Reference Number: CN605632439
Associated Permit Numbers: 146425, GHGPSDTX170, and PSDTX1518

Dear Ms Carter:

This correspondence is in response to Gulf Coast Growth Ventures LLC's (GCGV's) September 8, 2021 request to revise the AMOC representations for the Multipoint Ground Flare (MPGF) which is used to comply with Subchapter B: General Volatile Organic Compound Sources, Division 1: Storage of VOCs and Division 2: Vent Gas Control, as well as applicable federal rules.

We understand that GVGC is requesting that natural gas be used as fuel used during initial start-up of the site and when the MPGF system is in standby mode. This change in representations does not result in a change in the method of control of emissions, a change in the character of emissions, an increase in the emission rate of any air contaminant and will meet all permit and MAERT requirements. Additionally, GCGV confirms that the MPGF will continue to comply with the operational requirements of the AMOC and federal regulations.

The Texas Commission on Environmental Quality (TCEQ) Executive Director has made a final decision to approve your AMOC request. The updated AMOC Plan Conditions, which include updates to paragraphs (B) and (F)(1)(g), are attached to this correspondence. You are reminded that approval of any AMOC shall not abrogate the Executive Director or Administrator's authority under the Act or in any way prohibit later canceling the AMOC. By copy of this letter, we are informing the Environmental Protection Agency, Region 6.

This AMOC approval may supersede certain requirements or representations in Permit Nos. 146425, GHGPSDTX170, and PSDTX1518. To ensure effective and consistent enforceability, we request that GCGV incorporate this AMOC revision into the permits through submittal of alteration no later than 90 days after this approval.

P.O. Box 13087 • Austin, Texas 78711-3087 • 512-239-1000 • tceq.texas.gov

How is our customer service? tceq.texas.gov/customersurvey
printed on recycled paper

September 16, 2021
Page 2
MS CHRYSTAL CARTER

Re: Permit Numbers: 146425, GHGPSDTX170, and PSDTX1518

If you need further information or have any questions, please contact Ms. Anne Inman, P.E. at (512) 239-1276 or write to the Texas Commission on Environmental Quality, Office of Air, Air Permits Division, MC-163, P.O. Box 13087, Austin, Texas 78711-3087.

Sincerely,

A handwritten signature in black ink, appearing to read 'Samuel Short', followed by a long horizontal line extending to the right.

Samuel Short, Deputy Director
Air Permits Division
Office of Air
Texas Commission on Environmental Quality

cc: Air Section Manager, Region 14 - Corpus Christi
Rebecca Partee, Manager, Chemical New Source Review Permits Section, Air Permits Division,
OA: MC-163

Project Number: 333161

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY



Alternative Method of Control (AMOC) Plan

Gulf Coast Growth Ventures, LLC

AMOC No.: AMOC-138

**GCGV Complex Multi-Point Ground Flare (MPGF) System
Gregory, San Patricio County, Regulated Entity Number: RN109753731**

- A. This AMOC Plan Authorization shall apply at the Gulf Coast Growth Ventures, LLC (GCGV), Olefins and Polyethylene Plants located near Gregory, San Patricio County. This site is identified by Regulated Entity Number RN109753731. Under Title 30 Texas Administrative Code (TAC) Section 115.910 (§115.910) this plan authorizes a multi-point ground flare (MPGF) system identified as EPN UFFLARE01. This plan is specific to the high-pressure operations of MPGF system which will be used intermittently during routine process operations, planned maintenance, start-ups, and shutdowns (MSS), including but not limited to operational transitions, catalyst change outs, grade changes, and unplanned emergency and upset situations.
- B. A copy of the AMOC application and the AMOC Plan provisions must be kept on-site or at a centralized location and made available at the request of personnel from the TCEQ or any pollution control agency with jurisdiction. The AMOC application is defined by the application received December 19, 2019 and subsequent supporting information dated through August 18, 2020.
- C. This authorization is granted under § 115.910 for emissions sources regulated by 30 TAC Chapter 115, Subchapter B: General Volatile Organic Compound Sources, Division 2: Vent Gas Control.

This AMOC shall apply in lieu of the requirements listed above, as applicable. Compliance with this AMOC is independent of GCGV's obligation to comply with all other applicable requirements of 30 TAC Chapter 115, TCEQ permits, and applicable state and federal law. The monitoring and testing requirements of 30 TAC Chapter 115 shall continue to apply.

- D. In accordance with § 115.913(c), all representations submitted for this plan, as well as the provisions listed here, become conditions upon which this AMOC Plan is issued. It is unlawful to vary from the emission limits, control requirements, monitoring, testing, reporting or recordkeeping requirements of this Plan.
- E. The flare system is authorized under Permit Nos. 146425, PSDTX1518, and GHGPSDTX170 and subject to this AMOC plan. The flare system uses Zeeco Model MJ-4 burners controlling intermittent activities. When the high-pressure vent header sends waste gas to the MPGF, the burners will exceed the tip velocity portions of §60.18, §63.11, and 30 TAC Chapter 115. In these instances, the burners and stages will meet the requirements in paragraph F.

The MPGF system has 19 stages with a total of 630 burners with three (3) pilots per stage. All high-pressure stages are designed to operate as non-assisted. Operations of the MPGF burners will achieve a reduction in emissions at least equivalent to the reduction in emissions being controlled by a steam-assisted, air-assisted, or non-assisted flare complying with the requirements of §§ 115.122(a)(1)-(2) or 40 CFR 60.18(b).

- F. When regulated flare vent gas is being sent to the flare and the burners exceed the tip velocity requirements of §60.18, §63.11, and 30 TAC Chapter 115, the burners must be operated such that the following are met:
1. **Operating Requirements:** The net heating value of the flare vent gas combustion zone (NHV_{cz}) is greater than or equal to 800 British thermal units per standard cubic foot (Btu/scf); or the combustion zone gas lower flammability limit (LFL_{cz}) is less than or equal to 6.5 percent by volume. The owner or operator must

demonstrate compliance with the NHV_{cz} or LFL_{cz} metric by continuously complying with a 15-minute block average. The operator must calculate and monitor for the NHV_{cz} or LFL_{cz} according to the following:

a. Calculation of NHV_{cz}

- i. Option #1: If any owner or operator elects to use a monitoring system capable of continuously measuring, calculating, and recording the individual component concentrations present in the flare gas, the net heating value shall be determined using the following equation:

$$NHV_{vg} = \sum_{i=1}^n x_i NHV_i$$

Where:

NHV_{vg} = Net heating value of flare vent gas, British thermal units per standard cubic foot (Btu/scf).
Flare vent gas means all gas found just prior to the MPGFs. This gas includes all flare waste gas (i.e., gas from facility operations that is directed to a flare for the purpose of disposing of the gas), flare sweep gas, flare purge gas and flare supplemental gas, but does not include pilot gas.

i = Individual component in flare vent gas.

n = Number of components in flare vent gas.

x_i = Concentration of component i in flare vent gas, volume percent (vol %).

NHV_i = Net heating value of component i determined as the heat of combustion where the net enthalpy per mole of offgas is based on combustion at 25 degrees Celsius (°C) and 1 atmosphere (or constant pressure) with water in the gaseous state from values published in the literature, and then the values converted to a volumetric basis using 20 °C for "standard temperature." Table 1 summarizes component properties including net heating values.

- ii. Option #2: If the owner or operator uses a continuous net heating value monitor, the owner or operator may, at their discretion, install, operate, calibrate, and maintain a monitoring system capable of continuously measuring, calculating, and recording the hydrogen concentration in the flare vent gas. The owner or operator shall use the following equation to determine NHV_{vg} for each sample measured via the net heating value monitoring system.

$$NHV_{vg} = NHV_{measured} + 938 X_{H2}$$

Where:

NHV_{vg} = Net heating value of flare vent gas, BTU/scf.

$NHV_{measured}$ = Net heating value of flare vent gas stream as measured by the continuous net heating value monitoring system, BTU/scf.

X_{H2} = Concentration of hydrogen in flare vent gas at the time the sample was input into the net heating value monitoring system, volume fraction.

938 = Net correction for the measured heating value of hydrogen (1,212 - 274 BTU/scf).

- iii. For this MPGF, $NHV_{vg} = NHV_{cz}$.

b. Calculation of LFL_{cz}

- (i) The owner or operator shall determine LFL_{cz} from compositional analysis data by using the following equation:

$$LFL_{vg} = \frac{1}{\sum_{i=1}^n \left[\frac{X_i}{LFL_i} \right]} * 100 \%$$

Where:

LFL_{vg} = Lower flammability limit of flare vent gas, volume percent (vol %)

n = Number of components in the vent gas.

i = Individual component in the vent gas.

X_i = Concentration of component i in the vent gas, vol %.

LFL_i = Lower flammability limit of component i as determined using values published by the U.S. Bureau of Mines (Zabetakis, 1965), vol %. All inerts, including nitrogen, are assumed to have an infinite LFL (e.g., $LFL_{N2} = \infty$, so that $cN2 / LFL_{N2} = 0$). LFL values for common flare vent gas components are provided in Table 1.

- ii. For this MPGF, $LFL_{vg} = LFL_{cz}$.

- c. Calculation of Vtip is not applicable to this MPGF.
- d. The operator shall install, operate, calibrate and maintain a monitoring system capable of continuously measuring flare vent gas volumetric flow rate (Q_{vg}) and the total steam volumetric flow rate (Q_s), as applicable.
 - i. The flow rate monitoring system must be able to correct for the temperature and pressure of the system and output parameters in standard conditions (i.e., a temperature of 20 degrees C (68 ° F) and a pressure of 1 atmosphere).
 - ii. Mass flow monitors may be used for determining volumetric flow rate of flare vent gas provided the molecular weight of the flare vent gas is determined using compositional analysis so that the mass flow rate can be converted to volumetric flow at standard conditions using the following equation:

$$Q_{vol} = \frac{Q_{mass} \times 385.3}{MW_t}$$

Where:

Q_{vol} = volumetric flow rate in scf per second (scf/s).

Q_{mass} = mass flow rate in pounds per second (lb/s)

385.3 = conversion factor scf per pound-mole

MW_t = molecular weight of the gas at the flow monitoring location, pounds per pound-mole

- e. The operator shall install, operate, calibrate and maintain a monitoring system capable of continuously measuring (i.e., at least once every 15-minutes) temperature consistent with the applicable requirements in 30 TAC Chapter 115 for purposes of correcting flow rate to standard conditions. The monitor must meet the accuracy and calibration specifications annually.

For each measurement produced by monitoring systems, the operator shall determine the 15-minute block average as the arithmetic average of all measurements made by the monitoring system within the 15-minute period.

- f. The operator must follow the calibration and maintenance procedures according to Table 2. Monitor downtime associated with maintenance periods, instrument adjustments or checks to maintain precision and accuracy and zero and span adjustments may not exceed 5 percent of the time the flare is receiving regulated material. Calibration and maintenance procedures conducted when the flare is not receiving regulated material are excluded from the monitor downtime calculation.
- g. During flare standby, the operator will maintain the net heating value at a minimum of 800 Btu/scf by applying a continuous ethane or natural gas backflow purge into the flare charge header. Maintaining a high minimum BTU in the flare charge header will ensure proper flare operation (cross-lighting and flame stability) upon initiation of a flaring event. This continuous ethane or natural gas backflow purge is set at a fixed flow rate which will be estimated using engineering calculations in lieu of continuous volumetric flow monitoring.

2. Pilot Flame Requirements:

- a. The MPGF systems shall be operated with a flame present at all times when in use.
- b. Each stage of MPGF burners must have at least two pilots with a continuously lit pilot flame.
- c. Each pilot flame must be continuously monitored by a thermocouple or any other equivalent device (such as the video camera required for visible emission monitoring as outlined in 3 below), used to detect the presence of a flame.
- d. The time, date and duration of any complete loss of pilot flame on any stage of burners must be recorded.
- e. Each monitoring device must be maintained or replaced at a frequency in accordance with the manufacturer's specifications.

3. Visible Emission Requirements:

- a. When the flare is receiving regulated material, the flare system shall be operated with no visible emissions except for periods not to exceed a total of 5 minutes during any 2 consecutive hours.
- b. A video camera that is capable of continuously recording (*i.e.*, at least one frame every 15 seconds with time and date stamps) images of the flare flame and a reasonable distance above the flare flame at an angle suitable for visible emissions observations must be used to demonstrate compliance with this requirement.
- c. The owner or operator must provide real-time video surveillance camera output to the control room or other continuously manned location where the video camera images may be viewed at any time.

Video camera downtime associated with maintenance periods and camera adjustments may not exceed 5 percent of the time the flare is receiving regulated material. Maintenance and adjustment procedures conducted when the flare is not receiving regulated material are excluded from the video camera downtime calculation.

4. Pressure Monitor Requirements:

- a. The operator of the flare system shall install and operate pressure monitor(s) on the main flare header, and
- b. a valve position indicator monitoring systems for each staging valve to ensure that the flare system operates within the range of tested conditions or within the range of the manufacturer's specifications.
- c. The pressure monitor shall meet the requirements in Table 2.
- d. Monitor downtime associated with maintenance periods, instrument adjustments or checks to maintain precision and accuracy and zero and span adjustments may not exceed 5 percent of the time the flare is receiving regulated material. Calibration and maintenance procedures conducted when the flare is not receiving regulated material are excluded from the monitor downtime calculation.

5. Recordkeeping Requirements:

All data must be recorded and maintained for a minimum of five years or for as long as applicable rule subpart(s) specify flare records should be kept, whichever is longer. Records must be maintained onsite and made available upon request by authorized representatives of the executive director, U.S. EPA, and any local air pollution control agency with jurisdiction.

6. Reporting Requirements

- a. The information specified in (b) and (c) below should be reported in the timeline specified by the applicable rules for which the flare system will control emissions.
- b. Owners or operators should include the final operating requirements for each flare in their initial Notification of Compliance (NOC) status report (including but not limited to the items listed in F.6.c.).
- c. The owner or operator shall notify the Administrator of periods of excess emissions in their Periodic Reports.
- d. All MPGF shall include the following in their NOC, reports, and records:
 - i. Each 15-minute block during which there was at least one minute when regulated material was routed to the MPGFs and a complete loss of pilot flame on any stage or any individual burner(s) occurred.
 - ii. Periods of visible emissions events (including time and date stamp) that exceed more than 5 minutes in any 2 hour consecutive period.
 - iii. Each 15-minute block period for which an applicable combustion zone operating limit (*i.e.*, NHV_{cz} or LFL_{cz}) is not met for the flare system when regulated material is being combusted in the flare. Indicate the date and time for each period, the NHV_{cz} and/or LFL_{cz} operating parameter for the period, the type of

monitoring system used to determine compliance with the operating parameters (e.g., gas chromatograph or calorimeter), and the flare stages which were in use.

- iv. Periods when the pressure monitor(s) on the main flare header show the flare burners are operating outside the range of tested conditions or outside the range of the manufacturer's specifications. Indicate the date and time for each period, the pressure measurement, the stage(s) and number of flare burners affected and the range of tested conditions or manufacturer's specifications.
- v. Periods when the staging valve position indicator monitoring system indicates a stage of the flare system should not be in operation but is; or when a stage of the MPGF should be in operation but is not. Indicate the date and time for each period, whether the stage was supposed to be open but was closed or vice versa and the stage(s) and number of flare burners affected.

Table 1 — Individual Component Properties

Component	Molecular Formula	MW_i (lb/ lb mol)	NHV_i (Btu/scf)	LFL_i (volume %)
Acetylene	C ₂ H ₂	26.04	1,404	2.5
Benzene	C ₆ H ₆	78.11	3,591	1.3
1,2- Butadiene	C ₄ H ₆	54.09	2,794	2.0
1,3- Butadiene	C ₄ H ₆	54.09	2,690	2.0
iso-Butane	C ₄ H ₁₀	58.12	2,957	1.8
n-Butane	C ₄ H ₁₀	58.12	2,968	1.8
cis-Butene	C ₄ H ₈	56.11	2,830	1.6
iso-Butene	C ₄ H ₈	56.11	2,928	1.8
trans-Butene	C ₄ H ₈	56.11	2,826	1.7
Carbon Dioxide	CO ₂	44.01	0	∞
Carbon Monoxide	CO	28.01	316	12.5
Cyclopropane	C ₃ H ₆	42.08	2,185	2.4
Ethane	C ₂ H ₆	30.07	1,595	3.0
Ethylene	C ₂ H ₄	28.05	1,477	2.7
Hydrogen	H ₂	2.02	1,212 ^(*)	4.0
Hydrogen Sulfide	H ₂ S	34.08	587	4.0
Methane	CH ₄	16.04	896	5.0
MethylAcetylene	C ₃ H ₄	40.06	2,088	1.7
Nitrogen	N ₂	28.01	0	∞
Oxygen	O ₂	32.00	0	∞
Pentane+ (C5+)	C ₅ H ₁₂	72.15	3,655	1.4
Propadiene	C ₃ H ₄	40.06	2,066	2.16
Propane	C ₃ H ₈	44.10	2,281	2.1
Propylene	C ₃ H ₆	42.08	2,150	2.4
Water	H ₂ O	18.02	0	∞

* The theoretical net heating value for hydrogen is 274 BTU/scf, but for the purposes of the flare requirement, a net heating value of 1,212 BTU/scf shall be used.

Table 2 — Accuracy and Calibration Requirements

Parameter	Accuracy requirements	Calibration requirements
Flare Vent Gas Flow Rate	<p>±20 percent of flow rate at velocities ranging from 0.1 to 1 feet per second.</p> <p>±5 percent of flow rate at velocities greater than 1 foot per second.</p>	<p>Performance evaluation biennially (every two years) and following any period of more than 24 hours throughout which the flow rate exceeded the maximum rated flow rate of the sensor, or the data recorder was off scale.</p> <p>Conduct monthly AVO fugitive emission monitoring on each connection point. Visual inspections and checks of system operation every 3 months, unless the system has a redundant flow sensor.</p> <p>Select a representative measurement location where swirling flow or abnormal velocity distributions due to upstream and downstream disturbances at the point of measurement are minimized.</p>
Flow Rate for All Flows Other Than Flare Vent Gas	<p>± 5% over normal range of flow measured or 0.5 gal/min whichever greater for liquid flow.</p> <p>± 5% over normal range of flow measured 10 ft³/min, whichever greater for gas flow.</p> <p>± 5% over normal range measured for mass flow</p>	<p>Conduct a flow sensor calibration check at least biennially (every 2 years); conduct a calibration check following any period of more than 24 hours throughout which the flow rate exceeded the manufacturer's specified maximum rated flow rate or install a new flow sensor. At least quarterly, inspect all components for leakage, unless the continuous parameter monitoring system (CPMS) has a redundant flow sensor. Record the results of each calibration check and inspection.</p> <p>Locate the flow sensor(s) and other necessary equipment (such as straightening vanes) in a position that provides representative flow; reduce swirling flow or abnormal velocity distributions due to upstream and downstream disturbances.</p>
Pressure	<p>±5 percent over the normal range measured or 0.12 kilopascals (0.5 inches of water column), whichever is greater.</p>	<p>Review pressure sensor readings at least once a week for straight-line (unchanging) pressure and perform corrective action to ensure proper pressure sensor operation if blockage is indicated.</p> <p>Performance evaluation annually and following any period of more than 24 hours throughout which the pressure exceeded the maximum rated pressure of the sensor, or the data recorder was off scale. Checks of all mechanical connections for leakage monthly. Visual inspection of all components for integrity, oxidation, and galvanic corrosion every 3 months, unless the system has a redundant pressure sensor.</p> <p>Select a representative measurement location that minimizes or eliminates pulsating pressure, vibration, and internal and external corrosion.</p>
Net Heating Value by Calorimeter	<p>±2 percent of span</p>	<p>Calibration requirements should follow manufacturer's recommendations at a minimum.</p> <p>Temperature control (heated and/or cooled as necessary) the sampling system to ensure proper year-round operation.</p> <p>Where feasible, select a sampling location at least two equivalent diameters downstream from and 0.5 equivalent diameters upstream from the nearest disturbance. Select the sampling location at least two equivalent duct diameters from the nearest control device, point of pollutant generation, air in leakages, or other point at which a change in the pollutant concentration or emission rate occurs.</p>
Net Heating Value by Gas Chromatograph	<p>As specified in Performance Specification 9 of 40 CFR part 60 Appendix B.</p>	<p>Follow the procedure in Performance Specification 9 of 40 CFR Part 60 Appendix B, except that a single daily mid-level calibration check can be used, a triplicate mid-level check weekly, and the multi-point calibration can be conducted quarterly (rather than monthly), and the sampling line temperature must be maintained at a minimum temperature of 60 °C (rather than 120 °C).</p>
Hydrogen Analyzer	<p>± 2% over concentration measured or 0.1 vol% whichever is greater</p>	<p>Specify calibration requirements in your site specific CPMS monitoring plan. Calibration requirements should follow manufacturer's recommendations at a minimum. Specify the sampling location at least 2 equivalent duct diameters from the nearest control device, point of pollutant generation, air in-leakages, or other point at which a change in the pollutant concentration occurs.</p>

Appendix A

Acronym List 311

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
CEMS	continuous emissions monitoring system
CFR	Code of Federal Regulations
COMS	continuous opacity monitoring system
CVS	closed vent system
D/FW	Dallas/Fort Worth (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
H ₂ S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MACT	Maximum Achievable Control Technology (40 CFR Part 63)
MMBtu/hr	Million British thermal units per hour
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NESHAP	National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PEMS	predictive emissions monitoring system
PM	particulate matter
ppmv	parts per million by volume
PRO	process unit
PSD	prevention of significant deterioration
psia	pounds per square inch absolute
SIP	state implementation plan
SO ₂	sulfur dioxide
TCEQ	Texas Commission on Environmental Quality
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	volatile organic compound

Appendix B

Major NSR Summary Table 313

Major NSR Summary Table

Permit Number: GHGPSDTX170				Issuance Date: 02/04/2021		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
O_FAF01	Pyrolysis Furnace A	CO ₂ (5)	—	5, 7	5, 7	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
O_FBF01	Pyrolysis Furnace B	CO ₂ (5)	—	5, 7	5, 7	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
O_FCF01	Pyrolysis Furnace C	CO ₂ (5)	—	5, 7	5, 7	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
O_FDF01	Pyrolysis Furnace D	CO ₂ (5)	—	5, 7	5, 7	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			

Major NSR Summary Table

Permit Number: GHGPSDTX170				Issuance Date: 02/04/2021		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
O_FEF01	Pyrolysis Furnace E	CO ₂ (5)	—	5, 7	5, 7	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
O_FFF01	Pyrolysis Furnace F	CO ₂ (5)	—	5, 7	5, 7	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
O_FGF01	Pyrolysis Furnace G	CO ₂ (5)	—	5, 7	5, 7	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
O_FHF01	Pyrolysis Furnace H	CO ₂ (5)	—	5, 7	5, 7	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			

Major NSR Summary Table

Permit Number: GHGPSDTX170				Issuance Date: 02/04/2021		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
O_F_CAP	Total Emissions from EPNs O_FAF01, O_FBF01, O_FCF01, O_FDF01, O_FEF01, O_FFF01, O_FGF01, O_FHF01	CO ₂ (5)	1555774.36	5, 7	5, 7	
		CH ₄ (5)	129.80			
		N ₂ O (5)	25.96			
		CO ₂ e	1566755.63			
UFFLARE01	Multi-point Ground Flare	CO ₂ (5)	—	8	8	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
UFFLARE02	Shared Elevated Flare	CO ₂ (5)	—	8	8	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
CAPUFFLR	Total Emissions from EPNs UFFLARE 01, UFFLARE02	CO ₂ (5)	150087.73	8	8	
		CH ₄ (5)	93.95			
		N ₂ O (5)	1.50			
		CO ₂ e	152883.64			

Major NSR Summary Table

Permit Number: GHGPSDTX170				Issuance Date: 02/04/2021		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
CAPUFFLR	Total Emissions from EPNs UFFLARE 01, UFFLARE02 (Shakedown Period)	CO ₂ (5)	191633.46	8, 11	8, 11	
		CH ₄ (5)	116.32			
		N ₂ O (5)	1.92			
		CO ₂ e	195085.70			
O-REGEN	Olefins Regeneration Vent	CO ₂ (5)	17.18			
		CO ₂ e	17.18			
GFFLARE01	MEG Elevated Flare	CO ₂ (5)	—	9	9	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
GBX02	MEG Thermal Oxidizer	CO ₂ (5)	—	9	9	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			

Major NSR Summary Table

Permit Number: GHGPSDTX170				Issuance Date: 02/04/2021		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
GLYCAP	Total Emissions from EPNs GFFLARE01, GBX02	CO ₂ (5)	428930.74	9	9	
		CH ₄ (5)	195.17			
		N ₂ O (5)	0.94			
		CO ₂ e	434091.18			
GLYCAP	Total Emissions from EPNs GFFLARE01, GBX02 (Shakedown Period)	CO ₂ (5)	435416.28	9, 11	9, 11	
		CH ₄ (5)	199.23			
		N ₂ O (5)	1.01			
		CO ₂ e	440697.54			
USSG01A	Utilities Boiler A	CO ₂ (5)	—	5, 6	5, 6	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
USSG01B	Utilities Boiler B	CO ₂ (5)	—	5, 6	5, 6	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			

Major NSR Summary Table

Permit Number: GHGPSDTX170				Issuance Date: 02/04/2021		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
USSG01C	Utilities Boiler C	CO ₂ (5)	—	5, 6	5, 6	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
USSG01CAP	Total Emissions from EPNs USSG01A, USSG01B, USSG01C	CO ₂ (5)	676557.06	5, 6	5, 6	
		CH ₄ (5)	45.63			
		N ₂ O (5)	9.13			
		CO ₂ e	680417.66			
UFF01A	Shared Thermal Oxidizer A	CO ₂ (5)	—	8	8	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
UFF01B	Shared Thermal Oxidizer B	CO ₂ (5)	—	8	8	
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			

Major NSR Summary Table

Permit Number: GHGPSDTX170				Issuance Date: 02/04/2021		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
UFF01	Total Emissions from EPNs UFF01A, UFF01B	CO ₂ (5)	63536.78	8	8	
		CH ₄ (5)	191.84			
		N ₂ O (5)	0.64			
		CO ₂ e	68522.08			
EMGGEN01	Olefins Emergency Generator No. 1	CO ₂ (5)	—			
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
EMGGEN02	Utilities Emergency Generator No. 2	CO ₂ (5)	—			
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
ADMINGEN	Admin Emergency Generator No. 1	CO ₂ (5)	—			
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			

Major NSR Summary Table

Permit Number: GHGPSDTX170				Issuance Date: 02/04/2021		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
FWP1	Firewater Pump No.1	CO ₂ (5)	—			
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
FWP2	Firewater Pump No. 2	CO ₂ (5)	—			
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
GLYGEN01	Glycol Emergency Generator No. 1	CO ₂ (5)	—			
		CH ₄ (5)	—			
		N ₂ O (5)	—			
		CO ₂ e	—			
ENGINECAP	Emergency Generator and Firewater Pump Cap	CO ₂ (5)	1132.44			
		CH ₄ (5)	0.05			
		N ₂ O (5)	0.01			
		CO ₂ e	1136.33			

Major NSR Summary Table

Permit Number: GHGPSDTX170				Issuance Date: 02/04/2021		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
MSS_CAP	Maintenance, Startup and Shutdown Cap	CO ₂ (5)	78.59	11	11	
		CH ₄ (5)	0.24			
		N ₂ O (5)	< 0.01			
		CO ₂ e	84.75			
MSS_TANK	Tank Maintenance, Startup and Shutdown Cap	CO ₂ (5)	314.34	11	11	
		CH ₄ (5)	0.95			
		N ₂ O (5)	< 0.01			
		CO ₂ e	339.01			
O_FUG	Olefins Unit Fugitives	CH ₄ (5)	10.49	10	10	
		CO ₂ e	262.21			
		CO ₂ e	—			
PE_FUG	Total Emissions from EPNs E_FUG, C_FUG	CH ₄ (5)	0.9	10	10	
		CO ₂ e	2.21			
G_FUG	Glycol Unit Fugitives	CO ₂ (5)	0.76	10	10	
		CH ₄ (5)	2.11			
		CO ₂ e	53.62			
U_FUG	Utilities Fugitives	CH ₄ (5)	6.27	10	10	
		CO ₂ e	156.69			

Major NSR Summary Table

Permit Number: GHGPSDTX170				Issuance Date: 02/04/2021		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
PE_REGEN	PE Regeneration Vent	CO ₂ (5)	38.40			
		CO ₂ e	38.40			
ZWSRCO1A/B	Equalization Tanks Catalytic Oxidizer	CO ₂ (5)	573.68	8	8	
		CH ₄ (5)	1.73			
		N ₂ O (5)	< 0.01			
		CO ₂ e	618.69			

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources, use area name or fugitive source name.

(3) CO₂ - carbon dioxide
 N₂O - nitrous oxide
 CH₄ - methane
 CO₂e - carbon dioxide equivalents based on the following Global Warming Potentials (1/2015):
 CO₂ (1), N₂O (298), CH₄(25), SF₆ (22,800), HFC (various), PFC (various)

(4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period. These rates include emissions from maintenance, startup, and shutdown.

(5) Emission rate is given for informational purposes only and does not constitute enforceable limit.

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
O_FAFO1	Pyrolysis Furnace A	CO	165.16	—	7, 18, 20, 21, 62, 63, 64, 66, 69	7, 18, 20, 21, 62, 63, 64, 66, 67	7, 62, 66
		NO _x	25.20	—			
		PM	4.32	—			
		PM ₁₀	4.32	—			
		PM _{2.5}	4.32	—			
		VOC	3.12	—			
		SO ₂	0.34	—			
		H ₂ SO ₄	0.03	—			
		NH ₃	2.51	—			
O_FBFO1	Pyrolysis Furnace B	CO	165.16	—	7, 18, 20, 21, 62, 63, 64, 66, 69	7, 18, 20, 21, 62, 63, 64, 66, 67	7, 62, 66
		NO _x	25.20	—			
		PM	4.32	—			
		PM ₁₀	4.32	—			
		PM _{2.5}	4.32	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		VOC	3.12	—			
		SO ₂	0.34	—			
		H ₂ SO ₄	0.03	—			
		NH ₃	2.51	—			
O_FCF01	Pyrolysis Furnace C	CO	165.16	—	7, 18, 20, 21, 62, 63, 64, 66, 69	7, 18, 20, 21, 62, 63, 64, 66, 67	7, 62, 66
		NO _x	25.20	—			
		PM	4.32	—			
		PM ₁₀	4.32	—			
		PM _{2.5}	4.32	—			
		VOC	3.12	—			
		SO ₂	0.34	—			
		H ₂ SO ₄	0.03	—			
		NH ₃	2.51	—			
O_FDF01	Pyrolysis Furnace D	CO	165.16	—	7, 18, 20, 21, 62, 63,	7, 18, 20, 21, 62, 63,	7, 62, 66

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		NO _x	25.20	—	64, 66, 69	64, 66, 67	
		PM	4.32	—			
		PM ₁₀	4.32	—			
		PM _{2.5}	4.32	—			
		VOC	3.12	—			
		SO ₂	0.34	—			
		H ₂ SO ₄	0.03	—			
		NH ₃	2.51	—			
O_FEF01	Pyrolysis Furnace E	CO	165.16	—	7, 18, 20, 21, 62, 63, 64, 66, 69	7, 18, 20, 21, 62, 63, 64, 66, 67	7, 62, 66
		NO _x	25.20	—			
		PM	4.32	—			
		PM ₁₀	4.32	—			
		PM _{2.5}	4.32	—			
		VOC	3.12	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
O_FFF01	Pyrolysis Furnace F	SO ₂	0.34	—			
		H ₂ SO ₄	0.03	—			
		NH ₃	2.51	—			
		CO	165.16	—	7,18, 20, 21, 62, 63, 64, 66, 69	7,18, 20, 21, 62, 63, 64, 66, 67	7, 62, 66
		NO _x	25.20	—			
		PM	4.32	—			
		PM ₁₀	4.32	—			
		PM _{2.5}	4.32	—			
		VOC	3.12	—			
		SO ₂	0.34	—			
		H ₂ SO ₄	0.03	—			
		NH ₃	2.51	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
O_FGF01	Pyrolysis Furnace G	CO	165.16	—	7, 18, 20, 21, 62, 63, 64, 66, 69	7, 18, 20, 21, 62, 63, 64, 66, 67	7, 62, 66
		NO _x	25.20	—			
		PM	4.32	—			
		PM ₁₀	4.32	—			
		PM _{2.5}	4.32	—			
		VOC	3.12	—			
		SO ₂	0.34	—			
		H ₂ SO ₄	0.03	—			
		NH ₃	2.51	—			
O_FHF01	Pyrolysis Furnace H	CO	165.16	—	7, 18, 20, 21, 62, 63, 64, 66, 69	7, 18, 20, 21, 62, 63, 64, 66, 67	7, 62, 66
		NO _x	25.20	—			
		PM	4.32	—			
		PM ₁₀	4.32	—			
		PM _{2.5}	4.32	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		VOC	3.12	—			
		SO ₂	0.34	—			
		H ₂ SO ₄	0.03	—			
		NH ₃	2.51	—			
O_F_CAP	Pyrolysis Furnaces Cap	CO	651.06	637.87	7, 20, 21	7, 20, 67	7, 66
		NO _x	53.70	196.22			
		NO _x Shakedown	53.70	184.22			
		PM	—	92.85			
		PM ₁₀	—	92.85			
		PM _{2.5}	—	92.85			
		VOC	—	67.20			
		SO ₂	—	7.33			
		H ₂ SO ₄	—	0.67			
		NH ₃	—	77.46			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
UFFLARE01	Multi-Point Ground Flare (Routine)	CO	165.05	—	41, 42, 44	41, 42, 67	42
		NO _x	107.92	—			
		VOC	500.00	—			
		SO ₂	22.00	—			
UFFLARE01	Multi-Point Ground Flare (Planned MSS, alternate operating mode and Shakedown Period) (8)	CO	4115.51	—	41, 42, 44	41, 42, 67	42
		NO _x	2690.91	—			
		VOC	5944.74	—			
		SO ₂	395.28	—			
UFFLARE02	Shared Elevated Flare (Routine)	CO	162.03	—	41, 42, 45	41, 42, 45, 67	42
		NO _x	31.80	—			
		VOC	300.00	—			
		SO ₂	98.00	—			
UFFLARE02	Shared Elevated Flare (Planned MSS, alternate operating	CO	340.99	—	41, 42, 45	41, 42, 45, 67	42
		NO _x	66.92	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
	mode and Shakedown Period) (8)	VOC	916.17	—			
		SO ₂	98.00	—			
CAPUFFLR	Shared Elevated and Ground Flare Cap	CO	—	295.13		67	
		NO _x	—	148.00			
		VOC	—	320.06			
		SO ₂	—	23.60			
CAPUFFLR	Shared Elevated and Ground Flare Cap (Shakedown period)	NO _x	—	192.67		67	
		CO	—	374.11			
		VOC	—	422.30			
		SO ₂	—	23.60			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
O_FUG	Olefins Unit Fugitives (5)	VOC	12.74	55.81	5,7, 33, 34, 35, 54, 70	5, 7, 33, 34,35, 54, 67, 70	5, 7, 33, 34
		VOC (9)	1.11	2.40			
		NH ₃	2.00	8.76			
		CO	0.04	0.16			
		H ₂ SO ₄	< 0.01	0.02			
		H ₂ S	< 0.01	0.01			
		NaOH	< 0.01	< 0.01			
O-REGEN	Olefins Regeneration Vent	VOC	0.18	0.06	10		
		CO	10.61	1.91			
GFFLARE01	MEG Elevated Flare (Routine)	CO	189.44	—	41, 42	41, 42, 67	42
		NO _x	37.18	—			
		VOC	38.59	—			
		SO ₂	22.74	—			
		Total Halide	0.92	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
GFFLARE01	MEG Elevated Flare (Planned MSS and Shakedown Period)	CO	307.90	—	41, 42	41, 42, 67	42
		NO _x	60.42	—			
		VOC	214.93	—			
		SO ₂	22.74	—			
		Total Halide	0.92	—			
GFFLARE01	MEG Elevated Flare	CO	—	88.60	41, 42, 45	41, 42, 45, 67	42
		NO _x	—	17.39			
		VOC	—	17.37			
		SO ₂	—	0.43			
		Total Halide	—	0.40			
GFFLARE01	MEG Elevated Flare (Shakedown Period)	CO	—	103.95	41, 42, 45	41, 42, 45, 67	42
		NO _x	—	20.40			
		VOC	—	21.37			
		SO ₂	—	0.43			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		Total Halide	—	0.40			
GBX02	MEG Thermal Oxidizer	NO _x	8.00	25.79	9, 18, 41, 42, 46, 62	9, 18, 41, 42, 46, 62, 67	42, 46, 62
		CO	11.06	35.65			
		VOC	21.10	41.43			
		SO ₂	1.75	0.38			
		PM	1.00	3.23			
		PM ₁₀	1.00	3.23			
		PM _{2.5}	1.00	3.23			
		Total Halide	0.92	4.04			
		NH ₃	0.04	< 0.01			
GDVAC	Glycol Vacuum Vent	VOC	3.43	0.34	9	9	
GAD09A-D	Glycol Moderator CAS	VOC	< 0.01	< 0.01	11, 47	47, 67	
G_FUG	Glycol Unit Fugitives (5)	VOC	2.22	9.73	5, 7, 33, 34, 54, 70	5, 7, 33, 34, 54, 67, 70	5, 7, 33, 34
		VOC (9)	0.02	0.09			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		CO	0.01	0.03			
UCCT01	Utilities Cooling Tower	VOC	115.29	91.13	36	36, 67	
		PM	8.07	31.56			
		PM ₁₀	5.65	22.09			
		PM _{2.5}	3.39	13.26			
		NaOH	0.03	0.01			
USSG01A	Utilities Boiler A	NO _x	35.25	—	5, 7, 18, 20, 23, 41, 62, 63, 64, 66	5, 7, 18, 20, 23, 41, 62, 63, 64, 66, 67	5, 7, 62, 66
		CO	186.00	—			
		PM	7.82	—			
		PM ₁₀	7.82	—			
		PM _{2.5}	7.82	—			
		VOC	5.66	—			
		SO ₂	5.22	—			
		H ₂ SO ₄	0.07	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		NH ₃	4.02	—			
USSG01B	Utilities Boiler B	NO _x	35.25	—	5, 7, 18, 20, 23, 41, 62, 63, 64, 66	5, 7, 18, 20, 23, 41, 62, 63, 64, 66, 67	5, 7, 62, 66
		CO	186.00	—			
		PM	7.82	—			
		PM ₁₀	7.82	—			
		PM _{2.5}	7.82	—			
		VOC	5.66	—			
		SO ₂	5.22	—			
		H ₂ SO ₄	0.07	—			
		NH ₃	4.02	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
USSG01C	Utilities Boiler C	NO _x	35.25	—	5, 7, 18, 20, 23, 41, 62, 63, 64, 66	5, 7, 18, 20, 23, 41, 62, 63, 64, 66, 67	5, 7, 62, 66
		CO	186.00	—			
		PM	7.82	—			
		PM ₁₀	7.82	—			
		PM _{2.5}	7.82	—			
		VOC	5.66	—			
		SO ₂	5.22	—			
		H ₂ SO ₄	0.07	—			
		NH ₃	4.02	—			
USSG01CAP	Utilities Boiler Cap	NO _x	39.66	69.02	5, 7, 20, 23	5, 7, 20, 23, 67	5, 7, 20, 66
		CO	198.85	239.40			
		PM	—	47.57			
		PM ₁₀	—	47.57			
		PM _{2.5}	—	47.57			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		VOC	—	34.43			
		SO ₂	8.03	5.18			
		H ₂ SO ₄	—	0.48			
		NH ₃	—	29.07			
UFF01A	Shared Thermal Oxidizer A	NO _x	—	—	18, 41, 42, 46, 62, 63, 64, 66	18, 41, 42, 46, 62, 63, 64, 66, 67	42, 46, 62, 66
		CO	—	—			
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
		VOC	—	—			
		SO ₂	—	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
UFF01B	Shared Thermal Oxidizer B	NO _x	—	—	18, 41, 42, 46, 62, 63, 64, 66	18, 41, 42, 46, 62, 63, 64, 66, 67	42, 46, 62, 66
		CO	—	—			
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
		VOC	—	—			
		SO ₂	—	—			
UFF01	Total emissions from EPNs UFF01A, UFF01B	NO _x	18.80	29.11	18, 41, 42	18, 41, 42, 67	42, 66
		CO	25.81	39.95			
		PM	2.34	3.61			
		PM ₁₀	2.34	3.61			
		PM _{2.5}	2.34	3.61			
		VOC	114.96	63.33			
		SO ₂	1.13	1.49			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
U_FUG	Utilities Fugitives (5)	VOC	0.95	4.18	5, 7, 33, 34, 35, 54, 70	5, 7, 33, 34, 35, 54, 67, 70	5, 7, 33
		VOC (9)	0.12	0.26			
		NH ₃	0.22	0.96			
		CO	< 0.01	0.02			
		H ₂ SO ₄	< 0.01	< 0.01			
EMGGEN01	Olefins Emergency Generator No. 1	NO _x	0.38	0.06	5, 7, 60	5, 7, 60, 67	5, 7
		CO	4.48	0.67			
		PM	0.02	< 0.01			
		PM ₁₀	0.02	< 0.01			
		PM _{2.5}	0.02	< 0.01			
		VOC	0.02	< 0.01			
		SO ₂	0.01	< 0.01			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
EMGGEN02	Utilities Emergency Generator No. 2	NO _x	0.38	0.06	5, 7, 60	5, 7, 60, 67	5, 7
		CO	4.48	0.67			
		PM	0.02	< 0.01			
		PM ₁₀	0.02	< 0.01			
		PM _{2.5}	0.02	< 0.01			
		VOC	0.02	< 0.01			
		SO ₂	0.01	< 0.01			
ADMINGEN	Admin Emergency Generator No. 1	NO _x	1.31	0.20	5, 7, 60	5, 7, 60, 67	5, 7
		CO	3.42	0.51			
		PM	0.12	0.02			
		PM ₁₀	0.12	0.02			
		PM _{2.5}	0.12	0.02			
		VOC	0.07	0.01			
		SO ₂	0.02	< 0.01			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
FWP1	Firewater Pump No. 1	NO _x	5.37	0.54	5, 7, 60	5, 7, 60, 67	5, 7
		CO	2.21	0.22			
		PM	0.31	0.03			
		PM ₁₀	0.31	0.03			
		PM _{2.5}	0.31	0.03			
		VOC	0.08	0.01			
		SO ₂	0.01	< 0.01			
FWP2	Firewater Pump No. 2	NO _x	5.37	0.54	5, 7, 60	5, 7, 60, 67	5, 7
		CO	2.21	0.22			
		PM	0.31	0.03			
		PM ₁₀	0.31	0.03			
		PM _{2.5}	0.31	0.03			
		VOC	0.08	0.01			
		SO ₂	0.01	< 0.01			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
GLYGEN01	Glycol Emergency Generator No. 1	NO _x	0.38	0.06	5, 7, 60	5, 7, 60, 67	5, 7
		CO	4.48	0.67			
		PM	0.02	< 0.01			
		PM ₁₀	0.02	< 0.01			
		PM _{2.5}	0.02	< 0.01			
		VOC	0.02	< 0.01			
		SO ₂	0.01	< 0.01			
LIQLOAD	Truck/Railcar Liquid Loading (Uncaptured Emissions)	VOC	4.81	0.64	28, 31	28, 29, 30, 32, 67	
		NaOH	1.31	0.06			
WWTP	Wastewater Plant (Uncontrolled emissions)	VOC	1.05	4.58	37, 38, 39, 40	37, 38, 39, 40, 67	
		NH ₃	< 0.01	< 0.01			
		Acetone	< 0.01	< 0.01			
		H ₂ S	< 0.01	0.01			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
ZWSRCO1A/B	Equalization Tanks Catalytic Oxidizer	VOC	0.04	0.18	39, 62	39, 62, 67	62
		NH ₃	< 0.01	< 0.01			
		Acetone	< 0.01	< 0.01			
		H ₂ S	< 0.01	< 0.01			
		NO _x	0.06	0.26			
		CO	0.02	0.10			
		PM	0.01	0.03			
		PM ₁₀	0.01	0.03			
		PM _{2.5}	0.01	0.03			
		SO ₂	0.01	0.06			
		HCl	< 0.01	0.01			
MSSATM	Maintenance, Startup and Shutdown (Uncontrolled emissions)	VOC	445.47	4.44	50, 53, 54	48, 49, 50, 53, 54, 67	
		PM	12.98	0.08			
		PM ₁₀	12.98	0.08			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		PM _{2.5}	12.98	0.08			
MSSILE	Inherently Low Emitting Activities	VOC	11.49	1.05		48, 49, 67	
		PM	0.02	0.01			
		PM ₁₀	0.02	0.01			
		PM _{2.5}	0.02	0.01			
MSSVAC	MSS Vacuum Trucks	VOC	72.16	1.82	55	48, 49, 55, 67	
MSSFRAC	MSS Frac Tanks	VOC	0.03	0.03	56	48, 49, 56, 67	
TMPCTRL	MSS Temporary Control Devices identified in Special Condition 57	NO _x	3.06	0.20	57	48, 49, 57, 67	
		CO	8.80	0.66			
		PM	0.30	0.02			
		PM ₁₀	0.30	0.02			
		PM _{2.5}	0.30	0.02			
		VOC	24.26	0.68			
		SO ₂	0.56	0.04			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
MSSTANK	Tank Maintenance Activities (Uncontrolled)	VOC	20.11	3.53	51, 52, 54, 56	48, 49, 51, 52, 54, 56, 67	
REFUSTN	Vehicle Refueling Station	VOC	2.03	0.17			
ELDC01	EPE granules feed bin dust collectors	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
EDFAN01	EPE granules hopper vent dust collector	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
EDDC04	EPE seed bed bin dust collector vent	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
ELDC03	EPE extruder dust collector	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
EPFAN01	EPE pellet silos dust collector	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
EMDC01, EMFAN01, EMFAN02	EPE pellet surge bin dust collector and pellet dryer vents	VOC	—	—	15, 16, 62	15, 16, 62, 67	62
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
ELFAN04, ELDC06, ELB01, ELB03, ELB05, ELFAN01	EPE weigh feed hopper extraction vent, zinc oxide drying hopper dust collector, additive vacuum blower vents and solids additives vent dust collector	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
EBFIL01, ECFIL04, ECFIL05, ECFIL06	EPE catalyst cylinder vent filter and catalyst hold tank filter vents	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
E_VENTCAP	EPE Vents Cap (6)	VOC	35.68	37.08	13, 14	13, 14, 67	
		PM	1.08	2.74			
		PM ₁₀	1.08	2.74			
		PM _{2.5}	1.08	2.74			
CLDC01	CPE granules feed bin dust collector	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
CDFAN01	CPE granules hopper vent dust collector	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
CDDC04	CPE seed bed bin dust collector vent	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
CLDC03	CPE extruder feed conveyor dust collector	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
CPFAN01	CPE pellet silos dust collector	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
CMD01, CMFAN01, CMFAN02	CPE pellet surge bin dust collector and pellet dryer vents	VOC	—	—	15, 16, 62	15, 16, 62, 67	62
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
CLFAN04, CLDC06, ELB02, ELB04, CLB03	CPE weigh feeder hopper extraction vent, zinc oxide drying hopper dust collector and additive vacuum blower vents	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			
		PM ₁₀	—	—			
		PM _{2.5}	—	—			
CBFIL01, CCFIL04, CCFIL05, CCFIL06	CPE catalyst cylinder vent filter and	VOC	—	—	15, 16	15, 16, 67	
		PM	—	—			

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
	catalyst hold tank filter vents	PM ₁₀	—	—			
		PM _{2.5}	—	—			
C_VENTCAP	CPE Vents Cap (7)	VOC	35.68	37.08	13, 14	13, 14, 67	
		PM	0.84	2.32			
		PM ₁₀	0.84	2.32			
		PM _{2.5}	0.84	2.32			
PE-REGEN	PE Regeneration Vent	VOC	< 0.01	< 0.01	10		
E_FUG, C_FUG	EPE and CPE Fugitives (5)	VOC	4.38	19.17	5, 7, 33, 34, 54, 70	5, 7, 33, 34, 54, 67, 70	5, 7, 33
		VOC (9)	0.60	1.30			
		CO	0.07	0.32			
ELD01	EPE Primary Run Tank	VOC	0.36	0.02	24, 25	24, 25, 26, 67	
ELD02	EPE Secondary Run Tank	VOC	0.36	0.03	24, 25	24, 25, 26, 67	
CCD81	CPE Seal Pot	VOC	0.04	< 0.01	24, 25	24, 25, 26, 67	

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
GETK02A	MEG Rundown Tank 2A	VOC	0.65	0.22	24, 25	24, 25, 26, 67	
GETK02B	MEG Rundown Tank 2B	VOC	0.65	0.22	24, 25	24, 25, 26, 67	
GDTK01	Glycol Catalyst Storage Tank	VOC	0.23	0.01	24, 25	24, 25, 26, 67	
GDD08	Glycol Catalyst Charge Vessel	VOC	0.03	< 0.01	24, 25	24, 25, 26, 67	
GDD09	Glycol Catalyst Drips Vessel	VOC	0.02	< 0.01	24, 25	24, 25, 26, 67	
GETK01	Glycol Slops Tank	VOC	0.58	0.03	24, 25	24, 25, 26, 67	
SCTOTE-GLY	Spent Glycol Catalyst Tote	VOC	0.04	< 0.01	24, 25	24, 25, 26, 67	
ZTTK02	Heavy Glycol Storage Tank	VOC	0.83	0.03	24, 25	24, 25, 26, 67	
ZTTK03	Glycol Bleed Storage Tank	VOC	0.83	0.03	24, 25	24, 25, 26, 67	
GED04	Glycol Drain Collection Vessel	VOC	0.03	< 0.01	24, 25	24, 25, 26, 67	
ZTTK05	Hexene Storage Tank	VOC	0.43	1.20	5, 24, 25,	5, 24, 25, 26, 67	
ZTTK06AMNT	Heavy Fuel Oil Storage Tank 6A	VOC	0.50	—	5, 7, 24, 25	5, 7, 24, 25, 26, 67	5, 7

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
ZTTK06BMNT	Heavy Fuel Oil Storage Tank 6B	VOC	0.50	—	5, 7, 24, 25	5, 7, 24, 25, 26, 67	5, 7
CAPTHFO	Total Emissions from EPNs ZTTK06AMNT, ZTTK06BMNT	VOC	—	0.03	5, 7, 24	5, 7, 24, 26, 67	5, 7
ZTTK04	Slop Oil Tank 1	VOC	0.72	2.48	5, 6, 7, 24, 25	5, 6, 7, 24, 25, 26, 67	5, 6, 7
FZTK01	Olefins Decoke Condensate Sump	VOC	0.64	0.02	27		
GFTK01	Glycol Flare Seal Sump	VOC	0.53	< 0.01	27		
ZFTK02B	Firewater Pump Diesel Tank 2B	VOC	0.04	< 0.01	24, 25	24, 25, 26, 67	
ZMTK02	Infrastructure Diesel Tank	VOC	0.38	< 0.01	24, 25	24, 25, 26, 67	
UKDGEN01TK	Olefins Emergency Generator No. 1 Diesel Tank	VOC	0.05	< 0.01	24, 25	24, 25, 26, 67	
UKDGEN02TK	Utilities Emergency Generator No. 2 Diesel Tank	VOC	0.05	< 0.01	24, 25	24, 25, 26, 67	
ADMINGENTK	Admin Emergency Generator No 1 Diesel Tank	VOC	0.12	< 0.01	24, 25	24, 25, 26, 67	

Major NSR Summary Table

Permit Numbers: 146425 and PSDTX1518					Issuance Date: September 23, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
ZFTK02C	Firewater Pump Diesel Tank 2C	VOC	0.04	< 0.01	24, 25	24, 25, 26, 67	
GUDGEN01TK	Glycol Generator Diesel Tank	VOC	0.05	< 0.01	24, 25	24, 25, 26, 67	
ZMTK01	Infrastructure Gasoline Tank	VOC	11.61	1.71	24, 25	24, 25, 26, 67	
TOTES	Site Totes	NaOCl	0.01	< 0.01			
U_LAB	Laboratory	VOC	2.65	0.48	59	59	
UTTK04	Sulfuric Acid Tank	H ₂ SO ₄	< 0.01	< 0.01	24, 25	24, 25, 26, 67	
UCTK01	Sodium Hypochlorite Tank	NaOCl	2.23	0.08	24, 25	24, 25, 26, 67	
UTD05	Aqueous Ammonia Vent Drum	NH ₃	1.94	0.15	61		
ZTTK01	Caustic Storage Tank	NaOH	0.33	0.03	24, 25	24, 25, 26, 67	

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources, use area name or fugitive source name.

- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
- NO_x - total oxides of nitrogen
- SO₂ - sulfur dioxide
- PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
- PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
- PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter

CO	- carbon monoxide
NaOH	- sodium hydroxide
NH ₃	- ammonia
HCl	- hydrogen chloride
HI	- hydrogen iodide
H ₂ SO ₄	- sulfuric acid mist
H ₂ S	- hydrogen sulfide
Total Halide	- combined emissions of hydrogen chloride and hydrogen iodide.
NaOCl	- sodium hypochlorite

- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
- (6) Includes total emissions for the following sources of emissions (designated by EPN): ELDC01, EDFAN01, EDDC04, ELDC03, EPFAN01, EMDC01, EMFAN01, EMFAN02, ELFAN04, ELDC06, ELB01, ELB03, ELB05, ELFAN01, EBFIL01, ECFIL04, ECFIL05, ECFIL06
- (7) Includes total emissions for the following sources of emissions (designated by EPN): CLDC01, CDFAN01, CDDC04, CLDC03, CPFAN01, CMDC01, CMFAN01, CMFAN02, CLFAN04, CLDC06, ELB02, ELB04, CLB03, CBFIL01, CCFIL04, CCFIL05, CCFIL06
- (8) Alternate operating mode as defined in Special Condition 48.
- (9) Additional emission limits for connectors during the initial unit shakedown period use of alternate fugitive monitoring per Special Condition 70.

Special Conditions

Permit Number GHGPSDTX170

1. This permit authorizes greenhouse gas (GHG) emissions only from those emission points listed in the attached table entitled "Emission Sources – Maximum Allowable Emission Rates" (MAERT), and the facilities covered by this permit are authorized to emit subject to the emission rate limits on that table and other operating conditions specified in this permit.

This permit authorizes GHG emissions from maintenance, startup, and shutdown (MSS) activities, provided that GHG emissions are limited as required by this Special Condition, and MSS activities are conducted pursuant to the requirements of Special Condition 7.

2. Any calculation for carbon dioxide equivalent (CO₂e) emission rates required by this permit shall employ Global Warming Potential (GWP) contained in Greenhouse Gas Regulations, 40 CFR Part 98, Subpart A, Table A-1, as amended on December 11, 2014 (79 FR 73779).

3. Where a methodology of 40 CFR Part 98 is referenced in this permit, such reference method shall be modified as follows:

- A. References to annual measurements shall be construed as rolling 12-month totals if the relevant parameter is measured on a monthly or more frequent basis.
- B. References to annual measurements that are not measured at a frequency greater than one month (e.g. quarterly or semiannual) shall be construed as the average of the most recent measurements based on a rolling 12-month period (e.g. average of 4 quarterly or 2 semiannual measurements).

4. Terms and definitions specified in Special Condition 2 of permit 146425 shall apply to this permit.

5. Pyrolysis furnaces and boilers (EPNs O_FAF01, O_FBF01, O_FCF01, O_FDF01, O_FEF01, O_FFF01, O_FGF01, O_FHF01, USSG01A, USSG01B, USSG01C) are subject to the following requirements.

- A. Rolling 12-month CO₂e emissions shall be calculated each month using the methods provided at 40 CFR § 98.243(a).
- B. The higher heating value (HHV) of the fuel shall be determined and recorded on a semiannual basis following procedures provided at 40 CFR § 98.34(a)(6).
The carbon content of the fuel shall be determined and recorded on a semiannual basis following the procedures provided at 40 CFR § 98.34(b)(3).
- C. The permit holder shall install, operate, and maintain an automated air/fuel controller in each combustion device.
- D. The permit holder shall continuously monitor and record the exhaust temperature and the oxygen content of the flue gas for each combustion device. Monitoring device shall reduce temperature and oxygen readings to six-minute average or less and record readings at that frequency.

The temperature monitor shall be installed, calibrated or have a calibration check performed at least annually, and maintained according to the manufacturer's specifications. The device shall have an accuracy of the greater of

±2 percent of the temperature being measured expressed in degrees Celsius or ±2.5°C.

Oxygen analyzers shall comply with Special Condition No. 66 of Permit 146425. **(02/21)**

- E. The permit holder shall install, calibrate, maintain, and operate a continuous fuel flow monitor and record the average hourly fuel gas consumption of each combustion device. Fuel flow meters shall be calibrated as provided for at 40 CFR § 98.34(b)(1).

6. Each boiler (EPNs USSG01A, USSG01B, USSG01C) shall be operated with a thermal efficiency of no less than 77 percent on a 12-month rolling average. This shall be ensured by using the following good combustion practices: operating each device at an optimum air-fuel ratio, limiting the device's operating temperature to the extent practicable, and reducing heat loss through the use of insulating materials where feasible.

Thermal efficiency shall be calculated and recorded at least monthly using the following equation, monitoring data collected as required under this permit and permit 146425, other quality-assured data, and engineering judgment.

7. The stack exhaust temperature for each pyrolysis furnace (EPNs O_FAF01, O_FBF01, O_FCF01, O_FDF01, O_FEF01, O_FFF01, O_FGF01, O_FHF01) shall not exceed 340° F on a 365-day rolling average, not including periods of startup, shutdown, hot steam standby, and decoking. This shall be ensured by using the following good combustion practices: operating each device at an optimum air-fuel ratio, limiting the device's operating temperature to the extent practicable, and reducing heat loss through the use of insulating materials where feasible.

8. Total rolling 12-month CO₂e emissions from the following control devices shall be calculated on a monthly basis as provided for at 40 CFR §§ 98.243(a) or 98.33(a)(1)(i), as applicable.

EPN	Source Name
UFFLARE01	Multi-point Ground Flare
UFFLARE02	Shared Elevated Flare
UFF01A	Shared Thermal Oxidizer A
UFF01B	Shared Thermal Oxidizer B
ZWSRCO1A/B	Equalization Tanks Catalytic Oxidizer

9. Total rolling 12-month CO₂e emissions from the Glycol Plant shall be calculated on a monthly basis using the procedures specified at 40 CFR § 98.243(a).

10. Emissions from leaking piping components (EPNs: O_FUG, PE_FUG, G_FUG, U_FUG) shall be minimized as follows.

A. The permit holder shall implement equipment leak fugitive programs as specified in Special Condition Nos. 33–34 of Permit 146425.

B. Total rolling 12-month CO₂e emissions shall be calculated as provided at 40 CFR 98.253(l), except that mass emission rates shall be converted and recorded in units of short tons per year.

11. The permit holder shall comply with all applicable control monitoring and recordkeeping requirements of permits 146425 applying to planned MSS activities.

Special Conditions
Permit Number GHGPSDTX170
Page 3

Date: February 4, 2021

Emission Sources - Maximum Allowable Emission Rates

Permit Number GHGPSDTX170

This table lists the maximum allowable emission rates of greenhouse gas (GHG) emissions, as defined in Title 30 Texas Administrative Code § 101.1, for all sources of GHG air contaminants on the applicant's property that are authorized by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities authorized by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates
			TPY (4)
O_FAF01	Pyrolysis Furnace A	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO ₂ e	—
O_FBF01	Pyrolysis Furnace B	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO ₂ e	—
O_FCF01	Pyrolysis Furnace C	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO ₂ e	—
O_FDF01	Pyrolysis Furnace D	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO ₂ e	—
O_FEF01	Pyrolysis Furnace E	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO ₂ e	—
O-FFF01	Pyrolysis Furnace F	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO ₂ e	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates
			TPY (4)
O_FGF01	Pyrolysis Furnace G	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—
O_FHF01	Pyrolysis Furnace H	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—
O_F_CAP	Pyrolysis Furnaces Cap	CO ₂ (5)	1555774.36
		CH ₄ (5)	129.80
		N ₂ O (5)	25.96
		CO _{2e}	1566755.63
UFFLARE01	Multi-point Ground Flare	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—
UFFLARE02	Shared Elevated Flare	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—
CAPUFFLR	Shared Elevated and Ground Flare Cap	CO ₂ (5)	150087.73
		CH ₄ (5)	93.95
		N ₂ O (5)	1.50
		CO _{2e}	152883.64
CAPUFFLR	Shared Elevated and Ground Flare Cap (Shakedown Period)	CO ₂ (5)	191633.46
		CH ₄ (5)	116.32
		N ₂ O (5)	1.92
		CO _{2e}	195085.70
O_FUG	Olefins Unit Fugitives	CH ₄	10.49
		CO _{2e}	262.21

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates
			TPY (4)
O-REGEN	Olefins Regeneration Vent	CO ₂ (5)	17.18
		CO _{2e}	17.18
GFFLARE01	MEG Elevated Flare	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—
GBX02	MEG Thermal Oxidizer	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—
G_FUG	Glycol Unit Fugitives	CO ₂ (5)	0.76
		CH ₄ (5)	2.11
		CO _{2e}	53.62
GLYCAP	MEG Elevated Flare and MEG Thermal Oxidizer Cap	CO ₂ (5)	428930.74
		CH ₄ (5)	195.17
		N ₂ O (5)	0.94
		CO _{2e}	434091.18
GLYCAP	MEG Elevated Flare and MEG Thermal Oxidizer Cap (Shakedown Period)	CO ₂ (5)	435416.28
		CH ₄ (5)	199.23
		N ₂ O (5)	1.01
		CO _{2e}	440697.54
USSG01A	Utilities Boiler A	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—
USSG01B	Utilities Boiler B	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates
			TPY (4)
USSG01C	Utilities Boiler C	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—
USSG01CAP	Utilities Boiler Cap	CO ₂ (5)	676557.06
		CH ₄ (5)	45.63
		N ₂ O (5)	9.13
		CO _{2e}	680417.66
UFF01A	Shared Thermal Oxidizer A	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—
UFF01B	Shared Thermal Oxidizer B	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—
UFF01	Shared Thermal Oxidizer Cap	CO ₂ (5)	63536.78
		CH ₄ (5)	191.84
		N ₂ O (5)	0.64
		CO _{2e}	68522.08
U_FUG	Utilities Fugitives	CH ₄	6.27
		CO _{2e}	156.69
EMGGEN01	Olefins Emergency Generator No. 1	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—
EMGGEN02	Utilities Emergency Generator No. 2	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO _{2e}	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates
			TPY (4)
ADMINGEN	Admin Emergency Generator No. 1	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO ₂ e	—
FWP1	Firewater Pump No.1	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO ₂ e	—
FWP2	Firewater Pump No. 2	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO ₂ e	—
GLYGEN01	Glycol Emergency Generator No. 1	CO ₂ (5)	—
		CH ₄ (5)	—
		N ₂ O (5)	—
		CO ₂ e	—
ENGINECAP	Emergency Generator and Firewater Pump Cap	CO ₂ (5)	1132.44
		CH ₄ (5)	0.05
		N ₂ O (5)	0.01
		CO ₂ e	1136.33
MSS_CAP	Maintenance, Startup and Shutdown Cap	CO ₂ (5)	78.59
		CH ₄ (5)	0.24
		N ₂ O (5)	< 0.01
		CO ₂ e	84.75
MSS_TANK	Tank Maintenance, Startup and Shutdown Cap	CO ₂ (5)	314.34
		CH ₄ (5)	0.95
		N ₂ O (5)	< 0.01
		CO ₂ e	339.01
PE_FUG	Total Emissions from EPNs E_FUG, C_FUG	CH ₄ (5)	0.09
		CO ₂ e	2.21

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates
			TPY (4)
PE_REGEN	PE Regeneration Vent	CO ₂ (5)	38.40
		CO ₂ e	38.40
ZWSRCO1A/B	Equalization Tanks Catalytic Oxidizer	CO ₂ (5)	573.68
		CH ₄ (5)	1.73
		N ₂ O (5)	< 0.01
		CO ₂ e	618.69

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
(2) Specific point source name. For fugitive sources, use area name or fugitive source name.
(3) CO₂ - carbon dioxide
N₂O - nitrous oxide
CH₄ - methane
CO₂e - carbon dioxide equivalents based on the following Global Warming Potentials (1/2015):
CO₂ (1), N₂O (298), CH₄(25), SF₆ (22,800), HFC (various), PFC (various)
(4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period. These rates include emissions from maintenance, startup, and shutdown.
(5) Emission rate is given for informational purposes only and does not constitute enforceable limit.

Date: February 4, 2021



Texas Commission on Environmental Quality Air Quality Permit

A Permit Is Hereby Issued To
Gulf Coast Growth Ventures LLC
Authorizing the Construction and Operation of
Gulf Coast Growth Ventures
Located at **Gregory, San Patricio County, Texas**
Latitude 27° 55' 47" Longitude -97° 19' 19"

Permits: 146425, GHGPSDTX170 and PSDTX1518

Revision Date: September 23, 2022

Expiration Date: June 12, 2029



For the Commission

1. **Facilities** covered by this permit shall be constructed and operated as specified in the application for the permit. All representations regarding construction plans and operation procedures contained in the permit application shall be conditions upon which the permit is issued. Variations from these representations shall be unlawful unless the permit holder first makes application to the Texas Commission on Environmental Quality (commission) Executive Director to amend this permit in that regard and such amendment is approved. [Title 30 Texas Administrative Code (TAC) Section 116.116 (30 TAC § 116.116)] ¹
2. **Voiding of Permit.** A permit or permit amendment is automatically void if the holder fails to begin construction within 18 months of the date of issuance, discontinues construction for more than 18 months prior to completion, or fails to complete construction within a reasonable time. Upon request, the executive director may grant an 18-month extension. Before the extension is granted the permit may be subject to revision based on best available control technology, lowest achievable emission rate, and netting or offsets as applicable. One additional extension of up to 18 months may be granted if the permit holder demonstrates that emissions from the facility will comply with all rules and regulations of the commission, the intent of the Texas Clean Air Act (TCAA), including protection of the public's health and physical property; and (b)(1) the permit holder is a party to litigation not of the permit holder's initiation regarding the issuance of the permit; or (b)(2) the permit holder has spent, or committed to spend, at least 10 percent of the estimated total cost of the project up to a maximum of \$5 million. A permit holder granted an extension under subsection (b)(1) of this section may receive one subsequent extension if the permit holder meets the conditions of subsection (b)(2) of this section. [30 TAC § 116.120]
3. **Construction Progress.** Start of construction, construction interruptions exceeding 45 days, and completion of construction shall be reported to the appropriate regional office of the commission not later than 15 working days after occurrence of the event. [30 TAC § 116.115(b)(2)(A)]
4. **Start-up Notification.** The appropriate air program regional office shall be notified prior to the commencement of operations of the facilities authorized by the permit in such a manner that a representative of the commission may be present. The permit holder shall provide a separate notification for the commencement of operations for each unit of phased construction, which may involve a series of units commencing operations at different times. Prior to operation of the facilities authorized by the permit, the permit holder shall identify the source or sources of allowances to be utilized for compliance with Chapter 101, Subchapter H, Division 3 of this title (relating to Mass Emissions Cap and Trade Program). [30 TAC § 116.115(b)(2)(B)]
5. **Sampling Requirements.** If sampling is required, the permit holder shall contact the commission's Office of Compliance and Enforcement prior to sampling to obtain the proper data forms and procedures. All sampling and testing procedures must be approved by the executive director and coordinated with the regional representatives of the commission. The permit holder is also responsible for providing sampling facilities and conducting the sampling operations or contracting with an independent sampling consultant. [30 TAC § 116.115(b)(2)(C)]
6. **Equivalency of Methods.** The permit holder must demonstrate or otherwise justify the equivalency of emission control methods, sampling or other emission testing methods, and monitoring methods proposed as alternatives to methods indicated in the conditions of the permit. Alternative methods shall be applied for in writing and must be reviewed and approved by the executive director prior to their use in fulfilling any requirements of the permit. [30 TAC § 116.115(b)(2)(D)]
7. **Recordkeeping.** The permit holder shall maintain a copy of the permit along with records containing the information and data sufficient to demonstrate compliance with the permit, including production records and

operating hours; keep all required records in a file at the plant site. If, however, the facility normally operates unattended, records shall be maintained at the nearest staffed location within Texas specified in the application; make the records available at the request of personnel from the commission or any air pollution control program having jurisdiction in a timely manner; comply with any additional recordkeeping requirements specified in special conditions in the permit; and retain information in the file for at least two years following the date that the information or data is obtained. [30 TAC § 116.115(b)(2)(E)]

8. **Maximum Allowable Emission Rates.** The total emissions of air contaminants from any of the sources of emissions must not exceed the values stated on the table attached to the permit entitled "Emission Sources-- Maximum Allowable Emission Rates." [30 TAC § 116.115(b)(2)(F)] ¹
9. **Maintenance of Emission Control.** The permitted facilities shall not be operated unless all air pollution emission capture and abatement equipment is maintained in good working order and operating properly during normal facility operations. The permit holder shall provide notification in accordance with 30 TAC §101.201, 101.211, and 101.221 of this title (relating to Emissions Event Reporting and Recordkeeping Requirements; Scheduled Maintenance, Startup, and Shutdown Reporting and Recordkeeping Requirements; and Operational Requirements). [30 TAC§ 116.115(b)(2)(G)]
10. **Compliance with Rules.** Acceptance of a permit by an applicant constitutes an acknowledgment and agreement that the permit holder will comply with all rules and orders of the commission issued in conformity with the TCAA and the conditions precedent to the granting of the permit. If more than one state or federal rule or regulation or permit condition is applicable, the most stringent limit or condition shall govern and be the standard by which compliance shall be demonstrated. Acceptance includes consent to the entrance of commission employees and agents into the permitted premises at reasonable times to investigate conditions relating to the emission or concentration of air contaminants, including compliance with the permit. [30 TAC § 116.115(b)(2)(H)]
11. **This** permit may not be transferred, assigned, or conveyed by the holder except as provided by rule. [30 TAC § 116.110(e)]
12. **There** may be additional special conditions attached to a permit upon issuance or modification of the permit. Such conditions in a permit may be more restrictive than the requirements of Title 30 of the Texas Administrative Code. [30 TAC § 116.115(c)]
13. **Emissions** from this facility must not cause or contribute to "air pollution" as defined in Texas Health and Safety Code (THSC) §382.003(3) or violate THSC § 382.085. If the executive director determines that such a condition or violation occurs, the holder shall implement additional abatement measures as necessary to control or prevent the condition or violation.
14. **The** permit holder shall comply with all the requirements of this permit. Emissions that exceed the limits of this permit are not authorized and are violations of this permit. ¹

¹ Please be advised that the requirements of this provision of the general conditions may not be applicable to greenhouse gas emissions.

Common Acronyms in Air Permits

°C = Temperature in degrees Celsius	GLCmax = maximum (predicted) ground-level concentration
°F = Temperature in degrees Fahrenheit	gpm = gallon per minute
°K = Temperature in degrees Kelvin	gr/1000scf = grain per 1000 standard cubic feet
µg = microgram	gr/dscf = grain per dry standard cubic feet
µg/m ³ = microgram per cubic meter	H ₂ CO = formaldehyde
acfm = actual cubic feet per minute	H ₂ S = hydrogen sulfide
AMOC = alternate means of control	H ₂ SO ₄ = sulfuric acid
AOS = alternative operating scenario	HAP = hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
AP-42 = Air Pollutant Emission Factors, 5th edition	HC = hydrocarbons
APD = Air Permits Division	HCl = hydrochloric acid, hydrogen chloride
API = American Petroleum Institute	Hg = mercury
APWL = air pollutant watch list	HGB = Houston/Galveston/Brazoria
BPA = Beaumont/ Port Arthur	hp = horsepower
BACT = best available control technology	hr = hour
BAE = baseline actual emissions	IFR = internal floating roof tank
bbl = barrel	in H ₂ O = inches of water
bbl/day = barrel per day	in Hg = inches of mercury
bhp = brake horsepower	IR = infrared
BMP = best management practices	ISC3 = Industrial Source Complex, a dispersion model
Btu = British thermal unit	ISCST3 = Industrial Source Complex Short-Term, a dispersion model
Btu/scf = British thermal unit per standard cubic foot or feet	K = Kelvin; extension of the degree Celsius scaled-down to absolute zero
CAA = Clean Air Act	LACT = lease automatic custody transfer
CAM = compliance-assurance monitoring	LAER = lowest achievable emission rate
CEMS = continuous emissions monitoring systems	lb = pound
cfm = cubic feet (per) minute	hp = horsepower
CFR = Code of Federal Regulations	hr = hour lb/day = pound per day
CN = customer ID number	lb/hr = pound per hour
CNG = compressed natural gas	lb/MMBtu = pound per million British thermal units
CO = carbon monoxide	LDAR = Leak Detection and Repair (Requirements)
COMS = continuous opacity monitoring system	LNG = liquefied natural gas
CPMS = continuous parametric monitoring system	LPG = liquefied petroleum gas
DFW = Dallas/ Fort Worth (Metroplex)	LT/D = long ton per day
DE = destruction efficiency	m = meter
DRE = destruction and removal efficiency	m ³ = cubic meter
dscf = dry standard cubic foot or feet	m/sec = meters per second
dscfm = dry standard cubic foot or feet per minute	MACT = maximum achievable control technology
ED = (TCEQ) Executive Director	MAERT = Maximum Allowable Emission Rate Table
EF = emissions factor	MERA = Modeling and Effects Review Applicability
EFR = external floating roof tank	mg = milligram
EGU = electric generating unit	mg/g = milligram per gram
EI = Emissions Inventory	mL = milliliter
ELP = El Paso	MMBtu = million British thermal units
EPA = (United States) Environmental Protection Agency	MMBtu/hr = million British thermal units per hour
EPN = emission point number	MSDS = material safety data sheet
ESL = effects screening level	MSS = maintenance, startup, and shutdown
ESP = electrostatic precipitator	MW = megawatt
FCAA = Federal Clean Air Act	NAAQS = National Ambient Air Quality Standards
FCCU = fluid catalytic cracking unit	NESHAP = National Emission Standards for Hazardous Air Pollutants
FID = flame ionization detector	NGL = natural gas liquids
FIN = facility identification number	NNSR = nonattainment new source review
ft = foot or feet	NO _x = total oxides of nitrogen
ft/sec = foot or feet per second	
g = gram	
gal/wk = gallon per week	
gal/yr = gallon per year	
GLC = ground level concentration	

NSPS = New Source Performance Standards
PAL = plant-wide applicability limit
PBR = Permit(s) by Rule
PCP = pollution control project
PEMS = predictive emission monitoring system
PID = photo ionization detector
PM = periodic monitoring
PM = total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
PM_{2.5} = particulate matter equal to or less than 2.5 microns in diameter
PM₁₀ = total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
POC = products of combustion
ppb = parts per billion
ppm = parts per million
ppmv = parts per million (by) volume
psia = pounds (per) square inch, absolute
psig = pounds (per) square inch, gage
PTE = potential to emit
RA = relative accuracy
RATA = relative accuracy test audit
RM = reference method
RVP = Reid vapor pressure
scf = standard cubic foot or feet
scfm = standard cubic foot or feet (per) minute
SCR = selective catalytic reduction
SIL = significant impact levels
SNCR = selective non-catalytic reduction
SO₂ = sulfur dioxide
SOCMI = synthetic organic chemical manufacturing industry
SRU = sulfur recovery unit
TAC = Texas Administrative Code
TCAA = Texas Clean Air Act
TCEQ = Texas Commission on Environmental Quality
TD = Toxicology Division
TLV = threshold limit value
TMDL = total maximum daily load
tpd = tons per day
tpy = tons per year
TVP = true vapor pressure
VOC = volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
VRU = vapor recovery unit or system

Special Conditions

Permit Numbers 146425 and PSDTX1518

1. This permit covers only those sources of emissions listed in the attached table entitled "Emission Sources - Maximum Allowable Emission Rates" (MAERT), and those sources are limited to the emission limits and other conditions specified in that table.

The names of chemical species referred to in these Special Conditions may be abbreviated as indicated in the attached MAERT.

Definitions

2. Terms used in this permit shall have the following meanings:
 - A. *Standard conditions* have the meaning assigned to it at 30 TAC § 101.1(99).
 - B. *Pyrolysis furnace* means a process heater subject to Special Condition 1 that produces hydrocarbon products from the endothermic cracking of feedstocks such as ethane, propane, butane, and naphtha using combustion to provide indirect heating for the cracking process.
 - C. *Boiler* means any combustion equipment other than a pyrolysis furnace which is subject to Special Condition 1 and is used to produce steam or to heat water.
 - D. *Combustion unit* means a boiler or pyrolysis furnace.
 - E. The following definitions apply to pyrolysis furnaces.
 - (1) *Non-routine operation* means decoking, hot steam standby, feed in, feed out, startup or shutdown.
 - (2) *Routine operation* means any period of operation other than non-routine operation.
 - (3) *Startup* means the period beginning when fuel is first introduced to the furnace, during either initial startup or following a shutdown; and ending when the SCR catalyst bed reaches its design operating temperature.
 - (4) *Shutdown* means the period beginning when the SCR catalyst bed drops below its design operating temperature and ending when all fuel is removed from the furnace.
 - (5) *Decoking* means the period beginning when air is introduced to the furnace cracking coils for the purpose of decoking, and ending when decoking air is removed.
 - (6) *Feed in* means the period beginning when hydrocarbon feed is first introduced to the furnace, following decoking, hot steam standby, or startup, and ending when the furnace reaches 70% of its design firing rate.
 - (7) *Feed out* means the period beginning when the furnace drops below 70% of its design firing rate and remains below that level; and ending when hydrocarbon feed is isolated from the furnace.
 - (8) *Hot steam standby* means operations occurring when the furnace is firing at or below 50% of its design firing rate and no hydrocarbon feed is being charged to the furnace, and the furnace is not in start-up or shut-down.
 - F. The following definitions apply to boilers.
 - (1) *Non-routine operation* means startup, shutdown, or low firing.
 - (2) *Startup* and *shutdown* have the meanings specified in 40 CFR § 63.7575.

- (3) *Low firing* means:
 - (a) With respect to an emission limitation for NO_x, operation of a boiler at a firing rate that is no greater than the lesser of:
 - i. 30% of the maximum rated heat duty for the boiler; or
 - ii. The firing rate at which the flue gas temperature is at the minimum design operating temperature of the SCR catalyst bed.
 - (b) With respect to any other requirement of the permit, operation of a boiler at a firing rate of no greater than 30% of the maximum rated heat duty of the boiler.
- G. *Flare Gas Recovery Unit* means a system of one or more compressors, piping and the associated water seal, rupture disk or similar device used to divert gas from the flare and direct the gas to the fuel gas system.
- H. The following engineering abbreviations shall have their customary meanings, reproduced as follows:
 - (1) HHV: Higher Heating Value
 - (2) LHV: Lower Heating Value, or Net Heating Value
 - (3) MMBtu: Million British Thermal Units
 - (4) ppbw: Parts per billion by weight
 - (5) ppmv: Parts per million by volume
 - (6) ppmvd: Parts per million by volume, dry basis
 - (7) ppmw: Parts per million by weight
 - (8) dscf: Dry standard cubic feet
 - (9) gr: Grains
 - (10) MMlb: million pounds
 - (11) gpm: Gallons per minute
 - (12) µmho/cm: micromho per centimeter
 - (13) mg/L: milligram per liter
 - (14) cfm: cubic feet per minute
- I. Other abbreviations shall have the following meanings:
 - (1) CEMS: continuous emissions monitoring system
 - (2) SCR: selective catalytic reduction
 - (3) CAS: carbon adsorption system
 - (4) EPN: emission point number
 - (5) TDS: total dissolved solids
 - (6) CFR: Code of Federal Regulations

- (7) IFR: Internal Floating Roof Tank
- (8) VFT: Vertical Fixed Roof Tank
- (9) HFT: Horizontal Fixed Roof Tank
- (10) TAC: Texas Administrative Code
- (11) CFR: Code of Federal Regulations
- (12) FR: *Federal Register*
- (13) EPA: U.S. Environmental Protection Agency
- (14) API: American Petroleum Institute
- (15) HAP: Hazardous Air Pollutants listed in § 112(b) of the Federal Clean Air Act, as modified in 40 CFR Part 63, Subpart C
- (16) TPDES: Texas Pollutant Discharge Elimination System

J. The following definitions apply to closed vent systems and control devices.

- (1) *Shared vent system* means a closed vent system which is designed and operated to collect air contaminant vapors and route the collected vapors to one or more of the following control devices or recovery systems:
 - (a) Either of the shared thermal oxidizers (EPNs UFF01A or UFF01B), operated as specified in Special Condition 46;
 - (b) The shared elevated flare (EPN UFFLARE02), operated as specified in Special Condition 45;
 - (c) The multi-point ground flare (EPN UFFLARE01), operated as specified in Special Condition 44; or
 - (d) The Flare Gas Recovery Unit.
- (2) *Glycol vent system* means a closed vent system which is designed and operated to collect air contaminant vapors and route the collected vapors to one or more of the following control devices:
 - (a) The MEG thermal oxidizer (EPN GBX02), operated as specified in Special Condition 46; or
 - (b) The MEG elevated flare (EPN GFFLARE01), operated as specified in Special Condition 45.

K. *Shakedown period* means **(02/21)**:

- (1) With respect to any long-term emissions limitation applying to the shared vent system control devices on a rolling 12-month basis, the 18-month period beginning with the initial start-up of the source of emissions subject to such emission limitation; and
- (2) With respect to any short-term emission limitation applying to the shared vent system control devices, the period beginning with the initial start-up of the source, and ending either:
 - (a) 180 days following start-up of the last unit of phased construction; or

- (b) Upon completion of stack sampling required under Special Condition 62 for the source and pollutant to which the emission limitation applies;
Whichever is sooner.
 - (3) With respect to any other long-term emission limitation applying on a rolling 12-month basis, the 12-month period beginning with the initial start-up of the source of emissions subject to such emission limitation; and
 - (4) With respect to any other short-term emission limitation, the period beginning with the initial start-up of the source subject to the emission limitation, and ending either:
 - (a) 180 days following start-up of the source; or
 - (b) Upon completion of stack sampling required under Special Condition 62 for the source and pollutant to which the emission limitation applies;
Whichever is sooner.
- 3. Emission or operating limits identified in Special Conditions 21 and 23 of this permit, which are expressed using units of heat, are based on the higher heating value of the fuel input to a combustion unit.
- 4. Except where otherwise indicated, emission limits expressed in terms of concentration of a pollutant in the exhaust of a combustion unit or control device shall be evaluated on a dry basis, corrected to 3% oxygen.

Federal Applicability

- 5. These facilities shall comply with all applicable requirements of the U.S. Environmental Protection Agency (EPA) regulations on Standards of Performance for New Stationary Sources promulgated in Title 40 Code of Federal Regulations Part 60 (40 CFR Part 60):
 - A. Subpart A, General Provisions.
 - B. Subpart Db, Industrial-Commercial-Institutional Steam Generating Units.
 - C. Subpart Kb, Volatile Organic Liquid Storage Vessels.
 - D. Subpart VVa, Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry (SOCMI).
 - E. Subpart DDD, Polymer Manufacturing Industry.
 - F. Subpart NNN, SOCMI Distillation Operations.
 - G. Subpart RRR, SOCMI Reactor Processes.
 - H. Subpart IIII, Stationary Compression Ignition Internal Combustion Engines.
- 6. These facilities shall comply with all applicable requirements of the EPA regulations on National Emission Standards for Hazardous Air Pollutants in 40 CFR Part 61:
 - A. Subpart A, General Provisions.

- B. Subpart J, Equipment Leaks of Benzene.
 - C. Subpart FF, Benzene Waste Operations.
7. These facilities shall comply with all applicable requirements of the U.S. Environmental Protection Agency (EPA) regulations on National Emission Standards for Hazardous Air Pollutants for Source Categories in 40 CFR Part 63: **(02/21)**
- A. Subpart A, General Provisions.
 - B. Subpart F, SOCM.
 - C. Subpart G, SOCM Process Vents, Storage Vessels, Transfer Operations, and Wastewater.
 - D. Subpart H, Equipment Leaks.
 - E. Subpart UU, Equipment Leaks— Control Level 2 Standards.
 - F. Subpart SS, Closed Vent Systems, Control Devices, Recovery Devices and Routing to a Fuel Gas System or a Process.
 - G. Subpart XX, Ethylene Manufacturing Process Units: Heat Exchange Systems and Waste Operations
 - H. Subpart YY, Generic Maximum Achievable Control Technology Standards.
 - I. Subpart EEEE, Organic Liquids Distribution (Non-Gasoline).
 - J. Subpart FFFF, Miscellaneous Organic Chemical Manufacturing.
 - K. Subpart ZZZZ, Stationary Reciprocating Internal Combustion Engines.
 - L. Subpart DDDDD, Industrial, Commercial, and Institutional Boilers and Process Heaters.

Process Vents

8. Non-fugitive emissions of gases containing volatile organic compounds (VOC) at a concentration of greater than 1 percent from relief valves, safety valves, or rupture discs are not authorized by this permit unless authorized on the MAERT. With the exception of devices which relieve to the atmosphere only in the event of a fire, any releases directly to atmosphere from relief valves, safety valves, or rupture discs of gases containing VOC at a concentration greater than 1 weight percent are not consistent with good practice for minimizing emissions.
9. All process vents from vacuum producing equipment in the Glycols plant shall be controlled using the MEG I Thermal Oxidizer (EPN GBX02) or the MEG Elevated Flare (GFFLARE01). This requirement does not apply, and the vents may be directed to the atmosphere, in case either of the following criteria are satisfied and the emission rates do not exceed the MAERT limits for the Glycol Vacuum Vent (EPN GDVAC): **(10/21)**
- A. Atmospheric venting occurs during planned start-up or shut-down of the Glycols plant that may result in an elevated oxygen concentration in the vacuum producing equipment.
 - B. The MEG Thermal Oxidizer (EPN GBX02) is out of service for planned maintenance.

Records of atmospheric venting for the Glycol Vacuum Vent (EPN GDVAC) shall be retained, and the permit holder shall make all reasonable efforts to limit the duration of atmospheric venting.

10. Prior to any uncontrolled venting from the Olefins Regeneration Vent (EPN O-REGEN) and the PE Regeneration Vent (EPN PE-REGEN), the associated vent streams shall be directed to the shared vent system for control to the maximum extent practicable.
11. All emissions from filling or depressurization of the Glycol Moderator Drum shall be directed to a CAS (EPN GAD09A-D) satisfying the requirements of Special Condition 47.

Polyethylene Residual VOC Emissions

12. Total VOC emitted to the atmosphere after the purge column through product loadout from each polyethylene unit shall not exceed 50 pounds per million pounds of polyethylene pellets produced.
13. Ongoing compliance with VOC emission limits specified in Special Condition 12 shall be determined by calculation using monthly production rates and monthly average sampling and testing of the polyethylene for residual VOC.
 - A. Samples of resin shall be collected at the following locations: ("point A") immediately after the purge column, and ("point B") at the final product loadout station.
 - B. Sampling shall be performed for each product type produced during a calendar month. An exemption from sampling may be claimed for a particular product type if both of the following conditions are satisfied:
 - (1) The product is produced for 72 hours or less during the month; and
 - (2) Sampling has been conducted at the plant for the same product during the preceding 60 months, and documentation of the sampling results has been retained. The most recent such results shall be used in the calculations specified in Special Condition 14.Additionally, the permit holder shall be exempt for failure to obtain a sample for each product type produced for 72 hours or less provided it is the first attempt during the calendar month. The permit holder shall record the time and date of the first sampling attempt, failure reason and make the records available upon request. **(02/21)**
 - C. Prior to the initial start-up of any polyethylene unit, the permit holder shall notify the appropriate TCEQ Regional Office of the sampling method that will be utilized to comply with this requirement. The sampling method shall ensure measurement of the total residual VOC content of the polymer being sampled. **(02/21)**
14. Polymer production rates, monitoring records, and emission calculations shall be maintained at the plant site:
 - A. Production and sampling records shall include (but are not limited to):
 - (1) Day and time of sample.
 - (2) Actual plant production rate at the time of sampling and monthly production rate.
 - (3) Product number, resin type and melt index.

(4) Sampled residual VOC concentrations for each product type at each sampling point.

B. Polymer handling emissions for a product type shall be calculated as follows: **(02/21)**

$$E_{Res} = C_A - C_B$$

Where:

E_{Res} is the total polymer handling emission rate, expressed in units of lb VOC per MMlb polymer (ppmwPE).

C_A is the residual VOC concentration of a representative sample of a particular polymer grade, taken at point A, expressed in units of ppmwPE; and

C_B is the residual VOC concentration of a representative sample of the same polymer grade, taken at point B, expressed in units of ppmwPE.

C. Monthly average VOC emissions for the polyethylene unit shall be calculated as follows:

$$E_{Res,Avg} = \sum_{i=1}^n w_i \times E_{Res}$$

Where:

$E_{Res,Avg}$ is the monthly average polymer handling emission rate, expressed in units of lb VOC per MMlb polymer.

n is the total number of product types produced during the month.

w_i is the mass fraction of total production at the unit consisting of product type i

E_{Res} is the residual VOC concentration calculated following paragraph B of this Special Condition.

Solids Handling

15. Particulate matter outlet grain loading shall not exceed 0.005 gr/dscf of air from any vent. There shall be no visible emissions exceeding 30 seconds in any six-minute period as determined using EPA Test Method 22.

The vents identified in Special Condition 17 shall not operate unless any control devices and associated equipment are maintained in good working order and operating. All vents identified in Special Condition 17 shall be inspected for visible emissions once per day and a spare parts filter inventory will be maintained on site. Records shall be maintained of all inspections and maintenance performed.

16. The following requirements apply to the particulate control devices identified in Special Condition 17.

A. The differential pressure across each particulate control device shall be continuously monitored and be recorded at least once an hour while the control device is operational. The permit holder may determine for each baghouse the pressure values that would indicate operational failure resulting in emissions of particulate matter to the atmosphere. When

available, these pressure values may be used in lieu of the daily inspections as indicators of baghouse operational failure. The list of baghouses and their respective failure pressures shall be maintained in the facility record on-site and made available to the TCEQ upon request. **(02/21)**

- B. The pressure drop shall meet the minimum and maximum pressure drop as specified in the corrected Table C-1 and Table C-2 dated September 2021 within the confidential file of the permit alteration with PI-1 dated August 24, 2021. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or at least annually, whichever is more frequent, and shall be accurate to within 0.5 inches water gauge pressure or 0.5 percent of span. **(11/21)**
 - C. Quality assured (or valid) data must be generated when the polyethylene unit is operating except during the performance of a daily zero check. Loss of valid data due to periods of monitor breakdown, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in hours) that the polyethylene unit operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.
17. The following sources of particulate emissions at the polyethylene units are covered by the permit. **(02/21)**

A. Plant "E" vents

Source Name	Vent type	EPN
EPE granules feed bin dust collector	Bag House	ELDC01
EPE granules hopper vent dust collector	Bag House	EDFAN01
EPE seed bed bin dust collector	Bag House	EDDC04
EPE extruder feed conveyor dust collector	Bag House	ELDC03
EPE pellet silo vents	Bag House	EPFAN01
EPE pellet dryer vents	Uncontrolled	EMFAN01, EMFAN02
Weigh feed hopper extraction vent	Sock Filter	ELFAN04
Zinc Oxide drying hopper dust collector	Bag House	ELDC06
Vacuum blower vents for additive transfer	Bag House	ELB01, ELB03, ELB05, ELFAN01
EPE Catalyst handling cylinder vent filters	Sintered Metal Filter	EBFIL01
EPE Catalyst hold tank filters	Sintered Metal Filter	ECFIL04, ECFIL05, ECFIL06
EPE pellet surge bin dust collector	Bag House	EMDC01

B. Plant "C" vents

Source Name	Vent type	EPN
CPE granules feed bin dust collector	Bag House	CLDC01
CPE granules hopper vent dust collector	Bag House	CDFAN01
CPE seed bed bin dust collector	Bag House	CDDC04
CPE extruder feed conveyor dust collector	Bag House	CLDC03
CPE pellet silo vents	Bag House	CPFAN01
CPE pellet dryer vents	Uncontrolled	CMFAN01, CMFAN02
CPE dry additive weigh feeder hopper extraction vent	vacuum system-no dust	CLFAN04
Zinc Oxide drying hopper dust collector	Bag House	CLDC06
Vacuum blower vents for additive transfer	Bag House	ELB02, ELB04, CLB03,
CPE catalyst handling cylinder vent filters	Sintered Metal Filter	CBFIL01
Catalyst hold tank vent filters	Sintered Metal Filter	CCFIL04, CCFIL05, CCFIL06
CPE pellet surge bin vent	Bag House	CMDC01

Combustion Devices

18. Opacity of emissions from each combustion unit and thermal oxidizer authorized by this permit shall not exceed 5 percent averaged over any six-minute period.

Opacity shall be determined by the U.S. Environmental Protection Agency (EPA) Test Method 9 during the initial compliance testing and at least once per year thereafter. In lieu of performing a required opacity test, the permit holder may verify that there are no visible emissions as determined by EPA Test Method 22. For opacity or visible emissions determinations other than those required during the initial compliance testing, determination of opacity or visible emissions for each pyrolysis furnace shall take place during decoking.

19. Reserved.
20. Combustion units are subject to the following requirements for fuel sulfur:
- A. Pyrolysis furnaces shall be fired with natural gas, olefins unit tail gas, and/or ethane.
 - B. Boilers shall be fired with natural gas, olefins unit tail gas, ethane, and/or flare gas recovery unit vent gas with a combined total sulfur content not to exceed 3.7 gr per 100 dscf on a rolling 365-day average.
 - C. Natural gas, olefins unit tail gas, and ethane shall have a total sulfur content not to exceed 5 gr per 100 dscf on a 1-hr average and 0.5 gr per 100 dscf on a rolling 12-month average.

- D. Compliance with the requirements of paragraph C of this Special Condition shall be verified through sampling of fuel gas in accordance with the requirements in Alternative Method of Compliance (AMOC) No. 181 authorized by TCEQ on July 16, 2021. Fuel gas streams identified in paragraph C may be sampled individually, or a representative sample of blended fuel gas may be taken from the fuel gas header. **(11/21)**

For natural gas and commercial ethane, tariff sheets, contract or vendor guarantee documenting the sulfur content of the fuel may be retained in lieu of performing sampling. **(02/21)**

21. Emissions Standards for Pyrolysis Furnaces.

- A. Except where provided otherwise in Paragraph D and E of this Special Condition, emissions of NO_x, CO, and NH₃ from each pyrolysis furnace shall not exceed the following values. Compliance with the NO_x emissions limits shall be achieved through the use of an SCR system. **(06/22)**

- (1) Short-term average limits:

Pollutant	Emission Limit	Averaging Period
NO _x	0.015 lb/MMBtu	1-hr block
CO	50 ppmvd	1-hr block
NH ₃	10 ppmvd	24-hr (rolling)

- (2) Long-term average limits:

Pollutant	Emission Limit	Averaging Period
NO _x	0.010 lb/MMBtu	Annual (rolling)

- B. Compliance with the NO_x and CO emission limits of paragraph A shall be demonstrated through use of CEMS.
- C. Compliance with the NH₃ emission limits of paragraph A shall be continuously demonstrated using one of the following options.
- (1) Install an NH₃ CEMS satisfying the requirements of Special Condition 66.
- (2) In addition to the NO_x CEMS required under paragraph B of this Special Condition, install a second NO_x CEMS upstream of the SCR system. Perform the measurements and calculations associated with the mass balance method specified in 30 TAC § 117.8130(1), using NO_x CEMS data to determine the NO_x concentration differential across the control device.
- D. The NO_x and CO emission limits of subparagraph A(1) of this Special Condition shall not apply to a pyrolysis furnace during non-routine operation of the pyrolysis furnace, and shall not apply during the shakedown period.
- E. The NO_x emission limit of subparagraph A(1) shall apply on a 24-hr rolling average until a NO_x CEMS that is not shared between two furnaces is installed on the furnace and a Relative Accuracy Test Audit is conducted for the specified furnace. **(06/22)**

22. During decoking operations, pyrolysis furnace effluent shall be captured and conveyed to a cyclone system, and the gaseous exhaust stream from the decoking system shall be directed to the flame zone of a pyrolysis furnace.

23. Emissions Standards for Boilers.

- A. Except where provided otherwise in Paragraph C of this Special Condition, emissions of NO_x, CO, and NH₃ from each boiler shall not exceed the following values. **(02/21)**

(1) Short-term average limits:

Pollutant	Emission Limit	Averaging Period
NO _x	0.015 lb/MMBtu	1-hr (block)
CO	100 ppmvd	1-hr (block)
NH ₃	10 ppmvd	24-hr (rolling)

(2) Long-term average limits:

Pollutant	Emission Limit	Averaging Period
NO _x	0.010 lb/MMBtu	Annual (rolling)

- B. Compliance with the NO_x and CO emission limits of paragraph A shall be demonstrated through use of CEMS.
- C. Compliance with the NH₃ emission limits of paragraph A shall be continuously demonstrated using one of the following options.
- (1) Install an NH₃ CEMS satisfying the requirements of Special Condition 66.
- (2) In addition to the NO_x CEMS required under paragraph B of this Special Condition, install a second NO_x CEMS upstream of the SCR system. Perform the measurements and calculations associated with the mass balance method specified in 30 TAC § 117.8130(1), using NO_x CEMS data to determine the NO_x concentration differential across the control device.
- D. During non-routine operations for a boiler, and during the shakedown period, the requirements of subparagraph A(1) shall not apply.

Records of boiler startup, shutdown, and low firing events shall specify the time and duration of the event.

Liquids Storage and Transfer Operations

Storage Facilities

24. Storage tanks are subject to the following requirements: The control requirements specified in paragraphs A–E of this Special Condition shall not apply (1) where the VOC has an aggregate partial pressure of less than 0.50 psia at the maximum feed temperature or 95°F, whichever is greater, or (2) to storage tanks smaller than 25,000 gallons.

The control requirements specified in paragraph F of this Special Condition shall not apply to a tank which has a maximum working volume of less than 25,000 gallons and stores a liquid with an aggregate VOC partial pressure of less than 0.50 psia at 95° F. This exemption is only for applicable representations included in the initial permit issued on June 12, 2019 and subsequent corrections in the as-built amendment with PI-1 dated April 20, 2020. **(02/21)**

- A. The tank emissions must be controlled as specified in one of the sections below. Tanks complying with section (2) or (3) are exempt from the requirements of paragraphs B–F of this Special Condition.
- (1) An internal floating deck or “roof” shall be installed. A domed external floating roof tank is equivalent to an internal floating roof tank.
- The floating deck shall be of welded construction.
- The floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the floating roof:
- (a) a liquid-mounted seal,
- (b) two continuous seals mounted one above the other, or
- (c) a mechanical shoe seal.
- (2) All vents from the tank shall be captured using a closed vent system and directed to a control device as specified in Special Condition 25.
- (3) The tank is a pressure vessel designed to operate without emissions to the atmosphere.
- B. For any tank equipped with a floating roof, the permit holder shall perform the visual inspections and any seal gap measurements specified in 40 CFR § 60.113b Testing and Procedures (as amended at 54 FR 32973, Aug. 11, 1989) to verify fitting and seal integrity. Records shall be maintained of the dates inspection was performed, any measurements made, results of inspections and measurements made (including raw data), and actions taken to correct any deficiencies noted.
- C. The floating roof design shall incorporate sufficient flotation to conform to the requirements of API Code 650 dated November 1, 1998 except that an internal floating cover need not be designed to meet rainfall support requirements and the materials of construction may be steel or other materials.
- D. The tanks shall be designed to completely drain its entire contents to a sump in a manner that limits the volume of free-standing liquid in the tank or the sump as follows:

NPS (in.)	V _U (gal.)
2	9
3	14
4	32
6	75

Where: NPS is the nominal piping size of the sump pipe; and

V_U is the maximum volume of free-standing liquid in the tank or sump.

- E. Tanks shall be constructed or equipped with a connection to a vapor recovery system that routes vapors from the vapor space under the landed roof to a control device.
- F. Except for labels, logos, etc. not to exceed 15 percent of the tank total surface area, uninsulated tank exterior surfaces exposed to the sun shall be white, or unpainted aluminum, or an equivalent light color. Storage tanks must be equipped with permanent submerged fill pipes. **(02/21)**

- G. The permit holder shall maintain an emissions record which includes calculated emissions of VOC from all storage tanks during the previous calendar month and the past consecutive 12-month period. The record shall include tank identification number, control method used, tank capacity in gallons, name of the material stored, VOC molecular weight, VOC monthly average temperature in degrees Fahrenheit, VOC vapor pressure at the monthly average material temperature in psia, VOC throughput for the previous month and year-to-date. Records of VOC monthly average temperature are not required to be kept for unheated tanks which receive liquids that are at or below ambient temperatures.
25. Emissions from tanks shall be calculated using the methods that were used to determine the MAERT limits in the permit application (Form PI-1 dated April 19, 2017, and in TCEQ Project 316526, Content ID 4700346 pages 84-93). Sample calculations from the application shall be retained at the plant site and made available upon request to authorized representatives of TCEQ. The following control requirements apply to the storage tanks specified below. **(09/22)**
- A. The catalyst tank (EPN CCD81) shall be equipped with a blanketing and vapor recovery system which creates an inert atmosphere inside of the storage tank, and directs recovered vapors to a control device covered by the permit, or to a diffusion chamber designed to absorb catalyst vapors in a mineral oil solution.
26. Tank service and maximum total working volumes shall be limited as follows. **(02/21)**

Tank EPN	Type	Service	Maximum total working volume for tank (gal)
ZTTK02,	VFT	Heavy Glycols	216,568
ZTTK03,	VFT	Glycol Bleed	179,768
ZTTK04	IFR	Slop Oil	911,954
ZTTK05,	IFR	1-Hexene	413,584
ZTTK06AMNT	VFT	Heavy Fuel Oil	75,197
ZTTK06BMNT	VFT	Heavy Fuel Oil	75,197
GDD08	VFT	Catalyst Solution	39,019
GDD09	HFT	Catalyst Solution	3,834
GED04	HFT	Glycol Slop	4,513
SCTOTE-GLY	HFT	Catalyst Solution	6,173
GDTK01	VFT	Catalyst Solution	414,524
GETK01	VFT	Glycol Slop	2,493,021
GETK02A	VFT	Monoethylene Glycol	2,493,021
GETK02B	VFT	Monoethylene Glycol	2,493,021
ELD01	VFT	PE Additive	1,028
ELD02	VFT	PE Additive	1,028
CCD81	VFT	Spent Catalyst Solution	582
GFTK01	HFT	Oily Water	3,023
FZTK01	HFT	Oily Water	23,499
ZFTK02B	HFT	Diesel	853
ZFTK02C	HFT	Diesel	853
UKDGEN01TK	HFT	Diesel	1,057

Tank EPN	Type	Service	Maximum total working volume for tank (gal)
UKDGEN02TK	HFT	Diesel	1,057
GUJGEN01TK	HFT	Diesel	1,057
ADMINGENTK	HFT	Diesel	2,115
ZMTK01	HFT	Motor Gasoline	15,039
ZMTK02	HFT	Diesel	15,039
UCTK01	VFT	Sodium Hypochlorite	24,063
UTTK04	VFT	Sulfuric Acid	24,063
ZTTK01	VFT	Caustic Solution	78,193

27. Reserved. **(02/21)**

Tanker Truck and Railcar Loading Operations

28. All lines and connectors shall be visually inspected for any defects prior to hookup. Lines and connectors that are visibly damaged shall be removed from service. Operations shall cease immediately upon detection of any liquid leaking from the lines or connections.
29. The following requirements apply to any tanker truck or railcar to be loaded with a liquid with a VOC vapor pressure of 0.50 psia or greater at 95° F.
- A. Each tank truck shall pass vapor-tight testing every 12 months using the methods described in 40 CFR Part 60, Subpart XX. The permit holder shall not allow a tank truck to be filled unless it has passed a leak-tight test within the past year as evidenced by a certificate which shows the date the tank truck last passed the leak-tight test required by this condition and the identification number of the tank truck.
 - B. The permit holder shall not allow a railcar to be filled unless it has a current certification in accordance with U.S. Department of Transportation (DOT) pressure test requirements of 49 CFR §173.31.
30. The loading of any liquid with a VOC vapor pressure of 0.50 psia or greater at 95° F shall be controlled through a closed vent system and a control device satisfying the applicable requirements of this permit. Truck Loading operations are limited to the liquids and rates specified below. **(02/21)**

Product	Maximum Fill Rate (gal/hr)	Required Controls
Heavy Fuel Oil, Slop Oil	24,000	Shared Vent System
Monoethylene Glycol, Heavy Glycols (henceforth "Glycols")	110,000	None
Waste Solvent	12,000	None

Railcar loading of Glycols shall be limited to a maximum fill rate of 110,000 gal/hr. The combined fill rate for simultaneous tanker truck and railcar loading of Glycols shall not exceed 110,000 gal/hr.

The loading of liquids into drums shall be submerged. **(02/21)**

31. Prior to venting any transfer line/hose to the atmosphere, the following procedure shall be performed following transfer of liquids with a VOC vapor pressure of 0.50 psia or greater at 95° F.

Upon completion of loading, the loading line/hose shall be isolated at the connection to the transfer rack piping. Pressurized nitrogen shall be connected to one end of the line/hose to purge liquids and vapors in the loading line/hose into the tanker truck/railcar per the site operating procedure. The tanker truck/railcar shall remain connected to the loading rack closed vent system and control shall be maintained as required in Special Condition 30 during purging of the transfer line/hose.

32. The permit holder shall maintain and update a monthly emissions record which includes calculated emissions of VOC from all loading operations over the previous rolling 12-month period. The record shall include the loading spot, control method used, quantity loaded in gallons, name of the liquid loaded, vapor molecular weight, liquid temperature in degrees Fahrenheit, liquid vapor pressure at the liquid temperature in psia, liquid throughput for the previous month and rolling 12 months to date. Records of VOC temperature are not required to be kept for liquids loaded from unheated tanks which receive liquids at or below ambient temperatures. Emissions shall be calculated using the TCEQ publication titled "Technical Guidance Package for Chemical Sources - Loading Operations."

Equipment Leaks

33. Piping, Valves, Connectors, Pumps, Agitators, and Compressors – 28VHP

Except as may be provided for in the Special Conditions of this permit, the following requirements apply to the above-referenced equipment:

- A. The requirements of paragraphs F and G shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.044 pounds per square inch, absolute (psia) at 68°F or (2) operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure. Equipment excluded from this condition shall be identified in a list or by one of the methods described below to be made readily available upon request.

The exempted components may be identified by one or more of the following methods:

- (1) piping and instrumentation diagram (PID);
 - (2) a written or electronic database or electronic file;
 - (3) color coding;
 - (4) a form of weatherproof identification; or
 - (5) designation of exempted process unit boundaries.
- B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable American National Standards Institute (ANSI), American Petroleum Institute (API), American Society of Mechanical Engineers (ASME), or equivalent codes.

- C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical. New and reworked buried connectors shall be welded.
- D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Difficult-to-monitor and unsafe-to-monitor valves, as defined by 30 TAC Chapter 115, shall be identified in a list to be made readily available upon request. The difficult-to-monitor and unsafe-to-monitor valves may be identified by one or more of the methods described in Paragraph A above. If an unsafe to monitor component is not considered safe to monitor within a calendar year, then it shall be monitored as soon as possible during safe to monitor times. A difficult to monitor component for which quarterly monitoring is specified may instead be monitored annually.
- E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. Gas or hydraulic testing of the new and reworked piping connections at no less than operating pressure shall be performed prior to returning the components to service or they shall be monitored for leaks using an approved gas analyzer within 15 days of the components being returned to service. Adjustments shall be made as necessary to obtain leak-free performance. Connectors shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through.

Each open-ended valve or line shall be equipped with an appropriately sized cap, blind flange, plug, or a second valve to seal the line. Except during sampling, both valves shall be closed. If the isolation of equipment for hot work or the removal of a component for repair or replacement results in an open ended line or valve, it is exempt from the requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is not completed within 72 hours, the permit holder must complete either of the following actions within that time period;

- (1) a cap, blind flange, plug, or second valve must be installed on the line or valve;
or
 - (2) the open-ended valve or line shall be monitored once for leaks above background for a plant or unit turnaround lasting up to 45 days with an approved gas analyzer and the results recorded. For all other situations, the open-ended valve or line shall be monitored once within the 72 hour period following the creation of the open ended line and monthly thereafter with an approved gas analyzer and the results recorded. For turnarounds and all other situations, leaks are indicated by readings of 500 ppmv and must be repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve.
- F. Accessible valves shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. If a relief valve is equipped with rupture disc, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity.

A check of the reading of the pressure-sensing device to verify disc integrity shall be performed at least quarterly and recorded in the unit log or equivalent. Pressure-sensing

devices that are continuously monitored with alarms are exempt from recordkeeping requirements specified in this paragraph. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

The gas analyzer shall conform to requirements listed in Method 21 of 40 CFR Part 60, Appendix A. The gas analyzer shall be calibrated with methane. In addition, the response factor of the instrument for a specific VOC of interest shall be determined and meet the requirements of Section 8 of Method 21. If a mixture of VOCs is being monitored, the response factor shall be calculated for the average composition of the process fluid. A calculated average is not required when all of the compounds in the mixture have a response factor less than 10 using methane. If a response factor less than 10 cannot be achieved using methane, then the instrument may be calibrated with one of the VOC to be measured or any other VOC so long as the instrument has a response factor of less than 10 for each of the VOC to be measured.

Replacements for leaking components shall be re-monitored within 15 days of being placed back into VOC service.

- G. Except as may be provided for in the special conditions of this permit, all pump, compressor, and agitator seals shall be monitored with an approved gas analyzer at least quarterly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with automatic seal failure detection and alarm system need not be monitored. These seal systems may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.
- H. Damaged or leaking valves or connectors found to be emitting VOC in excess of 500ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Damaged or leaking pump, compressor, and agitator seals found to be emitting VOC in excess of 2,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. A first attempt to repair the leak must be made within 5 days and a record of the attempt shall be maintained.
- I. A leaking component shall be repaired as soon as practicable, but no later than 15 days after the leak is found. If the repair of a component would require a unit shutdown that would create more emissions than the repair would eliminate, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging within 15 days of the detection of the leak. A listing of all components that qualify for delay of repair shall be maintained on a delay of repair list. The cumulative daily emissions from all components on the delay of repair list shall be estimated by multiplying by 24 the mass emission rate for each component calculated in accordance with the instructions in 30 TAC § 115.782(c)(1)(B)(i)(II). The calculations of the cumulative daily emissions from all components on the delay of repair list shall be updated within ten days of when the latest leaking component is added to the delay of repair list. When the cumulative daily emission rate of all components on the delay of repair list times the number of days until the next scheduled unit shutdown is equal to or exceeds the total emissions from a unit shut down as

calculated in accordance with 30 TAC § 115.782(c)(1)(B)(i)(I), the TCEQ Regional Manager and any local programs shall be notified and may require early unit shut down or other appropriate action based on the number and severity of tagged leaks awaiting shutdown. This notification shall be made within 15 days of making this determination.

- J. Records of repairs shall include date of repairs, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of instrument monitoring shall indicate dates and times, test methods, and instrument readings. The instrument monitoring record shall include the time that monitoring took place for no less than 95% of the instrument readings recorded. Records of physical inspections shall be noted in the operator's log or equivalent.
- K. Alternative monitoring frequency schedules of 30 TAC 115.352 - 115.359 or National Emission Standards for Organic Hazardous Air Pollutants, 40 CFR Part 63, Subpart H, may be used in lieu of Items G through H of this condition.
- L. Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable New Source Performance Standard (NSPS), or an applicable National Emission Standard for Hazardous Air Pollutants (NESHAPS) and does not constitute approval of alternative standards for these regulations.

34. Quarterly Monitoring of Connectors — 28CNTQ

In addition to the weekly physical inspection required by paragraph E of Special Condition 33, all accessible connectors in gas/vapor or light liquid service shall be monitored quarterly with an approved gas analyzer in accordance with paragraphs F–J of Special Condition 33.

- A. Allowance for reduced monitoring frequencies.
 - (1) The frequency of monitoring may be reduced from quarterly to semiannually if the percent of connectors leaking for two consecutive quarterly monitoring periods is less than 0.5 percent.
 - (2) The frequency of monitoring may be reduced from semiannually to annually if the percent of connectors leaking for two consecutive semiannual monitoring periods is less than 0.5 percent.
- B. If the percent of connectors leaking for any semiannual or annual monitoring period is 0.5 percent or greater, the facility shall revert to quarterly monitoring until the facility again qualifies for the alternative monitoring schedules previously outlined in this paragraph. The percent of connectors leaking used in paragraph A shall be determined using the following formula:

$$(CI + Cs) \times 100/Ct = Cp$$

Where:

CI = the number of connectors found leaking by the end of the monitoring period, either by Method 21 or sight, sound, and smell.

Cs = the number of connectors for which repair has been delayed and are listed on the facility shutdown log.

Ct = the total number of connectors in the facility subject to the monitoring requirements, as of the last day of the monitoring period, not including nonaccessible and unsafe-to-monitor connectors.

Cp = the percentage of leaking connectors for the monitoring period.

35. SCR System Piping, Valves, Pumps, and Compressors in contact with NH₃– 28AVO

Except as may be provided for in the Special Conditions of this permit, the following requirements apply to the above-referenced equipment:

- A. Audio, olfactory, and visual checks for leaks within the operating area shall be made once per shift.
- B. Immediately, but no later than 5 hours after detection of a leak, plant personnel shall take at least one of the following actions: **(02/21)**
 - (1) Isolate the leak.
 - (2) Commence repair or replacement of the leaking component.
 - (3) Use a leak collection/containment system to prevent the leak until repair or replacement can be made if immediate repair is not possible.

Date and time of each inspection shall be noted in the operator's log or equivalent. Records shall be maintained at the plant site of all repairs and replacements made due to leaks. These records shall be made available to representatives of the Texas Commission on Environmental Quality (TCEQ) upon request.

Heat Exchange Systems

36. The cooling tower (EPN UCCT01) and associated heat exchange systems shall be operated and monitored in accordance with the following:

- A. The actual cooling water circulation rate shall be measured at least hourly. Measurements shall be reduced to an hourly average and recorded for use in emission calculations. If multiple sampling points are used, then the actual cooling water circulation rate associated with each sampling point shall be determined and recorded. The circulation rate associated with a particular sampling point can be estimated using engineering judgment. The method used to estimate flow associated with a sampling point shall be documented.
- B. The VOC associated with cooling tower (EPN UCCT01) water shall be monitored with an air stripping system meeting the requirements of the TCEQ Sampling Procedures Manual, Appendix P (dated January 2003 or a later edition), a continuous on-line monitor conforming to the requirements of 30 TAC § 115.764(a)(6), or an approved equivalent sampling method. Monitoring is not required if the cooling tower is out of service for that month. **(02/21)**

The results of the monitoring, cooling water flow rate and maintenance activities on the cooling water system shall be recorded. The monitoring results and cooling water hourly mass flow rate shall be used to determine cooling tower hourly VOC emissions. The rolling 12-month cooling water emission rate shall be recorded on a monthly basis and be

determined by summing the VOC emissions between VOC monitoring instances over the rolling 12-month period. The emissions between VOC monitoring instances shall be obtained by multiplying the total cooling water mass flow between cooling water monitoring instances by the higher of the two VOC monitored results.

- C. The required frequency of sampling specified in paragraph B shall be at least once per week per sampling point. If no leak is identified during 26 consecutive weeks of weekly monitoring, the frequency of sampling may be reduced to monthly, and shall revert to weekly upon detection of a leak.
- D. Equipment shall be maintained so as to minimize VOC emissions into the cooling water. A leak (faulty equipment) is indicated by:
 - (1) Cooling tower water VOC concentrations above 80 ppbw at any sampling point; or
 - (2) For any sampling point covering cooling tower water associated with the Olefins Plant, a cooling tower water VOC concentration C (measured in units of ppbw) at such sampling point, such that:

$$500 \times 10^{-9} \times CR \times C \geq 6.73$$

Where: CR is the actual cooling water circulation rate in units of gpm, measured as required under paragraph A of this Special Condition.

Use of list of HAP at 40 CFR Part 63, Subpart XX in lieu of total VOC:

- (a) "Table 1 HAP" means the list of HAP appearing at 40 CFR Part 63, Subpart XX, Table 1.
- (b) The term "C" in the equation above shall refer to the total concentration of Table 1 HAP in the cooling tower water if either of the following are satisfied:
 - i. Sampling is conducted using a continuous on-line monitor conforming to the requirements of 30 TAC § 115.764(a)(6), which is capable of determining total Table 1 HAP and speciated Table 1 HAP concentrations in the cooling tower water; or
 - ii. Sampling is conducted following Section 6.2 of the TCEQ Sampling Procedures Manual, Appendix P to determine total Table 1 HAP and speciated Table 1 HAP concentrations in the cooling tower water.

Emissions from the cooling tower are not authorized if the VOC concentration of the water returning to the cooling tower exceeds 800 ppbw at any sampling point. Leaks associated with VOC concentrations above 800 ppbw are not subject to extensions for delay of repair under paragraph F of this permit condition.

- E. Leaks (faulty equipment) shall be repaired at the earliest opportunity but no later than 45 calendar days after a leak is detected, unless the leak qualifies for delayed repair under paragraph F of this Special Condition. If the leak qualifies for delayed repair, then the leak shall be repaired according to the schedule specified in paragraph F of this Special Condition. In no case may repairs be delayed beyond the next shutdown.
- F. The provisions of 40 CFR § 63.1088 (version published at 67 FR 46274; July 12, 2002), relating to situations where required repairs may be delayed, are incorporated by reference, except that each appearance of "HAP" shall be replaced by "VOC".

- G. Cooling towers shall each be equipped with drift eliminators having manufacturer's design assurance of 0.0005% drift or less. Drift eliminators shall be maintained and inspected at least annually. The permit holder shall maintain records of all inspections and repairs.
- H. The TDS content of the cooling water shall not exceed 5600 ppmw in any sample.
- I. Cooling towers shall be analyzed for particulate emissions using one of the following methods when in operation: **(02/21)**
 - (1) Cooling water shall be sampled at least once per day for TDS; or
 - (2) TDS monitoring may be reduced to weekly if conductivity is monitored daily and TDS is calculated using a ratio of TDS-to-conductivity (in ppmw per $\mu\text{mho/cm}$ or ppmw/siemens). The ratio of TDS-to-conductivity shall be determined by concurrently monitoring TDS and conductivity on a weekly basis. The permit holder may use the average of two consecutive TDS-to-conductivity ratios to calculate daily TDS.
 - (3) TDS monitoring may be reduced to quarterly if conductivity is monitored daily and TDS is calculated using a correlation factor established for each cooling tower. The correlation factor shall be the average of nine consecutive weekly TDS-to-conductivity ratios determined using I(2) above provided the highest ratio is not more than 10% larger than the smallest ratio.
 - (4) The permit holder shall validate the TDS-to-conductivity correlation factor once each calendar quarter. If the ratio of concurrently sampled TDS and conductivity is more than 10% higher or lower than the established factor, the permit holder shall increase TDS monitoring to weekly until a new correlation factor can be established.
- J. Cooling water sampling shall be representative of the cooling tower feed water and shall be conducted using approved methods.
 - (1) The analysis method for TDS shall be EPA Method 160.1, ASTM D5907, or SM 2540 C [SM - 19th edition of Standard Methods for Examination of Water]. Water samples should be capped upon collection, and transferred to a laboratory area for analysis.
 - (2) The analysis method for conductivity shall be either ASTM D1125-95A (field or routine laboratory testing) or ASTM D1125-95B (continuous monitor). The analysis may be conducted at the sample site or with a calibrated process conductivity meter. If a conductivity meter is used, it shall be calibrated at least annually. Documentation of the method and any associated calibration records shall be maintained.
 - (3) Alternate sampling and analysis methods may be used to comply with D(1) and D(2) with written approval from the TCEQ Regional Director.
 - (4) Records of all instrument calibrations and test results and process measurements used for the emission calculations shall be retained.
- K. Emission rates of total particulate shall be calculated using the measured TDS, the design drift rate, the calculation methodology specified in the permit application (form PI-1 dated April 19, 2017, and in TCEQ Project 316526, Content ID 4700346 pages 36-37), and the daily maximum and average actual cooling water circulation rate for the short term and annual average rates. Alternately, in lieu of the measurements required in Special Condition 36.A, the design maximum circulation rate may be used for all calculations. **(09/22)**

Emission rates of PM_{10} and $\text{PM}_{2.5}$ shall be calculated as follows.

- (1) The calculated PM₁₀ emission rate shall equal 70% of the total particulate emission rate; and
- (2) The calculated PM_{2.5} emission rate shall equal 42% of the total particulate emission rate.

Emission records shall be updated monthly.

Wastewater Treatment Facilities

37. Process wastewater drains shall be equipped with water seals or equivalent. Lift stations, manholes, junction boxes, any other wastewater collection system components, and conveyances used to convey wastewater generated at the Olefins Plant or the Glycols Plant shall be equipped with a closed vent system that routes all organic vapors to a control device covered by this permit. Wastewater system components whose use is limited to the draining of process vessels during planned MSS activities, and which are not capable of receiving any continuously generated process wastewater stream, are exempt from the requirements of this Special Condition.

Water seals shall be checked by visual or physical inspection quarterly for indications of low water levels or other conditions that would reduce the effectiveness of water seal controls. Water seals shall be restored as necessary within 24 hours. Records shall be maintained of these inspections and any corrective actions taken.

38. The daily wastewater flow into the wastewater treatment plant shall be monitored and recorded. The rolling 12-month wastewater flow shall be totaled on a monthly basis. Wastewater flow shall be measured immediately downstream of the point where the outlets of the two Equalization Tanks are combined.
39. The minimum mixed liquor total suspended solids (MLSS) concentration in the aeration basins on a daily average basis shall not be less than 2000 mg/L. The MLSS concentration is the arithmetic average of all samples collected during the 24-hour period. The MLSS concentrations shall be monitored and recorded daily using Method 160.2 (Methods for Chemical Analysis of Water and Wastes, EPA-600/4-79-020 or Method 2540D (Standard Methods of the Examination of Water and Wastewater, 18th Edition, American Public Health Association).

The MLSS limit of this Special Condition shall not apply during the shakedown period. **(02/21)**

Emissions of VOC from the Wastewater Equalization Tanks (FINs ZWTK01 and ZWTK02) shall be controlled by a catalytic oxidizer (EPN ZWSRCO1A/B) which achieves 99% control of VOC, or has a VOC exhaust concentration not to exceed 10 ppmvd, corrected to 3% oxygen. The temperature at the inlet of the catalyst bed shall be maintained at no less than 700° F on a six-minute average while waste gas is being fed to the oxidizer prior to the initial stack test. After the initial stack test has been completed, the six minute average temperature shall be equal to, or greater than the respective hourly average maintained during the most recent satisfactory stack testing required by Special Condition 62. **(06/22)**

The temperature at the inlet to the catalyst bed shall be continuously monitored and recorded when waste gas is directed to the oxidizer. The temperature measurement device shall reduce the temperature readings to an averaging period of 6 minutes or less and record it at that frequency.

The temperature measurement device shall be installed, calibrated, and maintained according to accepted practice and the manufacturer's specifications. The device shall have an accuracy of the greater of ± 0.75 percent of the temperature being measured expressed in degrees Celsius or $\pm 2.5^{\circ}\text{C}$.

Quality assured (or valid) data must be generated when the catalytic oxidizer is operating. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the catalytic oxidizer operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded. **(06/22)**

40. Wastewater treatment plant emissions shall be estimated every month using the following procedure.

- A. The permit holder shall sample the wastewater prior to the equalization tanks monthly to determine the concentrations of all air contaminants. Sampling locations, sampling procedures, test methods and calculations shall be as follows:
- (1) The sampling locations shall be at the inlets to each Equalization Tank;
 - (2) Sampling procedures shall be as specified in the Texas Pollutant Discharge Elimination Systems (TPDES) permit number WQ0005228000 (TX0137715) applicable to the site. A copy of the TPDES permit and any precedent application representations shall be retained on site and made available upon request; **(02/21)**
 - (3) Test methods shall include EPA SW-846 methods 8260B, 8270C, and 8015B; and
 - (4) Calculations shall be as specified in permit application, PI-1 dated April 19, 2017, and in TCEQ Project 316526, Content ID 4700346 page 96. **(09/22)**

The influent wastewater flow rates shall be measured and recorded when a sample required by this condition is collected. Records of sampling results shall be maintained for all air contaminants.

- B. The permit holder shall calculate short term loading rate in terms of lb/hr and rolling 12-month loading rate in terms of tpy for each air contaminant. The measured concentrations of each speciated air contaminant shall be converted to an equivalent mass emission rate based upon the flow rates during the sample collection period using the calculation methods and assumptions in the permit application, PI-1 dated April 19, 2017, and in TCEQ Project 316526, Content ID 4700346 page 96. The MLSS used in the emission calculation shall be either the minimum identified in Special Condition 39 or the measured concentration for the day the sampling required for this condition is completed. The short term emission rate calculations for such air contaminants shall be based on the concentrations and flow rates measured during sampling. The rolling 12-month emission rate calculation for each air contaminant shall be based on the rolling 12-month average contaminant concentration and the rolling 12-month wastewater flow. All other inputs into the calculation shall match those in the permit application for that averaging period (worst case). Total VOC mass emission rates shall be calculated as the sum of the individual speciated VOC mass emission rates. **(09/22)**

- C. All air contaminants ascertained by the analytical methods shall be evaluated. For any tentatively identified air contaminant that can be confirmed as present and that would have a calculated air contaminant mass emission rate more than 0.04 pound per hour (lb/hr) above that represented in the permit application (PI-1 dated April 19, 2017, and in TCEQ Project 316526, Content ID 4700346 page 96), the total emissions of that compound must satisfy the following: **(09/22)**
- (1) The Effect Screening Level (ESL) for an air contaminant shall be obtained from the current TCEQ ESL list or by written request to the TCEQ Toxicology Division.
 - (2) The information below shall be recorded for the air contaminant.
 - (a) Chemical name(s), composition, and chemical abstract registry number if available.
 - (b) True vapor pressure at maximum hourly and annual average temperature.
 - (c) Molecular weight.
 - (d) Date air contaminant was detected in the sample.
 - (e) Material Safety Data Sheet or equivalent.
 - (f) Concentration of air contaminant detected in the wastewater.
- D. Records of sampling location, sampling procedures, sample chain of custody forms, test methods, sampling results, calculated emission rates, and sample of calculations shall be maintained.

Control Device and Capture System Operational Specifications

41. The following requirements apply to vent gas combusted in any thermal control device (EPNs UFFLARE01, UFFLARE02, GFFLARE01, UFF01A, UFF01B and GBX02), and to the utility boilers (EPNs: USSG01A, USSG01B and USSG01C). **(02/21)**
- A. Vent gas in the glycol vent system shall have a total sulfur content not to exceed 5 gr per 100 dscf on a 3-hour average.
 - B. Compliance with the requirements of Special Condition 1 and paragraph A of this Special Condition shall be demonstrated as follows:
 - (1) A continuous total sulfur analyzer shall be installed on the vent gas stream to the shared thermal oxidizers, the multi-point ground flare, the shared elevated flare, and to the utility boilers.
 - (a) The analyzer shall be installed and operated as specified by the manufacturer.
 - (b) The permit holder shall comply with the *Sulfur Analyzer Periodic Performance Evaluations and Quality Assurance Procedures* in the confidential file of the permit alteration with PI-1 dated August 24, 2021. The permit holder shall retain of copy of the Sulfur Analyzer Periodic Performance Evaluations and Quality Assurance Procedures (August 2021) and the Total sulfur analyzer's manufacturer manual and make them available upon request by TCEQ personnel. **(11/21)**

The validation of the sulfur analyzer shall be monthly using the manufacturer's recommended procedure and the results recorded in the analyzer validation tracking system. The permit holder may reduce the validation frequency to quarterly provided the first six-month data proves quarterly validation is adequate. The permit holder shall notify regional office with the complete six-month validation data and obtain Region's approval before reducing the validation frequency. **(02/21)**

- (c) The analyzer shall operate as required by this section at least 95% of the time when vent gas is routed to the thermal control device, averaged over a rolling 12-month period. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the thermal control device operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgement and the methods used recorded.

- (2) A sample of the vent gas to the MEG thermal oxidizer and the MEG elevated flare shall be taken on a semi-annual basis and analyzed for total sulfur. For the natural gas and commercial ethane components of the vent gas stream, tariff sheets, contracts, or vendor guarantees documenting the sulfur content of the natural gas and commercial ethane may be retained in lieu of performing sampling. **(03/22)**

42. The following requirements apply to capture systems for each of the thermal control devices (EPNs UFFLARE01, UFFLARE02, GFFLARE01, UFF01A, UFF01B, and GBX02).

A. Complete either of the following.

- (1) Conduct a once a month visual, audible, and/or olfactory inspection of the capture system to verify there are no leaking components in the capture system; or
- (2) Once a year, verify the capture system is leak-free by inspecting in accordance with 40 CFR Part 60, Appendix A, Test Method 21. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppmv above background.

B. Bypass of control devices shall be prevented through compliance with one of the following options:

- (1) The control device shall not have a bypass; or
- (2) If there is a bypass for the control device, comply with either of the following requirements:
 - (a) Install a position indicator that records the valve position, or a flow indicator that records the flow immediately downstream of each valve that if opened would allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere. The indicator must record flow or position and verify zero flow at least once every 15 minutes; or
 - (b) Once a month, inspect the valves, verifying that the position of the valves and the condition of the car seals prevent flow out the bypass.

A bypass does not include authorized analyzer vents, highpoint bleeder vents, low point drains, or rupture discs upstream of pressure relief valves if the pressure between the disc and relief valve is monitored and recorded at least weekly. A deviation shall be reported if the monitoring or inspections indicate bypass of the control device when it is required to be in service.

- C. Records of the inspections required shall be maintained and if the results of any of the above inspections are not satisfactory, the permit holder shall promptly take necessary corrective action.

43. Reserved.

Multi-Point Ground Flare

- 44. The multi-point ground flare (EPN UFFLARE01) shall be designed and operated in accordance with the following requirements in Alternative Method of Control (AMOC) No. 138 authorized by TCEQ on August 27, 2020 or an Alternative Means of Emissions Limitation (AMEL) authorized by EPA, if applicable. **(9/20)**

Elevated Flare

- 45. Elevated flares (EPNs UFFLARE02 and GFFLARE01) shall be designed and operated in accordance with the following requirements:
 - A. The flare systems shall be designed such that the combined assist natural gas and waste stream to each flare meets the 40 CFR § 60.18 specifications of minimum heating value and maximum tip velocity at all times when emissions may be vented to them.

The heating value and velocity requirements shall be satisfied during operations authorized by this permit. Flare testing per 40 CFR § 60.18(f) may be requested by the appropriate regional office to demonstrate compliance with these requirements.
 - B. The flare shall be operated with a flame present at all times and/or have a constant pilot flame. The pilot flame shall be continuously monitored by a thermocouple, infrared monitor, or ultraviolet monitor. The time, date, and duration of any loss of pilot flame shall be recorded. Each monitoring device shall be accurate to, and shall be calibrated at a frequency in accordance with, the manufacturer's specifications.
 - C. The flare shall be operated with no visible emissions except periods not to exceed a total of five minutes during any two consecutive hours. Compliance with this requirement shall be demonstrated by monitoring the flare tip with a video camera and retaining copies of video recordings.
 - D. The permit holder shall install a continuous flow monitor and calorimeter that provides a record of the actual flow rate and the net heating value of the vent stream to the flare. The flow monitor sensor and analyzer sample points shall be installed in the vent stream as near as possible to the flare inlet such that the total vent stream to the flare is measured and analyzed. Readings shall be taken at least once every 15 minutes and the average hourly values of the flow and composition (or Btu content) shall be recorded each hour.

The monitors shall be calibrated or have a calibration check performed on an annual basis to meet the following accuracy specifications: the flow monitor shall be accurate to $\pm 5.0\%$ of flow for velocities greater than 1 ft/s, and accurate to $\pm 20\%$ of flow for velocities between 0.1 ft/s and 1 ft/s; the temperature monitor shall be accurate to $\pm 2.0\%$ at absolute temperature; and pressure monitor shall be accurate to ± 5.0 mm Hg.

The calorimeter shall be calibrated, installed, operated, and maintained, in accordance with manufacturer recommendations, to continuously measure and record the net heating value of the gas sent to the flare, in British thermal units/standard cubic foot of the gas.

The monitors and analyzers shall operate as required by this section at least 95% of the time when the flare is operational, averaged over a rolling 12-month period. Flared gas net heating value and actual exit velocity determined in accordance with 40 CFR §§60.18(f)(3) and 60.18(f)(4) shall be recorded at least once every hour. Hourly mass emission rates shall be determined and recorded using the above readings and the emission factors used in the permit application, April 19, 2017, and in TCEQ Project 316526, Content ID 4700346 pages 28-30 and 33-35. **(09/22)**

- E. [Reserved for additional requirements].

Thermal Oxidizers

46. The following requirements apply to the thermal oxidizers (EPNs UFF01A, UFF01B, and GBX02).

- A. Each of the shared thermal oxidizers (EPNs UFF01A and UFF01B) shall maintain the VOC concentration in the exhaust gas less than 10 ppmv, or achieve a VOC destruction efficiency greater than:
- (1) 99.9 percent for low-pressure vents from the olefins plant, resin degassing operations, storage tank emissions, and truck/railcar loading operations.
 - (2) 99 percent:
 - (a) During planned maintenance, startup or shutdown activities employing the shared thermal oxidizers as control; and
 - (b) for any combination of vent streams which includes spent nitrogen from polyethylene reactor grade transitions or from the regeneration of polyethylene feed treater beds.
- B. The MEG thermal oxidizer (EPN GBX02) shall maintain the VOC concentration in the exhaust gas less than 10 ppmv, or achieve a VOC destruction efficiency greater than:
- (1) 99.9 percent for the glycol purge vent stream.
 - (2) 99 percent for all other vent streams.
- C. The firebox exit temperature of each thermal oxidizer shall be maintained at not less than 1400° F and exhaust oxygen concentration not less than 3 percent on a six-minute average while waste gas is being fed into the oxidizer prior to initial stack testing. After the initial stack test has been completed, the six minute average temperature shall be equal to, or greater than the respective hourly average maintained during the most recent satisfactory stack testing required by Special Condition 62 as follows:

- (1) For each shared thermal oxidizers, the minimum temperature shall be the higher of the hourly average temperatures maintained under the two sampling scenarios referred to in Special Conditions 62.H(3)(a)–(b).
 - (2) For the MEG thermal oxidizer, the minimum temperature shall be the higher of the hourly average temperatures maintained under the two sampling scenarios referred to in Special Condition 62.H(4)(a)–(b).
- D. The firebox exit temperature of each thermal oxidizer shall be continuously monitored and recorded when waste gas is directed to the oxidizer. The temperature measurement device shall reduce the temperature readings to an averaging period of 6 minutes or less and record it at that frequency. The temperature measurement device shall be installed, calibrated, and maintained according to accepted practice and the manufacturer's specifications. The device shall have an accuracy of the greater of ± 0.75 percent of the temperature being measured expressed in degrees Celsius or $\pm 2.5^{\circ}\text{C}$.
- Quality assured (or valid) data must be generated when the thermal oxidizer is operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the thermal oxidizer operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.
- E. The oxygen analyzer used to satisfy Paragraph C of this Special Condition shall continuously monitor and record oxygen concentration when waste gas is directed to the oxidizer. It shall reduce the oxygen readings to an averaging period of 6 minutes or less and record it at that frequency.
- F. The oxygen analyzer for the Shared Thermal Oxidizers (EPNs UFF01A, UFF01B) shall comply with the requirements of Special Condition No. 66.B(3). **(11/21)**
- G. The permit holder shall install a continuous flow monitor that provides a record of the actual flow rate of the vent stream to each thermal oxidizer. The flow monitor sensor shall be installed in the vent stream as near as possible to the control device inlet such that the total vent stream to the control device is measured and analyzed. Readings shall be taken at least once every 15 minutes and the average hourly values of the flow shall be recorded each hour.
- H. The monitors shall be calibrated or have a calibration check performed on an annual basis to meet the following accuracy specifications: the flow monitor shall be $\pm 5.0\%$, temperature monitor shall be $\pm 2.0\%$ at absolute temperature, and pressure monitor shall be ± 5.0 mm Hg.
- I. Quality assured (or valid) data must be generated when the thermal oxidizer is operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the thermal oxidizer operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.

- J. Emissions of NO_x shall not exceed 0.06 lb/MMBtu (HHV basis) from each thermal oxidizer. Compliance with this NO_x limit can be based on a vendor guarantee for the burner NO_x rate. **(02/21)**

Carbon Adsorption Systems

47. Except where otherwise noted in the Special Conditions of this permit, the following requirements apply to each CAS required by the permit.
- A. The CAS shall be sampled once per hour when organic compounds may be directed to it, to determine breakthrough of VOC. The sampling point shall be at the outlet of the initial canister but before the inlet to the second or final polishing canister. Sampling shall be done during transfer of organic liquids into the Glycol Moderator Drum.
- B. The VOC sampling and analysis shall be performed using an instrument with a flame ionization detector (FID), photo ionization detector (PID) or a TCEQ-approved alternative detector. The instrument must meet all requirements specified in Section 8.1 of EPA Method 21 (40 CFR 60, Appendix A). Sampling and analysis for VOC breakthrough shall be performed as follows: **(02/21)**
- (1) Immediately prior to performing sampling, the instrument shall be calibrated with zero and span calibration gas mixtures. Zero gas shall be certified to contain less than 0.1 ppmv total hydrocarbons. Span calibration gas shall be methane or isobutylene at a concentration within ± 10 percent of 100 ppmv, and certified by the manufacturer to be ± 2 percent accurate. Calibration error for the zero and span calibration gas checks must be less than ± 5 percent of the span calibration gas value before sampling may be conducted. **(11/21)**
 - (2) The sampling point shall be at the outlet of the initial canister but before the inlet to the second or final polishing canister. Sample ports or connections must be designed such that air leakage into the sample port does not occur during sampling.
 - (3) During sampling, data recording shall not begin until after two times the instrument response time. The VOC concentration shall be monitored for at least 5 minutes, and readings shall be recorded at least once per minute.
- C. Breakthrough shall be defined as the highest 1-minute average measured VOC concentration at or exceeding 100 ppmv. When the condition of breakthrough of VOC from the initial saturation canister occurs, the waste gas flow shall be switched to the second canister and a fresh canister shall be placed as the new final polishing canister prior to the commencement of the next loading activity. Sufficient new activated carbon canisters shall be maintained at the site to replace spent carbon canisters such that replacements can be done in the above specified time frame.
- D. Records of the CAS monitoring maintained at the plant site, shall include (but are not limited to) the following:
- (1) Sample time and date.
 - (2) Monitoring results (ppmv).
 - (3) Corrective action taken including the time and date of that action.
 - (4) Process operations occurring at the time of sampling.

- E. Alternate monitoring or sampling requirements that are equivalent or better may be approved by the TCEQ Regional Manager. Alternate requirements must be approved in writing before they can be used for compliance purposes.
- F. The design of the CAS shall satisfy either of the following options:
 - (1) Either canister is capable of adsorbing all vapors generated from a transfer activity under anticipated worst-case operating conditions, and the permit holder retains the following records:
 - (a) Documentation of the anticipated worst-case operating conditions; and
 - (b) A copy of the CAS vendor or EPC contractor's statement as to the canister capacity for the specific VOC constituent(s) to be adsorbed; or
 - (2) The requirements of subparagraph (1) are not satisfied, and the required interval for replacement of canisters specified in paragraph C of this Special Condition shall be reduced to one hour.

Maintenance, Startup and Shutdown Activities

General

48. This permit authorizes the planned maintenance, startup, and shutdown (MSS) activities summarized in the MSS Activity Summary (Special Condition 49.C) attached to this permit.

Special Condition 49.A identifies the inherently low emitting MSS activities that may be performed at the plant. Emissions from activities identified in Special Condition 49.A shall be considered to be equal to the potential to emit represented in the permit application. The estimated emissions from the activities listed in Special Condition 49.A must be revalidated annually. This revalidation shall consist of the estimated emissions for each type of activity and the basis for that emission estimate.

Routine maintenance activities, as identified in Special Condition 49.B may be tracked through the work orders or equivalent. Emissions from activities identified in Special Condition 49.B shall be calculated using the number of work orders or equivalent that month and the emissions associated with that activity identified in the permit application.

The performance of each planned MSS activity not identified in Paragraphs A and B of Special Condition 49 and the emissions associated with it shall be recorded and include at least the following information:

- A. the process unit at which emissions from the MSS activity occurred, including the emission point number and common name of the process unit;
- B. the type of planned MSS activity and the reason for the planned activity;
- C. the common name and the facility identification number, if applicable, of the facilities at which the MSS activity and emissions occurred;
- D. the date and time of the MSS activity and its duration;

- E. the estimated quantity of each air contaminant, or mixture of air contaminants, emitted with the data and methods used to determine it. The emissions shall be estimated using the methods identified in the permit application, and in TCEQ Project 316526, Content ID 4700346 pages 54-81, consistent with good engineering practice. **(09/22)**

The permit additionally authorizes the alternate operating mode summarized below. Records shall be created for each such activity containing the information specified in paragraphs A–E of this Special Condition, except that each instance of the phrase “MSS activity” or “planned MSS activity” shall be replaced by “activity.”

Facility	Activity	EPN
Olefins, EPE, CPE and Utilities Plants	Operating during planned outage or low firing of two or more boilers; and operation during planned outage of both of the shared thermal oxidizers.	Shared Vent System

49. All MSS emissions shall be summed monthly and the rolling 12-month emissions shall be updated on a monthly basis. This permit authorizes emissions from the following temporary facilities used to support planned MSS activities at permanent site facilities: vacuum trucks, portable control devices identified in Special Condition 57, and controlled recovery systems. Emissions from temporary facilities are authorized provided the temporary facility (a) does not remain on the plant site for more than 12 consecutive months, (b) is used solely to support planned MSS activities at the permanent site facilities listed in this Special Condition, and (c) does not operate as a replacement for an existing authorized facility.

Planned startup and shutdown emissions due to the activities identified in this Special Condition are authorized from the facilities and temporary equipment and control devices identified in the Special Conditions of the permit.

A. Inherently low emitting maintenance activities

- Reactor sampling
- Low point drains
- Management of sludge from pits, ponds, sumps, and water conveyances
- Aerosol cans
- Calibration of analytical equipment
- Carbon canister replacement
- Instrumentation/analyzer maintenance
- Meter proving
- Replacement of analyzer filters and screens
- Pipeline pigging
- Filter/strainer changeouts
- Steam condensate drum flash

B. Routine maintenance

Pump repair/replacement

Fugitive component (valve, pipe, flange) repair/replacement (isolated volume \leq 150 ft.³)

Compressor repair/replacement (not including cracked gas compressor, propylene refrigerant compressor or ethylene refrigerant compressor)

Heat exchanger repair/replacement

Vessel repair/replacement (isolated volume \leq 50 ft.³)

Transfer of solid catalyst and desiccant to/from process equipment

Instrument/analyzer maintenance

C. MSS Activity Summary

Facility	Activity	EPN
Olefins, EPE, CPE and Utilities plants	Process startup and shutdown	Shared Vent System
Glycol plant	Process startup and shutdown	Glycol Vent System
Olefins, EPE, CPE, Utilities and Glycol plants	Depressurize and drain equipment following shutdown	Shared Vent System, Glycol Vent System
Floating roof storage tanks	Operate tank with landed roof, controlled degassing	TMPCTRL
All storage tanks	Ventilation, cleaning and inspection	MSSTANK
Vacuum trucks	Operate vacuum truck	MSSVAC
Frac Tanks	Operate frac tank	MSSFRAC
Olefins, EPE, CPE and Utilities plant piping, compressors, process vessels and reactors	Cleaning, inspection and maintenance activities not identified in paragraph B	MSSATM, TMPCTRL, Shared Vent System
Storage tanks, loading facilities, and wastewater facilities	Cleaning, inspection and maintenance activities not identified in paragraph B	MSSATM, TMPCTRL, Shared Vent System
Glycol plant piping, process vessels and reactors	Cleaning, inspection and maintenance activities not identified in paragraph B	MSSATM, TMPCTRL, Glycol Vent System
Routine maintenance activities	See paragraph B	MSSATM, TMPCTRL, Shared Vent System, Glycol Vent System
Inherently low emitting activities	See paragraph A	MSSILE

De-inventory of process units

50. Process units and facilities, with the exception of those identified in Special Conditions 26, 49.A, and 56 shall be depressurized, emptied, degassed, and placed in service in accordance with the following requirements. **(03/22)**

- A. The process equipment shall be depressurized to a control device or a controlled recovery system prior to venting to atmosphere, degassing, or draining liquid. Equipment that only contains material that is liquid with VOC partial pressure less than 0.50 psi at the normal process temperature and 95°F may be opened to atmosphere and drained in accordance with paragraph C of this Special Condition. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded.
- B. If mixed phase materials must be removed from process equipment, the cleared material shall be routed to a knockout drum or equivalent to allow for managed initial phase separation. If the VOC partial pressure is greater than 0.50 psi at either the normal process temperature or 95°F, any vents in the system must be routed to a control device or a controlled recovery system. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded. Control must remain in place until degassing has been completed or the system is no longer vented to atmosphere.
- C. All liquids from process equipment or storage vessels must be removed to the maximum extent practical prior to opening equipment to commence degassing and/or maintenance. Liquids must be drained into a closed vessel or closed liquid recovery system unless prevented by the physical configuration of the equipment. If it is necessary to drain liquid into an open pan or sump, the liquid must be covered or transferred to a covered vessel within one hour of being drained.
- D. If the VOC partial pressure is greater than 0.50 psi at the normal process temperature or 95°F, facilities shall be degassed using good engineering practice to ensure air contaminants are removed from the system through the control device or controlled recovery system to the extent allowed by process equipment or storage vessel design. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded. The facilities to be degassed shall not be vented directly to atmosphere, except as necessary to establish isolation of the work area or to monitor VOC concentration following controlled depressurization. The venting shall be minimized to the maximum extent practicable and actions taken recorded. The control device or recovery system utilized shall be recorded with the estimated emissions from controlled and uncontrolled degassing calculated using the methods that were used to determine allowable emissions for the permit application.
 - (1) For MSS activities identified in Special Condition 49.B, the following option may be used in lieu of (2) below. The facilities being prepared for maintenance shall not be vented directly to atmosphere until the VOC concentration has been verified to be less than 10 percent of the lower explosive limit (LEL) per the site safety procedures.
 - (2) The locations and/or identifiers where the purge gas or steam enters the process equipment or storage vessel and the exit points for the exhaust gases shall be recorded (process flow diagrams [PFDs] or piping and instrumentation diagrams [P&IDs] may be used to demonstrate compliance with the requirement). If the process equipment is purged with a gas, two system volumes of purge gas must have passed through the control device or controlled recovery system before the vent stream may be sampled to verify acceptable VOC concentration prior to uncontrolled venting. The VOC sampling and analysis shall be performed using an instrument meeting the requirements of Special Condition 54. The sampling point shall be upstream of the

inlet to the control device or controlled recovery system. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the process equipment or vessel being purged. If there is not a connection (such as a sample, vent, or drain valve) available from which a representative sample may be obtained, a sample may be taken upon entry into the system after degassing has been completed. The sample shall be taken from inside the vessel so as to minimize any air or dilution from the entry point. The facilities shall be degassed to a control device or controlled recovery system until the VOC concentration is less than 10,000 ppmv or 10 percent of the LEL. Documented site procedures used to de-inventory equipment to a control device for safety purposes (i.e., hot work or vessel entry procedures) that achieve at least the same level of purging may be used in lieu of the above.

- E. Gases and vapors with VOC partial pressure greater than 0.50 psi may be vented directly to atmosphere if all the following criteria are met:
- (1) It is not technically practicable to depressurize or degas, as applicable, into the process.
 - (2) There is not an available connection to a plant control system (flare).
 - (3) There is no more than 50 lb of air contaminant to be vented to atmosphere during shutdown or startup, as applicable.

All instances of venting directly to atmosphere provided for under paragraph E of this Special Condition shall be documented when occurring as part of any MSS activity. The emissions associated with venting without control must be included in the work order or equivalent for those planned MSS activities identified in Attachment B.

Storage Tanks

51. This permit authorizes emissions from EPNs MSSTANK and from control devices identified in Special Condition 57 (controlled sources) for the floating roof storage tanks identified in Special Condition 26 during planned floating roof landings. Tank roof landings include all operations when the tank floating roof is on its supporting legs. These emissions are subject to the maximum allowable emission rates indicated in the MAERT. The following requirements apply to tank roof landings.
- A. At all times that the roof is resting on its leg supports, the tank emissions shall be controlled by a closed vent system and control device meeting the following specifications:
- (1) The closed vent system shall be designed to collect all VOC vapors and gases discharged from the storage vessel and operated with no detectable emissions as indicated by an instrument reading of less than 500 ppm above background and visual inspections, as determined in 40 CFR Part 60, Subpart VV, § 60.485(b).
 - (2) The locations and identifiers of vents other than permanent roof fittings and seals, control device or controlled recovery system, and controlled exhaust stream shall be recorded. There shall be no other gas/vapor flow out of the vapor space under the floating roof when the vapor space is directed to the control device. The vapor recovery system collection rate shall be no less than 100 cubic feet per minute when the tank is

idle or the tank is being drained, and two times the fill rate when the tank is being refilled.

- (3) The control device shall be operated as required by Special Condition No 57.

The roof shall be landed on its lowest legs unless entry or inspection is planned.

The requirements of this Paragraph do not apply to uncontrolled degassing and/or ventilation conducted pursuant to Paragraphs C–E of this Special Condition.

- B. The control requirements of Paragraph A of this Special Condition may be waived during emptying and set-up for tank degassing if the following conditions are met:

- (1) The tank will be completely emptied for the purposes of inspection and maintenance.
- (2) The process of emptying the tank when the roof is resting on the leg supports shall be continuous and shall be accomplished as rapidly as practicable.
- (3) Degassing of the vapor space under the landed roof begins within 24 hours after the tank has been emptied.

- C. After the tank has been completely emptied, the tank shall not be opened except as necessary to set up for degassing and cleaning. Floating roof tanks with liquid capacities less than 100,000 gallons may be degassed without control if the VOC partial pressure of the standing liquid in the tank has been reduced to less than 0.02 psia prior to ventilating the tank. Controlled degassing of the vapor space under the landed roof shall be completed as follows:

- (1) Any gas or vapor removed from the vapor space under the floating roof must be routed to a control device or controlled recovery system and controlled degassing must be maintained until the VOC concentration is less than 10,000 ppmv or 10 percent of the LEL. The locations and identifiers of vents other than permanent roof fittings and seals, control device or controlled recovery system, and controlled exhaust stream shall be recorded. There shall be no other gas/vapor flow out of the vapor space under the floating roof when degassing to the control device or controlled recovery system.
- (2) The vapor space under the floating roof shall be vented using good engineering practice to ensure air contaminants are flushed out of the tank through the control device or controlled recovery system to the extent allowed by the storage tank design.
- (3) A volume of purge gas equivalent to twice the volume of the vapor space under the floating roof must have passed through the control device or into a controlled recovery system, before the vent stream may be sampled to verify acceptable VOC concentration. The measurement of purge gas volume shall not include any make-up air introduced into the control device or recovery system. The VOC sampling and analysis shall be performed as specified in Special Condition No. 54.
- (4) The sampling point shall be upstream of the inlet to the control device or controlled recovery system. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the process equipment or vessel being purged.
- (5) Degassing must be performed every 24 hours unless there is no standing liquid in the tank or the VOC partial pressure of the remaining liquid in the tank is less than 0.15 psia.

- D. The tank shall not be opened or ventilated without control, except as allowed by (1) or (2) below until one of the criteria in Paragraph E of this Special Condition is satisfied.
- (1) Minimize air circulation in the tank vapor space.
 - (a) One manway may be opened to allow access to the tank to remove or de-volatilize the remaining liquid. Other manways or access points may be opened as necessary to remove or de-volatilize the remaining liquid. Wind barriers shall be installed at all open manways and access points to minimize air flow through the tank.
 - (b) Access points shall be closed when not in use.
 - (2) Minimize time and VOC partial pressure. (this option may be used only if justified by the applicant)
 - (a) The VOC partial pressure of the liquid remaining in the tank shall not exceed 0.044 psia as documented by the method specified in subparagraph D(1) of this condition;
 - (b) Blowers may be used to move air through the tank without emission control at a rate not to exceed 1000 cfm for no more than 72 hours. All standing liquid shall be removed from the tank during this period; and
 - (c) Records shall be maintained of the blower circulation rate, the duration of uncontrolled ventilation, and the date and time all standing liquid was removed from the tank.
- E. The tank may be opened without restriction and ventilated without control after all standing liquid has been removed from the tank or the liquid remaining in the tank has a VOC partial pressure of less than 0.02 psia. These criteria shall be demonstrated in one of the following ways:
- (1) Low VOC partial pressure liquid that is soluble with the liquid previously stored may be added to the tank to lower the VOC partial pressure of the liquid mixture remaining in the tank to less than 0.02 psia. This liquid shall be added during tank degassing if practicable. The estimated volume of liquid remaining in the drained tank and the volume and type of liquid added shall be recorded. The liquid VOC partial pressure may be estimated based on this information and engineering calculations.
 - (2) If water is added or sprayed into the tank to remove standing VOC, one of the following must be demonstrated:
 - (a) Take a representative sample of the liquid remaining in the tank and verify no visible sheen using the static sheen test from 40 CFR Part 435, Subpart A, Appendix 1.
 - (b) Take a representative sample of the liquid remaining in the tank and verify that the hexane soluble VOC concentration is less than 1000 ppmw using EPA method 1664.
 - (c) Stop ventilation and close the tank for at least 24 hours. When the tank manway is opened after this period, verify that the VOC concentration is less than 1000 ppmw through the procedure in Special Condition No 54.

- (3) No standing liquid, verified through visual inspection.

The permit holder shall maintain records to document the method used to release the tank.

- F. The occurrence of each roof landing and the associated emissions shall be recorded and the rolling 12-month tank roof landing emissions shall be updated on a monthly basis. These records shall include at least the following information (as applicable):
 - (1) The identification of the tank and emission point number, and any control devices or controlled recovery systems used to reduce emissions;
 - (2) The reason for the tank roof landing;
 - (3) For the purpose of estimating emissions, the date, time, and other information specified for each of the following events:
 - (a) The roof was initially landed;
 - (b) All liquid was pumped from the tank to the extent practicable;
 - (c) Start and completion of controlled degassing, and total volumetric flow;
 - (d) All standing liquid was removed from the tank or any transfers of low VOC partial pressure liquid to or from the tank including volumes and vapor pressures to reduce tank liquid VOC partial pressure to < 0.02 psia.
 - (e) If there is liquid in the tank, VOC partial pressure of liquid, start and completion of uncontrolled degassing, and total volumetric flow;
 - (f) Refilling commenced, liquid filling the tank, and the volume necessary to float the roof; and
 - (g) Tank roof off supporting legs, floating on liquid.
 - (4) The estimated quantity of each air contaminant, or mixture of air contaminants, emitted between events (c) and (g) with the data and methods used to determine it. The emissions associated with roof landing activities shall be calculated using the methods described in Section 7.1.3.2 of AP 42 "Compilation of Air Pollution Emission Factors, Chapter 7—Storage of Organic Liquids" dated November 2006 (or later edition) and the permit application.

- 52. Fixed roof storage tanks are subject to the requirements of Special Condition 51.D and 51.E. If the ventilation of the vapor space is controlled, the emission control system shall meet the requirements of Special Condition 51.C(1)–(4). Records shall be maintained per Special Condition 51.F(3)(c)–(e) and 51.F(4).

Solids Handling

- 53. Transfer of solid materials, including catalyst and desiccant, to or from process equipment shall be conducted consistent with the following requirements:
 - A. Particulate emissions shall be minimized as follows during loading of solids into process equipment:

- (1) Equipment for loading solids shall be designed and configured such that solids are dropped from a height not to exceed 2 feet; or
 - (2) A vacuum or vacuum truck shall be used to convey solids, where the vacuum/vacuum truck exhaust is controlled using a HEPA filter or portable dust collector.
- B. Particulate emissions shall be minimized as follows during unloading of solids from process equipment using one of the following methods:
- (1) Process equipment shall be flooded with water prior to transfer of solids;
 - (2) Solids shall be transferred to a bin or container which minimize the action of wind currents on dust formation; or
 - (3) If a portable vacuum or vacuum truck is used to remove solids, the system shall be enclosed such that the only vent to the atmosphere is through the vacuum/vacuum truck exhaust, and such exhaust shall be controlled using a HEPA filter or portable dust collector.
- C. The permit holder shall record the type of solids transferred, the method of transfer, and the type of control device employed (if any).

Analytical Methods

54. Air contaminant concentration shall be measured using an instrument/detector meeting one set of requirements specified below.
- A. VOC concentration shall be measured using an instrument meeting all the requirements specified in EPA Method 21 (40 CFR 60, Appendix A) with the following exceptions:
- (1) The instrument shall be calibrated within 24 hours of use with a calibration gas such that the response factor (RF) of the VOC (or mixture of VOCs) to be monitored shall be less than 2.0. The calibration gas and the gas to be measured, and its approximate RF shall be recorded. If the RF of the VOC (or mixture of VOCs) to be monitored is greater than 2.0, the VOC concentration shall be determined as follows:
$$\text{VOC Concentration} = \text{Concentration as read from the instrument} \times \text{RF}$$

In no case should a calibration gas be used such that the RF of the VOC (or mixture of VOCs) to be monitored is greater than 5.0.
 - (2) Sampling shall be performed as directed by this permit in lieu of section 8.3 of Method 21. During sampling, data recording shall not begin until after two times the instrument response time. The date and time shall be recorded, and VOC concentration shall be monitored for at least 5 minutes, recording VOC concentration each minute. As an alternative, the VOC concentration may be monitored over a five-minute period with an instrument designed to continuously measure concentration and record the highest concentration read. The highest measured VOC concentration shall be recorded and shall not exceed the specified VOC concentration limit prior to uncontrolled venting.
- B. Colorimetric gas detector tubes may be used to determine air contaminant concentrations if they are used in accordance with the following requirements.
- (1) The air contaminant concentration measured as defined in (3) is less than 80 percent of the range of the tube and is at least 20 percent of the maximum range of the tube.

- (2) The tube is used in accordance with the manufacturer's guidelines.
- (3) At least 2 samples taken at least 5 minutes apart must satisfy the following prior to uncontrolled venting:

measured contaminant concentration (ppmv) < release concentration.

Where the release concentration is:

10,000*mole fraction of the total air contaminants present that can be detected by the tube.

The mole fraction may be estimated based on process knowledge. The release concentration and basis for its determination shall be recorded.

Records shall be maintained of the tube type, range, measured concentrations, and time the samples were taken.

C. Lower explosive limit measured with a lower explosive limit detector.

- (1) The calibration gas shall be documented in the site safety procedures.
- (2) The detector shall be calibrated within 30 days of use with a certified gas standard at 25% of the lower explosive limit (LEL) for the calibration gas. Records of the calibration date/time and calibration result (pass/fail) shall be maintained.
- (3) A functionality test shall be performed on each detector within 24 hours of use with a certified gas standard at 25% of the LEL for the calibration gas. The LEL monitor shall read no lower than 90% of the calibration gas certified value. Records, including the date/time and test results, shall be maintained.
- (4) A certified methane gas standard equivalent to 25% of the LEL for the calibration gas may be used for calibration and functionality tests provided that the LEL response is within 95% of that for the calibration gas.

Temporary facilities and control devices

55. The following requirements apply to vacuum and air mover truck operations to support planned MSS at this site:

- A. Prior to initial use, identify any liquid in the truck. Record the liquid level and document the VOC partial pressure. After each liquid transfer, identify the liquid, the volume transferred, and its VOC partial pressure.
- B. If vacuum pumps or blowers are operated when liquid is in or being transferred to the truck, the following requirements apply:
 - (1) If the VOC partial pressure of the liquid in or being transferred to the truck is greater than 0.50 psi at 95°F, the vacuum/blower exhaust shall be routed to a control device or a controlled recovery system.
 - (2) Equip fill line intake with a "duckbill" or equivalent attachment if the hose end cannot be submerged in the liquid being collected.
 - (3) A daily record containing the information identified below is required for each vacuum truck in operation at the site each day.

- (a) For each liquid transfer made with the vacuum operating, record the duration of any periods when air may have been entrained with the liquid transfer. The reason for operating in this manner and whether a “duckbill” or equivalent was used shall be recorded. Short, incidental periods, such as those necessary to walk from the truck to the fill line intake, do not need to be documented.
 - (b) If the vacuum truck exhaust is controlled with a control device other than an engine or oxidizer, VOC exhaust concentration upon commencing each transfer, at the end of each transfer, and at least every hour during each transfer shall be recorded, measured using an instrument meeting the requirements of Special Condition 54.A or 54.B.
 - C. Record the volume in the vacuum truck at the end of the day, or the volume unloaded, as applicable.
 - D. The permit holder shall determine the vacuum truck emissions each month using the daily vacuum truck records and the calculation methods utilized in the permit application. If records of the volume of liquid transferred for each pick-up are not maintained, the emissions shall be determined using the physical properties of the liquid vacuumed with the greatest potential emissions. Rolling 12-month vacuum truck emissions shall also be determined on a monthly basis.
 - E. If the permit holder determines that the VOC partial pressure of all the liquids vacuumed into the truck is less than 0.10 psi, such determination shall be recorded when the truck is unloaded or leaves the plant site and the emissions may be estimated as the maximum potential to emit for a truck in that service as documented in the permit application. The recordkeeping requirements in Paragraphs A–D do not apply.
56. The following requirements apply to frac, or temporary, tanks and vessels used in support of MSS activities.
- A. The exterior surfaces of these tanks/vessels that are exposed to the sun shall be white or aluminum. This requirement does not apply to tanks/vessels that only vent to atmosphere when being filled, sampled, gauged, or when removing material.
 - B. These tanks/vessels must be covered and equipped with fill pipes that discharge within 6 inches of the tank/vessel bottom.
 - C. These requirements do not apply to vessels storing less than 450 gallons of liquid that are closed such that the vessel does not vent to atmosphere except when filling, sampling, gauging, or when removing material.
 - D. The permit holder shall maintain an emissions record which includes calculated emissions of VOC from all frac tanks during the previous calendar month and the past consecutive 12-month period. This record must be updated by the last day of the month following. The record shall include tank identification number, dates put into and removed from service, control method used, tank capacity and volume of liquid stored in gallons, name of the material stored, VOC molecular weight, and VOC partial pressure at the estimated monthly average material temperature in psia. Filling emissions for tanks shall be calculated using the TCEQ publication titled “Technical Guidance Package for Chemical Sources - Loading Operations” and standing emissions determined using: the TCEQ publication titled “Technical Guidance Package for Chemical Sources - Storage Tanks.”

- E. If the tank/vessel is used to store liquid with VOC partial pressure less than 0.10 psi at 95°F, records may be limited to the days the tank is in service and the liquid stored. Emissions may be estimated based upon the potential to emit as identified in the permit application.
57. Control devices required by this permit for emissions from planned MSS activities are limited to those types identified in this condition. Control devices shall be operated with no visible emissions except periods not to exceed a total of 5 minutes during any two consecutive hours. Each device used must meet all the requirements identified for that type of control device.

Controlled recovery systems identified in this permit shall be directed to an operating process or to a collection system that is vented through a control device meeting the requirements of this permit condition.

A. Carbon Adsorption System (CAS).

- (1) The CAS shall consist of 2 carbon canisters in series with adequate carbon supply for the emission control operation.
- (2) The CAS shall be sampled downstream of the first can and the concentration recorded at least once every hour of CAS run time to determine breakthrough of the VOC.
- (3) The method of VOC sampling and analysis shall be by detector meeting the requirements of Special Condition 54.A or B.
- (4) Breakthrough is defined as the highest measured VOC concentration at or exceeding 100 ppmv above background. When the condition of breakthrough of VOC from the initial saturation canister occurs, the waste gas flow shall be switched to the second canister and a fresh canister shall be placed as the new final polishing canister within 4 hours. Sufficient new activated carbon canisters shall be maintained at the site to replace spent carbon canisters such that replacements can be done in the above specified time frame.
- (5) Records of CAS monitoring shall include the following:
 - (a) Sample time and date.
 - (b) Monitoring results (ppmv).
 - (c) Canister replacement log.
- (6) Single canister systems are allowed if the time the carbon canister is in service is limited to no more than 30 percent of the minimum potential saturation time. The permit holder shall maintain records for these systems, including the calculations performed to determine the saturation time. The time limit on carbon canister service shall be recorded and the expiration date attached to the carbon can.

B. Thermal Oxidizer.

- (1) The thermal oxidizer firebox exit temperature shall be maintained at not less than 1400°F and waste gas flows shall be limited to assure at least a 0.5 second residence time in the fire box while waste gas is being fed into the oxidizer.

- (2) The thermal oxidizer exhaust temperature shall be continuously monitored and recorded when waste gas is directed to the oxidizer. The temperature measurements shall be made at intervals of six minutes or less and recorded at that frequency.

The temperature measurement device shall be installed, calibrated, and maintained according to accepted practice and the manufacturer's specifications. The device shall have an accuracy of the greater of ± 0.75 percent of the temperature being measured expressed in degrees Celsius or $\pm 2.5^{\circ}\text{C}$.

C. Internal Combustion Engine.

- (1) The internal combustion engine shall have a VOC destruction efficiency of at least 99 percent.
- (2) The engine must have been stack tested with butane or propane to confirm the required destruction efficiency within the period specified in subparagraph 3 below. VOC shall be measured in accordance with the applicable EPA Reference Method during the stack test and the exhaust flow rate may be determined from measured fuel flow rate and measured oxygen concentration. A copy of the stack test report shall be maintained with the engine. There shall also be documentation of acceptable VOC emissions following each occurrence of engine maintenance that may reasonably be expected to increase emissions including oxygen sensor replacement and catalyst cleaning or replacement. Stain tube indicators specifically designed to measure VOC concentration shall be acceptable for this documentation, provided a hot air probe or equivalent device is used to prevent error due to high stack temperature, and three sets of concentration measurements are made and averaged. Portable VOC analyzers meeting the requirements of Special Condition 54.A are also acceptable for this documentation.

- (3) The engine shall be operated and monitored as specified below.

- (a) If the engine is operated with an oxygen sensor-based air-to-fuel ratio (AFR) controller, documentation for each AFR controller that the manufacturer's or supplier's recommended maintenance has been performed, including replacement of the oxygen sensor as necessary for oxygen sensor-based controllers shall be maintained with the engine. The oxygen sensor shall be replaced at least quarterly in the absence of a specific written recommendation. The engine must have been stack tested within the past 12 months in accordance with Subparagraph (2) above.

The test period may be extended to 24 months if the engine exhaust is sampled once an hour when waste gas is directed to the engine using a detector meeting the requirements of Special Condition 54.A. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the engine. The concentrations shall be recorded and the MSS activity shall be stopped as soon as possible if the VOC concentration exceeds 100 ppmv above background.

- (b) If an oxygen sensor-based AFR controller is not used, the engine exhaust to atmosphere shall be monitored continuously and the VOC concentration recorded at least once every 15 minutes when waste gas is directed to the engine. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection

system downstream of the engine. The method of VOC sampling and analysis shall be by detector meeting the requirements of Special Condition 54.A. An alarm shall be installed such that an operator is alerted when outlet VOC concentration exceeds 100 ppmv above background. The MSS activity shall be stopped as soon as possible if the VOC concentration exceeds 100 ppmv above background for more than one minute. The date and time of all alarms and the actions taken shall be recorded. The engine must have been stack tested within the past 24 months in accordance with Subparagraph (2) above.

- D. A permanent control device specified in the permit, operated as required in the applicable permit Special Conditions.
- E. A liquid scrubbing system may be used upstream of carbon adsorption. A single carbon can or a liquid scrubbing system may be used as the sole control device if the requirements below are satisfied.
 - (1) The exhaust to atmosphere shall be monitored continuously and the VOC concentration recorded at least once every 15 minutes when waste gas is directed to the scrubber.
 - (2) The method of VOC sampling and analysis shall be by detector meeting the requirements of Special Condition 54.A.
 - (3) An alarm shall be installed such that an operator is alerted when outlet VOC concentration exceeds 100 ppmv above background. The MSS activity shall be stopped as soon as possible when the VOC concentration exceeds 100 ppmv above background for more than one minute. The date and time of all alarms and the actions taken shall be recorded.
- F. A closed loop refrigerated vapor recovery system
 - (1) The vapor recovery system shall be installed on the facility to be degassed using good engineering practice to ensure air contaminants are flushed from the facility through the refrigerated vapor condensers and back to the facility being degassed. The vapor recovery system and facility being degassed shall be enclosed except as necessary to insure structural integrity (such as roof vents on a floating roof tank).
 - (2) VOC concentration in vapor being circulated by the system shall be sampled and recorded at least once every 4 hours at the inlet of the condenser unit with an instrument meeting the requirements of Special Condition 54.
 - (3) The quantity of liquid recovered from the tank vapors and the tank pressure shall be monitored and recorded each hour. The liquid recovered must increase with each reading and the tank pressure shall not exceed one inch water pressure while the system is operating.

Use of permits by rule

- 58. Additional occurrences of MSS activities authorized by this permit may be authorized under permit by rule only if conducted in compliance with this permit's procedures, emission controls, monitoring, and recordkeeping requirements applicable to the activity.

Miscellaneous Sources

59. Reserved. **(02/21)**
60. The following requirements apply to emergency generators (EPNs EMGGEN01, EMGGEN02, ADMINGEN, GLYGEN01) and the emergency firewater pumps (EPN FWP1, FWP2). **(11/21)**
- A. Fuel for the engines shall be limited to ultra-low sulfur diesel (ULSD) containing no more than 15 ppmw total sulfur.
 - B. In addition to the allowable emission rates indicated in the MAERT, each engine shall be limited to the non-emergency operating hours as defined at 40 CFR § 63.6640(f).
 - C. Each engine shall be equipped with a non-resettable hour meter.
 - D. Each emergency generator shall satisfy the Tier 4 exhaust emission standards specified at 40 CFR § 1039.101 for model years 2015 and later.
 - E. Each firewater pump shall satisfy the Tier 3 exhaust emission standards specified at 40 CFR § 89.112.
 - F. Compliance with the emission limits of paragraph D and E of this Special Condition shall be demonstrated by retaining a copy of the manufacturers' certificate of conformity, vendor guarantee, or through other methods receiving prior written approval of the TCEQ Executive Director.
61. All ammonia vapors generated during unloading of ammonia and depressurization of ammonia storage and transport vessels shall be captured and directed to Aqueous Ammonia Vent Drum (EPN: UTD05). The ammonia vent drum shall capture 100% of ammonia vapors directed to it, as demonstrated through compliance with paragraphs A–B of this Special Condition. **(02/21)**
- A. Prior to introduction of ammonia, the ammonia vent drum shall be filled with no less than two gallons of fresh water per pound of ammonia vapors that may be discharged into the vent drum.
 - B. The ammonia vent drum shall be designed to ensure complete mixing of ammonia vapors into the standing water.
 - C. The permit holder shall complete removal of wastewater from the ammonia vent drum to a closed storage vessel or treatment system as soon as practicable, and removal shall commence within one hour of completion of the transfer or depressurization activity.

Initial Demonstration of Compliance

62. The permit holder shall perform stack sampling and other testing as required to establish the actual pattern and quantities of air contaminants being emitted into the atmosphere from the sources of emissions specified in Paragraph G of this Special Condition, and to demonstrate compliance with Special Conditions 1, 21, 23, 39, and 46. The permit holder is responsible for providing sampling and testing facilities and conducting the sampling and testing operations at his expense. Sampling shall be conducted in accordance with the appropriate procedures of the TCEQ Sampling Procedures Manual and the EPA Reference Methods.

Requests to waive testing for any pollutant specified in this condition shall be submitted to the TCEQ Office of Air, Air Permits Division. Test waivers and alternate/equivalent procedure proposals for Title 40 Code of Federal Regulation Part 60 (40 CFR Part 60) testing which must have EPA approval shall be submitted to the TCEQ Regional Director.

- A. The appropriate TCEQ Regional Office shall be notified not less than 45 days prior to sampling. The notice shall include:

- (1) Proposed date for pretest meeting.
- (2) Date sampling will occur.
- (3) Name of firm conducting sampling.
- (4) Type of sampling equipment to be used.
- (5) Method or procedure to be used in sampling.
- (6) Description of any proposed deviation from the sampling procedures specified in this permit or TCEQ/EPA sampling procedures.
- (7) Procedure/parameters to be used to determine worst case emissions during the sampling period.

The purpose of the pretest meeting is to review the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, and to review the format procedures for the test reports. The TCEQ Regional Director must approve any deviation from specified sampling procedures.

- B. Air contaminants to be tested for include (but are not limited to) those specified in paragraph G of this Special Condition. Sampling for SO₂ shall be required for one of the utility boilers and for one of the shared thermal oxidizers. Sampling for VOC shall be required for one dryer per PE unit.
- C. Sampling shall occur within 60 days after achieving the maximum operating rate, but no later than 180 days after initial start-up of the facilities and at such other times as may be required by the TCEQ Executive Director. Additionally, sampling for CO and NO_x shall be repeated at an interval of once every five years for the MEG Thermal Oxidizer. The requirement to complete sampling for shared thermal oxidizers shall be extended to no later than 365 days after initial start-up of any polyethylene unit. Requests for additional time to perform sampling shall be submitted to the appropriate TCEQ Regional Office.
- D. The facility being sampled shall operate as indicated in Paragraph H during stack emission testing. These conditions/parameters and any other primary operating parameters that affect the emission rate shall be monitored and recorded during the stack test. Any additional parameters shall be determined at the pretest meeting and shall be stated in the sampling report. Permit conditions and parameter limits may be waived during stack testing performed under this condition if the proposed condition/parameter range is identified in the test notice specified in Paragraph A and accepted by the TCEQ Regional Office. Permit allowable emissions and emission control requirements are not waived and still apply during stack testing periods.

During subsequent operations, stack sampling shall be performed within 120 days for the following sources if the following requirements are satisfied. This sampling may be waived by the TCEQ Air Section Manager for the Region.

- (1) For each combustion unit, with respect to sampling for NO_x, if the 3-hr average firing rate exceeds the higher of:
 - (a) the firing rate demonstrated during the most recent stack test for the combustion unit; or
 - (b) the firing rate demonstrated during the most recent stack test for any identical combustion unit.
 - (2) For any pyrolysis furnace, sampling for PM₁₀ shall be required if a violation of Special Condition 18 occurs during decoking operations. The time required to complete sampling shall be extended to 365 days. This requirement shall not apply more than one time per furnace.
 - (3) For each dryer vent, if the unit produces a grade of resin with a total residual VOC content that exceeds 150% of that determined during the most recent stack test.
- E. Copies of the final sampling report shall be forwarded to the offices below within 60 days after sampling is completed. Sampling reports shall comply with the attached provisions entitled "Chapter 14, Contents of Sampling Reports" of the TCEQ Sampling Procedures Manual. The reports shall be distributed as follows:
- One copy to the appropriate TCEQ Regional Office.
One copy to each local air pollution control program.
- F. Sampling ports and platform(s) shall be incorporated into the design of each source listed in paragraph G according to the specifications set forth in the attachment entitled "Chapter 2, Guidelines for Stack Sampling Facilities" of the TCEQ Sampling Procedures Manual. Alternate sampling facility designs must be submitted for approval to the TCEQ Regional Director.
- G. Sources of Emissions subject to stack sampling requirements, and pollutants to be tested, are as follows:

EPN	Source Name	Pollutant (required sampling indicated by X; conditional sampling indicated by †)					
		VOC	CO	NO _x	NH ₃	PM ₁₀	SO ₂
O_FAF01	Pyrolysis Furnace A		X	X	X	†	
O_FBF01	Pyrolysis Furnace B		X	X	X		
O_FCF01	Pyrolysis Furnace C		X	X	X		
O_FDF01	Pyrolysis Furnace D		X	X	X		
O_FEF01	Pyrolysis Furnace E		X	X	X		
O_FFF01	Pyrolysis Furnace F		X	X	X		
O_FGF01	Pyrolysis Furnace G		X	X	X		
O_FHF01	Pyrolysis Furnace H		X	X	X		
USSG01A	Utilities Boiler A		X	X	X		X
USSG01B	Utilities Boiler B		X	X	X		
USSG01C	Utilities Boiler C		X	X	X		
UFF01A	Shared Thermal Oxidizer A	X	X	X			X

EPN	Source Name	Pollutant (required sampling indicated by X; conditional sampling indicated by †)					
		VOC	CO	NO _x	NH ₃	PM ₁₀	SO ₂
UFF01B	Shared Thermal Oxidizer B	X	X	X			
GBX02	MEG Thermal Oxidizer	X	X	X			
ZWSRCO1A/B	Equalization Tanks Catalytic Oxidizer	X					
EMFAN01	EPE Pellet Dryer 1 Vent	X					
EMFAN02	EPE Pellet Dryer 2 Vent						
CMFAN01	CPE Pellet Dryer 1 Vent	X					
CMFAN02	CPE Pellet Dryer 2 Vent						

H. Facilities shall operate as follows during sampling:

- (1) For pyrolysis furnaces, sampling shall occur at the maximum heat duty that can be reasonably achieved during sampling (NO_x, CO and NH₃). In case sampling for PM₁₀ is required for any furnace, such sampling shall occur during decoking operations.
- (2) For utility boilers, sampling shall occur at the maximum heat duty that can be reasonably achieved during sampling. During sampling for SO₂, the sulfur content of the fuel shall be monitored.
- (3) For the shared thermal oxidizers:
 - (a) Sampling to determine compliance with Special Condition 46.A(2) shall occur when the thermal oxidizer receives a nitrogen-rich vent gas stream during purging of a polyethylene unit reactor for a grade transition or shutdown. In place of determining compliance when the activities in Special Condition 46.A(2) are occurring, the applicant has the option of sampling while a simulation of the activity waste stream is routed to the shared thermal oxidizers. If the activity is simulated, then the sampling report submitted in accordance with Paragraph E of this Special Condition shall include documentation as to why the simulation represented the worst case that would occur during the activity and demonstrated compliance from the start to finish of the activities in Special Condition 46.A(2) as would actually occur. **(01/22)**
 - (b) Sampling to determine compliance with Special Condition 46.A(1) shall occur at any time that the Olefins plant is in operation.
 - (c) Sampling referred to in subsections (a) and (b) may consist of a single test, if the relevant conditions for each test are satisfied.
- (4) For the MEG thermal oxidizers:
 - (a) Sampling to determine compliance with Special Condition 46.B(2) shall occur when the Glycol plant is in operation, and the glycol purge vent stream is redirected to the MEG Elevated flare.
 - (b) Sampling to determine compliance with Special Condition 46.B(1) shall occur when the Glycol plant is in operation and the glycol purge vent stream is routed to the thermal oxidizer.

- (c) Sampling referred to in subsections (a) and (b) may consist of a single test, if the relevant conditions for each test are satisfied.
- (5) For each pellet dryer vent, sampling shall occur during production of a resin expected to have the maximum total residual VOC content, at the maximum achievable production rate for the unit. A sample of the resin being produced during the stack test shall be collected and analyzed using the methods referred to in Special Condition 13.C.
- (6) For the wastewater treatment plant catalytic oxidizer, sampling shall occur when the Equalization Tanks are receiving influent wastewater.

Continuous Demonstration of Compliance

- 63. The permit holder shall install and operate a fuel flow meter to measure the gas fuel usage for each device listed in Special Condition 65. The monitored data shall be reduced to an hourly average flow rate at least once every day, using a minimum of four equally-spaced data points from each one-hour period. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or at least annually, whichever is more frequent, and shall be accurate to within 5 percent. In lieu of monitoring fuel flow, the permit holder may monitor stack exhaust flow using the flow monitoring specifications of 40 CFR Part 60, Appendix B, Performance Specification 6 or 40 CFR Part 75, Appendix A.
- 64. The permit holder shall install and operate an analyzer which continuously monitors the heat content of fuel supplied to each combustion unit and the shared thermal oxidizers. For combustion devices which receive fuel from a common fuel gas header, a single analyzer may be installed in the fuel gas header.
- 65. CEMS shall be installed and operated as follows for equipment covered by the permit. Special Condition 23.C specifies acceptable alternatives to installation of an NH₃ CEMS.

EPN	Source Name	CEMS required for pollutant (indicated by X)			
		O ₂	CO	NO _x	NH ₃
O_FAF01	Pyrolysis Furnace A	X	X	X	X
O_FBF01	Pyrolysis Furnace B	X	X	X	X
O_FCF01	Pyrolysis Furnace C	X	X	X	X
O_FDF01	Pyrolysis Furnace D	X	X	X	X
O_FEF01	Pyrolysis Furnace E	X	X	X	X
O_FFF01	Pyrolysis Furnace F	X	X	X	X
O_FGF01	Pyrolysis Furnace G	X	X	X	X
O_FHF01	Pyrolysis Furnace H	X	X	X	X
USSG01A	Utilities Boiler A	X	X	X	X
USSG01B	Utilities Boiler B	X	X	X	X
USSG01C	Utilities Boiler C	X	X	X	X
UFF01A	Shared Thermal Oxidizer A	X	X	X	
UFF01B	Shared Thermal Oxidizer B	X	X	X	

- 66. Each CEMS required under this permit shall satisfy the following requirements.

- A. The CEMS shall meet the design and performance specifications, pass the field tests, and meet the installation requirements and the data analysis and reporting requirements specified in the applicable Performance Specification Nos. 1 through 9, 40 CFR Part 60, Appendix B. The permit holder shall comply with the Ammonia Analyzer Periodic Performance Evaluations and Quality Assurance Procedures in the confidential file of the permit alteration with PI-1 dated December 7, 2021. The permit holder shall retain of copy of the Ammonia Analyzer Periodic Performance Evaluations and Quality Assurance Procedures (January 2022) and the ammonia analyzer's manufacturer manual and make it available upon request by TCEQ personnel. **(03/22)**
- B. Subparagraph (1) below applies to sources subject to the quality-assurance requirements of 40 CFR Part 60, Appendix F; and Subparagraph (2) applies to all other sources. Subparagraph (3) applies to all sources:
- (1) The permit holder shall assure that the CEMS meets the applicable quality-assurance requirements specified in 40 CFR Part 60, Appendix F, Procedure 1. Relative accuracy exceedances, as specified in 40 CFR Part 60, Appendix F, § 5.2.3 and any CEMS downtime shall be reported to the appropriate TCEQ Regional Manager, and necessary corrective action shall be taken. Supplemental stack concentration measurements may be required at the discretion of the appropriate TCEQ Regional Manager.
 - (2) Unless Appendix F is otherwise required by NSPS, state law or regulation, or permit or approval, in lieu of the requirements of 40 CFR Part 60 Appendix F 5.1.1, 5.1.3, and 5.1.4, the permit holder may conduct:
 - (a) either a Relative Accuracy Audit (RAA) or a Relative Accuracy Test Audit (RATA) once every three (3) years; and
 - (b) a Cylinder Gas Audit (CGA) each calendar quarter in which the RAA or RATA is not performed.
 - (3) The system shall be zeroed and spanned daily, and corrective action taken when the 24-hour span drift exceeds two times the amounts specified in the applicable Performance Specification Nos. 1 through 9, 40 CFR Part 60, Appendix B, or as specified by the TCEQ if not specified in Appendix B. Zero and span is not required on weekends and plant holidays if instrument technicians are not normally scheduled on those days.

Each monitor shall be quality-assured at least quarterly using Cylinder Gas Audits (CGA) in accordance with 40 CFR Part 60, Appendix F, Procedure 1, Section 5.1.2, with the following exception: a relative accuracy test audit (RATA) is not required once every four quarters (i.e., four successive quarterly CGA may be conducted). An equivalent quality-assurance method approved by the TCEQ may also be used. Successive quarterly audits shall occur no closer than two months.

All CGA exceedances of ± 15 percent accuracy indicate that the CEMS is out of control.
- C. The monitoring data shall be reduced to (averaging period) average concentrations at least once every day, using a minimum of four equally-spaced data points from each one-hour period. The individual average concentrations shall be reduced to units of ppmvd, lb/MMBtu, and/or lb/hr, as applicable at least once every week as follows:

- (1) The measured 1-hr average concentration (in units of ppmvd) from the CEMS shall be converted to a dry basis and corrected to the reference oxygen concentration.
- (2) The converted concentration, corrected for oxygen, shall be converted to an emissions factor (in units of lb/MMBtu) by using an appropriate F-factor determined as specified in EPA Method 19, Equation 19-13, determined using the measured hydrogen content of the fuel gas.
- (3) The emission rate (in units of lb/hr) shall be determined by multiplying the emission factor by the fuel flow rate and fuel heat content measured as required under Special Conditions 63–64.
- (4) In case the permit holder elects to monitor stack exhaust flow as provided for in Special Condition 63, the emission rate (in units of lb/hr) shall be determined by multiplying the measured concentration (converted and corrected as needed) by the exhaust flow rate; and the emission factor (in units of lb/MMBtu) shall be determined by dividing the emission rate by the monitored fuel flow rate, using fuel flow rate and fuel heat content data measured as required under Special Conditions 63–64.

A CEMS may be shared between two stacks if it is capable of generating quality-assured data at the frequency required by this Special Condition for each stack.

- D. All monitoring data and quality-assurance data shall be maintained by the source. The data from the CEMS may, at the discretion of the TCEQ, be used to determine compliance with the conditions of this permit.
- E. The appropriate TCEQ Regional Office shall be notified at least 30 days prior to any required RATA in order to provide them the opportunity to observe the testing.
- F. Quality-assured (or valid) data must be generated when the source generating air emissions is operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the source operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded. Options to increase system reliability to an acceptable value, including a redundant CEMS, may be required by the TCEQ Regional Manager.

Recordkeeping

67. The records retention period specified under General Condition 7 shall be extended to five years.
68. Reserved.

Miscellaneous Provisions

69. Stack Testing of the Pyrolysis Furnaces as required in Special Condition 62 and Initial RATA per Special Condition 66.A are granted an extension to conduct the testing by December 31, 2022. The stack testing shall include the initial RATA following the requirements of 40 CFR Part 60 Appendix B and the Ammonia CEMS Quality Assurance Plan to certify the CEMS on each furnace.

CGAs shall be conducted on each furnace quarterly starting in June 2022, until the RATA is completed and requirements of Special Condition 66.B and F shall apply. **(06/22)**

Optical Gas Imaging

70. The following modifications to the 28VHP and 28CNTQ programs specified in Special Condition Nos. 33 and 34 may be implemented as an alternative monitoring program during the initial 180 day shakedown period of each unit. These modifications are specified in order for the permit holder to be allowed to implement an alternate work practice (AWP) as an alternative to the current Method 21 monitoring requirements specified in Special Condition Nos. 33 and 34. **(5/21)**
- A. In lieu of the Method 21 monitoring requirements of Special Condition Nos. 33 and 34 and 40 CFR Part 63, Subpart FFFF, the permit holder shall monitor connectors on a monthly basis using an optical gas imaging camera (OGIC) meeting the requirements of 40 Code of Federal Regulations (CFR) §60.18(i)(1) as described in the OGIC Monitoring Plan in the permit amendment file with PI-1 dated March 4, 2021 (Project 326390). Connectors that would be considered inaccessible (e.g., insulated connectors), difficult-to-monitor (DTM), or unsafe-to-monitor (UTM) when using a Method 21 instrument will be monitored with the OGIC so long as such connectors are not considered DTM or UTM, as defined in Paragraph G of this condition, when using an OGIC.
 - B. All connectors described above must also be monitored annually using an approved gas analyzer conforming to the requirements listed in Method 21 of 40 CFR part 60, appendix A. As an option, a facility may choose to space out the Method 21 monitoring of all connectors over a 12-month period, as long as all connectors are monitored on a set schedule every 12 months. This requirement does not apply to connectors that would be considered DTM or UTM when using a Method 21 instrument.
 - C. All OGIC operators shall meet the minimum training requirements as specified in subparagraph 2.1.5 of *the OGIC Monitoring Plan*.
 - D. An OGIC daily verification check shall be performed prior to a monitoring survey as specified in 40 CFR 60.18 (i) (2) (i) through (iv). The daily OGIC verification check shall be conducted by each separate OGIC operator that will be performing imaging using the same OGIC for that day.
 - E. Monthly monitoring using the OGIC will be performed following the procedures outlined in paragraph 2 and subparagraphs 2.1.1 through 2.1.6 of *the OGIC Monitoring Plan*.
 - F. When monitoring using the OGIC, connectors within the OGIC field of view will be observed for a minimum of three seconds. All component emissions imaged by the optical gas-imaging instrument are considered to be leaks and are subject to repair. All component emissions visible to the naked eye are also considered to be leaks and are subject to repair.
 - G. When a connector leak is identified with the OGIC, an approved gas analyzer conforming to the requirements listed in Method 21 of 40 CFR part 60, appendix A will be used to monitor and record the concentration of the connector leak before and after the repair. Scenarios where a connector leak is detected by the OGIC but a Method 21 approved gas analyzer reading is not required include; connectors that are considered DTM or UTM with a Method 21 instrument and connectors that are insulated and therefore not accessible for Method 21 instrument monitoring.

A difficult-to-monitor connector is a connector that cannot be inspected without elevating the monitoring personnel more than two meters above a permanent support surface or that requires a permit for confined space entry as defined in 29 CFR §1910.146. An unsafe-to-monitor connector is a connector that the owner or operator determines is unsafe to monitor because monitoring personnel would be exposed to an immediate danger as a consequence of conducting the monitoring.

- H. The alternative monitoring schedule authorized in Subparagraph K of Special Condition No. 33 is not applicable.
- I. The following records shall be kept for a period of at least 5 years and be made available to the TCEQ Executive Director or designated representative upon request:
 - (1) Records of the make, model, and manufacturer specifications of each OGIC used to demonstrate compliance with Subparagraph A of this condition.
 - (2) Records demonstrating compliance with Subparagraph C of this condition.
 - (3) The equipment, processes, and facilities for which the owner or operator chooses to use the alternative work practice.
 - (4) Confirmation that the detection sensitivity level was 60 grams per hour for the optical gas-imaging instrument.
 - (5) The analysis to determine the piece of equipment in contact with the lowest mass fraction of chemicals that are detectable, as specified in paragraph (i)(2)(i)(A) of 40 CFR 60.18.
 - (6) The technical basis for the mass fraction of detectable chemicals used in the equation in paragraph (i)(2)(i)(B) of 40 CFR 60.18.
 - (7) Records of the daily OGIC verification check. Record the distance, per paragraph (i)(2)(iv)(B) of 40 CFR 60.18, and the flow meter reading, per paragraph (i)(2)(iv)(C) of 40 CFR 60.18, at which the gas was imaged during the daily OGIC verification check. Keep a video record of the daily instrument check for each configuration of the optical gas imaging instrument used during the connector leak survey (for example, the daily instrument check must be conducted for each lens used). The video record must include a time and date stamp for each daily instrument check. The video record must be kept for 5 years.
 - (8) Records of OGIC monitoring shall indicate dates, times, connector areas monitored, results of imaging and the results of Method 21 monitoring for those connectors found leaking with the OGIC. In addition, a video record must be used to document the connector leak survey results. The video record must include a time and date stamp for each monitoring event. A video record can be used to meet the recordkeeping requirements if each piece of regulated equipment selected for this work practice can be identified in the video record. The video record must be kept for 5 years.
 - (9) The records of the annual Method 21 screening required in subparagraph B of this condition shall identify the equipment screened, the screening value measured by Method 21, the time and date of the screening, and calibration information required in Subparagraph F of Special Condition No. 33.

- (10) Records of repairs to fugitive connectors shall include date of repairs, repair results, justification for delay of repairs, and corrective actions taken for all connectors.
- (11) Records of maintenance to the OGIC, as applicable, will be maintained by the OGIC owner/operator. Records of the OGIC owner/operator contact information shall be maintained.

Date: September 23, 2022

Emission Sources - Maximum Allowable Emission Rates

Permit Numbers 146425 and PSDTX1518

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
O_FAFO1	Pyrolysis Furnace A	CO	165.16	—
		NO _x	25.20	—
		PM	4.32	—
		PM ₁₀	4.32	—
		PM _{2.5}	4.32	—
		VOC	3.12	—
		SO ₂	0.34	—
		H ₂ SO ₄	0.03	—
		NH ₃	2.51	—
O_FBFO	Pyrolysis Furnace B	CO	165.16	—
		NO _x	25.20	—
		PM	4.32	—
		PM ₁₀	4.32	—
		PM _{2.5}	4.32	—
		VOC	3.12	—
		SO ₂	0.34	—
		H ₂ SO ₄	0.03	—
		NH ₃	2.51	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
O_FCF01	Pyrolysis Furnace C	CO	165.16	—
		NO _x	25.20	—
		PM	4.32	—
		PM ₁₀	4.32	—
		PM _{2.5}	4.32	—
		VOC	3.12	—
		SO ₂	0.34	—
		H ₂ SO ₄	0.03	—
		NH ₃	2.51	—
O_FDF01	Pyrolysis Furnace D	CO	165.16	—
		NO _x	25.20	—
		PM	4.32	—
		PM ₁₀	4.32	—
		PM _{2.5}	4.32	—
		VOC	3.12	—
		SO ₂	0.34	—
		H ₂ SO ₄	0.03	—
		NH ₃	2.51	—
O_FEF01	Pyrolysis Furnace E	CO	165.16	—
		NO _x	25.20	—
		PM	4.32	—
		PM ₁₀	4.32	—
		PM _{2.5}	4.32	—
		VOC	3.12	—
		SO ₂	0.34	—
		H ₂ SO ₄	0.03	—
		NH ₃	2.51	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
O_FFF01	Pyrolysis Furnace F	CO	165.16	—
		NO _x	25.20	—
		PM	4.32	—
		PM ₁₀	4.32	—
		PM _{2.5}	4.32	—
		VOC	3.12	—
		SO ₂	0.34	—
		H ₂ SO ₄	0.03	—
		NH ₃	2.51	—
O_FGF01	Pyrolysis Furnace G	CO	165.16	—
		NO _x	25.20	—
		PM	4.32	—
		PM ₁₀	4.32	—
		PM _{2.5}	4.32	—
		VOC	3.12	—
		SO ₂	0.34	—
		H ₂ SO ₄	0.03	—
		NH ₃	2.51	—
O_FHF01	Pyrolysis Furnace H	CO	165.16	—
		NO _x	25.20	—
		PM	4.32	—
		PM ₁₀	4.32	—
		PM _{2.5}	4.32	—
		VOC	3.12	—
		SO ₂	0.34	—
		H ₂ SO ₄	0.03	—
		NH ₃	2.51	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
O_F_CAP	Pyrolysis Furnaces Cap	CO	651.06	637.87
		NO _x	53.70	196.22
		NO _x Shakedown	53.70	184.22
		PM	—	92.85
		PM ₁₀	—	92.85
		PM _{2.5}	—	92.85
		VOC	—	67.20
		SO ₂	—	7.33
		H ₂ SO ₄	—	0.67
		NH ₃	—	77.46
UFFLARE01	Multi-Point Ground Flare (Routine)	CO	165.05	—
		NO _x	107.92	—
		VOC	500.00	—
		SO ₂	22.00	—
UFFLARE01	Multi-Point Ground Flare (Planned MSS, alternate operating mode and Shakedown Period) (8)	CO	4115.51	—
		NO _x	2690.91	—
		VOC	5944.74	—
		SO ₂	395.28	—
UFFLARE02	Shared Elevated Flare (Routine)	CO	162.03	—
		NO _x	31.8	—
		VOC	300.00	—
		SO ₂	98.00	—
UFFLARE02	Shared Elevated Flare (Planned MSS, alternate operating mode and Shakedown Period) (8)	CO	340.99	—
		NO _x	66.92	—
		VOC	916.17	—
		SO ₂	98.00	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
CAPUFFLR	Shared Elevated and Ground Flare Cap	CO	—	295.13
		NO _x	—	148.00
		VOC	—	320.06
		SO ₂	—	23.60
CAPUFFLR	Shared Elevated and Ground Flare Cap (Shakedown period)	NO _x	—	192.67
		CO	—	374.11
		VOC	—	422.30
		SO ₂	—	23.60
O_FUG	Olefins Unit Fugitives (5)	VOC	12.74	55.81
		VOC (9)	1.11	2.40
		NH ₃	2.00	8.76
		CO	0.04	0.16
		H ₂ SO ₄	< 0.01	0.02
		H ₂ S	< 0.01	0.01
		NaOH	< 0.01	< 0.01
O-REGEN	Olefins Regeneration Vent	VOC	0.18	0.06
		CO	10.61	1.91
GFFLARE01	MEG Elevated Flare (Routine)	CO	189.44	—
		NO _x	37.18	—
		VOC	38.59	—
		SO ₂	22.74	—
		Total Halide	0.92	—
GFFLARE01	MEG Elevated Flare (Planned MSS and Shakedown Period)	CO	307.90	—
		NO _x	60.42	—
		VOC	214.93	—
		SO ₂	22.74	—
		Total Halide	0.92	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
GFFLARE01	MEG Elevated Flare	CO	—	88.60
		NO _x	—	17.39
		VOC	—	17.37
		SO ₂	—	0.43
		Total Halide	—	0.40
GFFLARE01	MEG Elevated Flare (Shakedown Period)	CO	—	103.95
		NO _x	—	20.40
		VOC	—	21.37
		SO ₂	—	0.43
		Total Halide	—	0.40
GBX02	MEG Thermal Oxidizer	NO _x	8.00	25.79
		CO	11.06	35.65
		VOC	21.10	41.43
		SO ₂	1.75	0.38
		PM	1.00	3.23
		PM ₁₀	1.00	3.23
		PM _{2.5}	1.00	3.23
		Total Halide	0.92	4.04
		NH ₃	0.04	< 0.01
GDVAC	Glycol Vacuum Vent	VOC	3.43	0.34
GAD09A-D	Glycol Moderator CAS	VOC	< 0.01	< 0.01
G_FUG	Glycol Unit Fugitives (5)	VOC	2.22	9.73
		VOC (9)	0.02	0.09
		CO	0.01	0.03

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
UCCT01	Utilities Cooling Tower	VOC	115.29	91.13
		PM	8.07	31.56
		PM ₁₀	5.65	22.09
		PM _{2.5}	3.39	13.26
		NaOH	0.03	0.01
USSG01A	Utilities Boiler A	NO _x	35.25	—
		CO	186.00	—
		PM	7.82	—
		PM ₁₀	7.82	—
		PM _{2.5}	7.82	—
		VOC	5.66	—
		SO ₂	5.22	—
		H ₂ SO ₄	0.07	—
		NH ₃	4.02	—
USSG01B	Utilities Boiler B	NO _x	35.25	—
		CO	186.00	—
		PM	7.82	—
		PM ₁₀	7.82	—
		PM _{2.5}	7.82	—
		VOC	5.66	—
		SO ₂	5.22	—
		H ₂ SO ₄	0.07	—
		NH ₃	4.02	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
USSG01C	Utilities Boiler C	NO _x	35.25	—
		CO	186.00	—
		PM	7.82	—
		PM ₁₀	7.82	—
		PM _{2.5}	7.82	—
		VOC	5.66	—
		SO ₂	5.22	—
		H ₂ SO ₄	0.07	—
		NH ₃	4.02	—
USSG01CAP	Utilities Boiler Cap	NO _x	39.66	69.02
		CO	198.85	239.40
		PM	—	47.57
		PM ₁₀	—	47.57
		PM _{2.5}	—	47.57
		VOC	—	34.43
		SO ₂	8.03	5.18
		H ₂ SO ₄	—	0.48
		NH ₃	—	29.07
UFF01A	Shared Thermal Oxidizer A	NO _x	—	—
		CO	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
		VOC	—	—
		SO ₂	—	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
UFF01B	Shared Thermal Oxidizer B	NO _x	—	—
		CO	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
		VOC	—	—
		SO ₂	—	—
UFF01	Shared Thermal Oxidizer Cap	NO _x	18.80	29.11
		CO	25.81	39.95
		PM	2.34	3.61
		PM ₁₀	2.34	3.61
		PM _{2.5}	2.34	3.61
		VOC	114.96	63.33
		SO ₂	1.13	1.49
U_FUG	Utilities Fugitives (5)	VOC	0.95	4.18
		VOC (9)	0.12	0.26
		NH ₃	0.22	0.96
		CO	< 0.01	0.02
		H ₂ SO ₄	< 0.01	< 0.01
EMGGEN01	Olefins Emergency Generator No. 1	NO _x	0.38	0.06
		CO	4.48	0.67
		PM	0.02	<0.01
		PM ₁₀	0.02	<0.01
		PM _{2.5}	—0.02	<0.01
		VOC	0.02	<0.01
		SO ₂	0.01	<0.01

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
EMGGEN02	Utilities Emergency Generator No. 2	NO _x	0.38	0.06
		CO	4.48	0.67
		PM	0.02	<0.01
		PM ₁₀	0.02	<0.01
		PM _{2.5}	0.02	<0.01
		VOC	0.02	<0.01
		SO ₂	0.01	<0.01
ADMINGEN	Admin Emergency Generator No. 1	NO _x	1.31	0.20
		CO	3.42	0.51
		PM	0.12	0.02
		PM ₁₀	0.12	0.02
		PM _{2.5}	0.12	0.02
		VOC	0.07	0.01
		SO ₂	0.02	<0.01
FWP1	Firewater Pump No. 1	NO _x	5.37	0.54
		CO	2.21	0.22
		PM	0.31	0.03
		PM ₁₀	0.31	0.03
		PM _{2.5}	0.31	0.03
		VOC	0.08	0.01
		SO ₂	0.01	<0.01

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
FWP2	Firewater Pump No. 2	NO _x	5.37	0.54
		CO	2.21	0.22
		PM	0.31	0.03
		PM ₁₀	0.31	0.03
		PM _{2.5}	0.31	0.03
		VOC	0.08	0.01
		SO ₂	0.01	<0.01
GLYGEN01	Glycol Emergency Generator No. 1	NO _x	0.38	0.06
		CO	4.48	0.67
		PM	0.02	<0.01
		PM ₁₀	0.02	<0.01
		PM _{2.5}	0.02	<0.01
		VOC	0.02	<0.01
		SO ₂	0.01	<0.01
LIQLOAD	Truck/Railcar/Drum Liquid Loading (Uncaptured Emissions)	VOC	4.81	0.64
		NaOH	1.31	0.06
WWTP	Wastewater Plant (Uncontrolled emissions)	VOC	1.05	4.58
		NH ₃	< 0.01	< 0.01
		Acetone	< 0.01	< 0.01
		H ₂ S	< 0.01	0.01

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
ZWSRCO1A/B	Equalization Tanks Catalytic Oxidizer	VOC	0.04	0.18
		NH ₃	< 0.01	< 0.01
		Acetone	< 0.01	< 0.01
		H ₂ S	< 0.01	< 0.01
		NO _x	0.06	0.26
		CO	0.02	0.10
		PM	0.01	0.03
		PM ₁₀	0.01	0.03
		PM _{2.5}	0.01	0.03
		SO ₂	0.01	0.06
		HCl	< 0.01	0.01
MSSATM	Maintenance, Startup and Shutdown (Uncontrolled emissions)	VOC	445.47	4.44
		PM	12.98	0.08
		PM ₁₀	12.98	0.08
		PM _{2.5}	12.98	0.08
MSSILE	Inherently Low Emitting Activities	VOC	11.49	1.05
		PM	0.02	0.01
		PM ₁₀	0.02	0.01
		PM _{2.5}	0.02	0.01
MSSVAC	MSS Vacuum Trucks	VOC	72.16	1.82
MSSFRAC	MSS Frac Tanks	VOC	0.03	0.03

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
TMPCTRL	MSS Temporary Control Devices identified in Special Condition 57	NO _x	3.06	0.20
		CO	8.80	0.66
		PM	0.30	0.02
		PM ₁₀	0.30	0.02
		PM _{2.5}	0.30	0.02
		VOC	24.26	0.68
		SO ₂	0.56	0.04
MSSTANK	Tank Maintenance Activities (Uncontrolled)	VOC	20.11	3.53
REFUSTN	Vehicle Refueling Station	VOC	2.03	0.17
ELDC01,	EPE Granules Feed Bin Dust Collector	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
EDFAN01	EPE Granules Hopper Vent Dust Collector	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
EDDC04	EPE Seed Bed Bin Dust Collector Vent	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
ELDC03,	EPE Extruder Feed Conveyor Dust Collector	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
EPFAN01	EPE Pellet Silos Dust Collector	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
EMDC01, EMFAN01, EMFAN02	EPE Pellet Surge Bin Dust Collector and Pellet Dryer Vents	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
ELFAN04, ELDC06, ELB01, ELB03, ELB05, ELFAN01	EPE Weigh Feeder Hopper Extraction Vent, Zinc Oxide Drying Hopper Dust Collector, Additive Vacuum Blower Vents and Solids Additives Vent Dust Collector	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
EBFIL01, ECFIL04, ECFIL05, ECFIL06	EPE Catalyst Cylinder Vent Filter and Catalyst Hold Tank Filter Vents	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
E_VENTCAP	EPE Vents Cap (6)	VOC	35.68	37.08
		PM	1.08	2.74
		PM ₁₀	1.08	2.74
		PM _{2.5}	1.08	2.74
CLDC01	CPE Granules Feed Bin Dust Collector	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
CDFAN01	CPE Granules Hopper Vent Dust Collector	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
CDDC04	CPE Seed Bed Bin Dust Collector Vent	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
CLDC03	CPE Extruder Feed Conveyor Dust Collector	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
CPFAN01	CPE Pellet Silos Dust Collector	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
CMD01, CMFAN01, CMFAN02	CPE Pellet Surge Bin Dust Collector and Pellet Dryer Vents	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
CLFAN04, CLDC06, ELB02, ELB04, CLB03,	CPE Weigh Feeder Hopper Extraction Vent, Zinc Oxide Drying Hopper Dust Collector and Additive Vacuum Blower Vents	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
CBFIL01CCFIL04, CCFIL05, CCFIL06	CPE Catalyst Cylinder Vent Filter and Catalyst Hold Tank Filter Vents	VOC	—	—
		PM	—	—
		PM ₁₀	—	—
		PM _{2.5}	—	—
C_VENTCAP	CPE Vents Cap (7)	VOC	35.68	37.08
		PM	0.84	2.32
		PM ₁₀	0.84	2.32
		PM _{2.5}	0.84	2.32
PE-REGEN	PE Regeneration Vent	VOC	< 0.01	< 0.01
E_FUG, C_FUG	EPE and CPE Fugitives (5)	VOC	4.38	19.17
		VOC (9)	0.60	1.30
		CO	0.07	0.32
ELD01	EPE Primary Run Tank	VOC	0.36	0.02
ELD02	EPE Secondary Run Tank	VOC	0.36	0.03
CCD81	CPE Seal Pot	VOC	0.04	<0.01
GETK02A	MEG Rundown Tank 2A	VOC	0.65	0.22
GETK02B	MEG Rundown Tank 2B	VOC	0.65	0.22
GDTK01	Glycol Catalyst Storage Tank	VOC	0.23	0.01
GDD08	Glycol Catalyst Charge Vessel	VOC	0.03	<0.01
GDD09	Glycol Catalyst Drips Vessel	VOC	0.02	< 0.01
GETK01	Glycol Slops Tank	VOC	0.58	0.03
SCTOTE-GLY	Spent Glycol Catalyst Tote	VOC	0.04	< 0.01
ZTTK02	Heavy Glycol Storage Tank	VOC	0.83	0.03
ZTTK03	Glycol Bleed Storage Tank	VOC	0.83	0.03
GED04	Glycol Drain Collection Vessel	VOC	0.03	<0.01
ZTTK05	Hexene Storage Tank	VOC	0.43	1.20
ZTTK06AMNT	Heavy Fuel Oil Storage Tank	VOC	0.5	—

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
ZTTK06BMNT	Heavy Fuel Oil Storage Tank	VOC	0.5	—
CAPTHFO	Total Emissions from EPNs ZTTK06AMNT, ZTTK06BMNT	VOC	—	0.03
ZTTK04	Slop Oil Tank 1	VOC	0.72	2.48
FZTK01	Olefins Decoke Condensate Sump	VOC	0.64	0.02
GFTK01	Glycol Flare Seal Sump	VOC	0.53	<0.01
ZFTK02B	Firewater Pump Diesel Tank 2B	VOC	0.04	<0.01
ZMTK02	Infrastructure Diesel Tank	VOC	0.38	<0.01
UKDGEN01TK	Olefins Emergency Generator No. 1 Diesel Tank	VOC	0.05	<0.01
UKDGEN02TK	Utilities Emergency Generator No. 2 Diesel Tank	VOC	0.05	<0.01
ADMINGENTK	Admin Emergency Generator No 1 Diesel Tank	VOC	0.12	<0.01
ZFTK02C	Firewater Pump Diesel Tank 2C	VOC	0.04	<0.01
GUDGEN01TK	Glycol Generator Diesel Tank	VOC	0.05	<0.01
ZMTK01	Infrastructure Gasoline Tank	VOC	11.61	1.71
TOTES	Site Totes	NaOCl	0.01	<0.01
U_LAB	Laboratory	VOC	2.65	0.48
UTTK04	Sulfuric Acid Tank	H ₂ SO ₄	<0.01	<0.01
UCTK01	Sodium Hypochlorite Tank	NaOCl	2.23	0.08
UTD05	Aqueous Ammonia Vent Drum	NH ₃	1.94	0.15
ZTTK01	Caustic Storage Tank	NaOH	0.33	0.03

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources, use area name or fugitive source name.

(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO_x - total oxides of nitrogen

SO₂ - sulfur dioxide

PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented

PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented

PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter

Emission Sources - Maximum Allowable Emission Rates

CO	- carbon monoxide
NaOH	- sodium hydroxide
NH ₃	- ammonia
HCl	- hydrogen chloride
HI	- hydrogen iodide
H ₂ SO ₄	- sulfuric acid mist
H ₂ S	- hydrogen sulfide
Total Halide	- combined emissions of hydrogen chloride and hydrogen iodide.
NaOCl	- sodium hypochlorite

- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
- (6) Includes total emissions for the following sources of emissions (designated by EPN): ELDC01, EDFAN01, EDDC04, ELDC03, EPFAN01, EMDC01, EMFAN01, EMFAN02, ELFAN04, ELDC06, ELB01, ELB03, ELB05, ELFAN01, EBFIL01, ECFIL04, ECFIL05, ECFIL06
- (7) Includes total emissions for the following sources of emissions (designated by EPN): CLDC01, CDFAN01, CDDC04, CLDC03, CPFAN01, CMDC01, CMFAN01, CMFAN02, CLFAN04, CLDC06, ELB02, ELB04, CLB03, CBFIL01, CCFIL04, CCFIL05, CCFIL06
- (8) Alternate operating mode as defined in Special Condition 48.
- (9) Additional emission limits for connectors during the initial unit shakedown period use of alternate fugitive monitoring per Special Condition 70.

Date: May 21, 2021